

Development of the Surface Urban Energy and Water balance Scheme (SUEWS) for cold climate cities

L. Järvi¹, C. S. B. Grimmond², M. Taka³, A. Nordbo¹, H. Setälä⁴ and I. B. Strachan⁵

[1]{University of Helsinki, Department of Physics, Helsinki, Finland}

[2]{University of Reading, Department of Meteorology, Reading, United Kingdom}

[3]{University of Helsinki, Department of Geosciences and Geography, Helsinki, Finland}

[4]{University of Helsinki, Department of Environmental Sciences, Helsinki, Finland}

[5]{McGill University, Department of Natural Resource Sciences, QC, Canada}

Correspondence to: L. Järvi (leena.jarvi@helsinki.fi)

Abstract

The Surface Urban Energy and Water balance Scheme (SUEWS) is developed to include snow. The processes addressed include accumulation of snow on the different urban surface types; snow albedo and density aging, snow melting and re-freezing of melt water. Individual model parameters are assessed and independently evaluated using long-term observations in the two cold climate cities of Helsinki and Montreal. Eddy covariance sensible and latent heat fluxes and snow depth observations are available for two sites in Montreal and one in Helsinki. Surface runoff from two catchments (24 and 45 ha) in Helsinki and snow properties (albedo and density) from two sites in Montreal are also analysed. As multiple observation sites with different land-cover characteristics are available in both cities, model development is conducted independently of evaluation.

The developed model simulates snowmelt related runoff well (within 19% and 3% for the two catchments in Helsinki when there is snow on the ground), with the springtime peak estimated correctly. However, the observed runoff peaks tend to be smoother than the simulated ones, likely due to the water holding capacity of the catchments and the missing time lag between the catchment and the observation point in the model. For all three sites the model simulates the timing of the snow accumulation and melt events well, but underestimates the total snow depth by 18-20% in Helsinki and 29-33% in Montreal. The

model is able to reproduce the diurnal pattern of net radiation and turbulent fluxes of sensible and latent heat during cold snow, melting snow and snow-free periods. Largest model uncertainties are related to the timing of the melting period and the parameterization of the snow melt. The results show that the enhanced model can simulate correctly the exchange of energy and water in cold climate cities at sites with varying surface cover.

1 Introduction

Today more than half of world's population resides in urban areas, and this fraction is expected to increase in the next decades (Martine and Marshall, 2007). Thus, the ability to understand and forecast the urban climate is crucial for sustainable urban planning and our quality of life. The exchanges of heat and water between the surface and the atmosphere are of great importance to urban climate studies. These exchanges describe the surface forcing in numerical weather prediction, air quality and climate models.

In urban areas several land surface models, with different complexity, simulate these energy exchanges, but none of the models consistently outperforms the others (Grimmond et al., 2011). The latent heat flux is commonly underestimated and sometimes even ignored, which further increases the direct heat emissions to the atmosphere. Furthermore, most of these models only concentrate on the surface-atmosphere interactions without any connections to the water cycles in urban areas. Similarly, several hydrological models to simulate urban drainage and the surface runoff in urban areas have been developed (Mitchell et al., 2003, 2008; Easton et al., 2007; Jacobson, 2011), but these do not typically consider the full energy balance.

Both in land surface and hydrological model studies, urban areas located in cold climates have been little studied despite their particular sensitivity to regional and global climate change. Thus appropriate, robust, well tested modeling tools are needed. Modeling studies of cold cities are focused on a few sites mainly in North-America (e.g. Valeo and Ho, 2004; Lemonsu et al., 2010; Leroyer et al., 2010) and Scandinavia (e.g. Semádeni-Davies et al., 1998). These emphasize the need for correct description of snow cover in hydrological models. Snow affects surface energy partitioning via albedo and snowmelt, re-freezing and the phase change related energy fluxes. The energy required for snow melt can be of the same magnitude as the sensible and latent heat fluxes (Lemonsu et al., 2010). Snow impacts water availability and its melt may cause springtime floods in urban areas (Semádeni-Davies and

Bengtsson, 1998). To keep cities operational, snow is often redistributed within neighborhoods and/or is transported away (Semádeni-Davies and Bengtsson, 1998, 1999), which impacts both the energy and water cycles.

The lack of observational data in urban areas with continuous winter snow cover makes the determination of model parameters and flux evaluation challenging. Surface-atmosphere exchange of sensible and latent heat can be measured directly using the eddy covariance technique, but these observations are relatively rare especially in cold climate cities. Notable exceptions include the work of Lemonsu et al. (2008), Vesala et al. (2008), Bergeron and Strachan (2012) and Nordbo et al. (2012a,b). These studies have found a strong seasonality in the energy exchanges and a need for correct estimation of anthropogenic heat emissions from building sources, notably heating in winter. Similarly, the few hydrological studies have shown strong seasonality in stormwater runoff and differences in the amount of the snow melt when compared to natural environments (Bengtsson and Westerström, 1992; Semádeni-Davies and Bengtsson, 1998; Valtanen et al., 2013).

The purpose of this study is to develop a model that can correctly simulate both the energy and water balances in cold climate cities. The model developed is included in the Surface Urban Energy and Water balance Scheme (SUEWS, Järvi et al., 2011) with particular attention to the accumulation and melting of snow. The development and independent evaluation of the model uses several years of data collected in Helsinki (60°N, 24°W) and Montreal (45°N, 73°W). These include turbulent fluxes of heat and water measured with the eddy covariance technique, stormwater runoff and snow properties. In addition to snow related processes, the parameterization of the leaf area index has been improved to be more applicable for cold climate cities (Appendix A).

2 Methods

2.1 The Surface Urban Energy and Water balance Scheme (SUEWS)

The Surface Urban Energy and Water balance Scheme SUEWS (Järvi et al., 2011) simulates the urban energy and water balance components from local or neighborhood scale using hourly meteorological forcing data. These data inputs are kept to a minimum to enhance the flexibility of the model and commonly include: measured solar radiation (probably least frequently measured), air temperature, relative humidity, surface air pressure, wind speed and

precipitation. In addition, SUEWS requires information about the characteristics of the area to be simulated, such as surface cover fractions of paved, buildings, evergreen trees/shrubs, deciduous trees/shrubs, irrigated grass, non-irrigated grass and water, and population density and building and tree heights.

Rates of evaporation-interception for a single layer for each of the surface types are calculated and below each surface type, except water, there is a single soil layer. At each time step (5 min to 1 h) the moisture state of each surface and soil type is calculated. Horizontal water movements at the surface and in the soil are incorporated. Latent heat flux is calculated with a modified Penman-Monteith equation and sensible heat flux as a residual from the available energy minus the latent heat. The model contains several sub-models, for example for net all-wave radiation (NARP, Offerle et al., 2003; Loridan et al., 2011), storage heat fluxes (Grimmond et al., 1991), anthropogenic heat fluxes, and external irrigation.

2.1.1 New developments

The new version of SUEWS presented here incorporates a parameterization for snow cover. Previously, snow cover was a required input that was assumed to cover the whole grid area and only directly impacted the radiation. Now, accumulation and melting of snow are estimated, with impact to net all-wave radiation, evaporation, and other water balance components included. For each surface type, the energy and water balances are calculated separately for snow-free and snow-covered areas and the model outputs are weighted according to their respective fractions. The energy and water flow calculations in the snow-free surface types follow those in the original version of the model (Järvi et al., 2011). Here we present the equations related to the snow covered surface which is treated as a single snow layer.

The energy balance of the snow covered surface modified for urban areas can be written as (e.g. Oke, 1987; Cline, 1997)

$$Q_M + \Delta Q_{S,I} = Q^* + Q_F - Q_H - Q_E + Q_P - Q_g + \Delta Q_A \quad (\text{W m}^{-2}) \quad (1)$$

where Q_M is the latent heat storage change caused by melting or freezing, $\Delta Q_{S,I}$ is the change in the storage heat of the snow, Q^* is the net all-wave radiation, Q_F is the anthropogenic heat flux, Q_H and Q_E are the turbulent sensible and latent heat fluxes, Q_P is the heat released by liquid precipitation on snow, Q_g is the heat exchange between the snow and the soil below and ΔQ_A is the net advective heat flux. Snow melt occurs if the net energy input to the snow is

positive (i.e. right-hand side of the eq. (1) > 0). Q_F is calculated based on cooling and heating degree days (Järvi et al., 2011). Advection occurs at a number of scales. The micro-scale (or sub-grid-scale) advection is not resolved in the model, but rather embedded within the coefficients obtained using model optimization. The inter-grid advection is assumed to be negligible. This is consistent with the eddy covariance fluxes used to assess the model. To resolve advection at this scale would require the model to be embedded in a meso-scale model. The ground heat flux Q_g is not separately resolved and is assumed to be included within the parameterization coefficients.

The link to the snow mass balance is through Q_E or evaporation (E):

$$P + F = E + R + T_R + \Delta S_{WE} \quad (\text{mm h}^{-1}) \quad (2)$$

where P is precipitation (snowfall, rain), F is liquid water that freezes on a snow-free surface, R is the runoff from the snowpack, T_R is the transport of snow from the study area (e.g. via snow-clearing) and ΔS_{WE} is the change in (liquid and solid phase) snow water equivalent (S_{WE}).

Surface albedo

Snow affects Q^* by modifying the albedo of the surface and thus the reflected short-wave radiation, and the upwelling long wave radiation as the surface temperature of snow and snow-free surface are different. The snow albedo (α_s) varies with snow age for each time step (Δt), based on whether it is the ‘cold snow period’ when melting does not occur (Baker et al., 1990):

$$\alpha_s(t + \Delta t) = \alpha_s(t) - \tau_a \frac{\Delta t}{\tau_d} \quad (3)$$

or the ‘warm snow period’ when snow melt occurs (Verseghy, 1991):

$$\alpha_s(t + \Delta t) = [\alpha_s(t) - \alpha_s^{min}] \exp\left(-\tau_f \frac{\Delta t}{\tau_d}\right) + \alpha_s^{min} \quad (4)$$

For simplicity, the warm snow period is defined as times when air temperature (T_a) is above 0°C . α_s^{min} is the minimum snow albedo, τ_d is a period of one day (86400 s), and τ_a and τ_f are time constants related to the snow aging. After new snowfall, when S_{WE} exceeds 2 mm (Koivusalo and Kokkonen, 2002), the snow albedo is reset to its maximum (fresh snow) value (α_s^{max}). The upward long-wave radiation uses a constant snow emissivity.

Snow heat storage

The net heat storage in the snow can be considered to describe the convergence or divergence of sensible heat fluxes within the snowpack volume. This is calculated using the objective hysteresis model (OHM; Grimmond et al., 1991):

$$\Delta Q_{s,l} = a_1 Q^* + a_2 \frac{\Delta Q^*}{\Delta t} + a_3 \quad (5)$$

where a_1 , a_2 and a_3 parameters are set by the model user. The first term describes the direct heating by radiation, the second term the hysteresis of the warming and cooling phases, and the third the time lag. $\Delta Q_{s,l}$ is negative when the snowpack loses energy and the snowpack cools increasing the ‘cold content’ of the snow (energy needed to heat the snow to 0°C), and positive when the snow is heated towards 0°C and the cold content is filled. Cold content is the total energy needed before the melting of snow can start (Bengtsson, 1982).

Energy for melting and freezing

There are two main approaches to estimate the snowmelt and refreezing of the melt water (M) and the related energy (e.g. Martinec, 1989; Tobin et al., 2013): 1) the energy balance method, where M is calculated as a residual from the other energy balance components, and 2) the degree day method where M is calculated using daily or hourly air temperatures and possibly solar radiation. Although the first is more physically-based it requires more input variables, whereas the latter uses more readily available variables. Comparisons of the two methods have found insignificant differences in the melted water calculated (Kustas et al., 1994; Debele et al., 2010). However, the site specific degree day parameters need to be assessed (Bengtsson, 1984).

In SUEWS the second approach is used via a radiation-temperature index for each surface type i (Kustas et al., 1994; Semadeni-Davies et al., 2001; Tobin et al., 2013). Snowmelt induced runoff is delayed by re-freezing of melted water (Bengtsson, 1982), particularly in spring, when the diurnal variations in air and snow surface temperatures are large. Daytime melt-water refreezes after sunset, releasing energy. Traditionally, the degree-day methods have utilized a daily time step, but in urban areas this has poor performance (Bengtsson, 1984). Therefore an hourly time step is utilized here. Melting and freezing occurs as a function of air temperature (T_a) and Q^* under three conditions:

$$\begin{cases} M_i = a_r Q^* & Q^* > 0 \text{ W m}^{-2}, T_a \geq 0^\circ\text{C} \\ M_i = a_t T_a & Q^* < 0 \text{ W m}^{-2}, T_a \geq 0^\circ\text{C} \\ M_i = a_f T_a & T_a < 0^\circ\text{C} \end{cases} \quad (6)$$

with factors for radiation melt a_r ($\text{mm W}^{-1} \text{h}^{-1}$), temperature melt a_t and freezing a_f ($\text{mm } ^\circ\text{C}^{-1} \text{h}^{-1}$) which are typically linearly related with $a_f \leq a_t$ (Tobin et al., 2013). M_i cannot be larger than the amount of solid snow in the pack and the amount of freezing water cannot exceed the amount of liquid water in the snow. The energy consumed in melting and re-freezing is

$$Q_{M,i} = \rho_w M_i L_f, \quad (7)$$

where ρ_w is the liquid water density at 0°C (kg m^{-3}) and L_f is the latent heat of fusion at 0°C (J kg^{-1}).

Besides re-freezing of melted water, the snowmelt runoff from the snowpack is delayed by the amount of liquid water the snow can hold (Bengtsson, 1982; Semádeni-Davies and Bengtsson, 1998). In SUEWS, this liquid water retention capacity (C^R) is calculated as a function of snow density (ρ_s , kg m^{-3}) (Anderson, 1979; Jin et al., 1999):

$$C_i^R = \begin{cases} C_{min}^R, & \rho_s \geq \rho_e \\ C_{min}^R + (C_{max}^R - C_{min}^R) \frac{\rho_s - \rho_e}{\rho_s}, & \rho_s < \rho_e \end{cases} \quad (\text{kg kg}^{-1}) \quad (8)$$

where C_{min}^R and C_{max}^R are the minimum and maximum capacities and ρ_e is a threshold density set to 200 kg m^{-3} . With time, the snow density changes (Verseghy, 1991):

$$\rho_s(t + \Delta t) = [\rho_s(t) - \rho_s^{max}] \exp\left(-\frac{\tau_r \Delta t}{\tau_h}\right) + \rho_s^{max} \quad (9)$$

to a maximum snow density ρ_s^{max} with a time constant τ_r . τ_h is the seconds in an hour (3600 s h^{-1}). After snowfall, ρ_s is calculated as the weighted average of the fresh (ρ_s^{min}) and previous snow densities.

Heat release by rain on snow

A rain on snow event provides heat, when the precipitation temperature is above the liquid/solid threshold (T_{lim}) (Sun et al., 1999):

$$Q_{P,i} = \rho_w c_w P_i (T_a - T_{lim}), \quad (10)$$

where c_w is the specific heat capacity of water ($\text{J kg}^{-1} \text{K}^{-1}$), and P_i is the precipitation on i th surface (m s^{-1}). Here, it is assumed that the temperature of the precipitation is at the air temperature (Sun et al., 1999). Rain stays as a liquid and is routed to melt water store.

Latent heat flux and evaporation

To calculate the latent heat flux (Q_E) a modified Penman-Monteith equation is used with a negligible surface resistance for the snow covered surfaces and an available energy that is constrained by snowmelt and re-freezing of the melt water:

$$Q_{E,i} = \frac{s(Q_p - Q_s) + \frac{c_p \rho V}{r_a}}{s + \gamma}, \quad (11)$$

where s is the slope of the saturation vapour pressure curve over ice ($\text{Pa } ^\circ\text{C}^{-1}$) calculated according to Lowe (1977), γ in the psychrometric constant ($\text{Pa } ^\circ\text{C}^{-1}$), c_p is the heat capacity of air ($\text{J kg}^{-1} \text{K}^{-1}$), ρ is the density of air (kg m^{-3}), V is the vapour pressure deficit (Pa) and r_a is the aerodynamic resistance (s m^{-1}). To calculate the r_a for the snow surface, the roughness length for heat and water vapour (z_{ov} , m) is calculated using (Voogt and Grimmond, 2000):

$$z_{ov} = z_{0m} \exp(-20), \quad (12)$$

where z_{0m} is the roughness length for momentum (m).

Change in snow water equivalent

For the water mass balance calculations, the model adopts a 5-minute time step in order to respond to precipitation and snowmelt events. When the surface is completely covered by snow, the snow water equivalent of the i th surface type ($S_{WE,i}$) is calculated:

$$S_{WE,i}(t + \Delta t) = S_{WE,i}(t) + (P_i + F_i - E_i - R_i - T_{R,i}). \quad (\text{mm (5 min)}^{-1}) \quad (13)$$

If melt occurs ($M_i > 0$) the water is held in the snowpack until the liquid water holding capacity C_i^R is exceeded. The excess water goes directly to runoff (R_i). If the surface is partially covered with snow, the excess water is added to the snow-free surface storage (S_i) and the snow-free surface equations are used (Järvi et al., 2011). If a negative $S_{WE,i}$ occurs, the calculated evaporation is assumed to be too large and is reduced by an equivalent amount (constrained by E_i).

Snow from paved and built surfaces ($T_{R,i}$) can be transported out from the study area. The amount removed is calculated as amount of excess snow above a defined threshold ($S_{WE,Lim}$). This behaviour is neighbourhood specific (e.g. city or neighbourhood ordinances, snow clearance priorities). The S_{WE} is assumed to be reduced to the $S_{WE,Lim}$ at the next site specific snow clearing time period. People are also assumed to redistribute snow (e.g. paths are cleared and the snow is piled elsewhere) within the study area, and this is considered via depletion curves (eq. 15a-c).

The snowpack starts to form when the surface temperature $T_s < 0^\circ\text{C}$ and under two conditions: when solid precipitation occurs; and/or when water on a snow-free surface freezes (F_i). The snow depth s_d (mm) is:

$$s_{d,i} = S_{WE,i} \frac{\rho_w}{\rho_s}. \quad (14)$$

Surface fraction of snow

One of the most important factors controlling the energy balance and snowmelt is the patchiness of snow (Swenson and Lawrence, 2012). This is particularly important in urban areas, where snow clearing from streets and roofs takes place regularly (Semádeni-Davies, 1999). During the melt period, surface type specific depletion curves are used to approximate the fraction of snow cover (f_s) as a function of S_{WE} (e.g. Ek et al., 2003; Valeo and Ho, 2004). These are a function of surface specific maximum snow water equivalent S_{WE}^{max} that control the initiation of snow patchiness (Swenson and Lawrence, 2012). For vegetated surfaces, the Swenson and Lawrence's (2012) form of the function is used with coefficients estimated using the data for vegetated surfaces from Ek et al. (2003):

$$f_{s,veg} = 1 - \left(\frac{1}{\pi} \arccos \left(2 \frac{S_{WE,veg}}{S_{WE,veg}^{max}} - 1 \right) \right)^{1.7} \quad (15a)$$

As this function was developed for climate models its application to smaller scales does require caution. For paved and built surfaces, the equations were derived from Valeo and Ho's (2004) data:

$$f_{s,pav} = \left(\frac{S_{WE}}{S_{WE,pav}^{max}} \right)^2 \quad (15b)$$

$$\begin{aligned} f_{s,bldg} &= 0.5 \left(\frac{S_{WE}}{S_{WE,bldg}^{max}} \right) & \frac{S_{WE}}{S_{WE,bldg}^{max}} < 0.9 \\ f_{s,bldg} &= \left(\frac{S_{WE}}{S_{WE,bldg}^{max}} \right)^8 & \frac{S_{WE}}{S_{WE,bldg}^{max}} \geq 0.9 \end{aligned} \quad (15c)$$

The forms of the depletion curves are shown in Appendix B. The different curves between vegetation and impervious surfaces are used as human activities redistribute snow. For example, large roadside snow piles are created that melt slowly through the spring. In contrast, during the accumulation period snow is assumed to fall evenly on all surfaces.

2.2 Measurement sites and measurements

The model is applied in two cities that typically have extended periods of snow cover: Helsinki and Montreal. As multiple observation sites with different land-cover characteristics are available in both cities, model development is conducted independently of evaluation.

2.1.1 Helsinki, Finland

Meteorological and hydrological observations from three areas of Helsinki are used (Fig. 1). At the Kumpula (Ku, SMEAR III) site both meteorological forcing and evaluation data are measured (Järvi et al., 2009a). In addition, the observed runoff from Pasila (Pa) and Pihlajamäki (Pi) catchments are used for model development and evaluation. Ku is located 4 km north-east of the Helsinki city centre in a suburban area and 3.8 km from Pa and Pi (Fig. 1). Both Pa and the built sector of Ku (Ku1) have large areas of impervious surfaces (62%). At both sites, the buildings are mostly office buildings with mean height of 15 m (Pa) and 11 m (Ku1). Pa has pedestrian areas at two heights with extensive concrete surfaces creating a complex morphology. The other two sectors around the SMEAR III flux tower (Ku2, Ku3) and the Pi catchment are more vegetated (Table 1). Pi, with 34% impervious surfaces, is a typical suburban area in Helsinki with multi-family block houses.

Tower based eddy covariance (EC) sensible and latent heat fluxes measured at 31 m, with an ultrasonic anemometer (Metek, USA-1) and a closed-path infrared gas analyser (LI-7000, respectively, Li-COR Biosciences, Lincoln, NE, USA) at Ku are used. Post-processing of the 10 Hz data use commonly accepted procedures described in detail in Järvi et al. (2009b) and Nordbo et al. (2012a).

Tower-top air temperature (platinum resistant thermometer, Pt-100, “in-house”), wind speed (Thies Clima 2.1x, Goettingen, Germany) and incoming and outgoing short- and long-wave radiation (CNR1, Kipp&Zonen, Delft, Netherlands) are used to force and test the model. Other forcing data measured on a nearby roof (24 m a.g.l.) include air pressure (Vaisala DPA500, Vaisala Oyj, Vantaa, Finland), relative humidity (Vaisala HMP243), and precipitation (rain gauge, Pluvio2, Ott Messtechnik GmbH, Germany). Snow depth measured next to the tower by the Finnish Meteorological Institute is used in the model evaluation.

Runoff was monitored at one minute intervals using a OCM Pro CF flow meter (Nivus GmbH, Eppingen, Germany) mounted in the two catchment storm flow discharge pipes from September 2010 to 30 April 2011 (See Table 2 for data availability). In Pi, excess pipe flow

was observed causing runoff at unexpected times. Because of the water quality observed, this is thought to be associated with pipe leakage in household water systems. From the beginning of September, the excess pipe flow observed was $0.0038 \text{ m}^3 \text{ s}^{-1}$ which had increased to $0.0125 \text{ m}^3 \text{ s}^{-1}$ by the end of the measurement campaign. This pipe flow was removed from the analysis when assessing the runoff as pipe leakage is not modelled currently.

2.1.2 Montreal, Canada

Two residential areas with impervious cover of 71 % (Rl, Rosemont-La-Petite-Patrie borough) and 49 % (Pr, Pierrefonds-Roxboro borough) 18 km apart were modelled (see Bergeron and Strachan (2012) for map). The more densely populated Rl has two to three storey buildings, whereas the suburban Pr is a single family house residential area (Table 1).

At both sites, a tower mounted (26 m a.g.l.) sonic anemometer (CSAT3, Campbell Scientific Canada Corp., Edmonton, AB, Canada) and an open-path infrared gas analyser (LI-7500, LICOR Biosciences, Lincoln, NE, USA) provided the 20 Hz data that are post-processed to EC fluxes of sensible and latent heat (Bergeron and Strachan, 2012). Forcing data of air temperature and relative humidity (HMP45C-212 at Rl, HMP45C at Pr, Campbell Scientific Canada Corp.), pressure (Barometric pressure sensor, RM Young Model 61205V, RM Young Company, Michigan, USA) and radiation (CNR1) are from the EC tower at 25 m a.g.l. Snow depths were monitored in the backyard of Pr and on the roof at Rl with snow ranging sensors (SR5, Campbell Scientific Canada Corp.). Snow properties, including snow density and albedo, were regularly (weekly: 2007/08 winter or bi-monthly: 2008/009 winter) observed for undisturbed snow, sidewalks, lawns and rooftops. Observations from Coteau-du-Lac (35 km southwest from Pr) and Pierre Elliot Trudeau Airport data (7 km from Pr and 16 km from Rl) (National Climate Data and Information Archive of Canada, 2013) are used to create a precipitation dataset with separation of snow/rain.

2.3. Model runs

In Helsinki, SUEWS was run for Ku for three years (January 2010 till December 2012) and for the two catchments for 16 months (January 2010 – April 2011, as observations are available for a shorter period). At all three sites, the first seven months are a spin-up period for the model that is neither used in model development nor testing. The spin-up time allows the model to become independent of the initial conditions set by the user. Even in urban areas, soil moisture initial state has a large impact on urban land surface model performance

(Best and Grimmond, 2013). The remainder of the periods are used for model development and evaluation. In Ku, data prior to 2012 are used to develop and adjust model parameters: Q^* , upward shortwave radiation, and upward and downward long wave radiation are used to adjust the snow, and surface albedo (Eq. 3 and 4), and Q_H and Q_E to test the parameterizations for Q_M and $\Delta Q_{S,I}$ (Eq. 5 and 6). The runoff measured in the denser catchment (Pa) is used to constrain the temperature and radiation melt rates (Eq. 6), retention capacity of the snow (Eq. 8) and the limit for the liquid precipitation. Q^* and its components, Q_H and Q_E , the snow depth from Ku in 2012, and the runoff from the medium-intensity catchment are used to independently evaluate the model.

The meteorological data measured at the Ku site are used to force the model for all three Helsinki sites. The data are gap filled using the procedures described in Järvi et al. (2012). Due to the very different characteristics surrounding the Kumpula tower, the model is run for the three surface cover areas within a 1 km radius circle. The flux time series evaluated against observations are combined from the surface cover areas (Ku1-3) based on the prevailing wind direction.

In Montreal, only the first month of the 22 months (December 2007 till September 2009) is used as a spin-up. The short spin-up time is chosen to allow two snow melt periods in model development and testing. The remainder of the suburban dataset (Q^* , Q_H , Q_E , snow depth, snow density and albedo) is used for the model development: snow density and albedo are used to determine the shape of the snow aging curves (Eq. 3, 4 and 9), Q^* the surface and snow albedo, and Q_H , Q_E the other snow related parameterizations. The urban site observations are used for independent evaluation of the model. The model domain is a 1 km radius circle around the flux tower.

The results are analysed by considering snow-free, cold snow and melting snow periods. For snow-free, the simulated snow depth is zero, whereas the cold snow and melting snow periods are separated by the air temperature 0°C .

2.4 Evaluation statistics

Several statistics are used to evaluate the model performance (e.g. Daley, 1991). Linear regression is used to describe the linear dependence between the independent variable, in this case the model output X_{Mod} , and the dependent variable, the observations (X_{Obs}). The slope

(*S*) relative to 1, and intercept (*I*) relative to zero, provide information on the model performance. Further, goodness of fit is evaluated using the root mean square error (RMSE):

$$RMSE = \sqrt{\frac{\sum (X_{Mod}(t) - X_{Obs}(t))^2}{N}} \quad (16)$$

where *N* is the number of data points. Like the intercept in the linear regression, the RMSE has the units of the variables being evaluated and it depends on the magnitude of the mean variables. Therefore it is useful to normalize the RMSE (nRMSE) relative to the range of values observed (Järvi et al. 2011):

$$nRMSE = \frac{RMSE}{X_{Obs,max} - X_{Obs,min}} \quad (17)$$

When comparing the performance of the model to simulate different variables, the RMSE can also be normalized with the standard deviation of the observations σ_{Obs} (Taylor 2001):

$$sRMSE = \frac{RMSE}{\sigma_{Obs}} \quad (18)$$

In addition, the mean bias error (MBE) between the modelled and observed time series is considered:

$$MBE = \sum (\bar{X}_{Mod} - \bar{X}_{Obs}), \quad (19)$$

where the over bar indicates an average. Ideally, the RMSE, nRMSE, sRMSE and MBE would all be zero.

2.5 General weather conditions

The weather conditions during the modelled period for Helsinki and Montreal are shown in Figs. 2 and 3, respectively. Daytime solar radiation exhibits a strong seasonal pattern, with the 15° latitudinal difference causing more rapid changes and stronger amplitude in Helsinki than Montreal. In summer, K_{\downarrow} reaches 970 W m⁻² in Montreal, whereas in Helsinki the maxima remain below 830 W m⁻². In winter, the solar radiation in Helsinki is very low (< 120 W m⁻²), whereas Montreal peaks are below 400 W m⁻². Despite the difference in K_{\downarrow} , air temperatures are fairly similar in both cities. Daily maxima mean temperatures are around 26°C in summer, while the minimum daily mean temperature in winter in Helsinki is -20°C and in Montreal -23°C. In both cities precipitation is quite evenly distributed throughout the year.

During the three years of measurements, the daily snow depths in Helsinki are all below 0.8 m, with a longer snow period in winter 2010/2011 than 2011/2012. The timing of snowpack formation depends strongly on the year. In 2010, it was initiated in November, whereas in the following winter this was delayed until January 2012. This will have a large influence not only on both natural energy and water exchanges, but also urban activities. In Montreal, snowpack depth and timing has large variability between years; for example a 1 m snow pack is observed in March 2008 with melting in late April, compared to only 0.6 m the next year, with snow melted by the end of March.

3. Results

3.1 Model optimization

Snow properties

The time constants to describe the aging of snow, the minimum and maximum snow albedo, and density were determined by optimization using observations undertaken at the suburban site in Montreal (Pr). The observed snow properties are treated as averages from the measured surface types, in order for them to be compatible with the scale of the simulations. To evaluate the snow albedo, the observed reflected shortwave radiation ($K\uparrow$) in Helsinki in 2011 is also used. To assess the radiative exchanges, SUEWS is run using the radiation measurements source area (99% FOV) estimated as a 31 m radius circle around the 31 m tall measurement tower (Nordbo et al., 2012a). The surface cover characteristics are different for this area to those within the turbulent flux source area; with 49% paved surface, 4% buildings, 3% deciduous trees/shrubs and 44% grass.

Comparison of these observations with the Lemonsu et al. (2010) (hereafter Le10) aging functions used for the suburban site in Montreal, shows that modifications to the coefficients are needed for both snow albedo and density (Fig. 4). The Le10 maximum density of 350 kg m⁻³ is too small for the current observations. Thus, the maximum snow density is set to 400 kg m⁻³; the minimum value ρ_s^{min} is kept at 100 kg m⁻³. In addition, the time constant τ_r is decreased to 0.043. After these modifications, the simulated snow density follows the behaviour of the median observations well (Fig. 4a). Similarly from the observations, the minimum (α_s^{min}) and maximum (α_s^{max}) snow albedo are set to 0.18 and 0.85 respectively, which differ from Le10 (α_n^{min} = 0.15 - 0.30 across the different surface cover types). Le10's

snow albedo aging time constants ($\tau_f = 0.174$, $\tau_a = 0.008$) could not be fully evaluated due to lack of data. However, τ_a compared to our observations is too small. When increased to 0.018, τ_f decreases to 0.11. Again good correspondence between the observed snow albedo and model output are seen (Fig. 4b), and between the observed and modelled $K\uparrow$ in Helsinki in 2012 (not shown). During the cold snow period, the linear fit statistics are $S = 0.68 \pm 0.02 \text{ W}^{-1} \text{ m}^2$, $I = 0.27 \pm 0.47 \text{ W m}^{-2}$ (RMSE = 11.3 W m^{-2} , $N = 2232$), and during the warm snow period $S = 0.50 \pm 0.01 \text{ W}^{-1} \text{ m}^2$ and $I = 0.85 \pm 0.47 \text{ W m}^{-2}$ (RMSE = 11.4 W m^{-2} , $N = 604$). One likely reason for the poorer model performance during the warm snow period is the sensitivity of the albedo to the fraction of snow covered surface. In the model, the fraction of snow is parameterized based on the maximum S_{WE} , but it is likely that this is site dependent at a neighbourhood scale due to redistribution and transport of snow. However, as the other net all-wave radiation components are larger in magnitude than $K\uparrow$, the negative bias during the melting period is likely to have small impact on the available energy.

Melt and freezing factors

The freeze and melt factors (a_r and a_t), representative for the neighbourhood scale, are optimized using runoff from Pa and snow depth from Ku (Helsinki). SUEWS was run using a_r values between 0.0008 and $0.002 \text{ mm W}^{-1} \text{ h}^{-1}$ using $0.0001 \text{ mm W}^{-1} \text{ h}^{-1}$ resolution, and a_t between 0.05 and $0.15 \text{ mm } ^\circ\text{C}^{-1} \text{ h}^{-1}$ with $0.01 \text{ mm } ^\circ\text{C}^{-1} \text{ h}^{-1}$ resolution. The 146 modelled combinations were analysed with respect to the amount of accumulated melt water during the snow covered period and the timing for complete snow melt (Table 3). The smallest differences compared to the observations are obtained with $a_r = 0.0016 \text{ mm W}^{-1} \text{ h}^{-1}$ and $a_t = 0.12 \text{ mm } ^\circ\text{C}^{-1} \text{ h}^{-1}$. Thus, these are used in the model runs. Values are slightly larger, but of the same order of magnitude, to those obtained for hourly factors at an Arctic watershed in Alaska ($a_r = 0.001 \text{ mm W}^{-1} \text{ h}^{-1}$ and $a_t = 0.095 \text{ mm } ^\circ\text{C}^{-1} \text{ h}^{-1}$; Kane et al., 1997). Unfortunately, no hourly values for urban areas were found in the literature. However, using these factors, the daily melt rates are the same order of magnitude to those that have been typically reported for urban areas (Bengtsson and Semádeni-Davies, 2011).

Snow storage heat

To determine the storage heat flux coefficients a_1 , a_2 and a_3 for snow (Eq. 5) shallow water values were used as an initial basis with $a_1 = 0.50$, $a_2 = 0.21$ and $a_3 = -39.1$ (Souch et al., 1998). Given the assumption that the snow heat capacity is around half that of water (Rogers and Yau, 1996), a_1 is set to 0.25 for snow. The other two coefficients (a_2 and a_3) are assessed

relative to their effect on the sensible heat flux by running SUEWS for Pr over a range of values during the snow covered period. The homogenous area of Pr was used to optimize $\Delta Q_{s,l}$. The RMSE between the observed and modelled Q_H varies between 44.4 – 49.0 W m⁻² and MBE between -23.1 – 28.0 W m⁻², when a_2 varies between 0 and 1.2 and a_3 between -60 and 0 (Table 3). The optimal result with minimum RMSE = 48.2 W m⁻² and MBE = 0.19 W m⁻² is obtained with $a_2 = 0.60$ and $a_3 = -30$. Thus, these coefficients are used in the model to calculate the snow storage heat or the internal energy of the snow. The values imply a smaller slope or fraction of radiative energy entering/leaving (a_1), a greater hysteresis (a_2) and a similar phase or time lag (a_3) for snow relative to water. Heuristically this appears appropriate.

3.2 Model evaluation

Table 4 lists the parameters, both for the snow covered and snow-free surface, used in the model runs. The snow parameters are optimized (Section 3.1), whereas the limit values for the snow transport ($S_{WE,Lim}$) were estimated based on maximum mass allowances of water at the Pa catchment. The same values were used at all sites as no additional information was available. Sensitivity analyses (Section 3.4) suggest the model is fairly insensitive to $S_{WE,Lim}$ despite the expectation for values to be neighbourhood specific.

3.2.1. Surface runoff

Figure 5 shows the daily observed and modelled runoff from the two catchments in Helsinki. The grey line separates the non-snow and snow related runoff as the continuous winter snow cover formed on 18 November 2010. At both sites, the model simulates the snow melt induced runoff well, reproducing both the spring melt peak and the recession in April. When the model is run treating the catchments as a whole, it tends to overestimate the runoff peaks and to be flashier than observations (Fig. 5), which have smaller but longer runoff peaks. Partly this can be explained by the absence of time lags for the water to move from the most distant points (hydrologically and hydraulically) because the catchment is modelled as one unit (in the current setup). However, in terms of hourly performance, the correlation between the observed (R_{obs}) and modelled (R_{mod}) runoff is good with $S = 1.20$ (mm h⁻¹)⁻¹ and $I = -0.01$ mm h⁻¹ (RMSE = 0.14 mm h⁻¹, $r = 0.75$) in Pa, and $S = 1.24$ (mm h⁻¹)⁻¹ and $I = 0.02$ mm h⁻¹ (RMSE = 0.16 mm h⁻¹, $r = 0.60$) in Pi. The coefficients are calculated for periods when both R_{mod} and R_{obs} are non-zero (675 and 760 hours in Pa and Pi, respectively). In Pa, the model

underestimates the cumulative runoff over the snow covered periods by 3 % as $R_{mod} = 82$ mm and $R_{obs} = 85$ mm (Fig. 6). In Pi, the cumulative runoff is overestimated by 19% as $R_{mod} = 97$ mm and $R_{obs} = 81$ mm.

Before the continuous snow cover, the model performs similarly at both catchments. Notably, the model overestimates runoff at Pi with high intensity precipitation. The overestimation is seen in the linear correlation between R_{obs} and R_{mod} as $S = 1.29$ (mm h⁻¹)⁻¹ and $I = 0.04$ mm h⁻¹ (RMSE = 0.20 mm h⁻¹, $r = 0.68$, $N = 668$) as well as in the modelled cumulative runoff, which is 47% higher than the observed in Pi (27 and 42 mm, respectively) (not shown). In Pa, $S = 1.26$ (mm h⁻¹)⁻¹ (RMSE = 0.20 mm h⁻¹, $r = 0.90$, $N = 743$), and the cumulative runoff is 4% underestimated by the model ($R_{obs} = 84$ mm and $R_{mod} = 88$ mm). Some of these differences are caused by the forcing precipitation and other meteorological variables being from the flux site Ku. This would particularly affect the model performance during convective precipitation, which accounts for 88% of the precipitation events between April and September (Punkka and Bister, 2005).

3.2.2. Snow depth

The model calculates snow water equivalent (S_{WE}) and snow depth (s_d) separately for each surface type. Due to snow removal and the different surface characteristics, s_d behaves differently for the vegetated and built surfaces. This can be seen when the modelled s_d for each surface (paved, building, grass and tree) is plotted with the observations for Helsinki (Fig. 7) and Montreal (Fig. 8). Unfortunately, the observations are each representative of individual point and surface types, whereas the model values are for the different surface types at the neighbourhood scale. Thus, some differences between the modelled and observed s_d are expected.

In Helsinki, the point observations are made in an open space that corresponds most appropriately to the modelled grass surface. Data for 2011 and 2012 are plotted separately as the first year is used in the model parameter determination whereas the latter is an independent dataset (Fig. 7). In both years, the model reproduces the accumulation of snow and melt events well, but underestimates the snow depth by 84 mm on average compared to the observations. The measured maximum snow depth in 2011 is 720 mm, whereas the modelled snow depth above grass is 587 mm. Similarly, for 2012 the observed depth is 630 mm and the modelled value is 504 mm. This underestimation is caused by either the

underestimation of modelled S_{WE} or by overestimation of snow density as the snow depth is a function of these two variables (Eq. 14). The model starts to accumulate snow four days later than the observations in January 2012, but later in the year the observed and modelled snow cover appear on the same date (29th November). In 2011, the snow melt is observed to have ended on 15th April, five days earlier than simulated, whereas in 2012 the snow melt finished on 12th April, one day later than modelled.

For Montreal, s_d is calculated separately for the suburban (Pr) and urban (Rl) sites for January 2008 – April 2009. In Pr, the observations are made on lawn corresponding to the modelled grass surface (Fig. 8a). The model follows the accumulation and melt events well, but like Helsinki, snow depths are underestimated especially in the 2007 – 2008 winter. The maximum observed s_d is 1020 mm, while 670 mm was modelled for grass. In winter 2008 – 2009, the maximum observed and simulated snow depths are 665 and 460 mm. In 2008, the modelled snow starts to accumulate on the same day (8th December) as observed. Snow melt is completed on 20th April 2008, which is three days after the modelled date. In 2009 the modelled snow melt finishes one day before observed (30th March).

In Rl, s_d is observed on a building roof. This has both lower snow amounts and earlier melt compared to the lawn observations in Montreal (Fig. 8b). The model simulates this behaviour well, but again under predicts the depths. The observed s_d maxima are 390 and 415 mm for the two winters, while 301 and 285 mm are modelled, respectively. Accumulation of snow takes place on the correct day in Rl, and the snow melts on the same day as observed (26 March) in 2008, and nine days later (7 March) in 2009 than observed.

The underestimation of s_d is also impacted by the precipitation measurements, as the difference between observed and modelled values begins during the snow accumulation period. Precipitation measurements are known to underestimate snowfall especially due to wind effects (Goodison et al., 1998; Savina et al., 2012).

3.2.3. Turbulent and radiative energy fluxes

The simulated Q^* , Q_H and Q_E are assessed for snow-free, cold snow and warm snow periods (Table 5, Fig. 9), with the diurnal behaviour of both the observed and modelled fluxes for the independent datasets in Helsinki and Montreal considered (Figs. 10 and 11).

Generally, the best simulated flux of the three is Q^* independent of whether there is snow on the ground or not. For the cold and warm snow periods, the RMSE varies between 27 – 41 W

m^{-2} (nRMSE = 0.037 – 0.061) and 31 – 41 W m^{-2} (nRMSE = 0.041 – 0.057) across the sites. At all sites, Q^* is underestimated in cold snow conditions with MBE between -34 and -13.5 W m^{-2} . Mostly this underestimation is related to the downward long-wave radiation that is calculated from air temperature and relative humidity (Loridan et al., 2011 - who suggest that use of cloud cover data as input with this technique is better). This parameterization works less well in cold conditions than above 0 °C. In Montreal, the warm snow underestimation is even larger (MBE = -37 to -25 W m^{-2}), compared to Helsinki where the underestimation decreases to -5 – -3 W m^{-2} . Especially during the warm snow periods, the fraction of snow cover plays an important part in the model performance. It affects both the snow albedo and outgoing long-wave radiation via surface temperature. The best performance for Q^* is under snow-free conditions, when the MBE is between -10 and 8 W m^{-2} and the nRMSE is clearly lower than for the periods with snow cover (Fig. 9a).

The scatter in the model performance is larger for Q_E than for the other energy balance components, with cold snow periods having the best and warm snow periods the poorest model performance (Fig. 9c). The RMSE during cold snow varies between 9 – 12 W m^{-2} (nRMSE = 0.038 - 0.059), and for warm snow between 22 - 34 W m^{-2} (nRMSE = 0.071 – 0.170). The increase in RMSE during warm snow periods is understandable as the energy consumed in melting snow and freezing melt water is higher and thus errors in the degree-day-method propagate more easily to Q_E (as well as to Q_H). During melting periods there can be advection from snow-free surfaces to the snowpack altering the energy balance as specified in Eq. (1) (Bengtsson and Semádeni-Davies, 2011). MBE varies between -11 – 4 W m^{-2} when there is snow on ground. During snow-free periods, the model underestimates Q_E at all sites with MBEs between -27 – -11 W m^{-2} , RMSEs between 26 – 35 W m^{-2} , and nRMSE between 0.058 – 0.066.

In SUEWS, Q_H is calculated as a residual from other energy fluxes; therefore the net error accumulates in Q_H . Despite this, the model is able to simulate its behaviour well. When there is snow on ground, the RMSE varies between 23 – 50 W m^{-2} and nRMSE between 0.067 and 0.118. During the cold snow periods, the simulated heat fluxes are slightly better than during warm snow periods, similar to Q_E . The model overestimates Q_H during snow cover, except in RI during cold snow periods, and MBEs vary between -25 – 9 W m^{-2} . In summer, the performance of the model in simulating Q_H improves following the performance of Q^* and Q_E .

The model performance for the energy fluxes is more dependent on the period of analysis than the site where it is run. An exception to this is Q_H at R1, where the model overestimates and shifts the diurnal peak flux earlier compared to the observations (Fig. 11). This appears whether there is snow on ground or not, suggesting that this is caused by the snow-free storage heat flux which is underestimated or anthropogenic heat flux that is overestimated by the model. RMSEs obtained for the warm snow periods in Pr are higher than Le10 obtained for the same suburban area in Montreal using the Town Energy Balance model in spring 2005. However, direct comparisons are difficult as in their one month of observations snow cover is present only on some days compared to the longer time period evaluated here.

3.3 Energy balance of urban snow covered surface

Snow cover and the related energy storage and the energy related to phase change alter the surface energy balance. The components at the most built-up site R1 are evaluated here (Fig. 12). During cold snow periods, the daytime energy balance is dominated by the net all-wave radiation (Q^*) and the sensible heat flux (Q_H), reaching 119 W m^{-2} and 113 W m^{-2} . Q_H is fuelled by both Q^* and Q_F (reaching 46 W m^{-2}), and it accounts on average for 68% of the daytime (10:00 – 15:00) available energy. The dominance of Q^* and Q_H are typical also for natural cold snow packs (e.g. Oke, 1987). Only 12% of $Q^* + Q_F$ is dissipated by evaporation, whereas the storage fractions are 10 and 8% at the snow and snow-free surfaces, respectively. At night, on the other hand, the urban surface loses long-wave radiation causing the internal energy of the snow to decrease i.e. the cold content of the snow increases. At the same time, the snow-free surface loses some energy (around 10 W m^{-2}) and both Q_F and Q_E remain positive (by more than 10 W m^{-2}), with Q_H less than 5 W m^{-2} .

During warm snow periods, Q^* is clearly the most important component of the surface energy balance reaching 200 W m^{-2} in daytime. Now the daytime Q_F is slightly smaller than during the cold periods reaching 35 W m^{-2} . Most of the energy, but clearly less than during the cold snow period, is partitioned to Q_H (46%), with the second largest contribution going to snow-free surface heat storage (29%). Evaporation consumes 17% of the energy, and only 4% and 3% is stored in the snow and consumed by snow melt. The largest Q_H and ΔQ_S are consistent with the observations obtained by Le10 at the suburban site, although they documented a larger contribution going to snow related processes than to evaporation. Moreover, the modelled fractions during the snow covered periods are of the same order of magnitude as obtained for observations at the same site (Bergeron and Strachan, 2012).

When the ground is free of snow, most energy ($Q^* + Q_F$) again goes to Q_H (188 W m⁻², 45%) followed by the storage heat flux (175 W m⁻², 42%). Due to the high impervious nature of the surface, daytime Q_E reaches 50 W m⁻², which is only 12% of the available energy. The resulting daytime Bowen ratio (Q_H/Q_E) is 3.7, which corresponds well with the expected relationship of the Bowen ratio with the site's vegetation fraction (Loridan and Grimmond, 2012).

3.4 Model sensitivity

To better understand the impact of both the optimized values and those estimated (Table 4) without detailed observation on the model performance, sensitivity analyses were undertaken. The analysis included the power of the vegetation depletion curve (eq. 15a), limit for the transport of snow from paved and roof surfaces ($S_{WE,Lim}$), snow heat storage (a_2 , a_3) and the melt water coefficients (a_r , a_t). SUEWS was run using the three independent datasets (Ku in 2012, RI and Pi) changing the parameters by $\pm 30\%$ using a 10% step. The results were compared to hourly measured Q_H , Q_E and runoff and the RMSE determined for each site and variable (Figure 13). The other parameters were held constant during each set of analyses. The impact of the coefficients on heat storage in snow pack is shown only for Q_H as their effect on Q_E and runoff is small or non-existent. $S_{WE,Lim}$ and the melt water coefficients have the largest impact on the heat fluxes at both sites, whereas the smallest effect is for the power used in the depletion curve. For runoff, the melt water coefficients have the largest effect. The differences in model performances are relatively small in the context of the urban land-surface model comparison (Grimmond et al. 2011) indicating that the model is fairly insensitive to changes in the studied parameters.

3 Conclusions

The Surface Urban Energy and Water balance Scheme (SUEWS) is developed to simulate the energy and water balances in cold climate cities with special attention on the simulation of snow cover. The new model considers the accumulation of snow, snow properties including snow water equivalent, snow depth, snow density and albedo, and snow melt and refreezing of melt water based on an hourly degree-day method. The development and independent evaluation is undertaken using observations from three sites in Helsinki and two sites in Montreal. Each of these sites varies in terms of surface cover characteristics. In Helsinki, the

1 observations include stormwater runoff from two catchments and turbulent fluxes of sensible
2 and latent heat from one site. In Montreal, the observations include snow properties as well as
3 the turbulent fluxes at both sites.

4 The model developments include an improved description of vegetation phenology (LAI) in
5 cold climate cities. The leaf-off period based on daily air temperature was accelerated, using
6 a combination of daily air temperatures and day length. Updated aging functions for snow
7 density and albedo in urban areas were developed based on snow observations in Montreal and
8 improved equation for the degree day method was used to calculate snow melt and freezing
9 of the melted water, and new parameter values developed to calculate the snow storage heat
10 flux using the objective hysteresis model (OHM).

11 The enhanced model can correctly simulate the winter and springtime melt-related runoff, but
12 the runoff peaks tend to be sharper than the observations partly due to the absence of time lag
13 to let the water flow to the observation point at the catchment discharge point. Despite this,
14 the modelled cumulative runoff during the snow covered periods corresponds well with the
15 observations. The formation and melting of the snowpack is simulated well both in Helsinki
16 and Montreal, but the snow depth is underestimated either due to overestimation of the snow
17 density or underestimation of snow water equivalent. Following the hydrological variables,
18 the net radiation and turbulent sensible and latent heat fluxes also are modelled well. The
19 model simulates their diurnal behaviour throughout the year, but the largest uncertainties
20 occur during the snow melt period at all sites. This is related to the uncertainties in
21 determining the snow covered surface fractions, as well as the propagating uncertainties from
22 the calculation of melt and freezing related energies based on the degree-day method.

23 The model can correctly simulate the energy and water cycles in cold climate cities and it can
24 potentially be used independently in urban planning purposes or nested to a meso- or global
25 scale atmospheric model. However, some of the parameterizations are still city and site
26 dependent; more observations from cold climate cities are needed to create more generalized
27 formulations.

29 **Acknowledgements**

30 This work was supported by the Academy of Finland (Project numbers 138328 and ICOS-
31 Finland, 263149), and the EU-funded-project BRIDGE. The Montreal data were obtained as
32 part of the Environmental Prediction in Canadian Cities Research network and funded

through a grant from the Natural Sciences and Engineering Research Council of Canada. We thank: Erkki Siivola and Petri Keronen for the instrument maintenance of the eddy covariance setups in Helsinki; Eric Christensen for the collection of snow data in Montreal; and Onil Bergeron for the eddy covariance data quality in Montreal. A compiled version model with manual and example input and output files can be obtained from <http://LondonClimate.info>. If you are interested in the code itself please contact Sue Grimmond (C.S.Grimmond@reading.ac.uk)

References

- Anderson, E. A.: A point energy and mass balance model of a snow cover, NOAA Technical Report NWS 19, 61-62, 1976.
- Auer, A. H.: The rain versus snow threshold temperatures, *Weatherwise* 27, 67, 1974.
- Baker, D. G., Ruschy, D. L., and Wall, D. B.: The albedo decay of prairie snows, *J. Appl. Meteor.* 29, 179-187, 1990.
- Bengtsson, L.: The importance of refreezing on the diurnal snowmelt cycle with application to a Northern Swedish catchment, *Nord. Hydrol.* 13, 1-12, 1982.
- Bengtsson, L.: Modeling snowmelt induced runoff with short time resolution. Proceedings of 3rd International Conference of Urban Storm Drainage, Gothenburg, Sweden, 305-314, 1984.
- Bengtsson, L. and Westerström, G.: Urban snowmelt and runoff in northern Sweden, *Hydrological Sciences* 37, 263-275, 1992.
- Bengtsson, L. and Semádeni-Davies, A. F.: Urban snow in *Encyclopedia of Snow, Ice and Glaciers*, Eds. Singh, V. P., Singh, P., and Haritashya, U. K., Springer Science, 1211-1217, 2011.
- Bergeron, O. and Strachan, I. B.: Wintertime radiation and energy budget along an urbanization gradient in Montreal, Canada, *Int. J. Clim.* 32, 137-152, 2012.
- Best, M. J. and Grimmond, C. S. B.: Analysis of the seasonal cycle within the first international urban land-surface model comparison, *Boundary-Layer Meteorol.* 146, 421-446, 2013.
- Cline, D. W.: Snow surface energy exchanges and snowmelt at a continental, midlatitude Alpine site, *Water Resour. Res.* 33, 689-701, 1997.

1 Daley, R.: Atmospheric Data Analysis, Cambridge University Press, Cambridge UK, 1991.

2 Debele, B., Srinivasan, R., and Gosain, A. K.: Comparison of process-based and temperature-
3 index snowmelt modeling in SWAT, *Water Resour. Manag.* 24, 1065-1088, 2010.

4 Easton, Z. M., Gérard-Marchant, P., Walter, M. T., Petrovic, A. M., and Steenhuis, T. S.:
5 Hydrologic assessment of an urban variable source watershed in the northeast United States,
6 *Water Resour. Res.* 43, W03413, doi: 10.1029/2006WR005076, 2007.

7 Ek, M. B., Mitchell, K. E., Lin, Y., Rogers, E., Grunmann, P., Koren, V., Gayno, G., and
8 Tarpley, J. D.: Implementation of Noah land surface model advances in the National Centers
9 for Environmental Prediction operational mesoscale Eta model, *J. Geophys. Res.* 108 (22),
10 8851, doi: 10.1029/2002JD003296, 2003.

11 Grimmond, C. S. B., Cleugh, H. A., and Oke, T. R.: An objective urban heat storage model
12 and its comparison with other schemes, *Atmos. Env.* 25B (3), 311-174, 1991.

13 Grimmond, C. S. B., Blackett, M., Best, M. J., Baik, J.-J., Belcher, S. E., Beringer, J.,
14 Bohnenstengel, S. I., Calmet, I., Chen, F., Coutts, A., Dandou, A., Fortuniak, K., Gouvea, M.
15 L., Hamdi, R., Hendry, M., Kanda, M., Kawai, T., Kawamoto, Y., Kondo, H., Krayenhoff, E.
16 S., Lee, S.-H., Loridan, T., Martilli, A., Masson, V., Miao, S., Oleson, K., Ooka, R., Pigeon,
17 R., Porson, A., Ryu, Y.-H., Salamanca, F., Steeneveld, G. J., Tombrou, M., Voogt, J. A.,
18 Young, D. T., and Zhang, N.: Initial results from Phase 2 of the international urban energy
19 balance model comparison, *Int. J. Climatol.*, DOI: 10.1002/joc.2227, 2011.

20 Goodison, B. E., Louie, P. Y. T., and Yang, D.: The WMO solid precipitation measurement
21 intercomparison, World Meteorological Organization, Instruments and observing methods
22 67, 1998.

23 Jacobson, C. R.: Identification and quantification of the hydrological impacts of
24 imperviousness in urban catchments: A review, *J. Environ. Manage.* 92 (6), 1438-1448, 2011.

25 Jin, J., Gao, X., Sorooshian, S., Yang, Z.-L., Bales, R., Dickinson, R. E., Sun, S.-F., and Wu,
26 G.-X.: One-dimensional snow water and energy balance model for vegetated surfaces.
27 *Hydrol. Process.* 13, 2467-2482, 1999.

28 Järvi, L., Hannuniemi, H., Hussein, T., Junninen, H., Aalto, P. P., Hillamo, R., Mäkelä, T.,
29 Keronen, P., Siivola, E., Vesala, T., and Kulmala, M.: The urban measurement station
30 SMEAR III: Continuous monitoring of air pollution and surface-atmosphere interactions in
31 Helsinki, Finland, *Boreal Env. Res.* 14 (Suppl. A), 86-109, 2009a.

1 Järvi, L., Mammarella, I., Eugster, W., Ibrom, A., Siivola, E., Dellwik, E., Keronen, P.,
2 Burba, G., and Vesala, T.: Comparison of net CO₂ fluxes measured with open- and closed-
3 path infrared gas analyzers in urban complex environment, *Boreal Env. Res.* 14, 499-514,
4 2009b.

5 Järvi, L., Grimmond, C. S. B., and Christen, A.: The surface urban energy and water balance
6 scheme (SUEWS): Evaluation in Los Angeles and Vancouver, *J. Hydrol.* 411, 219-237, 2011.

7 Järvi, L., Nordbo, A., Junninen, H., Riikonen, A., Moilanen, J., Nikinmaa, E., and Vesala, T.:
8 Seasonal and annual variation of carbon dioxide surface fluxes in Helsinki, Finland, in 2006-
9 2010, *Atmos. Chem. Phys.* 12, 8475-8489, 2012.

10 Kane, D. L., Gieck, R. E., and Hinzman, L. D.: Snowmelt modeling at small Alaskan Arctic
11 watershed, *J. Hydrol. Eng.* 2, 204-210, 1997.

12 Keskitalo, J., Bergquist, G., Gardeström, P., and Jansson, S.: A cellular timetable of autumn
13 senescence, *Plant Physiology* 139, 1635-1648, 1995.

14 Koivusalo, H. and Kokkonen, T.: Snow processes in a forest clearing and in a coniferous
15 forest, *J. Hydrol.* 262, 145-164, 2002.

16 Kustas, W. P., Rango, A., and Uijlenhoet, R.: Simple energy budget algorithm for the
17 snowmelt runoff model, *Water Resour. Res.* 30 (5), 1515-1527, 1994.

18 Lemonsu, A., Bélair, S., Mailhot, J., Benjamin, M., Chagnon, F., Morneau, G., Harvey, B.,
19 Voogt, J., and Jean, M.: Overview and first results of the Montreal Urban Snow Experiment
20 2005, *J. Appl. Meteorol. Clim.* 47, 59-75, 2008.

21 Lemonsu, A., Bélair, S., Mailhot, J., and Leroyer, S.: Evaluation of the Town Energy Balance
22 model in cold and snowy conditions during the Montreal Urban Snow Experiment 2005, *J.*
23 *Appl. Meteorol. Clim.* 49, 346-362, 2010.

24 Leroyer, S., Mailhot, J., Bélair, S., Lemonsu, A., and Strachan, I. B.: Modeling the surface
25 energy budget during the thawing period of the 2006 Montreal Urban Snow Experiment, *J.*
26 *Appl. Meteorol. Clim.* 49, 68-84, 2010.

27 Loridan, T., Grimmond, C. S. B., Offerle, B. D., Young, D. T., Smith, T., Järvi, L., and
28 Lindberg, F.: Local-scale Urban Meteorological Parameterization Scheme (LUMPS):
29 Longwave radiation parameterization and seasonality related developments, *J. Appl.*
30 *Meteorol. Clim.*, DOI: 10.1175/2010JAMC2474.1, 2011.

1 Loridan, T. and Grimmond, C. S. B.: Characterization of energy flux partitioning in urban
2 environments: Links with surface seasonal properties, *J. Appl. Meteorol. Clim.* 51, 219-241,
3 2012.

4 Lowe, P. R.: An approximation polynomial for the computation of saturation vapor pressure,
5 *J. Appl. Meteorol.* 16, 100-103, 1977.

6 Martine, G. and Marshall, A.: State of world population 2007: Unleashing the potential of
7 urban growth, U.N. Popul. Fund, New York, 2007.

8 Martinec, J.: Hour-to-hour snowmelt rates and lysimeter outflow during an entire ablation
9 period, *Snow cover and Glacier Variations, Proceedings of the Baltimore Symposium*,
10 Maryland, IAHS Publ. 183, 1989.

11 Mitchell, V. G., McMahon, T. A., and Mein, R. G.: Components of the total water balance of
12 an urban catchment, *Environ. Manage.* 32 (6), 735-746, 2003.

13 Mitchell, V. G., Cleugh, H. A., Grimmond, C. S. B., and Xu, J.: Linking urban water balance
14 and energy balance models to analyze urban design options, *Hydrol. Process* 22, 2891-2900,
15 2008.

16 Nordbo, A., Järvi, L., and Vesala, T.: Revised eddy covariance flux calculation
17 methodologies – effect on urban energy balance, *Tellus B* 48, 18184, 2012a.

18 Nordbo, A., Järvi, L., Haapanala, S., Moilanen, J., and Vesala, T.: Intra-City Variation in
19 Urban Morphology and Turbulence Structure in Helsinki, Finland, *Boundary-Layer*
20 *Meteorol.*, doi 10.1007/s10546-012-9773-y, 2012b.

21 Offerle, B., Grimmond, C. S. B., and Oke, T. R.: Parameterization of net all-wave radiation
22 for urban areas. *J. Appl. Meteor.* 42, 1157-1173, 2003.

23 Oke, T.: *Boundary Layer Climates*, Routledge, London, UK, 1987.

24 Punkka, A. J. and Bister, M.: Occurrence of summertime convective precipitation and
25 mesoscale convective systems in Finland during 2000-01, *Mon. Weather Rev.* 133, 362-373,
26 2005.

27 Rogers, R. R. and Yau, M. K.: *A short course in cloud physics*. Elsevier Science, Oxford,
28 UK, 1996.

1 Savina, M., Schäppi, B., Molnar, P., Burlando, P. and Sevruck B.: Comparison of a tipping-
2 bucket and electronic weighting precipitation gage for snowfall, *Atmos. Res.* 103, 45-51,
3 2012.

4 Semádeni-Davies, A. F. and Bengtsson, L.: Snowmelt sensitivity to radiation in the urban
5 environment, *Hydrol. Sci. J.* 43, 67-89, 1998.

6 Semádeni-Davies, A. F.: Snow heterogeneity in Luleå, Sweden, *Urban Water* 1, 39-47, 1999.

7 Semádeni-Davies, A. F. and Bengtsson, L.: The water balance of sub-arctic town, *Hydrol.*
8 *Process.* 13, 1871-1885, 1999.

9 Semádeni-Davies, A., Lundberg, A., and Bengtsson, L.: Radiation balance of urban snow: a
10 water management perspective, *Cold Reg. Sci. Technol.* 33, 59-76, 2001.

11 Souch, C., Grimmond, C. S. B., and Wolfe, C. P.: Evaporation rates from wetlands with
12 different disturbance histories: Indiana dunes national lakeshore, *Wetlands* 18, 216-229,
13 1998.

14 Sun, S., Jin, J., and Xue, Y.: A simple snow-atmosphere-soil transfer model, *J. Geophys. Res.*
15 104 (D16), 19587-19597, 1999.

16 Swenson, S. C. and Lawrence, D. M.: A new fractional snow-covered area parameterization
17 for the Community Land Model and its effect on the surface energy balance, *J. Geophys. Res.*
18 117, D21107, 2012.

19 Taylor K.E.: Summarizing multiple aspects of model performance in a single diagram, *J.*
20 *Geophys. Res.* 106, 7183-7192, 2001.

21 Tobin, C., Schaefli, B., Nicótina, L., Simoni, S., Barrenetxea, G., Smith, R., Parlange, M.,
22 and Rinaldo, A.: Improving the degree-day method for sub-daily melt simulations with
23 physically-based diurnal variations, *Adv. Water Resour.* 55, 149-164, 2013.

24 Valeo, C. and Ho, C. L. I.: Modelling urban snowmelt runoff, *J. Hydrol.* 299, 237-251, 2004.

25 Valtanen, M., Sillanpää, N., and Setälä, H.: Effects of land use intensity on stormwater runoff
26 and its temporal occurrence in cold climates, *Hydrol. Process.*, doi: 10.1002/hyp.9819, 2013.

27 Vargo, J., Habeeb, D., and Stone, Jr., B.: The importance of land cover change across urban-
28 rural typologies for climate modelling, *J. Environ. Manage.* 114, 243-252, 2013

29 Versegny, D. L.: CLASS – A Canadian land surface scheme for GCMS. 1, *Soil Model, Int. J.*
30 *Clim.* 11, 111-133, 1991.

- 1 Vesala, T., Järvi, L., Launiainen, S., Sogachev, A., Rannik, Ü., Mammarella, I., Siivola, E.,
2 Keronen, P., Rinne, J., Riikonen, A., and Nikinmaa, E.: Surface-atmosphere interactions over
3 complex urban terrain in Helsinki, Finland, *Tellus* 60B, 188-199, 2008.
- 4 Voogt, J. A. and Grimmond, C. S. B.: Modeling surface sensible heat flux using surface
5 radiative temperatures in a simple urban area, *J. Appl. Meteorol.* 39, 1679-1699, 2000.

6
7
8
9
10

Table 1. Site characteristics of the observational sites. Surface cover fractions for the EC sites are calculated for 1 km radius circles, whereas the fractions of the catchments are for the actual catchment areas. In Kumpula, the area is divided into three surface cover areas (Ku1, Ku2 and Ku3). For the abbreviations see Appendix C.

	<i>Helsinki</i>			<i>Montreal</i>	
	Kumpula			Urban	Suburban
Lat	60.203°N			45.457°N	45.501°N
Lon	24.961°E			73.592°W	73.811°W
Obs.	Q^* , Q_H , Q_E			Q^* , Q_H , Q_E , met.	Q^* , Q_H , Q_E , met.
z (m)	31			25	25
Site name	Ku1	Ku2	Ku3	Pa	Pi
λ_{pav}	0.42	0.39	0.30	0.42	0.22
λ_{bldg}	0.20	0.15	0.11	0.20	0.12
λ_{veg}	0.38	0.46	0.59	0.38	0.66
λ_{everg}	0.01	0	0.01	0	0.10
λ_{dec}	0.21	0.20	0.30	0.24	0.30
λ_{igrass}	0.15	0.20	0.21	0.10	0.02
λ_{grass}	0.01	0.06	0.10	0.02	0.1
λ_{unman}	0	0	0	0.02	0.14
λ_{water}	0	0.01	0.00	0	0
z_h (m)	10.4	11.5	12.6	15.2	10.8
z_t (m)	10	8.8	8.5	8	8
p (# ha ⁻¹)	31	37	44	42	55
A (ha)	44.7	78.2	78.2	23.8	44.8
Reference	Järvi et al. (2009a)			-	-
				Bergeron and Strachan (2012)	

1 Table 2. Time period and the spin-up time of the model simulations. Data availability refers to
2 the number of 60 min periods when observations are available for the non-spin-up period. EC
3 is the eddy covariance fluxes (Q_H and Q_E), R is the runoff and s_d the snow depth. A sub-set of
4 these data are used in parameter optimization and another for evaluation.

Measurement period		Spin-up period	Data availability during non-spin-up (%)
Ku	EC	2010-2012	44
	s_d		100
Pa	R	Sep 2010 – Apr 2011	93
Pi	R		86
Pr	EC	Dec 2007 – Sep 2009	53
	s_d		80
Rl	EC	Dec 2007	36
	s_d		85

Table 3. Results of the model optimization made for the snow storage heat and melt water calculations. Different evaluation criteria for the components were used.

	Range of tested values	Final value	Evaluation criteria	Range of the evaluation criteria	Site
a_r	0.0008-0.002	0.0016	Cumulative R/D_{sm}	-14 - -3/-7.6-16.1 (mm)	Pa, Ku
a_t	0.05-0.15	0.12	Cumulative R/D_{sm}	-14 - -3/-7.6-16.1 (mm)	Pa, Ku
a_2	0-1.2	0.5	RMSE/MBE of Q_H	44.4-49.0/-23.1-28.0 (W m ⁻²)	Pr
a_3	-60-0	-30	RMSE/MBE of Q_H	44.4-49.0/-23.1-28.0 (W m ⁻²)	Pr

Table 4. Parameters used in SUEWS for surfaces that are buildings (bldg), pavement (pav), evergreen vegetation (everg), deciduous vegetation (decid), grass and water. If the vegetation is irrigated, different values to describe the canopy are used. Sources of the values are as in Järvi et al. (2011) unless indicated otherwise below. Where different values are used for the different sites, this is indicated for Helsinki (Hel), and for the two sites in Montreal (Rl and Pr). Variable notation is given in Appendix C.

a)	Site	Units	Bldg	Pav	Everg.	Decid.	Irr. veg	Grass	Water
S_i		mm	0.25	0.48	1.3	0.3-0.8		1.9	0
$S_{soil,i}$	Hel/Rl	mm	50	100	150	150	150	150	-
	Pr	mm	150	150	150	150	150	150	-
$D_{0,i}$		mm	10	10	0.013	0.013	10	0.013	-
b		-	3	3	1.71	1.71	0.013	1.71	-
C_i		mm	0	0	0	0	0	0	0
$C_{soil,i}$	Hel/Rl	mm	50	100	150	150	150	150	-
	Pr	mm	150	150	150	150	150	150	-
α_i		-	0.15	0.09 ⁱ	0.10	0.16 ⁱⁱ	0.19	0.19 ⁱⁱ	0.08 ⁱⁱ
ε_i		-	0.95	0.91	0.98	0.98	0.93	0.93	0.95
$g_{i,max}$		mm s ⁻¹	-	-	7.4	11.7	40	33.1	-
Snow									
$S_{WE,0}$	Hel	mm	40	40	40	40	40	40	40
	Mon	mm	0	0	0	0	0	0	0
$f_{s,i,0}$	Hel	mm	1	1	1	1	1	1	1
	Mon	mm	0	0	0	0	0	0	0
$\rho_{s,0}$		kg m ⁻³	120	120	120	120	120	120	120
$S_{WE,i}^{max}$		mm	190	190	190	190	190	190	-
$S_{WE,Lim}$		mm	40	100					
b) Overall area parameter values									
α_s^{min}	0.18		$a_{0,\{wd,we\}}$	0.1 W m ⁻² (p ⁻¹ ha ⁻¹) ⁻¹ⁱ	G_4	3.36 g kg ⁻¹	res_{cap}	10 mm	
α_s^{max}	0.85		$a_{1,\{wd,we\}}$	9.9·10 ³ Wm ⁻² K ⁻¹ (p ⁻¹ ha ⁻¹) ⁻¹	G_5	11.07°C	res_{drain}	0.25 mm h ⁻¹	
ε_s	0.99		$a_{2,\{wd,we\}}$	0.0102 Wm ⁻² K ⁻¹ (p ⁻¹ ha ⁻¹) ⁻¹	G_6	0.018 mm	R_C	1.0 mm	
ρ_e	200 kg m ⁻³		$b_{0,a}$	-84.54 mm	GDD	300	S_1	0.45 mm	
ρ_s^{min}	100 kg m ⁻³		$b_{1,a}$	9.96 mm K ⁻¹	I_w	0 mm	S_2	15 mm	
ρ_s^{max}	400 kg m ⁻³		$b_{2,a}$	3.67 mm d ⁻¹	$K \downarrow_m$	1200 W m ⁻²	S_{Pipe}	100 mm	
τ_a	0.018		$b_{0,m}$	-25.36 mm	K_s	0.0005 mm s ⁻¹	SDD	-450	
τ_f	0.11		$b_{1,m}$	3.00 mm K ⁻¹	LAI _{max>everg}	5.1 m ² m ⁻²	$T_{BaseGDD}$	5°C	
a_1	0.25		$b_{2,m}$	1.10 mm d ⁻¹	LAI _{max>dec}	5.5 m ² m ⁻²	$T_{BaseSDD}$	10°C	
a_2	0.6		C_{min}^R	0.05 mm	LAI _{max>grass}	5.9 m ² m ⁻²	T_{BaseQF}	18.2°C	
a_3	-30		C_{max}^R	0.2 mm	LAI _{min>everg}	4.0 m ² m ⁻²	T_{lim}	2.2°C ⁱⁱⁱ	
a_f	1		G_1	16.48 mm s ⁻¹	LAI _{min>dec}	1.0 m ² m ⁻²	T_H	40°C	
a_r	0.0016 mm W ⁻¹ h ⁻¹		G_2	566.1 W m ⁻²	LAI _{min>grass}	1.6 m ² m ⁻²	T_L	10°C	
a_t	0.011 mm °C ⁻¹ h ⁻¹		G_3	0.216 kg g ⁻¹	$r_{s,max}$	9999 s m ⁻¹	T_{step}	300 s	

ⁱOptimized using data from Helsinki; ⁱⁱVargo et al. (2013); ⁱⁱⁱAuer (1974)

Table 5. Model evaluation statistics based on performance relative to observations of net all wave radiation (Q^* , $W m^{-2}$), sensible (Q_H , $W m^{-2}$) and latent heat fluxes (Q_E , $W m^{-2}$) undertaken for two years in Helsinki (Ku11 for 2011 and Ku12 for 2012) and two sites in Montreal (Pr and Rl). The statistics: RMSE is the root mean square error ($W m^{-2}$), nRMSE the normalized RMSE (eq. 17), sRMSE (eq. 18) is RMSE normalized with standard deviation of the observed value and N is the number of points in the linear fit.

		Cold snow					Melting snow					Snow-free				
		RMSE	nRMSE	sRMSE	N	MBE	RMSE	nRMSE	sRMSE	N	MBE	RMSE	nRMSE	sRMSE	N	MBE
Ku11	Q^*	34.3	0.0445	-1.3	1697	-13.7	38.1	0.0492	0.9	1020	-5.1	30.3	0.0303	0.43	5992	7.7
	Q_H	29	0.0719	1.3	756	-8.7	50.4	0.1009	0.95	435	-16.7	37.5	0.0628	0.76	3069	-1.1
	Q_E	12.3	0.0378	0.72	613	-2.1	23.7	0.0713	0.65	377	-10.8	25.8	0.0584	0.64	2627	-23.8
Ku12	Q^*	26.5	0.0371	-0.7	2238	-31	40.6	0.057	1.31	644	-3.1	29	0.0302	0.37	5584	7.3
	Q_H	23	0.0734	1.9	1056	-24.6	37.9	0.0822	0.74	284	-12.6	38.4	0.0555	0.74	3429	-8.2
	Q_E	9.7	0.0429	0.7	775	-5.5	21.9	0.0974	0.58	221	-10.5	26.5	0.0664	0.58	2868	-27
Pr	Q^*	38.3	0.055	-6.34	2980	-34.3	31.2	0.0411	0.42	1145	-37.1	24.6	0.0276	0.21	6952	-4.4
	Q_H	32.5	0.0826	1.41	2177	-8.4	45.7	0.1081	0.97	672	-16.8	32.2	0.0698	0.67	5598	-13.2
	Q_E	11.8	0.0398	0.74	2063	1.7	34.1	0.1704	0.82	649	3.6	34.8	0.0662	0.59	5463	-11.9
Rl	Q^*	40.9	0.0613	-57.64	2740	-13.5	31.6	0.0422	0.5	965	-25.4	26.7	0.0322	0.21	4521	-9.4
	Q_H	30.9	0.0673	0.64	1366	9.1	42.7	0.088	0.68	522	-16	47.7	0.0857	0.53	3762	-10
	Q_E	8.6	0.0587	0.55	1292	1.2	23.3	0.1189	0.76	499	3.4	28.5	0.0654	1.05	3661	-10.8




Figure 1. Aerial photograph of the measurement locations in Helsinki. Red dot is the SMEARIII-Kumpula site (Ku). The red dashed line is the 1 km radius circle that the surface cover fractions are calculated for, and the white squares show the approximate locations of the catchment areas (Pa left side and Pi top-right). © Kaupunkimittausosasto, Helsinki, 2011.




Figure 2. Time series of daily a) daytime (10:00 – 14:00) solar radiation ($K\downarrow$), b) air temperature (T_a), c) precipitation (P) measured in SMEAR III – Kumpula, and d) snow depth measured at Kumpula. Grey area shows the spin-up period.




Figure 3. As Fig.2 but for Montreal measured at the suburban site (Pr) with snow depth measured in a suburban back lawn (Pr) and on an urban roof (RI).




Figure 4. Observed and modelled a) snow density (ρ_s) and snow albedo (α_s) at the suburban site in Montreal (January 2008 – April 2009). Observed values are the medians from four locations and the error bars show the quartile deviations. Aging functions proposed in Lemonsu et al. (2010) ‘Le10’ and in the current study (‘New’).




Figure 5. Modelled and observed runoff at a) Pa and b) Pi (independent) sites. Grey line indicates when the snow starts to accumulate on ground; the snow melts by the end of April.




Figure 6. Modelled and observed cumulative runoff during the snow covered period (19 November 2010 – 31 April 2011) a) Pa and b) Pi (independent) catchments.




Figure 7. Simulated (by surface type) and observed snow depth in Helsinki in a) 2011 and b) 2012. Grey area shows the spin-up period.




Figure 8. As Fig 7 for Montreal in 2008 – 2009 a) suburban site with observations above (grass) lawn and b) urban site with (building) roof observations. Grey area shows the spin-up period.





Figure 9. Model performance for the three periods a) cold snow, b) warm snow and c) snow-free. Mean bias error (MBE) versus normalized root mean square error (nRMSE) for different sites and for Ku separately (years 2011 (Ku11) and 2012 (Ku12)).



2

3 Figure 10. Diurnal behaviour of the measured and modelled net all-wave radiation (Q^*) and
 4 turbulent energy fluxes (Q_H and Q_E) during a) cold snow, b) melting snow and c) snow-
 5 free periods in Helsinki in 2012. Only hours when observations are available were
 6 accounted. Dotted lines show the quartile deviations.

7

8

9

10

11

12

13




Figure 11. As Fig 10, for the urban site in Montreal (RI) in 2008 - 2009.




Figure 12. Energy balance at the urban site (RI) in Montreal during a) cold snow, b) warm snow and c) snow-free periods. Q^* = net all wave radiation, ΔQ_S = heat storage to snow-free surfaces, Q_F = anthropogenic heat flux, Q_H = sensible heat flux, Q_E = latent heat flux, Q_M = snow melt/freezing water related energy flux, and ΔQ_I = heat storage in snow pack.




Figure 13. Boxplot of RMSE's of the sensitivity analysis made for a) Q_H in Ku ($W m^{-2}$), b) Q_E in Ku ($W m^{-2}$), c) Q_H in Rl ($W m^{-2}$), d) Q_E in Rl ($W m^{-2}$) and e) runoff in Pi ($mm h^{-2}$). The sensitivity are to changes in: the power in the depletion curve (eq. 15a) (C1), $S_{WE, Lim}$ (C2), melt water coefficients (a_r, a_t) (C3), and storage heat flux coefficients (a_2, a_3) (C4). The final model values are indicated (*). For other details see text.

Appendix A. Leaf area index (LAI)

In SUEWS, changes in phenology, such as growing season length, are allowed to vary from year to year as a function of thermal conditions through growing degree days and senescence degree days. The thermal thresholds are changed to be appropriate for a location (e.g. latitude, continental vs. maritime climate) (Järvi et al., 2011). At high latitudes, air temperature is a good proxy for leaf growth in spring, whereas the leaf-off is initiated by day length (Keskitalo et al., 2005). However, air temperature still influences the rate of leaf fall. Thus the functions to calculate daily leaf area index ($LAI_{d,i}$) are modified to take also the day length into account according to

$$\begin{cases} LAI_{d,i} = LAI_{d-1,i}^{b_1} GDD \cdot c_1 + LAI_{d-1}, & \text{leaf-on, } T_d > T_{BaseGDD} \\ LAI_{d,i} = LAI_{d-1,i}^{b_2} SDD \cdot c_2 + LAI_{d-1}, & \text{leaf-off, } T_d < T_{BaseSDD}, \text{ or} \\ LAI_{d,i} = LAI_{d-1,i}^{b_3} (1 - GDD) \cdot c_3 + LAI_{d-1}, & \text{leaf-off, } t_d < 12 \text{ h} \end{cases} \quad (19)$$

where GDD and SDD are the growing and senescence degree days, $b_{1,2,3}$ and $c_{1,2,3}$ control the rate of change in LAI and $T_{BaseSDD}$ is the base temperature for senescence. Using the original LAI functions with coefficients $b_1 = b_2 = 0.03$ and $c_1 = c_2 = 5 \cdot 10^{-4}$ resulted too slow both leaf-on and leaf-off period at both cities when compared to visual inspection. Thus, for the leaf-on period the coefficients at both cities were changed to $b_1 = 0.04$ and $c_1 = 0.001$, and the new senescence parameterization (Eq. 20) based on the day length with parameters $b_3 = -1.5$ and $c_3 = 1.5 \cdot 10^{-3}$ was deployed. Unfortunately no measurements of LAI were available. The values are from visual surveys of leaf-on and leaf-off timings.

Appendix B. Snow fraction depletion curves for vegetated, paved and roof surfaces.




Figure B01. Surface snow fraction depletion curves for vegetated, paved and building surfaces. The paved and building curves were obtained from Valeo and Ho (2004), whereas the vegetation curve was obtained by fitting Swenson and Lawrence (2012) to Ek et al. (2003) data.

1 Appendix C. Notation used

2	α_i	Effective surface albedo (-)
3	α_s	Effective snow albedo (-)
4	α_s^{min}	Minimum snow albedo (-)
5	α_s^{max}	Maximum snow albedo (-)
6	ΔQ^*	Change in the net-all wave radiation in time step Δt ($W\ m^{-2}$)
7	ΔQ_A	Advective heat flux ($W\ m^{-2}$)
8	$\Delta Q_{S,I}$	Change in the snow heat storage ($W\ m^{-2}$)
9	ΔS_{WE}	Change in the snow water equivalent ($mm\ h^{-1}$)
10	Δt	Time step of the model (s)
11	ε_i	Effective surface emissivity (-)
12	ε_s	Effective surface emissivity of snow (-)
13	γ	Psychometric constant ($Pa\ ^\circ C^{-1}$)
14	λ_{bldg}	Surface fraction of buildings (-)
15	λ_{dec}	Surface fraction of deciduous trees (-)
16	λ_{ev}	Surface fraction of evergreens (-)
17	λ_{grass}	Surface fraction of non-irrigated grass (-)
18	λ_{igrass}	Surface fraction of grass (-)
19	λ_{pav}	Surface fraction of paved areas (-)
20	λ_{unman}	Surface fraction of unmanaged land (-)
21	λ_{veg}	Surface fraction of vegetation (-)
22	λ_{water}	Surface fraction of water (-)
23	ρ	Air density ($kg\ m^{-3}$)
24	ρ_e	Threshold value in the calculation of retention capacity ($kg\ m^{-3}$)
25	ρ_s	Snow density ($kg\ m^{-3}$)
26	$\rho_{s,0}$	Initial snow density ($kg\ m^{-3}$)
27	ρ_w	Water density ($kg\ m^{-3}$)
28	ρ_s^{max}	Maximum snow density ($kg\ m^{-3}$)
29	ρ_s^{min}	Minimum snow density ($kg\ m^{-3}$)
30	τ_a	Cold snow time constant for snow albedo aging (-)
31	σ_{Obs}	Standard deviation of observed values
32	τ_d	Seconds in one hour ($3600\ s\ h^{-1}$)
33	τ_h	Period of one day ($86400\ s$)
34	τ_f	Warm snow time constant for snow albedo aging (-)

1	τ_r	Time constant describing the snow density aging (-)
2	$a_{0,\{wd,we\}}$	Parameter defining the base Q_f per capita ($\text{W m}^{-2} (\text{capita}^{-1} \text{ ha}^{-1})^{-1}$)
3	$a_{1,\{wd,we\}}$	Parameter related to CDD ($\text{W m}^{-2} \text{ K}^{-1} (\text{capita}^{-1} \text{ ha}^{-1})^{-1}$)
4	$a_{2,\{wd,we\}}$	Parameter related to HDD ($\text{W m}^{-2} \text{ K}^{-1} (\text{capita}^{-1} \text{ ha}^{-1})^{-1}$)
5	$a_{1,2,3}$	Constants in the calculation of the snow heat storage
6	a_r	Radiation melt factor ($\text{mm W}^{-1} \text{ h}^{-1}$)
7	a_t	Temperature melt factor ($\text{mm } ^\circ\text{C}^{-1} \text{ h}^{-1}$)
8	a_f	Temperature freezing factor ($\text{mm } ^\circ\text{C}^{-1} \text{ h}^{-1}$)
9	A	Study area (ha)
10	b	Empirical coefficient in the calculation of drainage
11	$b_{1,2,3}$	Parameters controlling the speed of leaf on
12	$b_{1a,2a,3a}$	Parameters for automatic irrigation (mm , mm K^{-1} , mm d^{-1})
13	$b_{1m,2m,3m}$	Parameters for manual irrigation (mm , mm K^{-1} , mm d^{-1})
14	Bldg	Building surface type
15	$c_{1,2,3}$	Parameter to control the speed of leaf-off
16	c_p	Heat capacity of air ($\text{J kg}^{-1} \text{ K}^{-1}$)
17	c_w	Specific heat capacity of water ($\text{kJ kg}^{-1} ^\circ\text{C}^{-1}$)
18	C_i	Interception state of i th surface (mm)
19	$C_{soil,i}$	Soil water storage (mm)
20	C^R	Retention capacity (mm)
21	C_{min}^R	Minimum retention capacity (mm)
22	C_{max}^R	Maximum retention capacity (mm)
23	d	Day
24	$D_{0,i}$	Drainage rate (mm)
25	D_{sm}	Day of the snow melt
26	Decid	Deciduous surface type
27	E	Evaporation (mm h^{-1})
28	EC	Eddy covariance
29	Everg	Evergreen surface type
30	$f_{s,i}$	Fraction of snow on surface
31	$f_{s,i,0}$	Initial fraction of snow
32	F	Freezing water on surface (mm h^{-1})
33	$g_{i,max}$	Maximum conductance (m s^{-1})
34	G_{1-6}	Parameters related to surface conductance
35	GDD	Growing degree days

1	i	Surface type index
2	Irr. veg.	Irrigated vegetation type
3	I	Interception of linear regression
4	I_w	Additional water to water surface type (mm)
5	K_{\downarrow}	Downward shortwave radiation (W m^{-2})
6	$K_{\downarrow m}$	Maximum incoming solar radiation used in g_s calculation
7	K_{\uparrow}	Upward shortwave radiation (W m^{-2})
8	K_s	Saturated hydraulic conductivity (mm s^{-1})
9	Ku	Kumpula site
10	Ku1	Built sector at the Kumpula site
11	Ku2	Road sector at the Kumpula site
12	Ku3	Vegetation sector at the Kumpula site
13	L_f	Latent heat of fusion (J kg^{-1})
14	$LAI_{d,i}$	Daily leaf area index ($\text{m}^2 \text{m}^{-2}$)
15	$LAI_{\max,i}$	Maximum LAI of surface type i ($\text{m}^2 \text{m}^{-2}$)
16	$LAI_{\min,i}$	Minimum LAI of surface type i ($\text{m}^2 \text{m}^{-2}$)
17	Lat	Latitude ($^{\circ}$)
18	Lon	Longitude ($^{\circ}$)
19	M	Snow melt and re-freezing of melted water (mm h^{-1})
20	MBE	Mean biased error
21	nRMSE	Normalized root mean square error
22	N	Number of data points
23	OHM	Objective hysteresis model
24	p	Population density inside the grid (capita ha^{-1})
25	P	Precipitation (mm h^{-1})
26	Pa	Pasila site
27	Pav	Paved surface type
28	Pi	Pihlajamäki site
29	Pr	Pierrefonds-Roxboro site
30	Q^*	Net all-wave radiation (W m^{-2})
31	Q_A	Advective heat flux (W m^{-2})
32	Q_E	Latent heat flux (W m^{-2})
33	Q_f	Anthropogenic heat flux (W m^{-2})
34	Q_g	Ground heat flux (W m^{-2})
35	Q_H	Sensible heat flux (W m^{-2})

1	Q_M	Energy consumed to melt snow (W m^{-2})
2	Q_p	Heat released from rain on snow (W m^{-2})
3	r	Pearsons correlation coefficient
4	r_a	Aerodynamic resistance (s m^{-1})
5	$r_{s,max}$	Maximum surface resistance (s m^{-1})
6	res_{cap}	Surface water capacity in LUMPS (mm)
7	res_{drain}	Drainage rate of water bucket in LUMPS (mm h^{-1})
8	R	Runoff (mm)
9	R_C	Limit when surface is totally covered with water in LUMPS (mm)
10	RI	Rosemont-La-Petite-Patrie site
11	R_{mod}	Modelled runoff (mm)
12	R_{obs}	Observed runoff (mm)
13	RMSE	Root mean square error
14	s	Slope of the saturation vapour pressure curve over ice ($\text{Pa } ^\circ\text{C}^{-1}$)
15	s_d	Snow depth (m)
16	sRMSE	RMSE normalized with standard deviation of the observation
17	S	Slope of linear regression
18	S_{1-2}	Parameters related to surface conductance
19	S_i	State of the snow-free surface (mm)
20	S_{Pipe}	Maximum depth capacity of pipes (mm)
21	$S_{soil,i}$	Soil state (mm)
22	S_{WE}	Snow water equivalent (mm)
23	$S_{WE,0}$	Initial snow water equivalent (mm)
24	$S_{WE,Lim}$	Limit of the snow water equivalent for the snow removal (mm)
25	$S_{WE,i}^{max}$	Snow water equivalent when surface type i is fully covered with snow (mm)
26	SDD	Senescence degree days
27	SUEWS	the Surface Urban Energy and Water balance Scheme
28	t_d	Day length (h)
29	T_a	Air temperature ($^\circ\text{C}$)
30	$T_{BaseGDD}$	Base temperature for leaf growth ($^\circ\text{C}$)
31	$T_{BaseSDD}$	Base temperature for senescence ($^\circ\text{C}$)
32	T_{BaseQF}	Base temperature for Q_F ($^\circ\text{C}$)
33	T_H, T_L	Parameters related to calculation of g_s ($^\circ\text{C}$)
34	T_{lim}	Temperature limit for the liquid precipitation and snow ($^\circ\text{C}$)
35	T_s	Snow surface temperature ($^\circ\text{C}$)

1	T_{Step}	Time step for water balance calculation(s)
2	T_R	Transport of snow from the study area (mm)
3	V	Vapour pressure deficit (Pa)
4	X_{Mod}	Modelled variable X
5	$X_{Mod, max}$	Maximum value of observed time series
6	X_{Obs}	Observed variable X
7	$X_{Obs, max}$	Maximum value of observed time series
8	z	Height of the meteorological measurements (m)
9	z_{0v}	Roughness length for heat and water vapour (m)
10	z_{0m}	Roughness length for momentum (m)
11	z_h	Mean building height (m)
12	z_t	Mean tree height (m)

13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29