Geosci. Model Dev. Discuss., 8, 8193–8237, 2015 www.geosci-model-dev-discuss.net/8/8193/2015/ doi:10.5194/gmdd-8-8193-2015 © Author(s) 2015. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Geoscientific Model Development (GMD). Please refer to the corresponding final paper in GMD if available.

# r.randomwalk v1.0, a multi-functional conceptual tool for mass movement routing

# M. Mergili<sup>1,2</sup>, J. Krenn<sup>2,3</sup>, and H.-J. $\mathrm{Chu}^4$

<sup>1</sup>Geomorphological Systems and Risk Research, Department of Geography and Regional Research, University of Vienna, Universitätsstraße 7, 1190 Vienna, Austria

<sup>2</sup>Institute of Applied Geology, University of Natural Resources and Life Sciences (BOKU), Peter-Jordan-Straße 70, 1190 Vienna, Austria

<sup>3</sup>Department of Geological Sciences, University of Canterbury, Private Bag 4800,

Christchurch, New Zealand

<sup>4</sup>Department of Geomatics, National Cheng Kung University, 1 University Road, Tainan 701, Taiwan

Received: 4 August 2015 - Accepted: 3 September 2015 - Published: 25 September 2015

Correspondence to: M. Mergili (martin.mergili@boku.ac.at)

Published by Copernicus Publications on behalf of the European Geosciences Union.



# Abstract

We introduce r.randomwalk, a flexible and multi-functional open source tool for backward- and forward-analyses of mass movement propagation. r.randomwalk builds on GRASS GIS, the R software for statistical computing and the programming languages Python and C. Using constrained random walks, mass points are routed from defined release pixels of one to many mass movements through a digital elevation model until a defined break criterion is reached. Compared to existing tools, the major innovative features of r.randomwalk are: (i) multiple break criteria can be combined to compute an impact indicator score, (ii) the uncertainties of break criteria can be included by performing multiple parallel computations with randomized parameter settings, resulting in an impact indicator index in the range 0–1, (iii) built-in functions for validation and visualization of the results are provided, (iv) observed landslides can be back-analyzed to derive the density distribution of the observed angles of reach. This distribution can be employed to compute impact probabilities for each pixel. Further, impact indicator score, and probabilities can be combined with release indicator.

ther, impact indicator scores and probabilities can be combined with release indicator scores or probabilities, and with exposure indicator scores. We demonstrate the key functionalities of r.randomwalk (i) for a single event, the Acheron Rock Avalanche in New Zealand, (ii) for landslides in a 61.5 km<sup>2</sup> study area in the Kao Ping Watershed, Taiwan; and (iii) for lake outburst floods in a 2106 km<sup>2</sup> area in the Gunt Valley, Tajik istan.

#### 1 Introduction

25

Mass movement processes such as landslides, debris flows, rock avalanches or snow avalanches may lead to damages or even disasters when interacting with society. Computer models predicting travel distances, hazardous areas, impact energies or travel times may help the society to mitigate the effects of such processes and, consequently, to reduce the risk and the losses (Hungr et al., 2005).



Physically-based dynamic models are used for in-detailed analyses of specific events or situations (e.g., Savage and Hutter, 1989; Takahashi et al., 1992; Iverson, 1997; Pudasaini and Hutter, 2007; McDougall and Hungr, 2004, 2005; Pitman and Le, 2005; Christen, C. et al., 2010; Christen, M. et al., 2010; Mergili et al., 2012b, 2015; Pudasaini, 2012; Hergarten and Robl, 2015). Since the processes are complex in detail and the input parameters are uncertain, simplified conceptual models for the motion of mass flows are today used in combination with GIS. These models may be used for single events. However, they are particularly useful to indicate potential impact areas at broader scales. Hypothetic mass points are routed from a release pixel through a digital elevation model (DEM) until a defined break criterion is reached. Monte Carlo techniques (random walks, Pearson, 1905; Gamma, 2000) or multiple flow direction

algorithms (Horton et al., 2013) are employed to simulate the lateral spreading of the flow.

The break criteria often consist in threshold values of the angle of reach (i.e., the
<sup>15</sup> average slope of the path) or horizontal and vertical distances (Lied and Bakkehøi, 1980; Vandre, 1985; McClung and Lied, 1987; Burton and Bathurst, 1998; Corominas et al., 2003; Haeberli, 1983; Zimmermann, 1997; Huggel et al., 2002, 2003, 2004a, b), sometimes related to volume (Rickenmann, 1999; Scheidl and Rickenmann, 2009) are used as criteria. The scatter in the relationships is usually large. Using the worst case
<sup>20</sup> may be an appropriate first estimate, but is often too conservative for design issues

(Hungr et al., 2005).

Some approaches include simplified physically-based models going back to the mass flow model of Voellmy (1955), relating the shear traction to the square of the velocity and assuming an additional Coulomb friction effect (Pudasaini and Hutter, 2007).

They consider only the centre of the flowing mass, but not its deformation and the spatial distribution of the flow variables. This type of models is mainly used for snow avalanches and debris flows (Perla et al., 1980; Gamma, 2000; Wichmann and Becht, 2003; Fischer et al., 2012; Mergili et al., 2012a; Horton et al., 2013).



Various – mostly open source – software tools for conceptual modelling of mass movements (mainly flows) at medium or broad scales are available (e.g., Gamma, 2000; Wichmann and Becht, 2003; Mergili et al., 2012a; Horton et al., 2013). However, most of these tools are lacking substantial features: (i) they are limited to one single type of break criterion, (ii) they do not allow to directly account for the uncertainty of the break criteria, (iii) they do not allow to back-calculate the statistics of a set of observed mass movements, (iv) they do not offer built-in functionalities for evaluating the model results against observations. Consequently, the key objectives of the present study are:

- To introduce r.randomwalk, a freely available, comprehensive and flexible tool for routing mass movements.
- To demonstrate the various functionalities of r.randomwalk, particularly in terms of overcoming the issues (i)-(iv).
- To discuss the potentials and limitations of this tool.

Next, we will describe the r.randomwalk software tool (Sect. 2). Then we will present the test areas (Sect. 3) and the results (Sect. 4). We will discuss the findings (Sect. 5) and conclude with some key messages of the work (Sect. 6).

# 2 The r.randomwalk application

# 2.1 Computational implementation

20

10

r.randomwalk is implemented as a raster module of the open source software package GRASS GIS 7 (Neteler and Mitasova, 2007; GRASS Development Team, 2015). We use the Python programming language for data management, pre-processing and post-processing tasks. The routing procedure (see Sect. 2.2–2.4) is written in the C programming language. The R software environment for statistical computing and graphics (R Core Team, 2015) is employed for built-in validation and visualization functions (see



Sect. 2.5). Parallelization of multiple model runs is enabled. It allows the exploitation of all computational cores available, speeding up analysis processes. The parallelization procedure is implemented at the Python level (analogous to the way described in Mergili et al., 2014) and serves for two purposes:

- Analyses with multiple random subsets of the release areas or coordinates, ensuring a clear separation between model development and application/validation.
  - Analyses with multiple combinations of randomized input parameters, enabling to consider parameter uncertainties and to explore parameter sensitivity.

r.randomwalk was developed and tested with Ubuntu 12.04 LTS and is expected to work on other UNIX systems, too. A simple user interface is available. However, the tool may be started more efficiently through command line parameters, enabling a straightforward batching on the shell script level. This feature facilitates model testing, the combination with other GRASS GIS modules and the consideration of process chains (i.e., using the output of one analysis as the input for the next one). The logical framework is illustrated in Fig. 1.

# 2.2 Random walk routing

The term random walk refers to a Monte-Carlo-approach for routing an object through any type of space. The term was introduced by Pearson (1905). Constrained random walk approaches are used for routing mass movements such as debris flows
through elevation maps (DEMs) e.g., by Gamma (2000), Wichmann and Becht (2003), Mergili et al. (2012a) and Gruber and Mergili (2013). Such methods enable a certain degree of spreading of the movement by considering also other routing directions than the steepest descent. It avoids the concentration of flows – or any other types of mass movements – to linear features which would not be realistic for debris flows, snow avalanches or other types of mass movements. However, the routing is constrained or weighted by factors such as the slope or the perpetuation of the flow direction. An



alternative to constrained random walk routing would consist in a multiple flow direction algorithm (Horton et al., 2013).

In the context of r.randomwalk, each random walk routes a hypothetic mass point from a release pixel through the DEM until a break criterion is reached (see Sect. 2.3).

- <sup>5</sup> A large set of random walks is required for each mass point in order to achieve a satisfactory cover of the possible impact area. r.randomwalk is designed for:
  - One set of random walks for one mass movement, starting from a defined set of coordinates.
  - Multiple sets of random walks for one mass movement, one set starting from each pixel of the release area.
  - Sets of random walks for multiple mass movements in a study area (either starting from one set of coordinates per mass movement, or from all pixels defined as release areas).
  - One set of random walks starting from each pixel in the study area.

10

25

<sup>15</sup> Overlay rules for different random walks and sets of random walks are applied (see Sect. 2.4).

During the pixel-to-pixel routing procedure, turns of  $> 90^{\circ}$  are not supported. Neighbour pixels are further considered invalid as target pixels in case they are out of the study area or conflict with at least one of the following requirements:

- Equation (1) allows upward movements. In order to constrain upward movements, a user-defined maximum vertical run-up height  $R_{max}$  is introduced. It takes the lowest elevation the random walk has passed through as reference.
  - Certain types of mass flows (i.e., those with high viscosity) hardly change their flow direction sharply. The user-defined horizontal control distance  $L_{ctrl}$  defines the backward distance of each step over which the horizontal distance of motion has to increase (Fig. 2a).



8198

The probability  $P_p$  of any other neighbour pixel p to become the target pixel is

$$P_p = p_p / \sum_{q=1}^{q=n} p_q, p = f_d^* \cdot e^{f_\beta \tan \beta},$$

where *n* is the total number of valid neighbour pixels, and  $\beta$  is the local slope between the current pixel and the considered neighbour pixel.  $f_d^*$  and  $f_\beta$  are weighting factors for the perpetuation of the flow direction and for the slope.  $f_d^*$  is governed by the input parameter  $f_d$ :  $f_d^* = f_d^2$  for the same flow direction as the previous one,  $f_d^* = f_d$  for a 45° turn and  $f_d^* = 1$  for a 90° turn.

The break criteria for the random walks (see Sect. 2.3) are directly or indirectly related to the travel distance  $L_{max}$  i.e., the horizontal length between the release pixel and the terminal pixel measured along the flow path. Preliminary tests reveal that random walk routing through raster maps may result in quite uneven flow paths (see Fig. 2b). Consequently, the distance calculated by summing up all the pixel-to-pixel distances may be significantly longer than the more relevant distance along the observed main flow paths. Employing the sums of the pixel-to-pixel distances would lead to an underestimation of the angle of reach (Table 2) and, consequently, of the predicted travel distances and impact areas. We approach this problem by dividing the flow paths into straight segments with a user-defined maximum length of  $L_{seg}$ . The travel distance  $L_{max}$  is defined as the sum of the length of all segments (see Fig. 2b). Larger values of  $L_{seg}$  are expected to result in shorter travel distances due to the more pronounced smoothing of the path.

#### 2.3 Break criteria

25

Each random walk continues until at least one neighbour pixel is outside the study area, or until the user-defined break criterion is fulfilled. The break criteria are the key parameters for estimating the mass flow impact areas and can be defined in various ways (Table 1):

(1)

- The angle of reach  $\omega_{T}$  or the maximum travel distance  $L_{max}$  is computed from empirical-statistical rules or relationships, based on the analysis of observed events (Table 2). They usually refer to the distance between the highest spot of the release area and the most distant spot of the impact area along the flow path (the "Fahrböschung" according to Heim, 1932). Consequently, random walks using this type of break criterion have to start from the set of coordinates defining the highest point of the observed or expected mass movement. Alternatively, also a semi-deterministic model (Perla et al., 1980) can be used.

5

10

15

20

25

- Empirical-statistical relationships or the semi-deterministic model may be applied in a large number of parallel computations with randomized values of the parameters *a*, *b* and *c* (see Fig. 1 and Table 2). This allows to explore the effects of uncertainties in the relationships. Only one type of relationship is considered at once, and the output consists in a raster map of the impact indicator index III in the range 0–1, representing the fraction of tested parameter combinations predicting an impact on the pixel (i.e., where IIS = 1). Further, the results of all model runs are stored in a way ready to be analyzed with the parameter sensitivity tool AIMEC (Fischer, 2013).
- An impact probability raster map  $P_1$  in the range 0–1 is computed from a userdefined sample of observed values of  $\omega_T$  which is employed to build a cumulative density function (CDF). The CDF represents the probability that the movement reaches the pixel associated to each value of  $\omega_T$ . The sample of observed values may be divided into one subset of mass movements for building the CDF, and another one for computing  $P_1$ . This ensures a clear separation between model development and application/validation (see Sect. 2.5). Parallel processing may be used to repeat the analysis for many random subsets in order to achieve a more robust result.
- If an inventory of events is available, the observed impact areas may be backcalculated by routing each random walk until it leaves the observed impact area



of the corresponding mass movement. This mode can be used to explore the statistical distribution of  $\omega_T$ . The resulting CDF can be used as input to estimate  $P_1$ .

# 2.4 Overlay of random walk results

- <sup>5</sup> Each random walk does not stand for itself alone. Instead, it has to be overlaid with other random walks at two levels:
  - Random walks of the same mass point: IF is increased by 1 for each random walk predicting an impact. IIS is increased by 1 for each model where at least 1 random walk predicts an impact. The average angle of path – and therefore also
  - $P_{\rm I}$  are derived from the random walk with the shortest travel distance (i.e., the straightest flow path and the highest value of  $\omega$ ) at the considered pixel.
  - 2. Sets of random walks for different mass points: the values of IF for all random walks impacting a pixel are just added up whilst the maximum of IIS is applied to each pixel. The issue gets more complex when it comes to  $P_1$ : depending on the specific application, the maximum or the average out of all sets of random walks is more appropriate.

The resulting  $P_1$  or IIS maps can be automatically overlaid with a release probability or a release indicator score, and with an exposure indicator score derived from the land cover. These steps are not further considered in this article and are therefore not shown in Fig. 1.

#### 2.5 Validation

10

15

20

25

r.randomwalk includes three possibilities for validation of the model results. All three build on the availability of a raster map of the observed deposition area of the mass movement(s) under investigation. All parts of the observed impact areas outside of the observed deposition areas are set to no data (Fig. 3).



- For IIS, the true positive (TP), true negative (TN), false positive (FP) and false negative (FN) predictions are counted on the basis of pixels and put in relation. All pixels with IIS ≥ 1 are considered as observed positives (OP), all pixels with IIS = 0 are considered as observed negatives.
- ROC Plots are produced for III or *P*<sub>1</sub>: the true positive rate *r*<sub>TP</sub> (TP/OP) is plotted against the false positive rate *r*<sub>FP</sub> (FP/ON) for various levels of III or *P*<sub>1</sub>. The area under the curve connecting the resulting points, AUC<sub>ROC</sub>, is used as an indicator for the quality of the prediction (see Fig. 3). If the CDF for *P*<sub>1</sub> is derived from the same set of landslides, r.randomwalk includes the option to randomly split the set of observed landslides into a set for model development, and one for validation. This is done for a user-defined number of times, exploiting multiple processors (see Sect. 2.3 and Fig. 1). It results in an ROC Plot with multiple curves.
  - If only one mass movement is considered, a longitudinal profile may be defined by a set of coordinates of the profile vertices. The observed and predicted (IIS  $\ge$  1 or  $P_1 > 0$ ) travel distances are measured and compared along this profile.

# 3 Test sites and model parameterization

# 3.1 Acheron Rock Avalanche, New Zealand

The Acheron Rock Avalanche in Canterbury, New Zealand (Fig. 4), was triggered approx. 1100 years BP (Smith et al., 2006). Within the present study, the release volume V = 6.4 million m<sup>3</sup> is approximated from the reconstruction of the pre-failure topography and is lower than the value of V = 7.5 million m<sup>3</sup> estimated by Smith et al. (2006). We use a 10 m resolution DEM derived by stereo-matching of aerial photographs. Impact, release and deposition areas are derived from field and imagery interpretation as well as from data published by Smith et al. (2006). All random walks start from the highest pixel of the release area.



15

20

25

We use this case study for demonstrating how to compute the impact indicator index III from an elevation map, the release area and the release volume. Before doing so, we have to analyze the influence of the pixel size and the parameters  $n_{\text{walks}}$ ,  $R_{\text{max}}$ ,  $L_{\text{ctrl}}$ ,  $L_{\text{seg}}$ ,  $f_{\beta}$  and  $f_{d}$  on the model result. Preliminary tests have shown that r.randomwalk yields plausible results with the number of random walks  $n_{\text{walks}} = 10^4$ ,  $R_{\text{max}} = 10$  m,  $L_{\text{ctrl}} = 1000$  m,  $L_{\text{seg}} =$ , 100 m,  $f_{\beta} = 5$ ,  $f_{d} = 2$ , and a pixel size of 20 m. These values are taken as a basis to explore the sensitivity of the model results to the variation of each parameter and the best fit of the parameters in terms of the travel distance, AUC<sub>BOC</sub>

and the size of the predicted impact area (Table 3).  $\omega_T = 11.62^\circ$ , the angle of reach observed for the Acheron Rock Avalanche, is applied as the break criterion for all tests. Some of the tests are run in the back-calculation mode (flag b; see Tables 1 and 3).

III is computed by executing r.randomwalk for 100 times with the parameter values optimized according to Table 3. We explore an empirical–statistical relationship for  $\omega_T$  derived from a compilation of 127 case studies (Fig. 5). The offset of the equation

(b in Eq. 4 and Fig. 5) is randomly sampled between the lower and upper envelopes of the regression. The quality of the prediction is evaluated using an ROC Plot (see Figs. 1 and 3). Note that the Acheron Rock Avalanche (not included in the relationship developed in Fig. 5) is found close to the lower envelope, meaning that it was very mobile compared to most of the other events.

#### 20 3.2 Kao Ping Watershed, Taiwan

Between 7 and 9 August 2009, Typhoon Morakot struck Taiwan and triggered enormous landslides, causing significant land cover change (Fig. 6). More than 22 000 landslides were recorded in Southern Taiwan (Lin et al., 2011). One of the hot spots of mass wasting was the Kao Ping Watershed (Wu et al., 2011), where the extremely heavy rainfall (in total, more than 2000 mm depth and 90 h duration) triggered a catas-

heavy rainfall (in total, more than 2000 mm depth and 90 h duration) triggered a catastrophic landslide in the Hsiaolin Village (Kuo et al., 2013).



We consider a 61.5 km<sup>2</sup> subset of the Kao Ping Watershed for computing the landslide impact probability  $P_{\rm I}$ , based on the observed landslide release areas. 207 landslides are mapped in the shale, sandstone and colluvium slopes. (see Fig. 6). A 10 m DEM is used along with an inventory of the landslide impact areas. Release and deposition areas are extracted from the inventory. We assume that the values of  $n_{\rm runs}$ ,  $R_{\rm max}$ ,  $f_{\beta}$ ,  $f_d$ ,  $L_{\rm ctrl}$ ,  $L_{\rm seg}$  and the pixel size applied to the Acheron Rock Avalanche (see Sect. 3.1) are valid also for this study area.  $P_{\rm I}$  is computed as follows:

- 1. A set of random walks  $(n_{walks} = 10^4)$  is started from each release point (i.e., the highest pixel of each landslide). Each random walk stops as soon as it would leave the impact area of the same landslide (back-calculation, flag b).
- 2. After completing all random walks for the study area, the statistical distribution of  $\omega_T$  is analyzed. All landslides with  $L_{max} < 100$  m are excluded. A fraction of 20% out of all landslides (i.e., all values of  $\omega_T$  associated with those landslides) is randomly selected and retained for validation. We have identified the Gaussian distribution as the most suitable type of distribution for this purpose. Consequently, the Gaussian cumulative density function (CDF) stands for the probability that a moving mass point leaves the observed impact area at or below the associated threshold of  $\omega_T$ .
- 3. We perform a forward analysis of  $P_{\rm I}$  by starting a set of random walks ( $n_{\rm runs} = 10^4$ ) from the release points of the retained landslides, and assigning the cumulative density associated to the average angle of path to each pixel. The result is validated against the observed deposition zones of the retained landslides by means of an ROC Plot.
- 4. 2. and 3. are repeated for 100 randomly selected subsets (parallel processing is applied). The final map of  $P_{\rm I}$  is generated by applying for each pixel the maximum of the values yielded by all the model runs.



25

10

15

20

We refer to this work flow as Test 1 and repeat the analysis with starting random walks not only from the release points, but from all the pixels within the observed release areas (Test 2). This means that the CDF is derived from a much larger sample of data than when considering only one point per landslide for starting random walks. We exclude all sets of random walks yielding  $L_{max} < 100 \text{ m}$ , use a log-normal CDF and start a set of only  $10^3$  random walks from each release pixel for computing  $P_1$ .

# 3.3 Gunt Valley, Tajikistan

As most mountain areas worldwide, the Pamir of Tajikistan experiences a significant retreat of the glaciers. One of the consequences thereof consists in the formation and growth of lakes, some of which are subject to glacial lake outburst floods (GLOFs) which may evolve into destructive debris flows (Mergili and Schneider, 2011; Mergili et al., 2013; Gruber and Mergili, 2013). No records of historic GLOFs in the test area are known to the authors. However, in August 2002 a GLOF in the nearby Shakhdara Valley evolved into a debris flow which destroyed the village of Dasht, claiming dozens of lives (Mergili et al., 2011).

The frequency of such events is low and historical data are sparse. Consequently, possible travel distances of GLOFs may not be derived in a purely statistical way. Instead, we have to use published empirical–statistical relationships and simple rules to produce an impact indicator score (IIS) map.

<sup>20</sup> We compute IIS with regard to GLOFs for a 2106 km<sup>2</sup> study area in the Gunt Valley (Fig. 7). The analysis builds on the ASTER GDEM V2 and the coordinates and characteristics (estimates of *V* and  $Q_p$ ) of 113 lakes in the area (Gruber and Mergili, 2013).

A set of random walks ( $n_{walks} = 10^4$ ) is routed from the outlet of each lake through the DEM. Six break criteria are combined to compute IIS, partly following Gruber and Mergili (2013). The relationships and rules employed as beak criteria are summarized in Table 4. Rule 1 is applied with  $\omega_T = 11^\circ$  (Test 1 – according to Haeberli, 1983; Huggel et al., 2003, 2004 for debris flows from glacier- or moraine-dammed lakes; Zim-



mermann et al., 1997 for coarse- and medium-grained debris flows) and with  $\omega_{\tau} = 7^{\circ}$  (Test 2 – Zimmermann et al., 1997 for fine-grained debris flows). All other rules and relationships are used for both tests. For each pixel, IIS consists in the number of relationships or rules predicting an impact (i.e., IIS takes values in the range 0–6).

<sup>5</sup>  $R_{\text{max}}, L_{\text{ctrl}}, L_{\text{seg}}, f_{\beta}$  and  $f_d$  are set to the optimum values found for the Acheron Rock Avalanche, the pixel size is set to 60 m.

#### 4 Results

# 4.1 Acheron Rock Avalanche

Figure 8 summarizes the findings of the Tests 1–3 (see Table 3). Test 1 leads to the expected result that the predicted impact area increases with the number of random walks. However, the predicted impact area is also a function of the pixel size: with larger pixels, less random walks are needed to cover an area of similar size than with smaller pixels. Figure 8a further indicates that the possible impact area is not fully covered even at  $10^5$  random walks: no substantial flattening of the curves is observed. We conclude that (i) a very high value of  $n_{walks}$  would be necessary to fully cover the possible impact area, and (ii) this would lead to a substantial overestimation of the observed impact area.

On the other hand, the quality of the prediction in terms of AUC<sub>ROC</sub> reaches a constant level at  $n_{\text{walks}} \approx 10^2$  (pixel size 40 m) or  $n_{\text{walks}} \approx 10^4$  (pixel size 20 m), not further <sup>20</sup> increasing with higher values of  $n_{\text{walks}}$ . Also at a pixel size of 10 m, AUC<sub>ROC</sub> tends to converge to the same level of approx. 0.965 (see Fig. 8b). We may conclude that excessive numbers of random walks lead to an overestimation of the impact area rather than to a better prediction quality. Coarser pixel sizes allow to achieve the same level of coverage and the same prediction quality at lower values of  $n_{\text{walks}}$ . However, the pixel size

has to be fine enough to account for the main geometric characteristics of the process under investigation (see Sect. 5). All further tests are performed with  $n_{walks} = 10^4$ .



Figure 8c illustrates that, at  $L_{ctrl} = 1000 \text{ m}$ , the travel distance computed within the observed impact area decreases with increasing values of  $L_{seg}$  (Tests 2 and 3 in Table 3). This pattern is well explained by Fig. 2b. At short segment lengths, the effects of uneven flow paths are particularly evident for pixel sizes of 10 and 20 m.  $L_{max}$  drops below the observed value of 3550 m (see Fig. 4b) at  $25 \le L_{seg} \le 50 \text{ m}$  and then slowly

- <sup>5</sup> below the observed value of 3550 m (see Fig. 4b) at  $25 \le L_{seg} \le 50$  m and then slowly drops to 3200-3400 m at  $L_{seg} = 150$  m, the lower values associated to the coarser pixel sizes. With  $L_{seg} \ge 3050$  m, corresponding to the Euclidean distance between the release point and the terminal point of the Acheron Rock Avalanche,  $L_{max}$  would also take a value of 3050. At  $L_{ctrl} = 50$  m (only shown for a pixel size of 20 m), r.randomwalk tends
- <sup>10</sup> to predict too long travel distances, compared to the observation. This phenomenon occurs as flow directions are not well defined in the relatively plane deposition zone of the Acheron Rock Avalanche, so that flow paths may frequently shift their direction or even go backwards or in a circular way if such a behaviour is not impeded by sufficiently high values of  $L_{ctrl}$  (see Fig. 2a). Figure 8d indicates that this undesired behaviour (visible in the area marked by the X in the gray circle) disappears at  $L_{ctrl} > 200 \text{ m}$ .

On the other hand, the value of  $L_{ctrl}$  should not be chosen too high as this may negatively impact the model performance. In the case of the Acheron Rock Avalanche, a drop in AUC<sub>ROC</sub> is observed between  $L_{ctrl} \approx 2000$  and  $L_{ctrl} \approx 3000$  m (Fig. 9a). This drop is explained by an increasing number of false negative pixels in those areas which cannot be reached by the random walks due to this strict constraint of flow direction.

20

Within the tested ranges of parameter values, the quality of the prediction is highest at values of  $R_{\text{max}} \approx 5-30 \text{ m}$  (see Fig. 9b) and  $f_{\beta} \approx 3-6$  (see Fig. 9c) whilst it reacts insensitive to variations of  $f_d$  (see Fig. 9d). The predicted impact area increases with increasing  $R_{\text{max}}$  and  $f_d$  whilst it decreases with increasing  $f_{\beta}$ . Even though these findings are derived for a pixel size of 20 m we assume that the general trends are also valid for other pixel sizes.

Figures 8 and 9 indicate that the initial values of  $n_{\text{walks}}$ ,  $L_{\text{ctrl}}$ ,  $L_{\text{seg}}R_{\text{max}}$ ,  $f_{\beta}$ ,  $f_{d}$ , and the pixel size suggested in Sect. 3.1 and Table 3 are within the optimum range of values (see Sect. 5). Therefore, they are used for computing the impact indicator index for



the Acheron Rock Avalanche (Fig. 10a). Concerning the break criteria, this can be classified as a forward analysis. As expected from Fig. 5, where the Acheron Rock Avalanche falls in between the envelopes of the relationship employed, the upper part of the observed impact area displays a value of III = 1, whilst the remaining part of the observed impact area displays values of 1 > III > 0, decreasing towards the terminus

- <sup>5</sup> observed impact area displays values of 1 > III > 0, decreasing towards the terminus. As the event was comparatively mobile within the context of the relationship used (see Sect. 3.1 and Fig. 5), the values of III are close to zero in the terminal area, and the area with III > 0 does not reach far beyond the observed terminus. When using the full area shown in Figs. 4b and 10a as reference for validation (as it was also done in the
- Figs. 8b and 9),  $AUC_{ROC} = 0.97$  (see Fig. 10b). However, this extraordinarily high value is related to the high number of "cheap" true negative pixels away from the impact area. Considering only those pixels with either an observed or a predicted impact (i.e., only the true negative pixels within the dashed line in the bottom left pane of Fig. 3, yielding no true negatives for the threshold level 0.0),  $AUC_{ROC} = 0.75$  (reduced area – see Fig. 10b).

#### 4.2 Kao Ping Watershed

Starting sets of 10<sup>4</sup> random walks from the highest points of all landslides (Test 1) results in a range of values of  $16.4 \le \omega_T \le 45.1^\circ$ , an average of  $30.7^\circ$  and a standard deviation of 6.0° (derived from 121 landslides, excluding those with  $L_{max} < 100$  m). Re-

- <sup>20</sup> peating the analysis with 10<sup>4</sup> random walks started from each pixel within the landslide release areas (Test 2) we observe a range of values  $16.4 \le \omega_T \le 44.1^\circ$ , an average of 27.0° and a standard deviation of 4.8° (n = 1728). Figure 11 illustrates the histograms, probability density and cumulative density functions derived from both analyses. Even though the ranges of values are similar in both tests, Test 1 yields (i) a higher aver-
- <sup>25</sup> age of  $\omega_{T}$  and (ii) a broader range of values than Test 2. (i) is explained by the fact that those random walks starting from lower parts of the release areas are expected to leave the observed impact area at lower values of  $\omega_{T}$ . (ii) is most likely the consequence of a number of rather small landslides with high or low values of  $\omega_{T}$  strongly



reflected in the statistics. Such outliers are less prominent in the statistics of Test 2 due to the much higher number of cases, most of them related to the larger landslides.

Each of the impact probabilities shown in Fig. 12 represents the overlay of 100 analyses where random sets of 80% of the landslides are used for deriving the CDF and

- the remaining 20 % are used for computing the impact probabilities. The maps illustrate the maximum values of P<sub>1</sub> out of the overlay of the 100 results. Each of the results is derived using a slightly different CDF. Both tests yield largely similar patterns of P<sub>1</sub>. We note that (i) Test 2 predicts larger impact areas and higher values of P<sub>1</sub> than Test 1, and (ii) some random walks take the "wrong" direction in Test 2 (indicated by "1" in the
- yellow circle in Fig. 12b), a phenomenon not observed for Test 1. (i) is explained by the higher number and the broader distribution of release pixels in Test 2, compared to Test 1. The reason for (ii) is that random walks starting from the highest point of an observed landslide are forced to flow into the observed landslide area (Test 1), a constraint not applicable when starting random walks from each release pixel (Test 2). In
   this case it happens that pixels located at or near a crest produce random walks in both
- this case it happens that pixels located at or near a crest produce random walks in both directions.

The prediction quality is tested for each of the 100 model runs for the two tests, producing sets of 100 ROC Curves (Fig. 13). Considering the entire test area,  $AUC_{ROC} = 0.914 \pm 0.041$  for Test 1 and  $0.931 \pm 0.028$  for Test 2. With the reduced area,  $AUC_{ROC} = 0.668 \pm 0.083$  for Test 1 and  $0.678 \pm 0.064$  for Test 2 (refer to Sect. 4.1 for the explanation of full and reduced areas). As already indicated by Fig. 12, the performance levels differ only insignificantly between the two tests.

20

25

In contrast, the procedures demonstrated in the two tests vary strongly in their scope of applicability. We have demonstrated the methodologies by back-calculating observed landslides. As soon as this is done, one may go one step further:

 The methodology shown in Test 1 can be employed to make forward predictions for defined expected future landslides, given that a sufficient set of observed landslides of similar behaviour is available to derive the CDF.



 The methodology demonstrated in Test 2 can be used in combination with maps of landslide release probability to explore the composite probability of a landslide impact (see Sect. 2.4 and 5).

In either case the statistics (see Fig. 11) have to be derived with the same type of approach later used for producing the  $P_{\rm I}$  map.

# 4.3 Gunt Valley

Figure 14 illustrates the possible impact areas of GLOFs in the Gunt Valley study area according to the relationships listed in Table 4.

- Figure 14a shows the impact indicator score IIS i.e., the number of relationships predicting an impact, resulting from Test 1 (rule 1 applied with  $\omega_T = 11^\circ$ ). Except for one prominent exception, IIS > 3 (possible debris flow impact) only for the largely uninhabited upper portions of the tributaries to the Gunt Valley. In contrast, a possible flood impact ( $1 \le IIS \le 3$ ) is predicted for much of the main valley. Test 2 (rule 1 applied with  $\omega_T = 7^\circ$ ) predicts a possible debris flow impact also for part of the main valleys (see Fig. 14b). The impact frequency IF (per cent of random walks impacting each pixel) for
- Test 1 is shown in Fig. 14c for a subsection of the test area, classified by quantiles. IF is strongly governed by the width of the movement i.e., by the local topography, and may serve as a surrogate for the expected depth rather than as for the probability of an impact.
- Note that Fig. 14 only indicates the tendency of an already released GLOF to impact certain pixels. It does not provide any information on the susceptibility of a certain lake to produce a GLOF at all. Earlier, Mergili and Schneider (2011) and Gruber and Mergili (2013) have attempted to combine GLOF release indicators with impact indicators and land cover maps to generate hazard and risk indicator maps. However, the results of
- their studies may underestimate the possible impact areas as the travel distance was computed on a pixel-to-pixel basis, possibly yielding too low values of  $\omega_T$  (see Figs. 2 and 8).



The robustness and appropriateness of the rules and relationships for low-frequency events such as GLOFs (see Table 4) is questionable. The rules building on a unique value of  $\omega_{\tau}$  overpredict the possible impact areas for those lakes where not enough water is available to produce a flood in downstream valleys. Applying the rules and relationships for debris flows implies a blind assumption that enough entrainable sediment is available to produce a debris flow. Whilst  $\omega_{\tau} \ge 11^{\circ}$  is considered the worst case for debris flows of GLOFs from glacier- or-moraine-dammed lakes in the European Alps according to Haeberli (1983) and Huggel et al. (2002),  $\omega_{\tau} = 9.3^{\circ}$  was measured for the 2002 Dasht Event, the only well-documented GLOF near the test area (Mergili et al., 2011). Also the relationship proposed by Rickenmann (1999) severely underestimates

<sup>10</sup> 2011). Also the relationship proposed by Rickenmann (1999) severely underestimates the travel distance of this event, even when massive bulking is assumed. Applying  $\omega_T = 7^\circ$  as given by Zimmermann (1997) for fine-grained debris flows might be more suitable as worst-case assumption for debris flows from GLOFs in the Pamir, even though this threshold leads to very conservative predictions.

#### 15 **5** Discussion

Whilst conceptual tools are commonly applied for routing mass movements at medium and broad scales, most of them use single values or rules as break criteria, disregarding the high degree of uncertainty (e.g., Gamma, 2000; Wichmann and Becht, 2003; Huggel et al., 2002; Horton et al., 2013; Blahut et al., 2010). r.randomwalk introduces
<sup>20</sup> a set of tools to deal with uncertain break criteria in a flexible way, depending on the quality of rules or relationships available. In general, empirical–statistical relationships represent rough simplifications as mass movement processes may also stop when reaching valleys of higher order, run against opposite slopes or loose energy when bending sharply. However, relatively robust rules or relationships exist for the most
<sup>25</sup> common types of processes such as rock avalanches (Scheidegger, 1973; see Fig. 5) or debris flows (Rickenmann, 1999). They build on data sets large enough to derive meaningful envelopes and to compute impact indicator indices with r.randomwalk. Re-



lationships for less frequent types of processes are less robust as it was illustrated for GLOFs (Haeberli, 1983; Zimmermann; 1997; Huggel et al., 2002; Huggel, 2004; see Sect. 4.3). In such cases we recommend to compute impact indicator scores building on more than one model, as shown by Gruber and Mergili (2013) and in the present
 <sup>5</sup> work. Impact indicator indices and scores are mainly useful for anticipating the possible impact area of expected single events (see Sect. 4.1), or for application at broader scales (see Sect. 4.3).

The impact probability is useful for predicting possible impact areas of mass movements in areas where many events are documented, but the volumes of possible future events are not known. Whilst in the present paper it was demonstrated how to compute impact probabilities related to observed release areas, r.randomwalk also includes the option to combine the impact probability with release probability. Landslide release probability (susceptibility) maps are often produced from a landslide inventory and a set of environmental layers (e.g., Guzzetti, 2006). Starting random walks from each single pixel of a study area, and combining the release probability of this pixel with the impact probability allows to produce a composite probability map. Doing this is non-trivial and

requires specific strategies. It is therefore covered in a separate article (Mergili and Chu, 2015). Gruber and Mergili (2013) have combined release and impact indicator scores for various types of high-mountain hazards, and overlaid the results with a land <sup>20</sup> cover data set to produce a risk indicator score.

The sensitivity of r.randomwalk to variations of the parameters  $n_{runs}$ ,  $R_{max}$ ,  $f_{\beta}$ ,  $f_d$ ,  $L_{ctrl}$ ,  $L_{seg}$  (see Sect. 2.2) and the pixel size were tested for the Acheron Rock Avalanche. The findings are assumed to be valid also for other cases, even though the scale of the processes has to be considered. This is particularly true for the pixel size which has to be fine enough not to lose the geometrical characteristics governing the motion (Blahut et al., 2010). Furthermore, coarser pixels and a larger number of random walks make results more conservative.  $R_{max}$ ,  $f_{\beta}$  and  $f_d$  control the degree of lateral spreading and therefore influence the conservativeness of the results. In the future we plan to compare the performance of r.randomwalk to software tools using multiple flow direc-



tion algorithms (e.g., Flow-R; Horton et al., 2013) in terms of computational times and prediction success.

Figure 8c indicates that, with  $L_{seg} = 100 \text{ m}$ , the travel distance may be slightly underestimated due to smoothing of the flow path. However, this is clearly preferable over taking the risk of overestimating the travel distance at a certain pixel by choosing lower values of  $L_{seg}$ . Shorter travel distances at a certain pixel are associated to higher values of  $\omega$  and, consequently, larger predicted impact areas – i.e., more conservative results which are desirable for many applications. The values of  $R_{max}$  leading to the best prediction quality are considerably lower than run-up height observed for the Acheron Rock Avalanche. This phenomenon is explained by the facts that (i) the

observed maximum run-up height refers to a limited area, whilst r.randomwalk applies the run-up height defined by  $R_{max}$  in any place; and (ii) not all random walks reach the bottom of the valley before running up.

We have demonstrated how to estimate the prediction quality of III and *P*<sub>1</sub> maps. <sup>15</sup> Where sufficient reference data are available to prove the validity of the model, the results may be applied for hazard zoning. Where not, the outcomes of r.randomwalk are suitable for broad-scale overviews of possibly affected areas which have to be considered as rough indicators only. A suitable level of spatial aggregation may be necessary in such cases (Gruber and Mergili, 2013).

r.randomwalk includes a break criterion building on the two-parameter friction model of Perla et al. (1980) (see Sect. 1 and Table 2) which can be used to compute flow velocities (e.g., Wichmann and Becht, 2013; Mergili et al., 2012a; Horton et al., 2013). Evaluating this functionality has to build on (i) specific strategies for the sensitivity analysis and optimization of multiple parameters and (ii) a sound comparison with the out-

<sup>25</sup> come of physically-based models. This effort will be presented in a separate article (Krenn et al., submitted), using the parameter sensitivity and optimization code AIMEC (Fischer, 2013), which can be directly coupled to r.randomwalk, and the model application r.avaflow (Mergili et al., 2015).



# 6 Conclusions

We have introduced the open source GIS tool r.randomwalk, designed for conceptual modelling of the propagation of mass movements. r.randomwalk comes up with built-in functions for considering uncertainties and for validation. Employing a set of

- <sup>5</sup> three contrasting test areas, we have demonstrated (i) the possibility to combine results yielded with various break criteria into one impact indicator score, (ii) the option to explore multiple computational cores for combining the results obtained with many randomized parameter combinations into an impact indicator index, (iii) the possibility to back-calculate the CDF of the angles of reach of observed landslides, and to use this CDF to make forward predictions of the impact probability, (iv) integrated functions
- for the validation and visualization of the results. This includes strategies to properly separate the data sets for model development and validation.

We have further shown that controls for smoothing of the flow path and the avoidance of circular flows have to be introduced to avoid underestimating travel distances

and impact areas. The number of random walks executed for each mass point and the pixel size influence the level of conservativeness of the results rather than the quality of the prediction. The scope of applicability of r.randomwalk strongly depends on the availability of robust break criteria and on the availability of reference data for evaluation.

#### 20 Code availability

The model codes, a user manual, the scripts used for starting the tests presented in Sects. 3 and 4 and some of the test data are available at http://www.mergili.at/randomwalk.html.

Acknowledgements. The work was conducted as part of the international cooperation project "A GIS simulation model for avalanche and debris flows" funded by the Austrian Science Fund (FWF) and the German Research Foundation (DFG). Further, the support of Massimiliano Alvioli, Matthias Benedikt, Yi-Chin Chen, Ivan Marchesini and Tim Davies is acknowledged.



#### References

- Blahut, J., Horton, P., Sterlacchini, S., and Jaboyedoff, M.: Debris flow hazard modelling on medium scale: Valtellina di Tirano, Italy, Nat. Hazards Earth Syst. Sci., 10, 2379-2390, doi:10.5194/nhess-10-2379-2010, 2010.
- 5 Burton, A. and Bathurst, J. C.: Physically based modelling of shallow landslide sediment yield at a catchment scale, Environ. Geol., 35, 89-99, 1998.
  - Christen, C., Bartelt, P., and Kowalski, J.: Back calculation of the In den Arelen avalanche with RAMMS: interpretation of model results, Ann. Glaciol., 51, 161–168, 2010.
  - Christen, M., Kowalski, J., and Bartelt, B.: RAMMS: numerical simulation of dense snow avalanches in three-dimensional terrain, Cold Reg. Sci. Technol., 63, 1–14, 2010.
  - Corominas, J.: The angle of reach as a mobility index for small and large landslides, Can. Geotech. J., 33, 260-271, 1996.
  - Corominas, J., Copons, R., Vilaplana, J. M., Altamir, J., and Amigó, J.: Integrated landslide susceptibility analysis and hazard assessment in the principality of Andorra, Nat. Hazards. 30, 421-435, 2003.
- 15

10

Evans, S. G., Roberts, N. J., Ischuk, A., Delaney, K. B., Morozova, G. S., and Tutubalina, O.: Landslides triggered by the 1949 Khait earthquake, Tajikistan, and associated loss of life, Eng. Geol., 109, 195-212, 2009.

Fischer, J.-T.: A novel approach to evaluate and compare computational snow avalanche sim-

- ulation, Nat. Hazards Earth Syst. Sci., 13, 1655-1667, doi:10.5194/nhess-13-1655-2013, 20 2013.
  - Gamma, P.: Dfwalk Murgang-Simulationsmodell zur Gefahrenzonierung, Geographica Bernensia, G66, 2000.

GRASS Development Team: Geographic Resources Analysis Support System (GRASS) Soft-

- ware, Version 7.0, Open Source Geospatial Foundation, available at: http://grass.osgeo.org 25 (last access: 27 July 2015), 2015.
  - Gruber, F. E. and Mergili, M.: Regional-scale analysis of high-mountain multi-hazard and risk indicators in the Pamir (Tajikistan) with GRASS GIS, Nat. Hazards Earth Syst. Sci., 13, 2779– 2796, doi:10.5194/nhess-13-2779-2013, 2013.
- 30 Guo, D., Hamada, M., He, C., Wang, Y., and Zou, Y.: An empirical model for landslide travel distance prediction in Wenchuan earthquake area, Landslides, 11, 281–291, 2014. Guzzetti, F.: Landslide Hazard and Risk Assessment. PhD thesis. Bonn. 2006.



Haeberli, W.: Frequency and characteristics of glacier floods in the Swiss Alps, Ann. Glaciol., 4, 85–90, 1983.

Heim, A.: Bergsturz und Menschenleben, Fretz und Wasmuth, Zürich, 1932.

- Hergarten, S. and Robl, J.: Modelling rapid mass movements using the shallow water equations
- in Cartesian coordinates, Nat. Hazards Earth Syst. Sci., 15, 671-685, doi:10.5194/nhess-15-5 671-2015, 2015.
  - Horton, P., Jaboyedoff, M., Rudaz, B., and Zimmermann, M.: Flow-R, a model for susceptibility mapping of debris flows and other gravitational hazards at a regional scale, Nat. Hazards Earth Syst. Sci., 13, 869-885, doi:10.5194/nhess-13-869-2013, 2013.
- Huggel, C.: Assessment of Glacial Hazards based on Remote Sensing and GIS Modeling, PhD 10 thesis, University of Zurich, Schriftenreihe Physische Geographie Glaziologie und Geomorphodynamik, 2004.
  - Huggel, C., Kääb, A., Haeberli, W., Teysseire, P., and Paul, F.: Remote sensing based assessment of hazards from glacier lake outbursts: a case study in the Swiss Alps, Can. Geotech. J.,

39. 316-330. 2002. 15

20

25

Huggel, C., Kääb, A., Haeberli, W., and Krummenacher, B.: Regional-scale GIS-models for assessment of hazards from glacier lake outbursts: evaluation and application in the Swiss Alps, Nat. Hazards Earth Syst. Sci., 3, 647–662, doi:10.5194/nhess-3-647-2003, 2003.

Huggel, C., Haeberli, W., Kääb, A., Bieri, D., and Richardson, S.: Assessment procedures for glacial hazards in the Swiss Alps, Can. Geotech. J., 41, 1068-1083, 2004a.

Huggel, C., Kääb, A., and Salzmann, N.: GIS-based modeling of glacial hazards and their interactions using Landsat-TM and IKONOS imagery, Norwegian J. Geog., 58, 761-773, 2004b.

Hungr, O.: A model for the runout analysis of rapid flow slides, debris flows, and avalanches, Can. Geotech. J., 32, 610-623, 2005.

- Hungr, O., Corominas, J., and Eberhardt, E.: State of the art paper: estimating landslide motion mechanism, travel distance and velocity, in: Landslide Risk Management, Proceedings of the International Conference on Landslide Risk Management, Vancouver, Canada, 31 May-3 June 2005, edited by: Hungr, O., Fell, R., Couture, R., and Eberhardt, E., 129–158, 2005.
- Iverson, R. M.: The physics of debris flows, Rev. Geophys., 35, 245–296, 1997. 30
- Jibson, R. W., Harp, E. L., Schulz, W., and Keefer, D. K.: Large rock avalanches triggered by the M 7.9 Denali Fault, Alaska, earthquake of 3 November 2002, Eng. Geol., 83, 144-160, 2006.



- Kappes, M. S., Malet, J.-P., Remaître, A., Horton, P., Jaboyedoff, M., and Bell, R.: Assessment of debris-flow susceptibility at medium-scale in the Barcelonnette Basin, France, Nat. Hazards Earth Syst. Sci., 11, 627-641, doi:10.5194/nhess-11-627-2011, 2011.
- Kuo, Y. S., Tsai, Y. J., Chen, Y. S., Shieh, C. L., Miyamoto, K., and Itoh, T.: Movement of deepseated rainfall-induced landslide at Hsiaolin Village during Typhoon Morakot, Landslides, 10, 5 191-202, 2013.

Legros, F.: The mobility of long-runout landslides, Eng. Geol., 63, 301–331, 2002.

Lied, K. and Bakkehøi, S.: Empirical calculations of snow-avalanche run-out distance based on topographic parameters, J. Glaciol., 26, 165–177, 1980.

- 10 Lin, C. W., Chang, W. S., Liu, S. H., Tsai, T. T., Lee, S. P., Tsang, Y. C., Shieh, C. J., and Tseng, C. M.: Landslides triggered by the 7 August 2009 Typhoon Morakot in southern Taiwan, Eng. Geol., 123, 3-12, 2011.
  - McClung, D. M. and Lied, K.: Statistical and geometrical definition of snow avalanche runout, Cold Reg. Sci. Technol., 13, 107-119, 1987.
- McDougall, S. and Hungr, O.: A model for the analysis of rapid landslide motion across three-15 dimensional terrain, Can. Geotech. J., 41, 1084–1097, 2004.
  - McDougall, S. and Hungr, O.: Dynamic modeling of entrainment in rapid landslides, Can. Geotech. J., 42, 1437-1448, 2005.

Mergili, M. and Chu, H.-J.: Integrated statistical modelling of spatial landslide probability, Nat.

Hazards Earth Syst. Sci. Discuss., 3, 5677–5715, doi:10.5194/nhessd-3-5677-2015, 2015. 20 Mergili, M. and Schneider, J. F.: Regional-scale analysis of lake outburst hazards in the southwestern Pamir, Tajikistan, based on remote sensing and GIS, Nat. Hazards Earth Syst. Sci., 11, 1447–1462, doi:10.5194/nhess-11-1447-2011, 2011.

Mergili, M., Schneider, D., Worni, R., and Schneider, J. F.: Glacial lake outburst floods in the

Pamir of Tajikistan: challenges in prediction and modelling, in: Proceedings of the 5th In-25 ternational Conference on Debris-Flow Hazards Mitigation: Mechanics, Prediction and Assessment, Padua, Italy, 14-17 June 2011, Italian J. Eng. Geol. Environ. - Book, edited by: Genevois, R., Hamilton, D. L., and Prestininzi, A., 973-982, 2011.

Mergili, M., Fellin, W., Moreiras, S. M., and Stötter, J.: Simulation of debris flows in the Central Andes based on Open Source GIS: possibilities, limitations, and parameter sensitivity, Nat. 30

Hazards, 61, 1051–1081, 2012a.



Discussion

Paper

**Discussion** Paper

**Discussion** Paper

- Mergili, M., Schratz, K., Ostermann, A., and Fellin, W.: Physically-based modelling of granular flows with Open Source GIS, Nat. Hazards Earth Syst. Sci., 12, 187–200, doi:10.5194/nhess-12-187-2012, 2012b.
- Mergili, M., Müller, J. P., and Schneider, J. F.: Spatio-temporal development of high-mountain
- Iakes in the headwaters of the Amu Darya river (Central Asia), Global Planet. Change, 107, 13–24, 2013.
  - Mergili, M., Marchesini, I., Alvioli, M., Metz, M., Schneider-Muntau, B., Rossi, M., and Guzzetti, F.: A strategy for GIS-based 3-D slope stability modelling over large areas, Geosci. Model Dev., 7, 2969–2982, doi:10.5194/gmd-7-2969-2014, 2014.
- <sup>10</sup> Mergili, M., Fischer, J.-T., Fellin, W., Ostermann, A., and Pudasaini, S. P.: r.avaflow: An advanced open source computational framework for the GIS-based simulation of two-phase mass flows and process chains, Geophys. Res. Abs., 17, EGU2015-3886, EGU General Assembly, Vienna, 12–17 April 2015.

Neteler, M. and Mitasova, H.: Open Source GIS: a GRASS GIS Approach, Springer, New York, 2007.

15 \_ 200

20

Pearson, K.: The problem of the random walk, Nature, 72, p. 294, p. 318 and p. 342, 1905.

Perla, R., Cheng, T. T., and McClung, D. M.: A two-parameter model of snow avalanche motion, J. Glaciol., 26, 197–207, 1980.

Pitman, E. B. and Le, L.: A two-fluid model for avalanche and debris flows, Philos. T. R. Soc. A, 363, 1573–1601, 2005.

Pudasaini, S. P.: A general two-phase debris flow model, J. Geophys. Res., 117, F03010, doi:10.1029/2011JF002186, 2012.

Pudasaini, S. P. and Hutter, K.: Avalanche Dynamics: Dynamics of Rapid Flows of Dense Granular Avalanches, Springer, Berlin, Heidelberg, 2007.

R Core Team: R: a Language and Environment for Statistical Computing, R Foundation for Statistical Computing, Vienna, Austria, available at: http://www.R-project.org, last access: 27 July 2014.

Rickenmann, D.: Empirical relationships for debris flows, Nat. Hazards, 19, 47–77, 1999.

Savage, S. B. and Hutter, K.: The motion of a finite mass of granular material down a rough incline, J. Fluid Mech., 199, 177–215, 1989.

Scheidegger, A. E.: On the prediction of the reach and velocity of catastrophic landslides, Rock Mech., 5, 231–236, 1973.

GMDD					
8, 8193–8	8, 8193–8237, 2015				
r.random	walk v1.0				
M. Merç	M. Mergili et al.				
Title	Dogo				
The	Page				
Abstract	Introduction				
Conclusions	References				
Tables	Figures				
	_				
	►I				
	•				
Back	Close				
Full Scre	Full Screen / Esc				
Printer-friendly Version					
Interactive Discussion					
C () 87					

**Discussion** Paper

**Discussion** Paper

**Discussion** Paper

**Discussion** Paper

- Scheidl, C. and Rickenmann, D.: Empirical prediction of debris-flow mobility and deposition on fans, Earth Surf. Proc. Land., 35, 157–173, 2010.
- Smith, G. M., Davies, T. R., McSaveney, M. J., and Bell, D. H.: The Acheron rock avalanche, Canterbury, New Zealand morphology and dynamics, Landslides, 3, 62–72, 2006.
- <sup>5</sup> Sosio, R., Crosta, G. B., Chen, J. H., and Hungr, O.: Modelling rock avalanche propagation onto glaciers, Quaternary Sci. Rev., 47, 23–40, 2012.
  - Takahashi, T., Nakagawa, H., Harada, T., and Yamashiki, Y.: Routing debris flows with particle segregation, J. Hydr. Res., 118, 1490–1507, 1992.
  - Van Westen, C. J., van Asch, T. W. J., and Soeters, R.: Landslide hazard and risk zonation: why is it still so difficult?, B. Eng. Geol. Environ., 65, 176–184, 2005.

10

15

20

Vandre, B. C.: Rudd Creek debris flow, in: Delineation of Landslide, Flash Flood and Debris Flow Hazards in Utah, edited by: Bowles, D. S., Utah Water Research Laboratory, 117–131, 1985.

Voellmy, A.: Über die Zerstörungskraft von Lawinen, Schweizerische Bauzeitung, 73, 159–162, 212–217, 246–249, 280–285, 1955.

- Wichmann, V. and Becht, M.: Modelling of geomorphic processes in an Alpine catchment, in: Proceedings of the 7th International Conference on GeoComputation, Southampton, 2003.
- Wu, C. H., Chen, S. C., and Chou, H. T.: Geomorphologic characteristics of catastrophic landslides during typhoon Morakot in the Kaoping Watershed, Taiwan. Eng. Geol., 123, 13–21, 2011.
- Zimmermann, M., Mani, P., and Gamma, P.: Murganggefahr und Klimaänderung ein GIS basierter Ansatz, NFP 31 Schlussbericht, Hochschulverlag an der ETH, Zürich, 1997.



GM 8, 8193–8 r.random	GMDD 8, 8193–8237, 2015 r.randomwalk v1.0				
M. Merç	M. Mergili et al.				
Title	Page				
Abstract	Introduction				
Tables	Figures				
I⊲ ◄ Back Full Scre	►I ► Close een / Esc				
Printer-frier	ndly Version				
	Discussion				
	GM 8, 8193–8 r.random M. Merg Title Abstract Conclusions Tables I ■ Back Full Scre Printer-frier Interactive				

**Table 1.** Possibilities to define the break criteria. The flags provided through the command line or the user interface define the type of break criterion. RC = release coordinates (release from highest points of release areas), RP = release pixels (release from all pixels within release areas), • = relevant for most applications, • = relevant for some applications.

Flag	Mode	Rele RC	ease RP	Output	Validation	Multiple cores
q	Published relationships (see Table 2)	•		IIS	0	
т	Published relationship, multiple runs	٠		III	o	•
р	Impact probability	0	o	P	o	
p + n	Impact probability, multiple runs	o	0	PI	•	•
b	Reconstruction of observation	0	o	CDF		

<b>GMDD</b> 8, 8193–8237, 2015					
r.random	walk v1.0				
M. Merç	M. Mergili et al.				
Title	Page				
Abstract	Introduction				
Conclusions	References				
Tables	Figures				
14	►I.				
•	•				
Back	Close				
Full Scre	een / Esc				
Printer-frier	Printer-friendly Version				
Interactive Discussion					
CC D BY					

**Discussion Paper** 

**Discussion** Paper

**Discussion Paper** 

**Discussion Paper** 

**Table 2.** Types of rules and relationships supported by r.randomwalk.  $\omega_T$  = angle of reach, V = volume of motion,  $L_{max}$  = travel distance,  $Q_p$  = peak discharge at release,  $v_T$  = velocity at termination.

ID	Equation	Examples				
		Reference	Process	а	b	С
1	$\omega_T = a \ (2)$	Haeberli (1983); Huggel et al. (2002)	Debris flow from GLOF	11		
2	$\log_{10} \tan \omega_T = a \log_{10} V + b (3)$	Scheidegger (1973)	Rock avalanche	-0.15666	0.62419	
3	$L_{\rm max} = a V^b Z^c \ (4)$	Rickenmann (1999)	Debris flow	1.9	0.16	0.83
4	$\omega_T = a Q_p^b (5)$	Huggel (2004)	GLOF	18	-0.07	
5	$v_{\rm T} \leq 0$ (6)	Perla et al. (1980)				

**Table 3.** Tests of the parameters nruns,  $L_{\text{ctrl}}$ ,  $L_{\text{seg}}$ ,  $R_{\text{max}}$ ,  $f_{\beta}$ ,  $f_{d}$  and the pixel size. Where ranges of values are given in bold, the model is run with 100 random samples constrained by the minima and maxima indicated. Where values given in bold are separated by commas, exactly these values are tested.

Test	n <sub>walks</sub>	L <sub>ctrl</sub> (m)	$L_{seg}$ (m)	R <sub>max</sub> (m)	$f_{\beta}$	f <sub>d</sub>	Pixel size (m)
1 <sup>1,3</sup>	$10^0 - 10^6$	1000	100	10	5	2	10, 20, 40
2 <sup>2</sup>	10 <sup>4</sup>	50, 1000	10–150	1000	5	2	10, 20, 40
3 <sup>1,2,3</sup>	10 <sup>4</sup>	<b>50–1000<sup>2</sup></b>	100	1000 <sup>2</sup>	5	2	10, 20, 40 <sup>2</sup>
		1000–4000 <sup>1,3</sup>		10 <sup>1,3</sup>			20 <sup>1,3</sup>
4 <sup>1,3</sup>	10 <sup>4</sup>	1000	100	0–120	5	2	20
5 <sup>1,3</sup>	10 <sup>4</sup>	1000	100	10	0–10	2	20
6 <sup>1,3</sup>	10 <sup>4</sup>	1000	100	10	5	1–10	20

Test criteria: <sup>1</sup> impact area, <sup>2</sup> travel distance  $L_{max}$  (flag b), <sup>3</sup> AUC<sub>ROC</sub>.



**Discussion** Paper **GMDD** 8, 8193-8237, 2015 r.randomwalk v1.0 M. Mergili et al. **Discussion** Paper Title Page Abstract Introduction Conclusions References Tables Figures **Discussion Paper |**◀ Back Close Full Screen / Esc Printer-friendly Version **Discussion** Paper Interactive Discussion

**Table 4.** Empirical–statistical relationships and simple rules used for computing the IIS of GLOFs in the Gunt Valley (see Table 2).

IDTest	Relationship	Reference	Process
1 <sup>1</sup>	$\omega_T = 11^\circ$	Haeberli (1983); Zimmermann et al. (1997), Huggel et al. (2003, 2004)	Flood or debris flow
1 <sup>2</sup>	$\omega_T = 7^{\circ}$	Zimmermann et al. (1997)	
2 <sup>1,2</sup>	$\omega_T = 18 Q_p^{-0.07}$	Huggel (2004)	
3 <sup>1,2</sup>	$L_{\rm max} = 1.9 V^{0.16} Z^{0.83}$	Rickenmann (1999) <sup>3</sup>	
4 <sup>1,2</sup>	$\omega_T = 6^{\circ}$		Flood
5 <sup>1,2</sup>	$\omega_T = 4^{\circ}$		
6 <sup>1,2</sup>	$\omega_T = 2^\circ$	Haeberli et al. (1983), Huggel et al. (2004)	

 $^{1,2}$  ID(s) of test(s) where the rule or relationship is applied. <sup>3</sup> A bulking factor of 5 is applied to *V* (modified after lverson, 1997).



Figure 1. Logical framework of r.randomwalk. Only those components covered in the present article are shown.





Figure 2. Control length  $L_{ctrl}$  and segment length  $L_{seq}$ . (a) Application of  $L_{ctrl}$  to avoid sharp bending of the flow. (b) Smoothing of the flow path by introducing segments with maximum length of  $L_{seq}$ .





**Figure 3.** Model validation with an ROC Plot, relating the false positive rate  $r_{\text{FP}}$  and the true positive rate  $r_{\text{TP}}$ . This way of validation is suitable for predictor raster maps in the range 0–1, such as III or  $P_{\text{I}}$ . It can also be used for binary predictor maps (0 or 1). In such a case AUC<sub>ROC</sub> is computed from two threshold levels only.





**Figure 4.** Acheron Rock Avalanche. **(a)** Panoramic view, photo: M. Mergili, 28 February 2015. **(b)** Location and geometry.





**Figure 5.** Empirical–statistical relationship relating the angle of reach  $\omega_{\tau}$  to the volume V of avalanching flows of rock or debris. The data are compiled from Scheidegger (1973), Legros (2002), Jibson et al. (2006), Evans et al. (2009), Sosio et al. (2012), Guo et al. (2014).



**Discussion** Paper

**Discussion** Paper

Discussion Paper



**Figure 6.** Location, terrain and landslide inventory of the Kao Ping Watershed, Taiwan. Comparison of the satellite images illustrates the landslide-induced land cover changes associated with the Typhoon Morakot. The landslide inventory builds on the interpretation of the FORMOSAT-2 imagery.





**Figure 7.** The test area in the Gunt Valley, Tajikistan. (a) Location, topography, glaciers and lakes. (b) Proglacial lake in the upper Varshedzdara Valley, photo: M. Mergili, 18 August 2011.





**Figure 8.** Results of the Tests 1–3 (number of test indicated in the yellow circle). Number of random walks plotted against (a) the impact area and (b) the area under the ROC Curve. (c) Computed travel distance  $L_{max}$  as a function of  $L_{seg}$  (in the legend, the corresponding value of  $L_{ctrl}$  is given in brackets). (d) Computed  $L_{max}$  as a function of  $L_{ctrl}$ .





**Figure 9.** Sensitivity of impact area and  $AUC_{ROC}$  to selected input parameters. The numbers of the corresponding tests (see Table 3) are indicated in the yellow circles. (a) Control distance  $L_{ctrl}$ . (b) Maximum run-up height  $R_{max}$ . (c) Slope factor  $f_{\beta}$ . (d) Direction factor  $f_d$ .





**Figure 10.** Impact indicator score for the Acheron Rock Avalanche. (a) Classified III map. (b) ROC Plot, considering the full study area. (c) ROC Plot, considering only those areas with either an observed impact or III > 0, or both.





**Figure 11.** Histograms, probability densities and cumulative densities of  $\omega_{T}$  of mass movements in the test area in the Kao Ping Watershed. (a) Result for a set of  $10^{4}$  random walks started from the highest point of each landslide (Test 1). (b) Result for a set of  $10^{4}$  random walks started from each pixel within the release areas of all landslides (Test 2).





**Figure 12.** Impact probability in the range 0–1. **(a)** Result of Test 1 (random walks starting from the highest point of each landslide, cumulative density according to Fig. 11a). **(b)** Result of Test 2 (random walks starting from all release pixels, cumulative density according to Fig. 11b).





Figure 13. ROC Plots illustrating the prediction quality of Tests 1 and 2 for the full and for the reduced area (see Fig. 3). (a) Full area, Test 1. (b) Full area, Test 2. (c) Reduced area, Test 1. (d) Reduced area, Test 2.





Figure 14. Possible GLOF impact areas in the Gunt Valley, Tajikistan. (a) Impact indicator score derived with Test 1. (b) Impact indicator score derived with Test 2. (c) Impact frequency derived with Test 1, classified by quantiles.

