

Efficiently modelling urban heat storage: an interface conduction scheme in an urban land surface model (aTEB v2.0)

Mathew J. Lipson¹, Melissa A. Hart¹, Marcus Thatcher²

¹Climate Change Research Centre, UNSW and ARC Centre of Excellence for Climate System Science

²CSIRO Marine and Atmospheric Research, Aspendale, Australia

Correspondence to: M. Lipson (m.lipson@unsw.edu.au)

Summary

This document is the authors response to the Referee reviews and discussion of the manuscript:

<http://www.geosci-model-dev-discuss.net/gmd-2016-240/>

Three comments were received, and will be addressed in order:

- SC1: Executive Editor Comment from Astrid Kerkweg on 24 October 2016
- RC1: Anonymous Referee #1 on 13 December 2016
- RC2: Anonymous Referee #2 on 21 December 2016

The authors response is structured in three parts:

Part A: Referee and Editor comments are addressed by the authors, and a short description of manuscript changes is provided (if applicable).

Part B: Other minor changes to the manuscript are noted, made by the authors to improve clarity.

Part C: The complete revised manuscript with tracked changes comparing previous and revised versions.

Page and line references (P# L#) are listed for original manuscript (in red with referee comments) and for the revised manuscript (in black with author response).

Analysis and plotting code has also been updated to accommodate referee comments. The original and revised code and figures can be compared here: <https://bitbucket.org/matlipson/ics/commits/all>

Part A – Authors response to comments

RC1: Anonymous Referee #1

This paper presents a new heat conduction scheme which can be implemented in the urban land surface models and compares it with a well-established and widely used scheme in current land surface models. The study is interesting and in the scope of the Geoscientific Model Development. The author(s) made a reasonable effort and the research was carefully conducted. I think that this paper could be published promptly because the new proposed scheme and the discussions in the paper are helpful for the developers and users of the urban land surface models. However, there are some flaws in the manuscript, which I think that the authors should consider to revise before the manuscript is finally accepted.

Major: 1. One of my major concerns is about the structure of the manuscript. I feel a little confused when I read through the manuscript and had to go back and forth for a few times. I think it is clearer that if the authors can restructure section 2, into which part of section 3 and 4 can be moved. The new section 2 serves as a Methods section, where the authors introduce the two conduction schemes, the aTEB model, modeling setup, idealized method, as well as the data used. Then section 3 and section 4 serve as results sections to discuss about the idealized results and observational results.

We thank referee # 1 for their advice regarding the structure of the manuscript, which we have adopted. We feel these changes will help make the manuscript easier to read and understand. The parts of Section 3 and 4 which described methods and model description has been moved to Section 2. The remaining parts of Section 3 and 4 have been combined into a results Section 3. Discussion and conclusion Section 5 has become Section 4 and some other section titles have been revised. The old (left) and new outlines (right) are:

▼ 1 Introduction	▼ 1 Introduction
1.1 Measuring storage heat flux in cities	1.1 Measuring storage heat flux in cities
1.2 Simulating storage heat flux in cities	1.2 Simulating storage heat flux in cities
1.3 Material thermal parameters	1.3 Material thermal parameters
▼ 2 Description of conduction representations	▼ 2 Methods
2.1 Half-layer scheme	▼ 2.1 Conduction representations
2.2 Interface scheme	2.1.1 Half-layer scheme
2.3 Exact solution	2.1.2 Interface scheme
▼ 3 Idealised evaluation	2.1.3 Exact solution
3.1 Idealised method	2.2 Idealised evaluation methods
▼	▼ 2.3 Urban model evaluation methods
3.2.1 Idealised results: high-resolution simulation	2.3.1 Description of urban model: aTEB
3.2.2 Idealised results: realistic material parameters	2.3.2 Observational data
3.2.3 Idealised results: typical material parameters	▼ 3 Results
▼ 4 Observational evaluation	▼ 3.1 Idealised evaluation results
▼ 4.1 Observational methods	3.1.1 High-resolution simulation
4.1.1 Description of urban model: aTEB	3.1.2 Realistic material parameters
4.1.2 Observational data	3.1.2 Typically modelled parameters
▼ 4.2 Observational results	▼ 3.2 Urban model results
4.2.1 Observational results: heat storage	3.2.1 Impact on heat storage
4.2.1 Observational results: other fluxes	3.2.2 Impact on other fluxes
5 Discussion and Conclusion	4 Discussion and Conclusion

[Major] 2. The authors use two methods to assess the performance of the two schemes: idealized environment and observational datasets. When using observational dataset, the improvement in Qs and other fluxes when changing from half-layer scheme to interface scheme are rather small (< 5 W m⁻²). I wonder whether the magnitudes of these improvements are statistically significant? Could the authors provide any statistics to prove that?

As suggested, we have extended the study to test the statistical significance of mean improvements for all fluxes (Table 3). We undertake a paired, two-sided T-test for the null hypotheses that two dependent samples have the same mean values (i.e. we test the significance of the improvement of the interface scheme). In each case, the 95% confidence interval is reached. We note the significance in the text (last line of Taylor diagram section, previously P13 L6), and in the body and caption of Table 3.

Minor: 1. Page 2 Line 3: “the alternate method” -> “the alternative method”

P2 L2: Sentence has been reworded and “the alternate method” removed.

[Minor]2. Captions in Figure 4 and Figure 5: (a) flux density and (b) normalized error. I suppose the authors mean: (top panel) flux density and (bottom panel) normalized error

Yes, that was the intention, it has been revised.

Again, we thank the reviewer for these comments.

RC2: Anonymous Referee #2

This paper is concerned with the storage heat flux in areas with large thermal mass and multiple surface layers. It provides a really nice, through and useful analysis of the impact of where temperature nodes are in a layered system. My comments are very minor and easily addressed.

We thank Referee # 2 for these positive comments. The thoroughness of their review has improved the paper.

1) Notation is confusing for the storage heat flux as two sets of symbols are used for what should be the same (as the model is being evaluated against it- but is referred to differently between the model and observations

a. P1 L20 should be ΔQ_S (that notation throughout)

P1 L20: We agree and have changed notation to ΔQ_S throughout.

b. P2 L23 - Δ changing notation – Infer that the Δ is related to the residual whereas in fact for both it should be the net change in all components of the system e.g. trees, air, as well as the built materials. The observational method of a residual difference is not related to Δ . The notation is confusing relative to the net change in storage – the authors could create a subscript to distinguish the two but refer to it with the same notation or refer to observed as RES (residual) as commonly done

Revised P2 L24: In the original manuscript, we made a distinction between modelled net storage flux (Q_S) and observed net storage flux calculated as a residual (ΔQ_S). As noted the notation differs from established forms which has led to confusion, and on reflection is not necessary. We now refer only to ΔQ_S , meaning net storage heat flux density. Where a distinction is important, we note whether it is observed or modelled.

2) P2 L2 – there are multiple methods - so it is an additional method

Revised P2 L2: We have amended this sentence to make clear we are comparing a new alternative method with a well-established method.

3) P3 L5 – cite the original Grimmond et al. 1991

P3 L5: Done

4) P3 L12 – references should be in chronological order (throughout)

P3 L11: Done

5) P3 L29 – Homogenous – reference examples

Revised P3 L29: We have reworded sentence to make clearer the distinction between homogenous and composite materials, and updated other instances of “layered” materials to “composite” materials throughout. We have also changed ‘some models use...’ in this line to ‘modellers sometimes describe...’ to make a distinction that it is often a modellers choice to represent materials as homogenous (as opposed to being hardwired in a model). Lastly, we have moved the database descriptions (CLMU, SITE etc) to an Appendix for clearer flow of the article.

6) P4 L3 – Jackson et al. (date)

P14 L19: Done

7) P6 L1&2 – int – for the second R_{int}

P5 L9: Done

8) P6 L23 – for the respective time step?

P6 L23: Deleted lines 20-23 as they are not necessary and are confusing.

9) P8 L25 I assemblies or assemblages?

P10 L2: Assemblies, as an ordered group of components that work together, rather than an unordered assemblage.

10) P8 L24 – give accessible reference location

P10 L2: Done, referenced Fig. D.1

11) P9 line 2 – are representative of? The central tendency of ... later in sentence ‘represent’ or ‘are for the ...’

P10 L9: Done, replaced “are representative of” with “represent”.

12) P9/L18 – values have been multiplied by 100 % to be made a percent

P10 L24: We are unclear as to what change was required as the values on p9 are in the a 0-100% range.

13) P9 L19 – reword sentence

P10 L25: Done.

14) P10 – heading observational methods – some aspects have already been introduced, why this heading here? And why is the description of the model under observations?

Manuscript has been restructured per Referee #1 comments (see RC1 response). This section moved to P8 L16.

15) P11 L5 – net all-wave radiation

P8 L18: Done.

16) P11 L25 – notation now includes Δ

P11 L5: All Q_S now referred to as ΔQ_S , see response to 1b).

17) P12 L16 – define centred RMSE

P11 L29: Referenced Taylor (2001).

18) P14 top paragraph – consider work Salamanca, F., E.S. Krayenhoff, A. Martilli. 2009: On the derivation of material thermal properties representative of heterogeneous urban neighbourhoods, J. Appl. Meteorol. Climatol. 48, 1725-1732

P13 L15: The authors are aware of the interesting work by Salamanca et. al (2009), which considers various methods to aggregate material thermal properties (depth, conductivity and heat capacity) to give an overall homogenous material that is meant to be representative of patches of different urban materials. However, the current manuscript uses ‘typically modelled’ material thermal parameters sourced from previously published studies, and avoids creating new sets of thermal parameters. Therefore, the method described in Salamanca et. al (2009) was not considered relevant in this study.

19) P14 L21 enhance rather than benefit?

P13 L29: We feel in this case benefit is more appropriate, as enhance may suggests additional features, which is not the case.

20) Figure and Table caption in general need to be standalone so the material can be understood

Done, details below.

21) Appendix A – Tables A1 and A2 give references or basis for data sources here or indicate where these are given in the text. SITE, WRF uZE aTEB – need to be defined to

Done.

22) Figures 2 onwards – - units should have space between the dimensions. The extra headers should be removed (difference between talk and paper presentation)

Done

23) Figure 4 and 5 – give more details of types of conditions used

Done

24) Figure 6 – Caption is not complete enough to be stand alone. Need correct spacing on units $W m^{-2}$ – - fix units within plots

Done

25) Figure 7 – Label Y axis

Done

We thank the reviewer for these valuable comments.

Part B – Other changes

1) P1 L15

P1 L14: Added ‘of common’

2) P1 L19-25

P1 L19-25: Reworded first sentence in Introduction for clarity. Moved second sentence on land surface models down to P1L26 to locate with introduction of model intercomparison. Deleted some unnecessary words in third sentence for simplicity.

3) P2 L11

P2 L12: Where appropriate throughout replaced “surfaces” with “materials” to make clearer distinction with the skin surface of urban materials.

4) P2 L15

P2 L16: Added net (Δ) to advection flux Q_A for consistency with Referee #2 comment on net storage flux ΔQ_S .

5) P3 L6-9

P3 L6-9: Reworded two sentences for clarity. Added reference for PILPS-Urban. Made clearer reference to Best and Grimmond 2014b finding on methods for calculating net heat storage.

7) P7 L11 (end of 2.3 Exact Solutions)

P6 L20: Added the following paragraph to better describe the effective heat capacity presented in Fig. 3 and discussed in the paper:

Periodic areal heat capacity (ISO 13786:2007) is a useful measure of a composite materials ability to store heat over a sinusoidal cycle. It is a better measure than overall heat capacity or surface thermal admittance as it accounts for the periodic penetration depth of each material layer (for thick composites) as well as heat lost through transmittance (for thin composites). It can be calculated exactly as:

$$\kappa = \frac{P}{2\pi} \left| \frac{H_{22}^{-1}}{H_{12}} \right|, \quad (20)$$

with units $J m^{-2} K^{-1}$.

8) P15 L1

P14 L10: Added link to git repository in Code/ data availability.

11) Appendix A&B

Split into two appendices, A for material database information, B for model parameters. Moved material database description from body of manuscript to Appendix A (previously in Section 1.3). Updated other Appendix names and references. Renamed Table A2 to Table A1. Deleted 'transmittance' information from Table as not discussed in the manuscript.

9) Appendix C

Added wind speed information to formulae A2 & A3.

10) Figure 7

Made changes to improve clarity of Taylor diagram including adding y-axis label (per RC2 comment 25), adding label for cRMSE and making panel titles bold to stand out.

Part C – Revised Manuscript Changes

All changes from the originally submitted manuscript, with changes marked:

- Deleted items are red and struck out
- Added items are blue and underlined
- Moved items are green, either ~~struck out~~ (moved from) or underlined (moved to).

Efficiently modelling urban heat storage: an interface conduction scheme in ~~the aTEB~~ an urban land surface model (aTEB v2.0)

Mathew J. Lipson¹, Melissa A. Hart¹, Marcus Thatcher²

¹Climate Change Research Centre, UNSW and ARC Centre of Excellence for Climate System Science

²CSIRO Marine and Atmospheric Research, Aspendale, Australia

Correspondence to: M. Lipson (m.lipson@unsw.edu.au)

Abstract. Intercomparison studies of models simulating the partitioning of energy over urban land surfaces have shown the heat storage term is often poorly represented. In this study, two implicit discrete schemes representing heat conduction through urban materials are compared. We show that a well-established method of representing conduction systematically underestimates the magnitude of heat storage compared with exact solutions of one-dimensional heat transfer. We propose an alternative method of similar complexity that is better able to match exact solutions at typically employed resolutions. The proposed interface conduction scheme is implemented in an urban land surface model and its impact assessed over a 15-month observation period for a site in Melbourne, Australia, resulting in improved overall model performance for a variety of common material parameter choices and aerodynamic heat transfer parameterisations. The proposed scheme has the potential to benefit land surface models where computational constraints require a high level of discretisation in time and space, for example at neighbourhood/city scales, and where realistic material properties are preferred, for example in studies investigating impacts of urban planning changes.

1 Introduction

The climate of cities differ from surrounding natural landscapes because urban structures change the terms of the surface energy balance. Urban structures change the climate of cities by affecting the partitioning of energy from natural and anthropogenic sources (Oke, 1982). As climate affects human health, comfort and the energy use of buildings, many land surface models have been developed to simulate the impacts of different urban forms (Grimmond et al., 2009). An One important term in the energy balance of atmosphere surface interactions is storage heat flux density (ΔQ_S): the net flow of heat per unit area into and out of materials. In highly urbanised areas, ΔQ_S becomes the dominant term of the daytime urban energy balance (Cleugh and Grimmond, 2012). At night, During the day, excess-heat is absorbed by dense urban materials and at night is released back into the atmosphere. The altered behaviour of ΔQ_S fundamentally affects environmental processes such as atmospheric stability, the evolution of the boundary layer, convection, and pollution dispersion, and is key in establishing urban heat islands (Barlow, 2014). As climate affects human health, comfort and the energy use of buildings, many land surface models have been developed to simulate the impacts of different urban forms (Grimmond et al., 2009). However, the most recent urban model intercomparison project found most participants significantly under-represented heat storage, with average midday ΔQ_S bias errors of -50 W m^{-2} (Best and Grimmond, 2014a). In a world of rapid urbanisation and changing global climate, researchers and planners are interested in efficient and accurate models that are able to investigate urban climate impacts. Improving heat storage representations at the neighbourhood to city-scale will benefit those studies. This paper analyses the performance of a well-established method to represent heat storage in urban land surface models and compares it with a proposed ~~proposes an~~ alternative method ~~to represent heat storage in urban land surface models~~. Although the proposed scheme is similar in complexity and design to a current well-established method, the analysis undertaken here indicates the alternate method it is more accurate at relevant resolutions and reduces overall energy flux errors of an urban land surface model compared with the established approach. The paper is structured as follows. Section 1 introduces ~~Further in this introduction, k~~ key issues in measuring and modelling urban heat storage ~~are discussed~~. Section 2 ~~describes the~~ evaluated conduction schemes and evaluation methods. Section 3 ~~analyses~~ presents scheme results for a simple idealised environment, and within an urban model and subjected to observational forcing ~~their performance in isolation in an idealised environment~~. Section 4 ~~assesses their impact when implemented in an urban land surface model~~. Section 5 discusses and concludes findings.

1.1 Measuring storage heat flux in cities

In simple environments it is possible to measure ΔQ_S directly through a network of heat flux plates (Nunez and Oke, 1977), but the variety of urban materials, orientations, sky-view factors and internal building environments in a typical city make direct measurement at ~~desired~~ neighbourhood scales impractical. In order to practically account for the full diversity of ~~surfaces~~ materials in a heterogeneous urban landscape, the most commonly accepted method to measure ΔQ_S at the neighbourhood scale is by calculating heat storage as a residual of the urban energy balance (Roberts et al., 2006). Following Oke (1988) a full representation of the urban energy balance (in W m^{-2}) is:

$$Q^* + Q_F = Q_H + Q_E + \Delta Q_S + \Delta Q_A, \quad (1)$$

where inputs of net all-wave radiation flux (Q^*) and anthropogenic heat flux (Q_F) are balanced by sensible and latent turbulent heat fluxes (Q_H and Q_E), net heat storage (ΔQ_S), and net heat advection flux (ΔQ_A). Using radiometers and eddy covariance techniques, Q^* , Q_H and Q_E can be measured directly, and are considered representative of the neighbourhood if instruments are at a sufficient height above ground where effects of individual roughness elements are blended (Cleugh and Oke, 1986). ΔQ_A is often considered negligible and

excluded if areas adjoining observation sites have similar urban characteristics (Roberts et al., 2006). Q_F can be estimated through energy use and population density analysis (e.g. Sailor and Lu, 2004). Then, rearranging Eq.

(1) with known terms on the right, residual ~~(A)~~ heat storage is:

$$\Delta Q_S = (Q^* + Q_F) - (Q_H + Q_E).$$

(2)

The residual approach has the inherent problem of accumulating all observational errors, which can be significant for turbulent fluxes (Wilson et al., 2002). Estimates of Q_F and assumptions regarding ΔQ_A add to overall uncertainty. The daytime errors in ΔQ_S observations used in this study have previously been estimated at 23%, doubling at night (Best and Grimmond, 2014b). Given the significant observational uncertainties, this study first evaluates conduction schemes with exact solutions to one-dimensional heat transfer, before comparing with observations of ΔQ_S calculated as a residual of the urban energy balance.

1.2 Simulating storage heat flux in cities

At scales of individual buildings, ΔQ_S of walls and roofs can be accurately modelled by solving the three-dimensional heat conduction equation at high resolution. However, simulating urban weather and climate over larger scales requires simplification in order to keep computation practical (Martilli, 2007). Some urban models replace heat transfer calculations with empirical functions of net radiation (Grimmond et al., 1991) ~~(e.g. Grimmond and Oke, 2002)~~, or with idealised representations like the force-restore method (e.g. Porson et al., 2010). ~~However the most~~ Another common method, used by 23 of 32 most participants of the First International Urban Land Surface Model Comparison Project (PILPS-Urban), is to calculate a simplified-discretised version of the heat conduction equation (Grimmond et al., 2010) ~~(Best and Grimmond, 2014b)~~. Best and Grimmond (2014b) found models using this method were generally better at simulating Q_{S_z} ~~Although although all categories of models this method provided a benefit over other methods analysed, models utilising it failed to predict~~ ΔQ_S within-outside observational error in more than 50% of daytime intervals. Overall, ~~models~~ partitioned too little incoming energy into storage and too much into other fluxes, a result supported by a previous intercomparison at a different site (Grimmond et al., 2010; Best and Grimmond, 2015). Although other studies evaluating individual urban models have found good agreement between simulated and observed ΔQ_S (e.g. Roberts et al., 2006), PILPS-Urban showed that most models have difficulty predicting ΔQ_S at sites that had not previously been used to evaluate a model, where no parameter optimisation had been undertaken. This study suggests a method to improve ΔQ_S prediction using an urban model that is conceptually similar to many participants of PILPS-Urban.

1.3 Material thermal parameters

A potential weakness in evaluating urban model performance is the wide variety of parameters that could describe urban materials. Urban models are sensitive to material thermal parameter variation, particularly the magnitude and phase of storage heat flux and sensible heat flux (Oleson et al., 2008b). Selecting the best thermal parameters is not necessarily straightforward; as land surface models are a simplified representation of reality, model material parameters should only be viewed as abstract representations of observed physical quantities (Gupta et al., 1999). Researching and inputting realistic values based on local material parameters requires considerable effort, and can result in little improvement to performance, or even degrade it (Loridan and Grimmond, 2012). In PILPS-Urban, average model performance in ΔQ_S worsened as more site-specific (realistic) material thermal properties were provided to participants (Best and Grimmond, 2014b). As such, modellers sometimes use material parameters that do not match with the realities of the simulation site, but produce results that match well with observations (i.e. optimised parameters). This may pose problems for studies at new sites with different conditions, and studies that wish to ascertain impacts of changing urban materials. There is therefore interest in improving ΔQ_S performance-prediction using more realistic material parameters. Additionally, ~~some models~~ modellers sometimes describe urban materials with-use a single set of

material ~~thermal~~ parameters ~~to describe~~ (~~homogenous materials~~) ~~homogenous urban surfaces~~, while others allow ~~describe~~ distinct layers ~~with~~ ~~with~~ different ~~thermal~~ parameters (~~composite materials~~) ~~composing a composite assembly~~. In order to cover a range of modelling possibilities, we evaluate optimised, realistic, homogenous and ~~layered~~ ~~composite~~ material parameters by drawing from five material dataset sources, described ~~below and~~ in Appendix A.

CLMu (realistic, layered): From a dataset of global urban characteristics (Jackson et al., 2010) intended for use in the Community Land Model—Urban (CLMU) (Oleson et al., 2008a), or other global climate models. The database catalogues the properties of 32 common walls and roofs from around the world. Attempts are made by Jackson et al. (2010) to reconcile the whole wall/roof thermal conductivity with real world values by estimating the effects of thermal bridging, air leakage, and poor construction. For our analysis, all 10 layer composite walls and roofs were collapsed through each iteration down to two layers using depth weighted averages of conductivity and heat capacity, resulting in 288 representations of walls and roofs of varying thermal characteristics and complexity.

SITE (realistic, layered): As presented in PILPS Urban Phase 2 (Grimmond et al., 2011). Characteristics were derived from an area and depth weighted average of material thermal properties at the observation site. Roofs and walls were an aggregate of metal, terracotta, concrete and asbestos, insulation, lightweight framing and plasterboard, separated into four layers: external skin, structure, insulation and internal lining.

WRF (optimised, homogenous): From the WRF/urban integrated urban modelling system v3.2 (Chen et al., 2011), which includes the SLUCM and BEP urban schemes. In WRF, three default sets of parameters are available for various densities of urban land cover, here we use the low intensity residential set following the observation site’s classification by Loridan and Grimmond (2012). The WRF default parameters represent a generic homogenous material with a heat capacity and conductivity similar to lightweight concrete throughout.

UZE (optimised, homogenous): From updated WRF/urban parameters described in Loridan and Grimmond (2012) based on results of a multi-objective optimisation algorithm to minimise root mean square error (RMSE) over 15 urban locations. New parameter values were recommended for three categories of urban areas based on Urban Zone for Energy exchange (UZE: Loridan and Grimmond, 2011) and were subsequently included in releases of WRF/urban as an optional dataset. We use the medium urban category following the observation site’s classification by Loridan and Grimmond (2012).

aTEB (optimised, layered): From the ECOCLIMAP database (Masson et al., 2003) on which TEB (Masson, 2000) defaults are based, but with increased layer depths per Thatcher and Hurley (2012). The walls and roofs are not representative of typical building methods in Australia, but nonetheless give reasonable results for generic Australian cities. The roof is a layered composite with thermal conductivity and heat capacity of dense concrete, aerated concrete and insulation; the walls a composite of concrete and insulation and the road/soil of asphalt and dry soil.

2 Methods

2.1 Description of ~~e~~Conduction representations

Three calculation methods of heat storage are compared: two discrete schemes and an exact solution. The two discrete schemes lump a material’s heat capacitance at a temperature node and calculate solutions numerically at each timestep. The exact method calculates continuous harmonic solutions to a periodic forcing. All three solve Fourier’s law:

$$q = \lambda \frac{\partial T}{\partial a}, \quad (3)$$

and the one-dimensional continuity equation:

$$C \frac{\partial T}{\partial t} = \frac{\partial q}{\partial a}, \quad (4)$$

where q is the conduction heat flux density [W m^{-2}], C is volumetric heat capacity [$\text{J m}^{-3} \text{K}^{-1}$], λ the thermal conductivity [$\text{W m}^{-1} \text{K}^{-1}$], T the temperature [K], d the depth [m], C is volumetric heat capacity [$\text{J m}^{-3} \text{K}^{-1}$] and t is time [s].

2.1.1 Half-layer scheme

A common discretised approach is to locate the temperature node centrally within a homogenous layer – a half-layer scheme (Fig. 1 (a)). This approach is used in many urban land surface schemes, for example Town Energy Budget (TEB) (Masson, 2000), Single-Layer Urban Canopy Model (SLUCM) (Kusaka et al., 2001), Building Effect Parameterization (BEP) (Martilli et al., 2002), Community Land Model – Urban (CLMU) (Oleson et al., 2008a), Vegetated Urban Canopy Model (VUCM) (Lee and Park, 2008), and the Australian Town Energy Budget (aTEB) (Thatcher and Hurley, 2012). Models utilising this method vary in their spatial and temporal resolution, but typically resolve between 1 and 10 substrate temperature nodes, at between 5 and 60 minute timesteps (Grimmond et al., 2009, 2010). The half-layer method is based on well-established land surface models representation of thermal conduction through soil (e.g. Oleson et al., 2010), and is also used in multi-layer snow and sea ice models (e.g. West et al., 2016).

A discretised form of the conduction equation (Eq. 3) is:

$$q_{k,k+1}^m = \frac{\lambda_{k,k+1}}{d_{k,k+1}} (T_k^m - T_{k+1}^m), \quad (5)$$

where T_k^m is the temperature at the k th node at timestep index m . Conduction between temperature nodes occurs through material layers with homogenous and invariant thermal characteristics. Where two adjacent layers i and $i + 1$ have different depths d or conductivities λ , then the half-layer scheme will represent an effective conductance [$\text{W m}^{-2} \text{K}^{-1}$] between temperature nodes k and $k + 1$ as:

$$\frac{\lambda_{k,k+1}}{d_{k,k+1}} = \frac{1}{\frac{1}{2}(\frac{d_i}{\lambda_i} + \frac{d_{i+1}}{\lambda_{i+1}})} = \frac{1}{\frac{1}{2}(R_i + R_{i+1})}, \quad (6)$$

where resistance $R_i = d_i / \lambda_i$ (with $i = k$ hereafter, i is dropped). Then, combining Eq. (5) and (6) with the discretised form of the continuity Eq. (4) over timestep length Δt , the general implicit formulation of the half layer scheme is:

$$C_k d_k \left(\frac{T_k^{m+1} - T_k^m}{\Delta t} \right) = q_{k-1,k}^{m+1} - q_{k,k+1}^{m+1} = \frac{T_{k-1}^{m+1} - T_k^{m+1}}{\frac{1}{2}(R_{k-1} + R_k)} - \frac{T_k^{m+1} - T_{k+1}^{m+1}}{\frac{1}{2}(R_k + R_{k+1})}, \quad (7)$$

Net Hheat storage flux density through to the next timestep (ΔQ_S^{m+1}) is the sum of the change in energy stored in individual layers:

$$\Delta Q_{S, \text{half-layer}}^{m+1} = \sum_{k=1}^n \frac{C_k d_k (T_k^{m+1} - T_k^m)}{\Delta t}. \quad (8)$$

Energy conservation is demonstrated by the equivalency of Eq. (7) and Eq. (8) for layers 1 to n , as inner conduction fluxes ($q_{1,2}^{m+1} \dots q_{n-1,n}^{m+1}$) cancel, leaving heat storage flux density equal to outer conduction terms:

$$\Delta Q_{S, \text{half-layer}}^m = q_{ext}^m - q_{int}^m = \frac{T_{ext}^m - T_1^m}{\frac{1}{2}R_1 + R_{ext}} - \frac{T_n^m - T_{int}^m}{\frac{1}{2}R_n + R_{int}}, \quad (9)$$

where q_{ext}^m is the external admittance flux which drives transience in the system, q_{int}^m is the transmittance flux into the building, T_{ext}^m / T_{int}^m are external/ internal environmental temperatures, and R_{ext} / R_{int} are external/ internal surface thermal resistances.

2.1.2 Interface scheme

While the half-layer scheme lumps capacitance at the centre of layers, an alternative approach is to lump capacitance at the interface between layers (Figure 1(b)). Since the paths of conduction between nodes are now completely within homogenous layers, Eq. (6) simplifies to:

$$\frac{\lambda_{k,k+1}}{d_{k,k+1}} = \frac{\lambda_i}{d_i} = \frac{1}{R_i'} \quad (10)$$

where $i = k$. The capacitance of the temperature node now takes half the value of the adjacent layers; in effect, we have swapped the need for an effective conductance for an effective capacitance. The general implicit formulation for the interface scheme is:

$$\left(\frac{C_{k-1}d_{k-1} + C_k d_k}{2} \right) \left(\frac{T_k^{m+1} - T_k^m}{\Delta t} \right) = q_{k-1,k}^{m+1} - q_{k,k+1}^{m+1} = \frac{T_{k-1}^{m+1} - T_k^{m+1}}{R_{k-1}} - \frac{T_k^{m+1} - T_{k+1}^{m+1}}{R_k}, \quad (11)$$

with outer temperature nodes represented by half the outer layer heat capacity only, i.e. at $k = 1$; $C_0 d_0 = 0$ and $k = n + 1$; $C_{n+1} d_{n+1} = 0$ for an n layer system.

Total heat storage flux density for the interface scheme is:

$$\Delta Q_{S,interface}^{m+1} = \frac{1}{2} \frac{C_1 d_1 (T_1^{m+1} - T_1^m)}{\Delta t} + \sum_{k=2}^n \frac{1}{2} \frac{(C_{k-1} d_{k-1} + C_k d_k) (T_k^{m+1} - T_k^m)}{\Delta t} + \frac{1}{2} \frac{C_n d_n (T_{n+1}^{m+1} - T_{n+1}^m)}{\Delta t}. \quad (12)$$

Again, energy conservation is demonstrated through the equivalency of Eq. (11) and Eq. (12), which after cancelling inner conduction terms leaves heat storage flux density equal to outer conduction terms:

$$\Delta Q_{S,interface}^m = q_{ext}^m - q_{int}^m = \frac{T_{ext}^m - T_1^m}{R_{ext}} - \frac{T_{n+1}^m - T_{int}^m}{R_{int}}. \quad (13)$$

For the half-layer and interface conduction schemes, net heat storage calculated as a sum of the change of energy in each layer is equal to the sum of fluxes at external and internal surfaces. Although energy is conserved within each scheme, Eq. (9) and (13) show the calculated net heat storage fluxes are different.

2.1.3 Exact solution

Here we use the admittance procedure (Butcher, 2006; Davies, 1973), which calculates exact solutions to planar heat transfer through a series of homogenous layers when subject to a steady sinusoidal forcing on one side, with a fixed temperature on the other. The international standard ISO 13786:2007 documents the method. The exact solution to the heat storage flux density $\Delta Q_{S,exact}$ for a composite wall is the [net of outer conduction terms: the admittance flux density minus the transmittance flux density](#):

$$\Delta Q_{S,exact}(t) = q_{ext}(t) - q_{int}(t) = \left| \frac{1-H_{22}}{H_{12}} \right| \sin \left(\frac{2\pi}{P} t + \arg \left(\frac{1-H_{22}}{H_{12}} \right) \right), \quad (14)$$

where P is the period of sinusoidal forcing and H_{12} and H_{22} are components of a 2×2 complex-valued heat transfer matrix calculated via multiplication of individual heat transfer matrices over n homogenous layers:

$$\begin{pmatrix} H_{11} & H_{12} \\ H_{21} & H_{22} \end{pmatrix} = \begin{pmatrix} 1 & -R_{ext} \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} Z_{11}^1 & Z_{12}^1 \\ Z_{21}^1 & Z_{22}^1 \end{pmatrix} \cdot \begin{pmatrix} Z_{11}^2 & Z_{12}^2 \\ Z_{21}^2 & Z_{22}^2 \end{pmatrix} \cdots \begin{pmatrix} Z_{11}^{n-1} & Z_{12}^{n-1} \\ Z_{21}^{n-1} & Z_{22}^{n-1} \end{pmatrix} \cdot \begin{pmatrix} Z_{11}^n & Z_{12}^n \\ Z_{21}^n & Z_{22}^n \end{pmatrix} \cdot \begin{pmatrix} 1 & -R_{int} \\ 0 & 1 \end{pmatrix} \quad (15)$$

where R_{ext} and R_{int} are external and internal surface thermal resistances and Z_{ab}^i a component of the i th layer heat transfer matrix, from outside in. Components of the i th heat transfer matrix are:

$$Z_{11}^i = Z_{22}^i = \cosh \frac{d_i}{\delta_i} \cos \frac{d_i}{\delta_i} + j \sinh \frac{d_i}{\delta_i} \sin \frac{d_i}{\delta_i}, \quad (16)$$

$$Z_{12}^i = -\frac{\delta_i}{2\lambda_i} \left[\sinh \frac{d_i}{\delta_i} \cos \frac{d_i}{\delta_i} + \cosh \frac{d_i}{\delta_i} \sin \frac{d_i}{\delta_i} + j \left(\cosh \frac{d_i}{\delta_i} \sin \frac{d_i}{\delta_i} - \sinh \frac{d_i}{\delta_i} \cos \frac{d_i}{\delta_i} \right) \right], \quad (17)$$

$$Z_{21}^i = -\frac{\lambda_i}{\delta_i} \left[\sinh \frac{d_i}{\delta_i} \cos \frac{d_i}{\delta_i} - \cosh \frac{d_i}{\delta_i} \sin \frac{d_i}{\delta_i} + j \left(\sinh \frac{d_i}{\delta_i} \cos \frac{d_i}{\delta_i} + \cosh \frac{d_i}{\delta_i} \sin \frac{d_i}{\delta_i} \right) \right], \quad (18)$$

where j is the imaginary unit and:

$$\delta_i = \sqrt{\frac{\lambda_i P}{\pi c_i}}, \quad (19)$$

is the periodic penetration depth of the i th layer. [We use this method to calculate the exact time-varying \$\Delta Q_s\$ of a composite material over a forcing period.](#)

[Periodic areal heat capacity \(ISO 13786:2007\) is a useful measure of a composite materials ability to store heat over a sinusoidal cycle. It is a better measure than overall heat capacity or surface thermal admittance as it accounts for the periodic penetration depth of each material layer \(for thick composites\) as well as heat lost through transmittance \(for thin composites\). It can be calculated exactly as:](#)

$$\kappa = \frac{P}{2\pi} \left| \frac{H_{22}^{-1}}{H_{12}} \right|, \quad (20)$$

[with units \$\text{J m}^{-2} \text{K}^{-1}\$.](#)

[Cyclic heat capacity is similar to thermal admittance \(or inertia or effusivity\) in that it is a product of volumetric heat capacity and conductivity, but it also accounts for a material's composite nature, periodic penetration depth and heat lost through transmittance. Materials with low cyclic heat capacity \(e.g. lightweight framed walls or sheet metal\) do not absorb and store as much heat over the diurnal cycle as do materials with high cyclic heat capacity \(e.g. concrete or brick\).](#)

[2.2 Idealised evaluation methods](#)

~~3 Idealised evaluation~~

The half-layer and interface discrete schemes are compared with exact solutions of heat transfer ~~with a sinusoidal temperature forcing. Performance statistics are based those used in PILPS-Urban Phase 2, as described in Phase 1 (Grimmond et al., 2010).~~

~~3.1 Idealised method~~

The external boundary is forced by T_{ext} , a sinusoidal temperature variation of one degree over a 24-hour period representing the combined effects of external environment temperature and incident radiation (or sol-air temperature):

$$T_{ext} = T_0 + \sin\left(\frac{2\pi}{P} t\right), \quad (2021)$$

where $T_0 = 290 \text{ K}$ is the average external temperature. In this study, the internal boundary environment T_{int} is fixed, equal to T_0 . Boundaries have fixed surface thermal resistances representing both convective and radiative transfer. Values are standard horizontal heat transfer rates set out in ISO6946, where $R_{ext} = 0.04$ and $R_{int} = 0.13 \text{ m}^2 \text{ K W}^{-1}$ (ISO, 2007).

For both discrete schemes, a linear system of equations describing the temperature evolution of each node is generated and solved by decomposition and back-substitution of a tridiagonal matrix (Thomas' algorithm). Discrete schemes are run for 6 forcing periods of 24 hours, with the first five periods discarded as spin-up, and the last compared with the exact solution. For the exact solution, components of the heat transfer matrix are calculated numerically and harmonic solutions computed. [Performance statistics are based those used in PILPS-Urban Phase 2, as described in Phase 1 \(Grimmond et al., 2010\), and \(Taylor, 2001\).](#)

[2.3 Urban model evaluation methods](#)

[The discrete schemes are also compared within an urban land surface model \(aTEB\) forced by observations using the methodology of the PILPS-Urban Phase 2 \(Grimmond et al., 2011\).](#)

4.1.12.3.1 Description of urban model: aTEB

The proposed interface scheme was implemented in the Australian Town Energy Budget (aTEB) urban land surface model (Thatcher and Hurley, 2012). aTEB was developed to act as the urban component of a regional or global climate model, so takes the highly efficient building-averaged approach where the generic urban unit is an infinite street canyon (Nunez and Oke, 1977). Canyon surfaces (walls, road, snow and vegetation) are connected to a bulk canyon air layer via an aerodynamic resistance network. Roofs and canyon air are then connected in parallel to the overlying atmosphere.

Although written from the ground up, aTEB is conceptually based on the influential Town Energy Budget (TEB) urban canopy model (Masson, 2000) with some modifications for Australian conditions. Modifications include:

- In-canyon vegetation for suburban areas represented by a big-leaf model, adapted from Kowalczyk et al. (1994) but with a largely reduced set of prognostic variables.
- Air-conditioning component which pumps waste heat into canyons and prevents buildings acting as energy sinks during high temperature periods, allowing energy closure at each timestep.
- Two-wall canyon allowing radiative interactions between a sunlit and shaded walls, and a canyon airflow parameterisation with venting and recirculating regions, each integrated through 180° for all possible street orientations, adapted from Harman et al. (2004a, 2004b).

aTEB would be categorised as a 'complex' urban model following the methodology of Grimmond et al. (2010, 2011), primarily because of its canyon based approach. Conceptually similar models include TEB (Masson, 2000), SLUCM (Kusaka et al., 2001) and CLMU (Oleson et al., 2008a). A significant differentiator amongst conceptually similar models is the parameterisation of heat exchange between canyon surfaces and turbulent air. By default, the SLUCM uses a form of the Jürges formula (1924), while TEB and CLMU use a form of Rowley et al. (1930). An alternative approach was developed by Harman et al. (2004b) where aerodynamic conductance is separately calculated for each canyon surface based on the airflow in different regions of the canyon for different canyon geometries. Urban canopy models that utilise forms of the Harman circulation scheme include the Single Column Reading Urban Model (SCRUM) (Harman and Belcher, 2006), the Met Office Reading Urban Surface Exchange Scheme (MORUSES) (Porson et al., 2010) and aTEB (Thatcher and Hurley, 2012). In order to assess how the proposed conduction scheme is affected by different aerodynamic heat transfer parameterisations, the Jürges, Rowley and Harman methods have been implemented in aTEB as described in Appendix B.C. Further details on aTEB is available in Thatcher and Hurley (2012) and Luhar et al. (2014).

4.1.12.3.2 Observational data

Observational data were obtained from flux tower measurements in a suburban site in Melbourne, Australia (Coutts et al., 2007a, 2007b). Data includes up-welling and down-welling long and shortwave radiation (K_{\uparrow} , K_{\downarrow} , L_{\uparrow} , L_{\downarrow}), net all-wave radiation (Q^*), turbulent heat fluxes (Q_H , Q_E), air temperature, pressure, wind, humidity and rainfall. Sampling rates were between 1 and 10 Hertz, block averaged to 30-minute intervals over 474.4 continuous days from 13 August 2003 to 28 November 2004. Measurements were taken at 40 m above ground, at a height where the effects of individual buildings were sufficiently blended so that measurements were considered representative of the neighbourhood.

The gap-filled data used here is identical to that used in the First International Urban Land Surface Model Comparison Project (PILPS-Urban) Phase 2 (Grimmond et al., 2011), from which our evaluation methodology follows, that is:

- Observed downwelling radiation, air temperature, pressure, wind, humidity and rainfall data were used as forcing data to run the urban model offline, i.e. without the need to be coupled to a larger atmospheric/ earth system model.

- Observed upwelling radiation, turbulent heat and residual heat storage flux observations were compared with model output to evaluate the performance of the model.
- The initial 108.4 days of observation were treated as spin-up and excluded from analysis.
- The remaining 366 days were analysed, but if any flux were missing or gap filled in a time interval, all data in that interval were ignored, resulting in 8520 usable half-hour time intervals.

The site at Preston, Melbourne is typical of low to medium density suburban housing in Australia, with detached one to two story brick, timber and steel framed buildings, separated by roads, lawn and large trees. The site is classified in Best and Grimmond (2014b) as a local climate zone (LCZ) 6 (Stewart and Oke, 2012) or as an Urban Zone for Energy exchange (UZE) medium density (Loridan and Grimmond, 2011, 2012).

~~3.2 Idealised results~~ **3 Results**

Conduction schemes are evaluated through two independent methods: 1) in a highly idealised environment to allow comparison to exact solutions to heat transfer and 2) within an urban land surface model and compared with observations.

3.1 Idealised evaluation results

~~3.2.3.1.1~~ **3.1.1 Idealised results: hHigh-resolution simulation**

Discrete schemes are ~~tested~~ run at very high resolution (200 layers, each 1 mm deep) in order to test code validity. Table 1 shows the normalised standard deviation (SD) of high spatial resolution simulations over various timesteps, where an SD of 1.0 means amplitudes of discrete and exact solutions match. At the higher time and space resolutions, both schemes converge towards the exact solution as expected. As the temporal resolution is decreased to 30-minute timesteps amplitudes of ΔQ_S reduce in both schemes.

~~3.2.3.1.2~~ **3.1.2 Idealised results: rRealistic material parameters**

We now test the performances of the discrete schemes at space and time resolutions more practical and typical of urban land surface models. The twenty wall and twelve roof configurations described in the ~~CLM+~~ CLMU database were tested at 30-minute timesteps over various levels of complexity. In Fig. 2, errors for 2–10 layer configurations are plotted individually (288 total), along with layer means. Of the two discrete schemes, the interface scheme has an average normalised SD closer to the exact solution for each layer up to ten (Fig. 2(a)). The mean normalised SD of ΔQ_S for the interface scheme begins above the exact solution at two layers, but decreases as resolution increases. For the half-layer scheme, SD begins below the exact solution and increases as resolution increases. For the interface scheme at 30-minute timesteps, mean spatial and temporal discretisation normalised SD errors almost cancel at four layers, but never cancel for the half-layer scheme. Figure 2 (b) shows the layer mean of the interface scheme mean absolute errors (MAE) are smaller than the half-layer scheme. The normalised MAE for the half-layer scheme monotonically decreases as the number of layers increases. Time and space discretisations both lead to negative bias in ΔQ_S , so MAE is minimised by increasing the number of layers indefinitely. On the other hand, the interface scheme average MAE declines until a minimum at four layers, where the positive bias of spatial discretisation approximately balances the negative bias of temporal discretisation. Using the same method for 1, 15, 30 and 60-minute timesteps, we find the optimal numbers of layers for the interface scheme are: 8, 6, 4 and 2, while the half-layer scheme only

improves at higher resolutions (Appendix ED). At higher resolutions, the interface scheme provides less benefit over the half-layer scheme, but is still able to simulate ΔQ_S more accurately for a range of realistic wall and roof assemblies (Fig. D.1).

Having evaluated the performance of the two schemes over increasing material complexity, we evaluate performance for different composite thermal characteristics. Figure 3 shows the normalised SD and the MAE for each scheme at 30-minute timesteps for the 288 CLMU walls and roofs, plotted against the composite material's cyclic-periodic areal heat capacity of the composite material (Eq. 20), herein called thermal mass. ~~(calculated per ISO 13786:2007). Materials with low thermal mass (e.g. lightweight framed walls or sheet metal) do not absorb and store as much heat over the diurnal cycle as materials with high thermal mass (e.g. concrete or brick). Cyclic heat capacity is similar to thermal admittance (or inertia or effusivity) in that it is a product of volumetric heat capacity and conductivity, but it also accounts for a material's composite nature, periodic penetration depth and heat lost through transmittance. Materials with low cyclic heat capacity (e.g. lightweight framed walls or sheet metal) do not absorb and store as much heat over the diurnal cycle as do materials with high cyclic heat capacity (e.g. concrete or brick).~~ In contrast to discrete layers, cyclic heat capacity thermal mass varies continuously, so the response of each scheme is represented as a locally weighted linear regression (LOWESS) (Cleveland, 1979). The thicker lines ~~are representative of~~ represent all 288 material configurations, while the thin dashed lines represent a subset of walls and roofs with four layers (the number of layers used later in the urban model analyses).

Figure 3 (a) shows the interface scheme LOWESS of normalised SD is closer to the exact solution for all values of cyclic heat capacity thermal mass represented in the CLMu-CLMU database. The half-layer scheme's LOWESS of normalised SD shows an increasing negative bias for larger cyclic heat capacity thermal mass, while the interface scheme LOWESS is less steep. Figure 3 (b) plots MAE (non-normalised) and shows schemes have greater difference in absolute errors for assemblies with higher cyclic heat capacity thermal mass. Heat storage becomes a larger proportion of the energy balance in neighbourhoods with more heat capacity, so a scheme that is better able to represent ΔQ_S in those instances is beneficial.

~~3.2.33.1.2 Idealised results: t~~ Typically modelled material parameters

We now evaluate the performance of the discrete schemes using wall and roof characteristics that are typical of previous urban modelling studies. Figure 4 displays the results of four walls, one realistic (SITE) and three optimised (WRFu WRF, UZEm and aTEB). All walls are made up of four layers and later analysed in the aTEB urban model (Sect. 3.4.2). The upper panels show ΔQ_S amplitude through a 24-hour forcing period, while the lower panels show the error from the exact solution at each 30-minute timestep. In each case, the half-layer scheme under-simulates the diurnal amplitude of ΔQ_S , while the interface scheme matches more closely with the exact solution. The mean absolute error (MAE) normalised by the absolute mean of the exact solution (Fig. 4 lower panel) is smaller for walls represented with the interface scheme.

The same analysis is undertaken for roofs and shown in Fig. 5 ~~displays results for four layered roofs, which do not show the same degree of improvement from the interface scheme as the walls. Overall the interface scheme improves performance of these four-layer representations, however the degree of improvement is smaller than the walls analysed above.~~ Errors for both schemes are more pronounced in the UZE and aTEB roofs, which have greater total depths and therefore higher spatial discretisation errors (roof and wall characteristics listed in Appendix A). ~~Overall the interface scheme improves performance of these four-layer representations.~~

As a consequence of the method of discretisation, the interface scheme has one additional temperature node over the half-layer scheme for any given number of layers (see Fig. 1). In Fig. 2, the interface average errors are lower than half-layer average errors for assemblies with $n + 1$ layers, implying the benefit of the interface scheme is broader than simply adding an additional node. A further test can be undertaken by ~~be~~ dividing the first layer of a homogenous material equally for the half-layer scheme only ~~performed for the homogenous~~

assemblies in Fig 4 and 5 (WRF and UZE walls/roofs) giving the half-layer scheme an extra node by dividing the first layer equally; then both schemes are represented by the same number of nodes, and the first node has the same heat capacity. Considering the homogenous assemblies in Fig 4 and 5 (WRF and UZE walls/roofs) When MAE is calculated, in each case the no five-layered (five-node) half-layer system has higher MAE than outperforms the corresponding four-layered (five-node) interface system.

4 Observational evaluation

The discrete schemes are now compared within an urban land surface model (aTEB) forced by observations using the methodology of the PILPS Urban Phase 2 (Grimmond et al., 2011) in order to assess overall impact on flux predictions. The same four wall and roof thermal parameters from Sect. 3.2.3 were input into aTEB while all other parameters including urban morphology, roof/wall radiative properties were kept constant, including road/soil properties to minimise differences in hydrology (refer Appendix A for values).

4.1 Observational methods

4.1.1 Description of urban model: aTEB

The proposed interface scheme was implemented in the Australian Town Energy Budget (aTEB) urban land surface model (Thatcher and Hurley, 2012). aTEB was developed to act as the urban component of a regional or global climate model, so takes the highly efficient building-averaged approach where the generic urban unit is an infinite street canyon (Nunez and Oke, 1977). Canyon surfaces (walls, road, snow and vegetation) are connected to a bulk canyon air layer via an aerodynamic resistance network. Roofs and canyon air are then connected in parallel to the overlying atmosphere.

Although written from the ground up, aTEB is conceptually based on the influential Town Energy Budget (TEB) urban canopy model (Masson, 2000) with some modifications for Australian conditions. Modifications include:

- In-canyon vegetation for suburban areas represented by a big-leaf model, adapted from Kowalczyk et al. (1994) but with a largely reduced set of prognostic variables.
- Air-conditioning component which pumps waste heat into canyons and prevents buildings acting as energy sinks during high temperature periods, allowing energy closure at each timestep.
- Two-wall canyon allowing radiative interactions between a sunlit and shaded walls, and a canyon airflow parameterisation with venting and recirculating regions, each integrated through 180° for all possible street orientations, adapted from Harman et al. (2004a, 2004b).

aTEB would be categorised as a 'complex' urban model following the methodology of Grimmond et al. (2010, 2011), primarily because of its canyon-based approach. Conceptually similar models include TEB (Masson, 2000), SLUCM (Kusaka et al., 2001) and CLMU (Oleson et al., 2008a). A significant differentiator amongst conceptually similar models is the parameterisation of heat exchange between canyon surfaces and turbulent air. By default, the SLUCM uses a form of the Jürges formula (1924), while TEB and CLMU use a form of Rowley et al. (1930). An alternative approach was developed by Harman et al. (2004b) where aerodynamic conductance is separately calculated for each canyon surface based on the airflow in different regions of the canyon for different canyon geometries. Urban canopy models that utilise forms of the Harman circulation scheme include the Single Column Reading Urban Model (SCRUM) (Harman and Belcher, 2006), the Met Office Reading Urban Surface Exchange Scheme (MORUSES) (Porson et al., 2010) and aTEB (Thatcher and Hurley, 2012). In order to assess how the proposed conduction scheme is affected by different aerodynamic heat transfer parameterisations, the Jürges, Rowley and Harman methods have been implemented in aTEB as described in Appendix B. Further details on aTEB is available in Thatcher and Hurley (2012) and Luhar et al. (2014).

4.1.2 Observational data

Observational data were obtained from flux tower measurements in a suburban site in Melbourne, Australia (Coutts et al., 2007a, 2007b). Data includes up-welling and down-welling long and shortwave radiation (K_{\uparrow} , K_{\downarrow} , L_{\uparrow} , L_{\downarrow}), net radiation (Q^*), turbulent heat fluxes (Q_H , Q_E), air temperature, pressure, wind, humidity and rainfall. Sampling rates were between 1 and 10 Hertz, block averaged to 30 minute intervals over 474.4 continuous days from 13 August 2003 to 28 November 2004. Measurements were taken at 40 m above ground,

at a height where the effects of individual buildings were sufficiently blended so that measurements were considered representative of the neighbourhood.

The gap-filled data used here is identical to that used in the First International Urban Land Surface Model Comparison Project (PILPS-Urban) Phase 2 (Grimmond et al., 2011), from which our evaluation methodology follows, that is:

- Observed downwelling radiation, air temperature, pressure, wind, humidity and rainfall data were used as forcing data to run the urban model offline, i.e. without the need to be coupled to a larger atmospheric/earth system model.
- Observed upwelling radiation, turbulent heat and residual heat storage flux observations were compared with model output to evaluate the performance of the model.
- The initial 108.4 days of observation were treated as spin up and excluded from analysis.
- The remaining 366 days were analysed, but if any flux were missing in a time interval, all data in that interval were ignored, resulting in 8520 usable half hour time intervals.

The site at Preston, Melbourne is typical of low to medium density suburban housing in Australia, with detached one to two story brick, timber and steel framed buildings, separated by roads, lawn and large trees. The site is classified in Best and Grimmond (2014b) as a local climate zone (LCZ) 6 (Stewart and Oke, 2012) or as an Urban Zone for Energy exchange (UZE) medium density (Loridan and Grimmond, 2011, 2012).

3.24.2 Observational Urban model results

4.2.13.2.1 Observational results: Impact on heat storage

Figure 6 compares the residual net storage heat flux density (ΔQ_S) of observations and the urban model by calculating a mean flux for each hour of the day over the 12-month evaluation period. The method of determining observed ΔQ_S as the residual of the surface energy balance includes inherent uncertainty (refer Sect. 1.2.1), however the relatively long observation period used here reduces stochastic error. The upper panels show the mean hourly flux density over the diurnal cycle, the lower panels show error from observations. For each of the four datasets, the amplitude of the diurnal storage heat flux density increases when using the interface scheme compared to the half-layer scheme, similar to the behaviour seen in the exact analysis. As the half-layer method generally under-represents the magnitude of ΔQ_S , the interface scheme is better able to represent the observed storage heat flux over the full diurnal cycle. The interface scheme also improves simulated storage heat flux at the 25th and 75th quartiles, particularly during the day.

Half-hourly ΔQ_S performance statistics of aTEB using the Harman aerodynamic heat transfer method are listed in Table 2. For the four material databases, the interface scheme improves error metrics in almost every case most cases. These statistics are comparable to those reported in the PILPS-Urban Phase 2 intercomparison project, which used the same observational data (Grimmond et al., 2011). In that study, heat storage was the most poorly represented energy flux (Best and Grimmond, 2015), where the best ΔQ_S RMSE of any model in the final stage was 53 W m^{-2} , and the mean of participating models was 65 W m^{-2} .

The interface scheme in general improves the urban simulation performance in ΔQ_S for these four datasets. However, an improvement in improving the performance in ΔQ_S may simultaneously be offset by reduced deteriorate performance in another flux of the energy balance (Loridan et al., 2010; Loridan and Grimmond, 2012), and so assessing the impact of the proposed conduction scheme on other energetic fluxes is necessary.

4.2.1 Observational results: 3.2.2 Impact on other fluxes

In Fig. 7, a Taylor diagram (Taylor, 2001) extends the statistical evaluation of the two conduction schemes to include sensible and latent heat, and upwelling longwave radiation fluxes. Shortwave radiation flux is omitted because it is unaffected by the conduction schemes, and downwelling radiation fluxes are prescribed. A Taylor

diagram is useful in determining whether a change in the difference error ([measured in centred, or bias corrected, root mean square error: cRMSE](#)) (~~centred root mean square error: cRMSE~~) occurs from a change in variance (standard deviation: SD) or a change in pattern correlation (Pearson's correlation coefficient: r). cRMSE ([as defined in Taylor, 2001](#)) and SD are normalised by the standard deviation of corresponding flux observations to easily compare fluxes with different value ranges and variances. The two conduction schemes are tested with the four material datasets (Appendix A), along with three different aerodynamic heat transfer methods (Appendix BC) for a total of 24 simulations. We also plot the anonymous results of participants in the PILPS-urban Phase 2 intercomparison (Grimmond et al., 2011). Simulations using the half-layer scheme are represented by unfilled coloured markers and the interface scheme with filled markers, with the two conduction schemes connected by a line.

For ~~residual-net~~ storage heat flux (ΔQ_S), the interface scheme improves cRMSE for all simulations. The reduced cRMSE is primarily from improvement in normalised SD. Overall best performance is achieved with the aTEB default material parameters, followed by UZE, WRF and SITE. For each material dataset, the Harman heat transfer method performs better than the Rowley or Jürges methods. The length of the connecting line between conduction schemes compared to the tight grouping of the three heat transfer methods indicates the conduction scheme generally has greater impact on performance of ΔQ_S than the different aerodynamic heat transfer methods. The spread of the material datasets indicates the model is sensitive to material thermal parameter choices.

For upwelling longwave radiation flux (L_{\uparrow}), the interface scheme improves cRMSE for all simulations. Improvements in both normalised SD and r contribute to the lower cRMSE. Rowley and Harman methods perform better than the Jürges method, however the model is more sensitive to material dataset and the conduction scheme choice.

For sensible heat flux (Q_H), the interface scheme improves cRMSE for all simulations. The reduced cRMSE results primarily from improved normalised SD, as correlation is generally flat or slightly degraded. The Jürges and Harman methods perform better than the Rowley method. For Q_H , the difference between conduction schemes is less pronounced than for ΔQ_S and L_{\uparrow} .

For latent heat flux (Q_E), the impact of the interface scheme on cRMSE is mixed, but on average degrades performance. No clear pattern emerges from either SD or r , and all simulations are tightly grouped.

The mean change in performance from half-layer to interface schemes [for the 12 sets of experiments](#) are presented in Table 3, with improvements in bold. [A paired, two-sided t-test for significance of the mean change in metric surpasses the 95% confidence interval in each case.](#)

5.4 Discussion and Conclusion

We evaluated the performance of two implicit discrete schemes that represent heat conduction through urban ~~surfaces~~[materials](#). The half-layer scheme is well established and widely used in land surface models for urban structures, soil, snow and ice. It lumps heat capacitance at nodes centred within discrete layers. We proposed an alternative scheme of similar complexity that lumps heat capacitance at the interface between layers. We used two independent methods to evaluate the schemes: comparison with exact solutions to heat transfer in an idealised environment, and comparison with ~~a long time-series observations~~[long time-series observations](#) for an urban site with heat storage calculated as a residual of the urban energy balance.

In the idealised evaluation, ~~(Section 3)~~, a series of multi-layered assemblies of various complexities were subjected to a sinusoidal temperature forcing representing the diurnal cycle. The half-layer scheme was found to systematically under-estimate ΔQ_S magnitude compared to exact solutions of one-dimensional heat transfer, while the interface scheme better matched exact solutions. [For the half-layer scheme, t](#)Time and space discretisation errors ~~of the half-layer scheme~~ were both negatively signed, leading to under-representation of ΔQ_S . For the interface scheme, discretisation errors were oppositely signed, reducing average error. An optimal

combination of space and time discretisation can be found to approximately cancel bias errors; for 30-minute timesteps, the interface optimum was four material layers. Overall, the interface scheme provided greatest benefit for simpler representations (fewer layers), and for materials with larger [cyclic-periodic areal](#) heat capacity (higher thermal mass).

In the [observational-urban model](#) evaluation, ~~(Section 4)~~, we assessed the impact of implementing the interface scheme on performance of an urban land surface model (aTEB) [over a 15-month observation period for a site in Melbourne, Australia](#) ~~that is conceptually similar to many participants of the PILPS Urban intercomparison project~~. We evaluated four material parameter datasets and three common aerodynamic heat transfer parameterisations ~~over a 15-month observation period for a site in Melbourne, Australia~~. In the urban model, the interface scheme tended to increase the diurnal magnitude of ΔQ_S . In all simulations, heat storage was under-represented compared with observations, so increasing ΔQ_S magnitude improved performance. Each flux is linked via the urban surface energy balance and so ~~all~~ [other](#) fluxes were affected by a change in heat storage. As more energy was partitioned into storage, less was available for the turbulent fluxes and urban skin surface temperatures were lower. As both Q_H and L_{\uparrow} were over-represented, the interface scheme improved performance in these fluxes too. For Q_E , the impact of the interface scheme was mixed, but on average degraded performance. Material thermal characteristics were not chosen to achieve the lowest flux errors, but to assess the impact of the alternative conduction scheme for typical simulation setups. Four previously published material datasets were evaluated: SITE, WRF, UZE and aTEB. The interface scheme improved performance for all datasets, however overall errors were still large. The SITE material parameters, which were supposed to match most closely with realities of the site, performed the worst. The optimised material datasets with unrealistically large storage capacities performed better. Three common canyon surface aerodynamic heat transfer methods were also evaluated: Rowley, Jürges and Harman. The Harman method had lower ΔQ_S errors than equivalent experiments using Rowley or Jürges, but for other fluxes there was no clear best method. Overall, the urban model was more sensitive to material thermal dataset and conduction method than to aerodynamic heat transfer method.

By physical reasoning, the interface scheme increases storage available to the transient external environment by representing heat capacity at skin surfaces, resulting in larger diurnal amplitudes of ΔQ_S compared with the half-layer scheme. This on average improves performance for idealised wall and roof assemblies based on real-world construction and material properties, and where urban land surface models are under-representing heat storage magnitude. However, the interface scheme will degrade the performance of urban models if the magnitude of ΔQ_S is already well represented, which may be the case in models where thermal properties of urban [surfaces-materials](#) are optimised to increase [cyclic heat capacity](#) [thermal mass](#), which have higher temporal and spatial resolutions, or which have an altogether different representation of urban geometry. Other than affecting flux predictions, the interface scheme can provide structural benefits to urban land surface models. The skin temperatures of urban surfaces are used in balancing energy budgets and determining radiant and turbulent fluxes. The interface scheme calculates skin temperatures prognostically, while models using the half-layer schemes diagnose skin temperatures as an additional calculation, or assume the first layer bulk temperature is representative of the skin temperature. For aTEB, moving from a half-layer to an interface conduction scheme avoided the additional calculations required to diagnose skin temperatures, and resulted in a 5% reduction in average runtime for offline simulations.

In conclusion, the interface conduction scheme has the potential to benefit urban land surface models simulating environmental phenomena at scales that require a high level of discretisation in time and/or space for reasons of efficiency. Examples include numerical weather prediction, where many simulations are required in short timeframes, or climate studies that require simulation over long timescales. The interface scheme also improves performance in assemblies using realistic material thermal parameters, so may benefit large-scale studies investigating future impacts of urban design or climate mitigation measures. ~~Results presented here are based on a single urban model with multiple configurations, and on a single observation site, so future work may extend evaluation to other sites and other urban models.~~

Code/ data availability

All ~~models~~ Source, evaluation and plotting code is included in supplementary material, [available through the online git repository at: https://bitbucket.org/matlipson/ics](https://bitbucket.org/matlipson/ics) and further ~~and~~ described in [the README.txt](#). Idealised experiments ([Section 3](#)) can be run and plotted directly, however ~~observational~~ [urban model](#) experiments ([Section 4](#)) require three observational dataset files that must be acquired from the data owner Andrew Coutts (andrew.coutts@monash.edu):

- alpha01.dat (used as forcing data for the urban model, includes observation quality flags)
- observation_preston.csv (flux observations to assess model performance)
- [_QF.txt](#) (estimates of anthropogenic heat sources)

Appendix A: ~~Model parameters and m~~Material databases

CLMU (realistic, composite): [From a dataset of global urban characteristics \(Jackson et al., 2010\) intended for use in the Community Land Model – Urban \(CLMU\) \(Oleson et al., 2008a\), or other global climate models. The database catalogues the properties of 32 common walls and roofs from around the world. Attempts are made by Jackson et al. \(2010\) to reconcile the whole wall/roof thermal conductivity with real world values by estimating the effects of thermal bridging, air leakage, and poor construction. For our analysis, all 10-layer composite walls and roofs were collapsed through each iteration down to two layers using depth-weighted averages of conductivity and heat capacity, resulting in 288 representations of walls and roofs of varying thermal characteristics and complexity.](#)

SITE (realistic, composite): [As presented in PILPS-Urban Phase 2 \(Grimmond et al., 2011\). Characteristics were derived from an area and depth weighted average of material thermal properties at the observation site. Roofs and walls were an aggregate of metal, terracotta, concrete and asbestos, insulation, lightweight framing and plasterboard, separated into four layers: external skin, structure, insulation and internal lining.](#)

WRF (optimised, homogenous): [From the WRF/urban integrated urban modelling system v3.2 \(Chen et al., 2011\), which includes the SLUCM and BEP urban schemes. In WRF, three default sets of parameters are available for various densities of urban land cover, here we use the low intensity residential set following the observation site’s classification by Loridan and Grimmond \(2012\). The WRF default parameters represent a generic homogenous material with a heat capacity and conductivity similar to lightweight concrete throughout.](#)

UZE (optimised, homogenous): [From updated WRF/urban parameters described in Loridan and Grimmond \(2012\) based on results of a multi-objective optimisation algorithm to minimise root mean square error \(RMSE\) over 15 urban locations. New parameter values were recommended for three categories of urban areas based on Urban Zone for Energy exchange \(UZE: Loridan and Grimmond, 2011\) and were subsequently included in releases of WRF/urban as an optional dataset. We use the medium urban category following the observation site’s classification by Loridan and Grimmond \(2012\).](#)

aTEB (optimised, composite): [From the ECOCLIMAP database \(Masson et al., 2003\) on which TEB \(Masson, 2000\) defaults are based, but with increased layer depths per Thatcher and Hurley \(2012\). The walls and roofs are not representative of typical building methods in Australia, but nonetheless give reasonable results for generic Australian cities. The roof is a layered composite with thermal conductivity and heat capacity of dense concrete, aerated concrete and insulation; the walls a composite of concrete and insulation and the road/soil of asphalt and dry soil.](#)

Table A.1: ~~Urban land surface model parameters (constants)~~

Units

$\phi_{(bld,veg)}$	Area fraction: (vegetation, building)	(0.45, 0.38)
--------------------	---------------------------------------	--------------

h	Building height	6.4	m
h/w	Canyon height/width ratio	0.42	
$\alpha_{(roof,road,wall,veg)}$	Albedo: (roof, road, wall, vegetation)	(0.175, 0.10, 0.30, 0.20)	
$\epsilon_{(roof,road,wall,veg)}$	Emissivity: (roof, road, wall, vegetation)	(0.90, 0.94, 0.85, 0.96)	
$Z_{0,(roof,road,wall,veg)}$	Roughness: (roof, road, wall, vegetation)	(0.10, 0.01, 0.01, 0.25)	m
$d_{(1,2,3,4),road}$	Road depth: layers (1, 2, 3, 4)	(0.01, 0.04, 0.45, 3.50)	m
$\lambda_{(1,2,3,4),road}$	Road conductivity: layers (1, 2, 3, 4)	(0.7454, 0.7454, 0.2513, 0.251)	$W m^{-1} K^{-1}$
$C_{(1,2,3,4),road}$	Road heat capacity: layers (1, 2, 3, 4)	(1.94E6, 1.94E6, 1.28E6, 1.28E6)	$J m^{-3} K^{-1}$

Table A.21: Urban land surface model material dataset parameters. [References per text Appendix A.](#)

	Walls				Roofs			
	SITE	WRF	UZE	aTEB	SITE	WRF	UZE	aTEB
Depth (d) [m]								
Layer 1	0.0404	0.05	0.05	0.05	0.0116	0.05	0.05	0.01
Layer 2	0.054	0.05	0.05	0.05	0.05	0.05	0.10	0.09
Layer 3	0.042	0.05	0.10	0.05	0.04	0.05	0.15	0.40
Layer 4	0.0125	0.05	0.10	0.05	0.0125	0.05	0.20	0.10
Conductivity (λ) [$W m^{-1} K^{-1}$]								
Layer 1	0.61	0.67	1.00	0.9338	6.53	0.67	0.40	1.51
Layer 2	0.43	0.67	1.00	0.9338	0.025	0.67	0.40	1.51
Layer 3	0.024	0.67	1.00	0.9338	0.23	0.67	0.40	0.08
Layer 4	0.16	0.67	1.00	0.05	0.16	0.67	0.40	0.05
Volumetric heat capacity (C) [$J m^{-3} K^{-1}$]								
Layer 1	1.25E+0 6	1.00E+0 6	1.20E+0 6	1.55E+0 6	2.07E+0 6	1.00E+0 6	1.20E+0 6	2.11E+0 6
Layer 2	1.40E+0 6	1.00E+0 6	1.20E+0 6	1.55E+0 6	7.10E+0 3	1.00E+0 6	1.20E+0 6	2.11E+0 6
Layer 3	1.30E+0 3	1.00E+0 6	1.20E+0 6	1.55E+0 6	1.50E+0 6	1.00E+0 6	1.20E+0 6	0.28E+0 6
Layer 4	0.67E+0 6	1.00E+0 6	1.20E+0 6	0.29E+0 6	0.67E+0 6	1.00E+0 6	1.20E+0 6	0.29E+0 6
Whole assembly characteristics								
Overall dDepth: [m]	0.1489	0.2	0.3	0.2	0.1141	0.2	0.5	0.6
Transmittance:	0.495	3.35	3.333	0.862	0.444	3.35	0.80	0.142

$[W m^{-2} K^{-1}]$

Cyclic heat
capacity Thermal
mass:
 $[J m^{-2} K^{-1}]$

104 112 92 002 143 176 160 349 27 653 92 002 80 817 197 755

Appendix B: Model parameters

Table B.1: Urban land surface model parameters: constant in each experiment.

Based on observation site characteristics (Grimmond et. al, 2011) and aTEB defaults.

			Units
$\delta_{(bld,veg)}$	Area fraction: (vegetation, building)	(0.45, 0.38)	
h	Building height	6.4	m
h/w	Canyon height/width ratio	0.42	
$\alpha_{(roof,road,wall,veg)}$	Albedo: (roof, road, wall, vegetation)	(0.175, 0.10, 0.30, 0.20)	
$\varepsilon_{(roof,road,wall,veg)}$	Emissivity: (roof, road, wall, vegetation)	(0.90, 0.94, 0.85, 0.96)	
$Z_{0,(roof,road,wall,veg)}$	Roughness: (roof, road, wall, vegetation)	(0.10, 0.01, 0.01, 0.25)	m
$d_{(1,2,3,4),road}$	Road depth: layers (1, 2, 3, 4)	(0.01, 0.04, 0.45, 3.50)	m
$\lambda_{(1,2,3,4),road}$	Road conductivity: layers (1, 2, 3, 4)	(0.7454, 0.7454, 0.2513, 0.251)	$W m^{-1} K^{-1}$
$C_{(1,2,3,4),road}$	Road heat capacity: layers (1, 2, 3, 4)	(1.94E6, 1.94E6, 1.28E6, 1.28E6)	$J m^{-3} K^{-1}$

Appendix BC: Aerodynamic conductance formulations

Three parameterisations of heat exchange between surfaces and turbulent air are evaluated within aTEB: the Jürges, Rowley and Harman methods. Sensible heat flux between a surface (*) and air is

$$Q_{H,*} = \Omega_*^{-1} (T_* - T_{air}), \quad (A1)$$

where Ω_*^{-1} is aerodynamic heat conductance [$W m^{-2} K^{-1}$].

Jürges method

The Jürges method (Jürges, 1924) is implemented in aTEB as described by Kusaka et al., (2001):

$$\Omega_*^{-1} = 6.15 + 4.18 U_* \quad (\text{for } U_* \leq 5 \text{ m s}^{-1}), \quad (A2)$$

$$\Omega_*^{-1} = 7.51 U_*^{0.78} \quad (\text{for } U_* > 5 \text{ m s}^{-1}), \quad (A3)$$

where U_* is the wind speed in the canyon, shared by wall and road surfaces.

Rowley method

The Rowley method (Rowley et al., 1930) is implemented in aTEB as described by Masson (2000):

$$\Omega_*^{-1} = 11.8 + 4.2\sqrt{U_*^2 + W_*^2}, \quad (\text{A4})$$

where U_* is horizontal wind speed, and W_* vertical wind speed in the canyon, shared by wall and road surfaces.

Harman method

The Harman method (Harman et al., 2004b) is implemented in aTEB as described by Thatcher and Hurley (2012):

$$\Omega_*^{-1} = \frac{C_{air} \kappa^2 U_*}{\ln(0.1h/z_{0,*})(2.3 + \ln(0.1h/z_{0,*}))}, \quad (\text{A5})$$

where C_{air} is volumetric heat capacity of air, κ is the von Kármán constant, h is height of buildings, $z_{0,*}$ is the roughness length of a surface, and U_* is the wind speed over a surface calculated separately for each surface and air-flow region.

Appendix [E](#): Variable timestep response

In Fig. [E](#).1 the analysis of Sect. 3.2.1.2 is repeated for 1, 15, 30 and 60 minute timesteps. For the half-layer scheme, the optimum combination of timestep length and layer number is achieved by increasing the number of layers to 10+ for each timestep length. For the interface scheme, an optimal number of layers can be achieved because space and time discretisation biases for storage heat flux are oppositely signed, resulting in normalised standard deviations closer to 1 (Fig. [E](#).1(a)) and lower mean absolute errors (Fig. [E](#).1(b)). In higher resolution representations, the interface scheme advantage is relatively small.

Supplement link

To be added by publisher

Author contribution

M. Thatcher developed the original aTEB urban model. M. Lipson proposed and developed the interface scheme, wrote the analysis code and prepared the manuscript, with assistance from M. Hart and M. Thatcher.

Competing interests

The authors declare that they have no conflict of interest.

Acknowledgements

This study was supported by the Australian Research Council (ARC) Centre of Excellence for Climate System Science (CE110001028). Mathew Lipson was supported by an Australian Postgraduate Award. We thank Andrew Coutts for sharing original observational datasets and anthropogenic heat flux estimates. Martin Best, Sue Grimmond and Maggie Hendry for answering questions and providing additional information regarding the PILPS-Urban intercomparison analysis methods. Yannick Copin for the base Taylor diagram code. Andrew Pitman for useful feedback on the manuscript. [Finally, we thank the two anonymous reviewers whose comments improved the clarity and robustness of the study.](#)

References

- Barlow, J. F.: Progress in observing and modelling the urban boundary layer, *Urban Clim.*, 10, Part 2, 216–240, doi:10.1016/j.uclim.2014.03.011, 2014.
- Best, M. J. and Grimmond, C. S. B.: Importance of initial state and atmospheric conditions for urban land surface models' performance, *Urban Clim.*, 10, 387–406, doi:10.1016/j.uclim.2013.10.006, 2014a.
- Best, M. J. and Grimmond, C. S. B.: Key conclusions of the first international urban land surface model comparison project, *Bull. Am. Meteorol. Soc.*, doi:10.1175/BAMS-D-14-00122.1, 2014b.
- Best, M. J. and Grimmond, C. S. B.: Investigation of the impact of anthropogenic heat flux within an urban land surface model and PILPS-urban, *Theor. Appl. Climatol.*, 1–10, doi:10.1007/s00704-015-1554-3, 2015.
- Butcher, K. J.: CIBSE Guide A - Environmental Design (7th Edition), CIBSE., 2006.
- Chen, F., Kusaka, H., Bornstein, R., Ching, J., Grimmond, C. S. B., Grossman-Clarke, S., Loridan, T., Manning, K. W., Martilli, A., Miao, S., Sailor, D., Salamanca, F. P., Taha, H., Tewari, M., Wang, X., Wyszogrodzki, A. A. and Zhang, C.: The integrated WRF/urban modelling system: development, evaluation, and applications to urban environmental problems, *Int. J. Climatol.*, 31(2), 273–288, doi:10.1002/joc.2158, 2011.
- Cleugh, H. and Grimmond, C. S. B.: Urban Climates and Global Climate Change, in *The Future of the World's Climate*, pp. 47–76, Elsevier. [online] Available from: <http://linkinghub.elsevier.com/retrieve/pii/B9780123869173000038> (Accessed 15 June 2015), 2012.
- Cleugh, H. A. and Oke, T. R.: Suburban-rural energy balance comparisons in summer for Vancouver, B.C., *Bound.-Layer Meteorol.*, 36(4), 351–369, doi:10.1007/BF00118337, 1986.
- Cleveland, W. S.: Robust Locally Weighted Regression and Smoothing Scatterplots, *J. Am. Stat. Assoc.*, 74(368), 829–836, doi:10.1080/01621459.1979.10481038, 1979.
- Coutts, A. M., Beringer, J. and Tapper, N. J.: Characteristics influencing the variability of urban CO₂ fluxes in Melbourne, Australia, *Atmos. Environ.*, 41(1), 51–62, doi:10.1016/j.atmosenv.2006.08.030, 2007a.
- Coutts, A. M., Beringer, J. and Tapper, N. J.: Impact of Increasing Urban Density on Local Climate: Spatial and Temporal Variations in the Surface Energy Balance in Melbourne, Australia, *J. Appl. Meteorol. Climatol.*, 46(4), 477–493, doi:10.1175/JAM2462.1, 2007b.
- Davies, M. G.: The thermal admittance of layered walls, *Build. Sci.*, 8(3), 207–220, doi:10.1016/0007-3628(73)90002-9, 1973.
- Grimmond, C. S. B., Cleugh, H. A. and Oke, T. R.: An objective urban heat storage model and its comparison with other schemes, *Atmospheric Environ. Part B Urban Atmosphere*, 25(3), 311–326, doi:10.1016/0957-1272(91)90003-W, 1991.
- Grimmond, C. S. B., Best, M., Barlow, J., Arnfield, A. J., Baik, J.-J., Baklanov, A., Belcher, S., Bruse, M., Calmet, I., Chen, F., Clark, P., Dandou, A., Erell, E., Fortuniak, K., Hamdi, R., Kanda, M., Kawai, T., Kondo, H., Kravayehoff, S., Lee, S. H., Limor, S.-B., Martilli, A., Masson, V., Miao, S., Mills, G., Moriwaki, R., Oleson, K., Porson, A., Sievers, U., Tombrou, M., Voogt, J. and Williamson, T.: Urban Surface Energy Balance Models: Model Characteristics and Methodology for a Comparison Study, in *Meteorological and Air Quality Models for Urban Areas*, edited by A. Baklanov, G. Sue, M. Alexander, and M. Athanassiadou, pp. 97–123, Springer Berlin Heidelberg. [online] Available from: http://link.springer.com/chapter/10.1007/978-3-642-00298-4_11 (Accessed 1 May 2014), 2009.
- Grimmond, C. S. B., Blackett, M., Best, M. J., Barlow, J., Baik, J.-J., Belcher, S. E., Bohnenstengel, S. I., Calmet, I., Chen, F., Dandou, A., Fortuniak, K., Gouvea, M. L., Hamdi, R., Hendry, M., Kawai, T., Kawamoto, Y., Kondo, H., Kravayehoff, E. S., Lee, S.-H. and Loridan, T.: The International Urban Energy Balance Models Comparison Project: First Results from Phase 1, *J. Appl. Meteorol. Climatol.*, 49(6), 1268–1292, doi:10.1175/2010JAMC2354.1, 2010.
- Grimmond, C. S. B., Blackett, M., Best, M. J., Baik, J.-J., Belcher, S. E., Beringer, J., Bohnenstengel, S. I., Calmet, I., Chen, F., Coutts, A., Dandou, A., Fortuniak, K., Gouvea, M. L., Hamdi, R., Hendry, M., Kanda, M., Kawai, T., Kawamoto, Y., Kondo, H., Kravayehoff, E. S., Lee, S.-H., Loridan, T., Martilli, A., Masson, V., Miao, S., Oleson, K., Ooka, R., Pigeon, G., Porson, A., Ryu, Y.-H., Salamanca, F., Steeneveld, G. j., Tombrou, M., Voogt, J. A., Young, D. T. and Zhang, N.: Initial results from Phase 2 of the international urban energy balance model comparison, *Int. J. Climatol.*, 31(2), 244–272, doi:10.1002/joc.2227, 2011.

- Gupta, H. V., Bastidas, L. A., Sorooshian, S., Shuttleworth, W. J. and Yang, Z. L.: Parameter estimation of a land surface scheme using multicriteria methods, *J. Geophys. Res. Atmospheres*, 104(D16), 19491–19503, doi:10.1029/1999JD900154, 1999.
- Harman, I. N. and Belcher, S. E.: The surface energy balance and boundary layer over urban street canyons, *Q. J. R. Meteorol. Soc.*, 132(621), 2749–2768, doi:10.1256/qj.05.185, 2006.
- Harman, I. N., Best, M. J. and Belcher, S. E.: Radiative Exchange in an Urban Street Canyon, *Bound.-Layer Meteorol.*, 110(2), 301–316, doi:10.1023/A:1026029822517, 2004a.
- Harman, I. N., Barlow, J. F. and Belcher, S. E.: Scalar Fluxes from Urban Street Canyons Part II: Model, *Bound.-Layer Meteorol.*, 113(3), 387–410, doi:10.1007/s10546-004-6205-7, 2004b.
- ISO: ISO6946:2007(E) Building components and building elements - Thermal resistance and thermal transmittance - Calculation method, International Standard, International Organization for Standardization., 2007.
- Jackson, T. L., Feddema, J. J., Oleson, K. W., Bonan, G. B. and Bauer, J. T.: Parameterization of Urban Characteristics for Global Climate Modeling, *Ann. Assoc. Am. Geogr.*, 100(4), 848–865, doi:10.1080/00045608.2010.497328, 2010.
- Jürges, W.: *Der Wärmeübergang an einer ebenen Wand*, Druck und Verlag von R. Oldenbourg., 1924.
- Kowalczyk, E. A., Garratt, J. R., Krummel, P. B., Commonwealth Scientific and Industrial Research Organization (Australia) and Division of Atmospheric Research: Implementation of a soil-canopy scheme into the CSIRO GCM - regional aspects of the model response, CSIRO, Melbourne., 1994.
- Kusaka, H., Kondo, H., Kikegawa, Y. and Kimura, F.: A Simple Single-Layer Urban Canopy Model For Atmospheric Models: Comparison With Multi-Layer And Slab Models, *Bound.-Layer Meteorol.*, 101(3), 329–358, doi:10.1023/A:1019207923078, 2001.
- Lee, S.-H. and Park, S.-U.: A Vegetated Urban Canopy Model for Meteorological and Environmental Modelling, *Bound.-Layer Meteorol.*, 126(1), 73–102, doi:10.1007/s10546-007-9221-6, 2008.
- Loridan, T. and Grimmond, C. S. B.: Characterization of Energy Flux Partitioning in Urban Environments: Links with Surface Seasonal Properties, *J. Appl. Meteorol. Climatol.*, 51(2), 219–241, doi:10.1175/JAMC-D-11-038.1, 2011.
- Loridan, T. and Grimmond, C. s. b.: Multi-site evaluation of an urban land-surface model: intra-urban heterogeneity, seasonality and parameter complexity requirements, *Q. J. R. Meteorol. Soc.*, 138(665), 1094–1113, doi:10.1002/qj.963, 2012.
- Loridan, T., Grimmond, C. S. B., Grossman-Clarke, S., Chen, F., Tewari, M., Manning, K., Martilli, A., Kusaka, H. and Best, M.: Trade-offs and responsiveness of the single-layer urban canopy parametrization in WRF: An offline evaluation using the MOSCEM optimization algorithm and field observations, *Q. J. R. Meteorol. Soc.*, 136(649), 997–1019, doi:10.1002/qj.614, 2010.
- Luhar, A. K., Thatcher, M. and Hurley, P. J.: Evaluating a building-averaged urban surface scheme in an operational mesoscale model for flow and dispersion, *Atmos. Environ.*, 88, 47–58, doi:10.1016/j.atmosenv.2014.01.059, 2014.
- Martilli, A.: Current research and future challenges in urban mesoscale modelling, *Int. J. Climatol.*, 27(14), 1909–1918, doi:10.1002/joc.1620, 2007.
- Martilli, A., Clappier, A. and Rotach, M. W.: An Urban Surface Exchange Parameterisation for Mesoscale Models, *Bound.-Layer Meteorol.*, 104(2), 261–304, doi:10.1023/A:1016099921195, 2002.
- Masson, V.: A Physically-Based Scheme For The Urban Energy Budget In Atmospheric Models, *Bound.-Layer Meteorol.*, 94(3), 357–397, doi:10.1023/A:1002463829265, 2000.
- Masson, V., Champeaux, J.-L., Chauvin, F., Meriguet, C. and Lacaze, R.: A Global Database of Land Surface Parameters at 1-km Resolution in Meteorological and Climate Models, *J. Clim.*, 16(9), 1261, 2003.
- Nunez, M. and Oke, T. R.: The Energy Balance of an Urban Canyon, *J. Appl. Meteorol.*, 16(1), 11–19, doi:10.1175/1520-0450(1977)016<0011:TEBOAU>2.0.CO;2, 1977.
- Oke, T. R.: The energetic basis of the urban heat island, *Q. J. R. Meteorol. Soc.*, 108(455), 1–24, doi:10.1002/qj.49710845502, 1982.

- Oke, T. R.: The urban energy balance, *Prog. Phys. Geogr.*, 12(4), 471–508, doi:10.1177/030913338801200401, 1988.
- Oleson, K. W., Bonan, G. B., Feddema, J., Vertenstein, M. and Grimmond, C. S. B.: An Urban Parameterization for a Global Climate Model. Part I: Formulation and Evaluation for Two Cities, *J. Appl. Meteorol. Climatol.*, 47(4), 1038–1060, doi:10.1175/2007JAMC1597.1, 2008a.
- Oleson, K. W., Bonan, G. B., Feddema, J. and Vertenstein, M.: An Urban Parameterization for a Global Climate Model. Part II: Sensitivity to Input Parameters and the Simulated Urban Heat Island in Offline Simulations, *J. Appl. Meteorol. Climatol.*, 47(4), 1061–1076, doi:10.1175/2007JAMC1598.1, 2008b.
- Oleson, K. W., Lawrence, D. M., Bonan, G. B., Flanner, M. G., Kluzek, E., Lawrence, P. J., Levis, S., Swenson, S. C. and Thornton, P. E.: Technical description of version 4.0 of the Community Land Model (CLM)., NCAR, Climate and Global Dynamics Division, Boulder, Colorado., 2010.
- Porson, A., Clark, P. A., Harman, I. N., Best, M. J. and Belcher, S. E.: Implementation of a new urban energy budget scheme in the MetUM. Part I: Description and idealized simulations, *Q. J. R. Meteorol. Soc.*, 136(651), 1514–1529, doi:10.1002/qj.668, 2010.
- Roberts, S. M., Oke, T. R., Grimmond, C. S. B. and Voogt, J. A.: Comparison of Four Methods to Estimate Urban Heat Storage, *J. Appl. Meteorol. Climatol.*, 45(12), 1766–1781, doi:10.1175/JAM2432.1, 2006.
- Rowley, F., Algren, A. and Blackshaw, J.: Surface conductances as affected by air velocity, temperature and character of surface, *ASHRAE Trans*, 36, 429–446, 1930.
- Sailor, D. J. and Lu, L.: A top-down methodology for developing diurnal and seasonal anthropogenic heating profiles for urban areas, *Atmos. Environ.*, 38(17), 2737–2748, doi:10.1016/j.atmosenv.2004.01.034, 2004.
- Stewart, I. D. and Oke, T. R.: Local Climate Zones for Urban Temperature Studies, *Bull. Am. Meteorol. Soc.*, 93(12), 1879–1900, doi:10.1175/BAMS-D-11-00019.1, 2012.
- Taylor, K. E.: Summarizing multiple aspects of model performance in a single diagram, *J. Geophys. Res. Atmospheres*, 106(D7), 7183–7192, doi:10.1029/2000JD900719, 2001.
- Thatcher, M. and Hurley, P.: Simulating Australian Urban Climate in a Mesoscale Atmospheric Numerical Model, *Bound.-Layer Meteorol.*, 142(1), 149–175, doi:10.1007/s10546-011-9663-8, 2012.
- West, A. E., McLaren, A. J., Hewitt, H. T. and Best, M. J.: The location of the thermodynamic atmosphere–ice interface in fully coupled models – a case study using JULES and CICE, *Geosci. Model Dev.*, 9(3), 1125–1141, doi:10.5194/gmd-9-1125-2016, 2016.
- Wilson, K., Goldstein, A., Falge, E., Aubinet, M., Baldocchi, D., Berbigier, P., Bernhofer, C., Ceulemans, R., Dolman, H., Field, C., Grelle, A., Ibrom, A., Law, B. E., Kowalski, A., Meyers, T., Moncrieff, J., Monson, R., Oechel, W., Tenhunen, J., Valentini, R. and Verma, S.: Energy balance closure at FLUXNET sites, *Agric. For. Meteorol.*, 113(1–4), 223–243, doi:10.1016/S0168-1923(02)00109-0, 2002.

Figures

Figure 1: Conceptual diagram for two methods of discretising heat transfer through (three) homogenous layers. (a) The half-layer scheme as commonly implemented in urban land surface models, and (b) the proposed interface scheme, which moves temperature nodes (T_k) from the centre of layers to the interfaces between them, with heat capacity (C_i) half of each adjacent layer. Discrete paths of conduction ($q_{k,k+1}$) pass through layer resistances (R_i), while external and internal environment temperatures (T_{ext}, T_{int}) and surface thermal resistances (R_{ext}, R_{int}) control boundary fluxes (q_{ext}, q_{int}).

Figure 2: Heat storage errors of the ~~two-half-layer and the proposed interface discrete~~ schemes vs exact solutions over ~~for increasing number of various layers~~ levels of complexity. ~~Thirty-two roof and wall types from the CLMU database (Jackson et. al, 2010) were modelled with nine levels of complexity, for a total of 288 representations (dots). Mean of layer errors indicate scheme performance at different levels of complexity (lines).~~ For both (a) normalised standard deviation and (b) normalised mean absolute error, the interface scheme ~~on average mean~~ outperforms the half-layer scheme ~~at all levels. Mean improvement diminishes as the number of represented layers increases. of complexity and has an optimum of four layers for 30-minute timesteps.~~

Figure 3: Heat storage errors of the ~~two-half-layer and the proposed interface discrete~~ schemes vs exact solution over ~~for increasing cyclic-periodic areal~~ heat capacity (or thermal mass), with ~~lightweight framed construction on the left, and heavyweight stone/ rubble construction on the right.~~ For both (a) normalised standard deviation and (b) mean absolute error, the interface scheme locally weighted linear regression (LOWESS) ~~outperforms better than~~ the half-layer scheme ~~overall (solid lines) for realistic amounts of cyclic heat capacity.~~ Differences ~~between schemes~~ are more pronounced ~~for walls/roofs with large thermal mass, and those represented with fewer layers (4-layers shown dashed).~~

~~in four-layer representations.~~

Figure 4: ~~Storage heat flux (Q_s) response of four-layered walls to a 24h sinusoidal forcing~~ Heat storage response of half-layer and proposed interface schemes vs exact solutions for four wall types: ~~:(a) SITE: a composite of realistic materials at the Melbourne observation site (Grimmond et. al, 2011); (b) WRF: a homogenous material which forms the default parameters for WRF land surface schemes (Chen et al., 2011); (c) UZE: a homogenous material optimised to reduce WRF errors at 15 urban locations (Loridan and Grimmond, 2012); (d) an optimised composite used in aTEB (Thatcher and Hurley, 2012), based on the ECOCLIMAP database (Masson et al., 2003). For more information on material parameters, refer to Appendix A. Upper panels show storage heat flux density over a periodic cycle, lower panels show normalised error from exact solutions. The interface scheme reduces errors for these wall representations.~~

~~flux density and (b) normalised error.~~

Figure 5: Heat storage response of half-layer and proposed interface schemes vs exact solutions. Material datasets per Fig. 4 and Appendix A. Upper panels show storage heat flux density over a periodic cycle, lower panels show normalised error from exact solutions. ~~The interface scheme reduces errors for these roof representations, but improvements are less pronounced than for walls (Fig. 4).~~

~~Storage heat flux (Q_s) response of four-layered roofs to a 24h sinusoidal forcing: (a) flux density and (b) normalised error.~~

Figure 6: Hourly-averaged diurnal heat storage response of an urban land surface model to four wall/roof datasets over 12 months. ~~Material datasets per Fig. 4 and Appendix A. In each case, the interface scheme reduces errors by increasing heat storage amplitude. Only Harman aerodynamic heat transfer parameterisation shown (others qualitatively similar). When evaluation is limited to 3-month seasons, differences between schemes are qualitatively similar to annual results, although overall errors are higher in summer where radiation flux magnitudes are larger (not shown). The MAE for hourly-averaged fluxes of a mean day shown here is different to MAE of each half-hour timestep throughout the evaluation period (Table 2).~~

Figure 7: A Taylor diagram of energy fluxes for each simulation with interface scheme (filled markers) and half-layer scheme (unfilled markers) connected by a line. Change toward a normalised standard deviation (nSD) of 1 indicates improved variance (radial distance)

and toward the bottom axis indicates improved pattern correlation (radial angle). Where both are improved, the centred root mean square (cRMSE) error decreases towards zero (interior arcs). Different colours indicate different material parameter datasets (SITE, WRF, UZE, aTEB: refer Appendix A). Different marker shapes indicate different aerodynamic heat transfer parameterisations (Rowley, Harman, Jüges: refer Appendix C). Anonymous results of participants in the PILPS-urban Phase 2 intercomparison are also plotted (Grimmond et al., 2011). Overall the interface scheme improves storage heat, sensible heat and longwave radiation fluxes. Latent heat flux response is less clear, but on average the interface scheme degrades performance. Refer to Table 3 for summary statistics.

Figure C.1: Heat storage errors of the half-layer and discrete schemes for increasing number of layers. The 288 configuration layer means are shown for (a) normalised standard deviation and (b) normalised mean absolute errors. Optimum number of layers for each timestep is identified with a star. **Figure D.1:** Mean heat storage errors of the half-layer and the proposed interface schemes vs exact solutions over 2-10 layer representations and for 1, 15, 30 and 60 minute timesteps (per Fig. 2). For both (a) normalised standard deviation and (b) normalised mean absolute error, the interface scheme outperforms the half-layer scheme on average for the 288 representations of walls/roofs based on the CLMU database (Jackson et. al, 2010). Optimum number of layers for each timestep is identified with a star. The margin of improvement of the interface scheme is greatest at low time and space resolutions.

Tables

Table 1: Normalised standard deviation (SD) of Q_S for high-resolution (1mm deep) simulations: aTEB wall test case.

Timestep	1 second	1 minute	30 minute
Half-layer	0.999981	0.999185	0.976463
Interface	0.999986	0.999190	0.976469

Table 2: aTEB half-hourly performance statistics for ΔQ_S : difference conduction schemes (improvement in bold).

Dataset:	SITE		WRF		UZE		aTEB	
Scheme:	Half-layer	Interface	Half-layer	Interface	Half-layer	Interface	Half-layer	Interface
RMSE [$W\ m^{-2}$]:	71.60	66.87	60.80	57.42	58.13	54.79	54.03	51.21
MAE [$W\ m^{-2}$]:	46.17	42.27	38.29	35.67	35.23	32.97	33.38	33.34
r^2 :	0.66	0.72	0.74	0.77	0.80	0.80	0.78	0.80
normalised SD:	0.52	0.56	0.67	0.72	0.63	0.71	0.83	0.93

Table 3: Average performance statistics: change from half-layer to interface scheme for 12 pairs of experiments (improvement in bold). The significance value (p) of a paired, two-sided t-test for the null hypothesis is given in brackets; in all cases the 95% confidence level is reached.

Flux	RMSE [$W\ m^{-2}$]	MAE [$W\ m^{-2}$]	R^2	norm. SD	norm. cRMSE
Storage: ΔQ_S	3.27 ($p=5E-8$)	2.29 ($p=9E-5$)	0.017 ($p=4.7E-2$)	0.078 ($p=3E-6$)	0.033 ($p=4E-8$)
Longwave: L_{\uparrow}	2.38 ($p=5E-8$)	1.55 ($p=6E-7$)	0.010 ($p=1E-7$)	0.059 ($p=1E-7$)	0.062 ($p=9E-8$)
Sensible: Q_H	1.88 ($p=2E-6$)	1.27 ($p=1E-4$)	-0.004 ($p=3E-2$)	0.046 ($p=9E-7$)	0.022 ($p=2E-6$)
Latent: Q_E	-1.58 ($p=8E-3$)	-0.28 ($p=4E-2$)	-0.028 ($p=5E-3$)	0.022 ($p=2E-2$)	-0.033 ($p=8E-3$)

END