

Interactive comment on “GLOFRIM v1.0 – A globally applicable computational framework for integrated hydrological-hydrodynamic modelling” by Jannis M. Hoch et al.

D. P. Viero

daniele.viero@unipd.it

Received and published: 29 August 2017

The Authors wrote that "hydrodynamic models lack an advanced implementation of hydrological processes". Attempts have been made in this direction, in which a full feedback loop between hydrodynamics and hydrology is considered, and deserve to be mentioned (Kim et al., 2012; Viero et al., 2014).

Flooding patterns in populated environments are crucially affected by small-scale, linear features such as artificial embankments (roads, railways, levees of minor channels, etc.). To be applied at the global scale, the spatial resolution of a hydrodynamic model is necessarily coarse with respect to the width of these linear features. How can such a

Printer-friendly version

Discussion paper



“coarse” grid account for these effects? For instance, Vacondio et al. (2016) resampled a refined DTM to a coarser grid by retaining the highest terrain elevation, but such a strategy has obvious shortcomings if applied to cell size of the order of 1 km. Certainly, the use of a flexible mesh can be of aid.

Generally speaking, I fear that thinking of flooding “at a global scale” entails the risk of neglecting features and factors that are small from, e.g., a pure geometrical point of view, but play a major role in lowlands hydrodynamics. Modellers should always be aware of such a risk.

References:

Kim, J., A. Warnock, V. Y. Ivanov, and N. D. Katopodes (2012), Coupled modeling of hydrologic and hydrodynamic processes including overland and channel flow, *Adv. Water Resour.*, 37, 104–126, doi:10.1016/j.advwatres.2011.11.009.

Viero, D. P., P. Peruzzo, L. Carniello, and A. Defina (2014), Integrated mathematical modeling of hydrological and hydrodynamic response to rainfall events in rural lowland catchments, *Water Resour. Res.*, 50, 5941–5957, doi:10.1002/2013WR014293.

Vacondio, R., F. Aureli, A. Ferrari, P. Mignosa, and A. Dal Palu (2016), Simulation of the January 2014 flood on the Secchia River using a fast and high-resolution 2D parallel shallow-water numerical scheme, *Nat. Hazards*, 80, 103–125, doi:10.1007/s11069-015-1959-4.

Interactive comment on Geosci. Model Dev. Discuss., <https://doi.org/10.5194/gmd-2017-140>, 2017.

[Printer-friendly version](#)[Discussion paper](#)