

Instructions for generating plots shown in paper, “The ‘ABC-DA’ system (v1.4): a variational data assimilation system for convective scale research with a study of the impact of a balance constraint”

January 17, 2020

Further guidance on downloading, compiling, and running the software is available in the documentation on github (DOI: 10.5281/zenodo.3531926). The mentioned document also shows how the python plotting code is accessed.

The sample UM data mentioned in this document may be found at
www.met.reading.ac.uk/~ross/downloads/Member001.nc.gz

1 Figure 1

This is a schema, and so doesn’t require production of any results.

2 Figure 2

1. This requires the control variable transform (CVT) to first be calibrated. Make directory to contain *CVT.nc* file (call *Master_Calibration*), and enter this directory.
2. Make directory inside *Master_Calibration* (call *Master_Calibration_stage1*) and enter this directory.
3. Generate ensemble to be used for calibrating the CVT from given UM file (*Member001.nc* inside directory */home/data/UMdir* in this example). Run *Master_Calibration.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.4.1.

```
&UserOptions
! Reading and processing UM data
!
A          = 0.02,
B          = 0.01,
C          = 1.0E4,
dt         = 4.0,
Adv_tracer = .TRUE. ,
runlength  = 3600.0,
CalibRunStage = 1,
NEns       = 1,
EnsDirs (1) = '/home/data/UMdir',
NEnsMems   = 1,
NNMC        = 0,
Nlats       = 260,
latindex (1) = 11,
latindex (2) = 12,
latindex (3) = 13,
latindex (4) = 14,
latindex (5) = 15,
latindex (6) = 16,
latindex (7) = 17,
latindex (8) = 18,
latindex (9) = 19,
```

latindex (10)	= 20,
latindex (11)	= 21,
latindex (12)	= 22,
latindex (13)	= 23,
latindex (14)	= 24,
latindex (15)	= 25,
latindex (16)	= 26,
latindex (17)	= 27,
latindex (18)	= 28,
latindex (19)	= 29,
latindex (20)	= 30,
latindex (21)	= 31,
latindex (22)	= 32,
latindex (23)	= 33,
latindex (24)	= 34,
latindex (25)	= 35,
latindex (26)	= 36,
latindex (27)	= 37,
latindex (28)	= 38,
latindex (29)	= 39,
latindex (30)	= 40,
latindex (31)	= 41,
latindex (32)	= 42,
latindex (33)	= 43,
latindex (34)	= 44,
latindex (35)	= 45,
latindex (36)	= 46,
latindex (37)	= 47,
latindex (38)	= 48,
latindex (39)	= 49,
latindex (40)	= 50,
latindex (41)	= 51,
latindex (42)	= 52,
latindex (43)	= 53,
latindex (44)	= 54,
latindex (45)	= 55,
latindex (46)	= 56,
latindex (47)	= 57,
latindex (48)	= 58,
latindex (49)	= 59,
latindex (50)	= 60,
latindex (51)	= 61,
latindex (52)	= 62,
latindex (53)	= 63,
latindex (54)	= 64,
latindex (55)	= 65,
latindex (56)	= 66,
latindex (57)	= 67,
latindex (58)	= 68,
latindex (59)	= 69,
latindex (60)	= 70,
latindex (61)	= 71,
latindex (62)	= 72,
latindex (63)	= 73,
latindex (64)	= 74,
latindex (65)	= 75,
latindex (66)	= 76,
latindex (67)	= 77,
latindex (68)	= 78,
latindex (69)	= 79,
latindex (70)	= 80,

latindex (71)	= 81 ,
latindex (72)	= 82 ,
latindex (73)	= 83 ,
latindex (74)	= 84 ,
latindex (75)	= 85 ,
latindex (76)	= 86 ,
latindex (77)	= 87 ,
latindex (78)	= 88 ,
latindex (79)	= 89 ,
latindex (80)	= 90 ,
latindex (81)	= 91 ,
latindex (82)	= 92 ,
latindex (83)	= 93 ,
latindex (84)	= 94 ,
latindex (85)	= 95 ,
latindex (86)	= 96 ,
latindex (87)	= 97 ,
latindex (88)	= 98 ,
latindex (89)	= 99 ,
latindex (90)	= 100 ,
latindex (91)	= 101 ,
latindex (92)	= 102 ,
latindex (93)	= 103 ,
latindex (94)	= 104 ,
latindex (95)	= 105 ,
latindex (96)	= 106 ,
latindex (97)	= 107 ,
latindex (98)	= 108 ,
latindex (99)	= 109 ,
latindex (100)	= 110 ,
latindex (101)	= 111 ,
latindex (102)	= 112 ,
latindex (103)	= 113 ,
latindex (104)	= 114 ,
latindex (105)	= 115 ,
latindex (106)	= 116 ,
latindex (107)	= 117 ,
latindex (108)	= 118 ,
latindex (109)	= 119 ,
latindex (110)	= 120 ,
latindex (111)	= 121 ,
latindex (112)	= 122 ,
latindex (113)	= 123 ,
latindex (114)	= 124 ,
latindex (115)	= 125 ,
latindex (116)	= 126 ,
latindex (117)	= 127 ,
latindex (118)	= 128 ,
latindex (119)	= 129 ,
latindex (120)	= 130 ,
latindex (121)	= 131 ,
latindex (122)	= 132 ,
latindex (123)	= 133 ,
latindex (124)	= 134 ,
latindex (125)	= 135 ,
latindex (126)	= 136 ,
latindex (127)	= 137 ,
latindex (128)	= 138 ,
latindex (129)	= 139 ,
latindex (130)	= 140 ,
latindex (131)	= 141 ,

latindex (132)	= 142 ,
latindex (133)	= 143 ,
latindex (134)	= 144 ,
latindex (135)	= 145 ,
latindex (136)	= 146 ,
latindex (137)	= 147 ,
latindex (138)	= 148 ,
latindex (139)	= 149 ,
latindex (140)	= 150 ,
latindex (141)	= 151 ,
latindex (142)	= 152 ,
latindex (143)	= 153 ,
latindex (144)	= 154 ,
latindex (145)	= 155 ,
latindex (146)	= 156 ,
latindex (147)	= 157 ,
latindex (148)	= 158 ,
latindex (149)	= 159 ,
latindex (150)	= 160 ,
latindex (151)	= 161 ,
latindex (152)	= 162 ,
latindex (153)	= 163 ,
latindex (154)	= 164 ,
latindex (155)	= 165 ,
latindex (156)	= 166 ,
latindex (157)	= 167 ,
latindex (158)	= 168 ,
latindex (159)	= 169 ,
latindex (160)	= 170 ,
latindex (161)	= 171 ,
latindex (162)	= 172 ,
latindex (163)	= 173 ,
latindex (164)	= 174 ,
latindex (165)	= 175 ,
latindex (166)	= 176 ,
latindex (167)	= 177 ,
latindex (168)	= 178 ,
latindex (169)	= 179 ,
latindex (170)	= 180 ,
latindex (171)	= 181 ,
latindex (172)	= 182 ,
latindex (173)	= 183 ,
latindex (174)	= 184 ,
latindex (175)	= 185 ,
latindex (176)	= 186 ,
latindex (177)	= 187 ,
latindex (178)	= 188 ,
latindex (179)	= 189 ,
latindex (180)	= 190 ,
latindex (181)	= 191 ,
latindex (182)	= 192 ,
latindex (183)	= 193 ,
latindex (184)	= 194 ,
latindex (185)	= 195 ,
latindex (186)	= 196 ,
latindex (187)	= 197 ,
latindex (188)	= 198 ,
latindex (189)	= 199 ,
latindex (190)	= 200 ,
latindex (191)	= 201 ,
latindex (192)	= 202 ,

latindex (193)	= 203 ,
latindex (194)	= 204 ,
latindex (195)	= 205 ,
latindex (196)	= 206 ,
latindex (197)	= 207 ,
latindex (198)	= 208 ,
latindex (199)	= 209 ,
latindex (200)	= 210 ,
latindex (201)	= 211 ,
latindex (202)	= 212 ,
latindex (203)	= 213 ,
latindex (204)	= 214 ,
latindex (205)	= 215 ,
latindex (206)	= 216 ,
latindex (207)	= 217 ,
latindex (208)	= 218 ,
latindex (209)	= 219 ,
latindex (210)	= 220 ,
latindex (211)	= 221 ,
latindex (212)	= 222 ,
latindex (213)	= 223 ,
latindex (214)	= 224 ,
latindex (215)	= 225 ,
latindex (216)	= 226 ,
latindex (217)	= 227 ,
latindex (218)	= 228 ,
latindex (219)	= 229 ,
latindex (220)	= 230 ,
latindex (221)	= 231 ,
latindex (222)	= 232 ,
latindex (223)	= 233 ,
latindex (224)	= 234 ,
latindex (225)	= 235 ,
latindex (226)	= 236 ,
latindex (227)	= 237 ,
latindex (228)	= 238 ,
latindex (229)	= 239 ,
latindex (230)	= 240 ,
latindex (231)	= 241 ,
latindex (232)	= 242 ,
latindex (233)	= 243 ,
latindex (234)	= 244 ,
latindex (235)	= 245 ,
latindex (236)	= 246 ,
latindex (237)	= 247 ,
latindex (238)	= 248 ,
latindex (239)	= 249 ,
latindex (240)	= 250 ,
latindex (241)	= 251 ,
latindex (242)	= 252 ,
latindex (243)	= 253 ,
latindex (244)	= 254 ,
latindex (245)	= 255 ,
latindex (246)	= 256 ,
latindex (247)	= 257 ,
latindex (248)	= 258 ,
latindex (249)	= 259 ,
latindex (250)	= 260 ,
latindex (251)	= 261 ,
latindex (252)	= 262 ,
latindex (253)	= 263 ,

```

latindex(254)      = 264,
latindex(255)      = 265,
latindex(256)      = 266,
latindex(257)      = 267,
latindex(258)      = 268,
latindex(259)      = 269,
latindex(260)      = 270,
BoundSpread         = 100,
datadirABCfcs     = '.',',
datadirCVT         = '..',',
CVT_file           = 'CVT.nc',
CVT%CVT_order     = 1,
CVT%CVT_param_opt_gb = 1,
CVT%CVT_param_opt_gb = 1,
CVT%CVT_param_opt_ab = 2,
CVT%CVT_param_opt_reg = 1,
CVT%CVT_vert_opt_sym = 1,
CVT%CVT_stddev_opt = 2
/

```

4. Make directory inside *Master_Calibration* (call *Master_Calibration_stage2*) and enter this directory.
5. Generate ensemble mean state, and perturbations from this ensemble. Run *Master_Calibration.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.4.2.

```

&UserOptions
! Generating ensemble perturbations from ensemble forecasts
!
CalibRunStage      = 2,
NEns               = 1,
NEnsMems          = 1,
NNMC               = 0,
Nlats              = 260,
datadirABCfcs     = '../Master_Calibration_stage1',
datadirABCperts   = '.',',
datadirCVT         = '..',',
CVT_file           = 'CVT.nc'
/

```

6. Make directory inside *Master_Calibration* (call *Master_Calibration_stage3*) and enter this directory.
7. Generate vertical regression matrix. Run *Master_Calibration.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.4.3.

```

&UserOptions
! Generate vertical regression matrix
!
CalibRunStage      = 3,
NEns               = 1,
NEnsMems          = 1,
NNMC               = 0,
Nlats              = 260,
datadirRegression = '.',',
datadirABCperts   = '../Master_Calibration_stage2',
datadirCVT         = '..',',
CVT_file           = 'CVT.nc'
/

```

8. To plot figure 2(c), edit the python program *PlotRegressionMatrices.py* to set *datadirCVT* to *Master_Calibration*, and run the python program.

9. Make directory inside *Master_Calibration* (call *Master_Calibration_stage4*) and enter this directory.
10. Generate ensemble perturbations in terms of parameters. Run *Master_Calibration.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.4.4.

```
&UserOptions
! Generate parameter perturbations
! _____
CalibRunStage      = 4,
NEns              = 1,
NEnsMems          = 1,
NNMC              = 0,
Nlats              = 260,
datadirABCperts   = '../Master_Calibration_stage2',
datadirConParams  = '.',',
datadirCVT         = '.',',
CVT_file           = 'CVT.nc',
/
```

11. To plot Figs. 2(a,b,d), edit the python program *Plot_rp_pre+post_regress.py* to set *data_dir_stage2* to *Master_Calibration/Master_Calibration_stage2* and *data_dir_stage4* to *Master_Calibration/Master_Calibration_stage4* and run the python program.

3 Figure 3

1. Make directory inside *Master_Calibration* (call *Master_Calibration_stage5*) and enter this directory.
2. Generate spatial transform data (the remaining part of the calibration step). Run *Master_Calibration.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.4.5.

```
&UserOptions
! Calibrate spatial transforms
! _____
CalibRunStage      = 5,
NEns              = 1,
NEnsMems          = 1,
NNMC              = 0,
Nlats              = 260,
datadirABCperts   = '../Master_Calibration_stage2',
datadirConParams  = '../Master_Calibration_stage4',
datadirCVT         = '.',',
CVT_file           = 'CVT.nc'
/
```

3. Edit the python program *PlotCVT.py* to set *data_dir_CVT* to *Master_Calibration*, and run the python program.
4. This can be repeated for different experiment configurations to get the different lines in panel (c) of the paper.

4 Figure 4

1. This is also output from *PlotCVT.py* as run for Fig. 3.
2. This can be repeated for different experiment configurations to get the different lines in panel (c) of the paper.

5 Figure 5

1. This is also output from *PlotCVT.py* as run for Fig. 3.

6 Figure 6

- This plot requires the same data as used for Fig. 5, plus knowledge of the gravity wave speeds (found from a linear analysis). Run a linear analysis of the model by first creating a directory *Master_Linear_Analysis* (in the same place as directory *Master_Calibration*) and enter this directory. Run *Master_Linear_Analysis.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.3.

```
&UserOptions
! Linear analysis of ABC model equations
!
datadirLinearAnal ,      = '.',
A                  = 0.02
B                  = 0.01
C                  = 1.0E4
/

```

- Compile the c++ program *RossbyRadius.cpp* (contained in the same directory as the python plotting code, note the libraries that are required):

```
g++ -I/usr/include RossbyRadius.cpp -o RossbyRadius.out -L/usr/lib -lnetcdf_c++ -lnetcdf
```

- Run this code as follows from the command line inside directory *Master_Linear_Analysis*:

```
./RossbyRadius.out ../Master_Calibration .
```

- To plot Fig. 6, edit the python program *Plot_horizvars_unbalrho+Rossby.py* to set *CVT_file* to *Master_Calibration* and *lengths_file* to *Master_Linear_Analysis/VerticalModeCharacteristics.dat* and run the python program.

7 Figure 7

- Make a directory *Master_ImpliedCovs* (in the same place as directory *Master_Calibration*) and enter this directory. Run *Master_ImpliedCov.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.6.

```
&UserOptions
! Compute implied covariances
!
datadirImpliedCov      = '.', ,
datadirCVT              = '../Master_Calibration' ,
CVT_file                = 'CVT.nc' ,
datadirABCfcs           = '../Master_Calibration/Master_Calibration_stage1' ,
LS_file                 = 'FC_Ens001_Item001.nc' ,
ImplCov_npoints          = 1
longindex(1)             = 180
levindex(1)              = 25
/

```

- To plot panels (a), (b), and (c) of Fig. 7, edit the python program *Plot_Covs.py* to set *plot_raw_covs* to *False*, *plot_implied_covs* to *True*, *data_dir_ImpliedCovs* to *Master_ImpliedCovs*, *longindex* to [179], and *levindex* = [24], and run the python program. Note that the *longindex* and *levindex* are *longindex*(1)-1 and *levindex*(1)-1 respectively.
- This can be repeated for different experiment configurations to get the rows 2 and 3 of Fig. 7 in the paper.
- Make directory *Master_RawCov* (in the same place as directory *Master_Calibration*) and enter this directory. Run *Master_RawCov.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.7.

```

&UserOptions
! Compute raw covariances
! _____
datadirRawCov      = '.'
datadirABCperts    = '../Master_Calibration/Master_Calibration_stage2'
Nens               = 1
NensMems           = 1
Nlats              = 260
ImplCov_npoints   = 1
longindex(1)        = 180
levindex(1)         = 25
/

```

- To plot panels (j), (k), and (l) of Fig. 7, edit the python program *Plot_Covs.py* to set *plot_raw_covs* to *True*, *plot_implied_covs* to *False*, *data_dir_RawCovs* to *Master_RawCovs*, *Nens* to 1, *NEnsMems* to 260, *longindex* to [179], and *levindex* = [24], and run the python program. Note that the *longindex* and *levindex* are *longindex*(1)-1 and *levindex*(1)-1 respectively.

8 Figure 8

This is a schema, and so doesn't require production of any results.

9 Figure 9

- Make an ABC-style initial state (in order to generate synthetic observations and to measure errors from). Make a directory *Master_PrepABC_InitState* (in the same place as directory *Master_Calibration*) and enter this directory.
- Run *Master_PrepABC_InitState.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.1.

```

&UserOptions
! Master_PrepABC_InitState
! _____
Init_ABC_opt        = 3
datadirUM           = '/home/data/UMdir'
init_um_file        = 'Member0001.nc'
datadirABC_out      = '.'
init_ABC_file       = 'ABC_InitialConds.nc'
latitude            = 102
Regular_vert_grid   = .TRUE.
Adv_tracer          = .TRUE.
gravity_wave_switch = .FALSE.
f                   = 1.0E-4
A                   = 0.02
B                   = 0.01
C                   = 1.0E4
BoundSpread          = 100.
press_source_x      = 200
press_source_z      = 6
press_amp            = 0.005
x_scale              = 120
z_scale              = 14
/

```

- Make a short forecast from this initial state to spin-up characteristics of the ABC model. Make a directory *Master_RunNLModel* (in the same place as directory *Master_Calibration*) and enter this directory.

4. Run *Master_RunNLModel.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.2.

```
&UserOptions
! Running ABC model
!
datadirABC_in          = '../Master_PrepABC_InitState'
init_ABC_file           = 'ABC_InitialConds.nc'
datadirABC_out          = '.'
output_ABC_file         = 'Truth.nc'
diagnostics_file        = 'ABC_Diagnostics.dat'
runlength                = 7200.0
ndumps                   = 9
dt                       = 4.0
Lengthscale_diagnostics = .FALSE.
A                        = 0.02
B                        = 0.01
C                        = 1.0E4
Adv_tracer               = .TRUE.
/

```

5. Specify the observation network. Make directory *Master_MakeBgObs_ObsNetwork* (in the same place as directory *Master_Calibration*) and enter this directory.
6. Run *Master_MakeBgObs.out* with the following namelist file present (*UserOptions.nl*). See documentation, §4.8.

```
&UserOptions
! Specification of observation network
!
Generate_mode           = 1
ObsSpec%year0             = 2010
ObsSpec%month0            = 1
ObsSpec%day0               = 1
ObsSpec%hour0              = 0
ObsSpec%min0               = 0
ObsSpec%sec0               = 0
ObsSpec%NumBatches         = 7
datadir_ObsSpec           = '.'
ObsSpec_file               = 'ObsSpec.dat'
!
ObsSpec%batch(1)           = 1
ObsSpec%seconds(1)          = 0
ObsSpec%ob_of_what(1)        = 4      ! rp
ObsSpec%NumObs_long(1)       = 18
ObsSpec%NumObs_height(1)     = 20
ObsSpec%long_min(1)          = 10.0
ObsSpec%long_max(1)          = 530000.0
ObsSpec%height_min(1)        = 1.0
ObsSpec%height_max(1)        = 12000.0
ObsSpec%stddev(1)            = 0.0015
!
ObsSpec%batch(2)           = 2
ObsSpec%seconds(2)          = 600
ObsSpec%ob_of_what(2)        = 4      ! rp
ObsSpec%NumObs_long(2)       = 18
ObsSpec%NumObs_height(2)     = 20
ObsSpec%long_min(2)          = 10.0
ObsSpec%long_max(2)          = 530000.0
ObsSpec%height_min(2)        = 1.0

```

```

ObsSpec%height_max(2)      = 12000.0
ObsSpec%stddev(2)          = 0.0015
!
ObsSpec%batch(3)           = 3
ObsSpec%seconds(3)          = 1200
ObsSpec%ob_of_what(3)       = 4      ! rp
ObsSpec%NumObs_long(3)      = 18
ObsSpec%NumObs_height(3)    = 20
ObsSpec%long_min(3)         = 10.0
ObsSpec%long_max(3)         = 530000.0
ObsSpec%height_min(3)       = 1.0
ObsSpec%height_max(3)       = 12000.0
ObsSpec%stddev(3)           = 0.0015
!
ObsSpec%batch(4)           = 4
ObsSpec%seconds(4)          = 1800
ObsSpec%ob_of_what(4)       = 4      ! rp
ObsSpec%NumObs_long(4)      = 18
ObsSpec%NumObs_height(4)    = 20
ObsSpec%long_min(4)         = 10.0
ObsSpec%long_max(4)         = 530000.0
ObsSpec%height_min(4)       = 1.0
ObsSpec%height_max(4)       = 12000.0
ObsSpec%stddev(4)           = 0.0015
!
ObsSpec%batch(5)           = 5
ObsSpec%seconds(5)          = 2400
ObsSpec%ob_of_what(5)       = 4      ! rp
ObsSpec%NumObs_long(5)      = 18
ObsSpec%NumObs_height(5)    = 20
ObsSpec%long_min(5)         = 10.0
ObsSpec%long_max(5)         = 530000.0
ObsSpec%height_min(5)       = 1.0
ObsSpec%height_max(5)       = 12000.0
ObsSpec%stddev(5)           = 0.0015
!
ObsSpec%batch(6)           = 6
ObsSpec%seconds(6)          = 3000
ObsSpec%ob_of_what(6)       = 4      ! rp
ObsSpec%NumObs_long(6)      = 18
ObsSpec%NumObs_height(6)    = 20
ObsSpec%long_min(6)         = 10.0
ObsSpec%long_max(6)         = 530000.0
ObsSpec%height_min(6)       = 1.0
ObsSpec%height_max(6)       = 12000.0
ObsSpec%stddev(6)           = 0.0015
!
ObsSpec%batch(7)           = 7
ObsSpec%seconds(7)          = 3600
ObsSpec%ob_of_what(7)       = 4      ! rp
ObsSpec%NumObs_long(7)      = 18
ObsSpec%NumObs_height(7)    = 20
ObsSpec%long_min(7)         = 10.0
ObsSpec%long_max(7)         = 530000.0
ObsSpec%height_min(7)       = 1.0
ObsSpec%height_max(7)       = 12000.0
ObsSpec%stddev(7)           = 0.0015
/

```

7. Now run the cycled data assimilation. Make directory *CycledDA_obs_rp* (in the same place as directory *Master_Calibration*) and enter this directory.

8. Copy the bash script *DAcycle001.sh* to this directory and set *EXPERIMENT* to *CycledDA_obs_rp*, *BASE_DIR* to the full path to the parent of this directory appended with */\$EXPERIMENT*, *N_CYCLES* to 30, *N_OUTER_LOOPS* to 1, *N_INNER_LOOPS_MAX* to 100, *DA_WINDOW* to 3600.0, *DA_WINDOW_INT* to 3600, *OBS_NETWORK_DIR* to *\$BASE_DIR/..../Master_MakeBgObs_ObsNetwork*, *INITIAL_TRUTH_DIR* to *\$BASE_DIR/..../Master_RunNLModel*, *CVT_DIR* to *\$BASE_DIR/..../MasterCalibration*, *CODE_DIR* to the directory containing the main fortran code, *PLOT_CODE_DIR* to the directory containing the python plotting code, *BACKGROUND_ALREADY_COMPUTED* to 0, *A* to 0.02, *B* to 0.01, *C* to 1.0E4, and *PLOT* to 1.
9. Run the back script *DAcycle001.sh*.
10. The cost function diagnostics of Fig. 9 should appear inside *\$BASE_DIR/CycledDA_obs_rp/da_cycle_0007/Plots*.

10 Figure 10

The panels of Fig. 10 should also appear inside *\$BASE_DIR/CycledDA_obs_rp/da_cycle_0007/Plots*. as per instructions for Fig. 9.

11 Figure 11

Much of the data shown in Fig. 11 should appear inside *\$BASE_DIR/CycledDA_obs_rp/Plots* as per instructions for Fig. 9. The specific panels of Fig. 11 are made by editing *PlotMultiCycleErrors4paper.py*.

12 Figures 12 and 13

The above steps can be repeated for different options – in particular *CVT%CVT_param_opt_gb* can be set to 3 to turn-off the geostrophic balance constraint in the CVT, and *CVT%CVT_param_opt_reg* can be set to 2 to turn-off the vertical regression step that accompanies the geostrophic balance.