

Response to Editor

Grace

The reviewers' responses to your revised manuscript are available now.

Could you please address their comments?

I would like to emphasize that both reviewers (as also suggested by a reviewer in round 1) have recommended to add a case including a PREM based material model. This would significantly increase the relevance of the paper as PREM is used as a standard model in the literature. Also as highlighted by reviewer 2 providing access to the data file would be tremendously helpful for readers considering using Abaqus which would further increase the relevance of the work.

Thanks.

Lutz Gross

GMD Topical Editor

Dear Lutz,

Thank you for the reviews for our revised manuscript, we are grateful for further constructive comments. We have taken onboard the comment made by both reviewers regarding a PREM model and have implemented this earth model as an additional Abaqus test case. The results are included in Figs. 6a, 7a and B4 and discussed in the text (detailed responses are provided below). The Abaqus input file for this run has been added to the online repository, and furthermore we have added information to the Abaqus README text file to describe how future users may implement their own laterally varying earth models.

Please find in this final response a point-by-point reply (plain black text) to all reviewer comments (red text), including the changes we have made to the manuscript (marked in italics). The revised manuscript is attached below the response to the reviewers.

Please also note we have changed reference to Abaqus from upper case to lower case under advisement and have italicised "Abaqus" and "VISCO1D" in the text.

Kind Regards

Grace Nield & co-authors

Response to Reviewer 1

I would like to thank and acknowledge the effort made by authors in revising their manuscript. They have addressed most of my concerns, and I am mostly satisfied with their response although there are some misleading statements.

We thank the reviewer for taking the time to re-review our manuscript, and for the positive response to our amendments. We have responded to each comment in line below.

“We have not included the governing equations for the finite element formulation as this part of the study is not new work. The model is based on the finite element formulation of Wu (2004) and equations therein, as referenced on line 84. Instead, we focus the paper on describing the new aspects of this model –incorporating a fault plane and prescribing slip.”

The article Agata et al. 2019 cited by the authors seems to be implementing a fault plane and prescribing slip, not only for forward modelling but also for adjoint simulations.

Then readers will probably ask: what is the new contribution in this article as compared to Wu 2004 and Agata 2019? In this context, readers would appreciate some clarity on this.

The main difference between our model and that of Agata et al. (2019) is that we present a fully global self-gravitational model and Agata et al. (2019) restrict the spatial extent of their model to a local domain. We have clarified on line 57 that their model is not global.

Despite this question, I recognize the importance of this work, and therefore, I am willing to recommend this article for publication after a minor revision.

Minor comments:

“Using the Preliminary Reference Earth Model (PREM) instead would not add anything to the results in our opinion, and only complicate reproducibility of the results for others.”

I disagree, in particular with “...only complicate reproducibility of the results for others.” In fact, the PREM is the standard model for many geophysical simulations on a global scale.

We have taken on board this comment and have implemented a new Abaqus model using the PREM elastic properties along with viscosity profile from the existing benchmarking tests. We have not benchmarked this test case as the Okada analytical solution is valid only for a homogenous earth and would not provide a valid comparison. The results from this new model run are included in Figure 6a and Figure 7a, which now show displacement through time for the fault geometry in test case 3 with 3 different earth models: The simple earth model with Maxwell and Burgers rheology, and the PREM model. Furthermore, the surface displacement from this new model is also included in Appendix B (Fig. B4). The Abaqus input file has been added to the supplementary information.

We have added the following text to Section 4.1:

“Furthermore, we run the third test case in Abaqus using the elastic properties from PREM, keeping the same three-layer Maxwell viscosity profile as the benchmarking Earth model (Table 2). We do not benchmark the results from this test case as the Okada analytical solution is only valid for a homogeneous Earth.”

The following paragraph has been added to Section 4.3:

“Figs. 6a and 7a also show the displacement for test case 3 with the PREM elastic properties (green dotted lines). At 100 km distance from the fault (Fig. 6a), the different elastic structure results in slightly more coseismic displacement than the simple elastic structure used in the benchmarking tests, which results in greater postseismic displacement with time. At 300 km distance from the fault (Fig. 7a), the depth varying PREM elastic structure results in only very small differences. The surface coseismic and postseismic displacements at 10, 50 and 100 years after the earthquake are shown in Fig. B4, Appendix B.”

“We will change this term to “layered halfspace” but will also note on first use that it is also referred to as “flat-Earth” in other literature (e.g. Wu,2004) so as not to cause confusion to the reader.”

Personally, I am not against using the term “flat-Earth”, but these days, it seems to be associated more with the flat-earth conspiracies:)

Yes, we agree, and the term “layered half-space” is a good alternative.

“The moment-density tensor approach suggested by the reviewer is an alternative method of representing a fault within a spectral-element mesh (e.g., Gharti et al. 2019) whereby the mesh geometry is not required to conform to the geometry of the fault plane. However, our current knowledge is that this method cannot be implemented in a finite-element mesh in ABAQUS due to the restrictions of defining loads and forces on elements or surfaces within the mesh.”

I think this is untrue. Because the moment-density tensor approach is well adapted to weak formulations and ABAQUS being a finite-element tool, implementing the moment-density tensor approach in ABAQUS should be straightforward.

We concede there is a gap in our knowledge regarding the moment-density tensor approach. From research that we have done in response to this comment, we cannot ascertain how to implement this approach in Abaqus. It may be possible, but it is not clear in the documentation or from other literature, and therefore we feel reluctant to include this as an option within the manuscript.

Table A1.

Are those computation times for single or parallel processing?

The times quoted in Table A1 are for parallel processing on the 8 cores of the machine. We have added this into the text on new line 398.

Response to Reviewer 2

The authors of this paper present a spherical self-gravitating finite element model generated using the commercial code ABAQUS. The main purpose of the paper is to provide a numerical platform (ABAQUS input files) and associated benchmark useful for future studies of far-field postseismic (viscoelastic) deformation triggered by large earthquakes. A Spherical domain is required to overcome the limits imposed by flat surface analytical or semi-analytical solutions, and self-gravitation is important especially when we want to combine the deformation field from sources other than earthquakes (e.g. post-glacial rebound) or for multi-cycle simulations.

The ABAQUS input file presented in the paper is structured in two parts. The first part (*Static) controls the purely elastic coseismic phase and the implementation of fault slip using kinematic constraint equations. The second part (*Visco) controls the long term postseismic phase (viscoelastic relaxation) using Maxwell or Burgers rheology. The structure of the ABAQUS file is user friendly because provides a clear separation between the different phases of the simulation and is generally easy to modify from other people.

Large part of the paper is correctly focused on the benchmark of the coseismic and postseismic simulation against known analytical solutions. More specifically, for the coseismic phase, the authors compare the ABAQUS predicted displacement field with the well known Okada (1985) solutions for a rectangular source implemented in a homogeneous isotropic half-space. They show a general good agreement between the numerical and the analytical approaches. For the postseismic viscoelastic deformation they compare the ABAQUS predictions with the spherical harmonics code VISCO1D, showing again good agreement. The correct reproduction of analytical solutions using ABAQUS is very useful and proves the correct implementation of fault slip and viscoelastic relaxation.

In my opinion, this paper (technical activity) requires one or two additions before publication. I explain my point below.

I commend the authors for working on a such important and complex topic. However, I believe there is at least one (point 1 below) main issue to be discussed and solved before publication.

We thank the reviewer for providing helpful comments and suggestions for the manuscript and we have responded in line below.

1. I think it will more helpful for future users of your examples "ABAQUS input files" if you could provide at least one forward model that implements a different rheologic structure. For example PREM or any recent model with lateral variations in material properties (e.g. viscosity). This way any future user will have an example to learn and to modify for its own project. The same thing is noted from Reviewer 1 although you have not updated your work to accommodate this specific request. You have already successfully completed the benchmark. For that reason, you don't need to benchmark again against a code that implements PREM (although it will be useful). I feel that this work will be significantly improved if you present what described above.

We acknowledge this comment from both reviewers and have included an additional Abaqus run for the fault geometry in test case 3, using the PREM elastic structure along with the viscosity profile from the existing earth model presented in the paper. We have chosen not to benchmark this case as the Okada analytical solution is valid only for a homogenous earth, and VISCO1D does not lend itself easily to the number of layers needed to model PREM.

The results have been added to Figure 6a and Figure 7a and we have included the surface displacement in Appendix B (Fig. B4).

We have added the following text to Section 4.1:

“Furthermore, we run the third test case in Abaqus using the elastic properties from PREM, keeping the same three-layer Maxwell viscosity profile as the benchmarking Earth model (Table 2). We do not benchmark the results from this test case as the Okada analytical solution is only valid for a homogeneous Earth.”

The following paragraph has been added to Section 4.3:

“Figs. 6a and 7a also show the displacement for test case 3 with the PREM elastic properties (green dotted lines). At 100 km distance from the fault (Fig. 6a), the different elastic structure results in slightly more coseismic displacement than the simple elastic structure used in the benchmarking tests, which results in greater postseismic displacement with time. At 300 km distance from the fault (Fig. 7a), the depth varying PREM elastic structure results in only very small differences. The surface coseismic and postseismic displacements at 10, 50 and 100 years after the earthquake are shown in Fig. B4, Appendix B.”

The input file for this extra model run has been added to the online repository. Furthermore, to aid future users, we have included extra information in the Abaqus README file in this repository to describe how future users would implement different earth structures such as one containing lateral variations in viscosity.

2. I'm not sure if I completely understand the problem regarding the implementation of multiple faults. If I understand correctly, implementing multiple faults will require a verification of the mesh quality. Verifying the quality of the mesh is part of the FE modeling work anyway. ABAQUS will give you a warning if the elements are distorted, although it will most probably finish the calculation. You can easily implement multiple sources (or variable fault geometry) in ABAQUS, you will just have to take the time to verify your mesh using the appropriate metrics. Another solution will be to use an external meshing software like Trellis/Cubit, that will give you better control on the generation of the mesh, and subsequently use this mesh to generate the ABAQUS input file. I will agree however, that for the purpose of investigating far-field deformation, details regarding the fault geometry might be of secondary order.

Yes, this understanding is correct. One of the difficulties in Abaqus is to construct the geometry of a layered spherical Earth with more than one fault plane transecting the uppermost layer because this needs to be done with the accuracy of a specific strike/dip/length/width of fault plane. In addition to this, many partitions are

needed to enable the software to mesh the given geometry. This is not a trivial problem. Our aim was to make a code for Abaqus that would automatically generate the model for a fault plane with different strike, dip, length, and width and at present this does not work with 2 or more fault planes.

We agree with the reviewer, however, that it could be done by re-writing the code, or by implementing external meshing software. We have rephrased the language used in the manuscript (line 284-288) to reflect this as follows:

“The main limitation of the model at present is that the geometry is restricted to a single fault plane within the mesh and it cannot have multiple segments of a fault plane with different strike or dip. This is due to the difficulties of constructing a valid spherical mesh in Abaqus with brick elements that conform to verification checks. For the same reason, including more than one earthquake in the same model would be problematic. This issue could potentially be resolved by employing external meshing software (e.g., Gmsh (Geuzaine and Remacle, 2009)).”

A global, spherical, finite-element model for postseismic deformation using *Abaqus*BAQUS

Grace A. Nield^{1,2}, Matt A. King¹, Rebekka Steffen³, Bas Blank⁴

¹Surveying and Spatial Sciences, School of Technology, Environments and Design, University of Tasmania, Australia

5 ²Department of Geography, Durham University, Durham, UK.

³Lantmäteriet, Gävle, Sweden

⁴Faculty of Aerospace Engineering, Delft University of Technology, Delft, NL

Correspondence to: Grace A. Nield (grace.a.nield@durham.ac.uk)

Abstract. We present a finite-element model of postseismic solid Earth deformation built in the software package *ABAQUS* *Abaqus* (version 2018). The model is global and spherical, ~~and~~ includes self-gravitation and is built for the purpose of calculating postseismic deformation in the far-field (>~300km) of major earthquakes. An earthquake is simulated by prescribing slip on a fault plane in the mesh and the model relaxes under the resulting change in stress. Both linear Maxwell and biviscous (Burgers) rheological models have been implemented and the model can be easily adapted to include different rheological models and lateral variations in Earth structure, a particular advantage over existing models. We benchmark the model against an analytical coseismic solution and an existing open-source postseismic model code, demonstrating good agreement for all fault geometries tested. Due to the inclusion of self-gravity the model has the potential for predicting deformation in response to multiple sources of stress change, for example, changing ice thickness in tectonically active regions.

1 Introduction

Earthquakes cause deformation at the Earth's surface from the immediate coseismic fault slip and, thereafter, from several processes. Afterslip on the fault on or near the rupture zone (e.g. Huang et al., 2014) and poroelastic relaxation due to changes in fluid pressure (e.g. Masterlark and Wang, 2002) result in deformation of near-field locations (typically <300km from the fault). As the Earth responds to stress changes associated with the earthquake, the lower crust and upper mantle undergo prolonged postseismic viscoelastic deformation. This is the dominant mode of displacement in the far-field and, for very large earthquakes (> magnitude 9), this can be observed geodetically over 1000 km from the earthquake source (Shao et al., 2016) and be sustained over decades. For example, deformation from the 1960 magnitude 9.5 Chile earthquake was still being observed ~40 years after the event (Khazaradze and Klotz, 2003). Postseismic deformation can be observed by increasingly dense networks of geodetic measurements such as Global Positioning System (GPS) (e.g. Freed et al., 2012) and Interferometric Synthetic Aperture Radar (InSAR) (e.g. Wang and Fialko, 2018) motivating the development of models to help interpret geodetically-observed deformation. The study of postseismic deformation can provide useful information about the Earth and can be used to place constraints on the inferred Earth structure (Pollitz, 2005) or rheology (Freed et al., 2012). It is important to be able to accurately quantify postseismic deformation in regions where deformation occurs as a result of

multiple sources, for example in Alaska where the Earth is also deforming in response to a changing ice load (Suito and Freymueller, 2009).

35 Postseismic deformation has been studied using a variety of modelling techniques, from simple layered half-space (also known
as “flat-Earth”) models to models that consider Earth’s sphericity and three-dimensional material properties. For studying the
far-field effects of earthquakes consideration of sphericity is required (Pollitz, 1992). Pollitz (1997) developed a software
(*VISCOID*, freely available from the USGS at: <https://www.usgs.gov/software/visco1d>, which contains a link to download the
software) to calculate postseismic deformation on a spherical layered Earth incorporating an Earth model that varies in the
40 radial direction only. It uses viscoelastic normal mode theory and calculates deformation from spherical harmonic expansion
of global modes of relaxation. Deformation can be calculated both with and without the effect of gravity, that is, the restoring
forces within the Earth allowing it to regain gravitational equilibrium. The effect of including gravity is that deformation ceases
once the Earth has adjusted to the change in stress, whereas without gravity, deformation continues. This model has been
employed for a wide range of earthquake studies, such as constraining Earth properties and rheological behaviour in response
45 to the magnitude 7.9 2002 Denali earthquake in Alaska (Pollitz, 2005), computing postseismic gravity change following the
magnitude 9.1 2011 Tohoko-Okai earthquake gravity change (Han et al., 2014), and modelling postseismic deformation of
Antarctica (King and Santamaría-Gómez, 2016). Furthermore, *VISCOID* has been used to benchmark other codes of
postseismic deformation calculation (Wang et al., 2006). Whilst *VISCOID* is a powerful tool, it is limited to a one-dimensional
Earth model which may not be appropriate for some studies where lateral variations in Earth structure may be required to fully
50 explain geodetic observations (King and Santamaría-Gómez, 2016).

Several finite-element models of postseismic deformation have also been developed (Freed et al., 2006; Masterlark et al., 2001;
Takeuchi and Fialko, 2013), although the majority have been restricted to a half-space geometry. Hu and Wang (2012) updated
their finite-element model (Hu et al., 2004) to include spherical geometry and used it to study the 2004 magnitude 9.2 Sumatra
55 earthquake, where a spherical geometry allowed for more realistic slab and fault geometry to be included, however they limited
the spatial extent of the model to the case study region. Agata et al. (2019) modelled postseismic deformation following the
2011 magnitude 9.0 Tohoku-Okai earthquake with a finite-element model incorporating spherical (but not global) geometry,
restricting the model domain to 2500 km by 2500 km to allow for a high-resolution mesh. Whilst limiting the spatial extent is
computationally efficient and does not cause a problem for the estimation of postseismic deformation, to compute a fully self-
60 gravitational solution using spherical harmonics a full global model is required. Self-gravitation takes account of the change
in gravity field caused by deformation and the redistribution of mass within the Earth. The effect of self-gravitation due to
earthquake-related deformation is likely to be small for the majority of earthquakes, and not on the same scale as that caused
by glacial isostatic adjustment since the magnitude of deformation is much smaller, but including it allows consistent modelling
of deformation due to multiple sources (e.g. glacial cycles). Furthermore, for large earthquakes, the change in gravity field

65 resulting from deformation and redistribution of mass within the Earth could be significant, and, if the earthquake occurs under
the ocean, redistribution of water also contributes to the change in gravity and hence affects sea levels (Broerse et al., 2011).

The purpose of the model presented in this paper is to estimate far-field postseismic deformation primarily from large
earthquakes. The model is a global, spherical finite-element model constructed with the commercial software *ABAQUS-Abaqus*
70 (<https://www.3ds.com/products-services/simulia/products/abaqus/>; Hibbitt et al., 2016). It is an improvement on existing
models since it includes both global spherical geometry and the capability to use 3D variations in Earth properties which can
significantly affect viscoelastic deformation (e.g. Latychev et al., 2005; Zhong et al., 2003, [Wu et al., 2013](#)). Furthermore, the
model has the potential to simultaneously include different sources of Earth deformation, for example postseismic deformation
in a region undergoing, or which has previously undergone, surface-mass change (e.g., ice-mass change). This is needed, for
75 instance, to separate present-day surface deformation signals observed by GPS.

This paper describes the model setup and the methods implemented to estimate coseismic and postseismic deformation (Sects.
2 and 3). Since afterslip and poroelastic relaxation are considered only to affect deformation in the near-field of the fault for
all but the largest earthquakes (Peña et al., 2019) they are not included in our model. We benchmark model results for several
80 simple scenarios against existing codes (Sect. 4) and discuss the advantages and limitations of the model (Sect. 5). The input
files are available to allow other users to replicate results and use the methods to set up their own postseismic deformation
models.

2 Model Setup

85 2.1 Model Geometry and Mesh

The model is a global, spherical representation of the Earth, developed in *Abaqus-ABAQUS*-version 2018, but is also
compatible with older versions of the software as well. It is based on the finite-element model for computing glacial isostatic
adjustment following the methods described by Wu (2004), whereby we use the same set up of a viscoelastic Earth relaxing
in response to a stress change, but instead of applying a changing ice-surface load we implement a fault and associated slip.
90 We model a spherical Earth rather than taking a layered half-space approach so a more realistic geometry can be included and
gravity perturbations due to deformation can be accounted for by means of a spherical harmonic expansion. The model has
layers from the surface to the core-mantle boundary with computational feasibility being the only limit on the number of layers.
Each layer is assigned material properties according to user requirements and would typically consist of an elastic outer layer
representing the uppermost lithosphere, with viscoelastic lower lithosphere and mantle layers below.

95

An earthquake is simulated in the model by movement on a fault plane within the mesh (see Sect. 3 for details) and in order to compute deformation to a sufficient accuracy a high-resolution mesh is required in the vicinity of the fault. To balance the need for a high-resolution mesh against a model with a computationally feasible number of elements, we take the approach of constructing two separate parts (~~*Abaqus* *ABAQUS*~~-keyword *PART): one for the high-resolution fault region and one for the lower resolution surrounding earth (Fig. 1). The two parts are then tied together (~~*Abaqus* *ABAQUS*~~-keyword *Tie) using surface-to-surface tie constraints. This means that although the two separate meshes have non-conforming elements relative to each other, the tie constraints ensure there is no relative movement between the surfaces and that displacement and stress are continuous through the boundaries. Tie coefficients are generated and used to interpolate quantities from nodes on one side of the mesh to nodes on the other side of the mesh. The size of the part containing the fault and high resolution mesh can be changed according to the requirements of the individual case study, and in the simulations presented in this study, is large enough to contain the far-field area of interest. The high-resolution mesh block extends to 670 km depth (i.e. the base of the upper mantle) so that any deformation that may be caused by the fault movement is within the block and hence there is minimal stress to transfer across the tied surfaces. The element type used is an 8-node linear brick element (C3D8 in ~~*Abaqus* *ABAQUS*~~).

2.2 Rheology and Earth Parameters

All layers within the model are assigned a density (ρ), Poisson's ratio (ν) and Young's Modulus (E) (~~*Abaqus* *ABAQUS*~~-keywords *Density *Elastic). For viscoelastic layers below the purely elastic outer shell, a relaxation time is specified which is based on a Prony time series (~~*Abaqus* *ABAQUS*~~-key words *Viscoelastic). In this study we limit our benchmarking examples to a 1D linear viscoelastic rheology with one (Maxwell) or two (Burgers) relaxation times, and include one example implementing the elastic properties of the widely used Preliminary Reference Earth Model (PREM, Dziewonski & Anderson, 1981). ~~however~~ However, ~~*Abaqus* *ABAQUS*~~ has the capability of implementing a variety of rheological models, including user-specified constitutive equations. For example, Freed et al. (2012) combined power-law rheology with a transient phase to model postseismic deformation following the 1999 magnitude 7.1 Hector Mine earthquake, and van der Wal et al. (2010) used a composite rheology based on laboratory-derived flow laws for diffusion and dislocation creep (Hirth and Kohlstedt, 2003; Karato and Wu, 1993) to model global glacial isostatic adjustment. Furthermore, variations of our model could be constructed using a 3D Earth structure (e.g. van der Wal et al., 2015) (more information on how this can be done is included in the supplementary material (Nield, 2022)).

2.3 Boundary Conditions

We follow the approach described in Section 4.1 of Wu (2004) and apply elastic foundations (~~*Abaqus* *ABAQUS*~~-keyword *Foundation) to each layer boundary with a material density contrast occurring across it (including the surface and core-mantle-boundary). This means that advection of pre-stress is included and takes care of the restoring forces of buoyancy neglected in a conventional finite-element model (Wu, 2004, equation 3). The elastic foundations have a stiffness equal to the

130 difference in density multiplied by gravitational acceleration (see Wu (2004) equations 12a,b,c). Schmidt et al. (2012) show that the use of foundations at surfaces not perpendicular to the direction of gravity produces errors in results, but we ensure that density contrasts occur only at spherical layer boundaries in our model which satisfies this requirement. The foundations could be also replaced by spring elements when an inclined density contrast is used (Schmidt et al., 2012).

2.4 Time Steps

135 Once the model has been set up with the geometry, rheology, Earth parameters, boundary conditions, and fault slip (see Sect. 3); time steps are created to run the model. The first step of the run is a static step to allow the fault to slip. In this step all material properties are treated as elastic and the fault displaces immediately, hence no actual time needs to be assigned. All subsequent steps are for the simulation of postseismic relaxation and consequently must have a time assigned to them. One full run of all the time steps is one iteration.

2.5 Self-Gravitation

140 Movement of mass due to deformation of the Earth perturbs the gravity field which in turn affects the Earth's deformation. The effect of changes in the gravity field needs to be taken into account to make the model self-gravitating. This is done iteratively as described in Section 4.3 of Wu (2004), first using a non-self-gravitating model and computing the resulting gravitational potential from the radial displacement using the equations presented in Section 4 of Wu (2004). Applying this as a new load at the interfaces of the model where a density contrast occurs across them, the displacement is recalculated (i.e. another iteration is run). Wu (2004, Section 4.3) suggests running the model for 4-5 iterations to achieve convergence of the solution.

2.6 Outputs

150 ~~Abaqus~~ *ABAQUS* can compute many different output variables depending on the model setup. For our model the main output of interest is a global grid of deformation in the east, north and radial directions. It is also possible to output stress, strain, and perturbation to the geoid which could be used to correct satellite gravimetry data for the gravity change associated with very large earthquakes (e.g. Han et al. 2014).

3 Implementation of an Earthquake

3.1 Fault Geometry and Slip

155 In our model an earthquake is simulated by prescribing slip on a fault plane. In order to implement this in a finite-element mesh we require two separate surfaces that can move relative to each other. We take the approach of Steffen et al. (2014), whose model simulates fault slip due to changes in stress during glacial cycles, whereby the fault plane geometry is created

prior to meshing and then once generated, the mesh is subsequently altered to produce two surfaces. This is accomplished by duplicating the nodes that lie on the fault surface and then reassigning the duplicated nodes to the elements on one side of the fault plane, thereby creating a “cut” in the mesh. Although the elements on each side of the fault are defined by different nodes, the node pairs initially have the same coordinates (Fig. 2).

160

The model of Steffen et al. (2014) incorporates a complex stress history comprising tectonic stresses and stresses relating to glacial cycles allowing faults to slip in response to the changing conditions. Our model differs from this approach because the amount of slip that occurs on the fault plane is prescribed. This negates the need to specify any fault surface parameters such as coefficient of friction or cohesion but does require detailed knowledge of the earthquake event. Prescribing an amount of slip on the fault plane is a reasonable approach as fault properties, such as length, width, strike, dip, rake, and slip are often solved through independent means such as fault inversion studies (Hayes, 2017) and detailed fault slip information is not required when studying far-field deformation. Furthermore, we do not include any pre-stress in the model, that is, there is no tectonic or background stress applied before the fault slips. This has no effect for models that use Maxwell or Burgers rheology as they are independent of stress.

165

170 3.2 Coseismic Slip

Once the finite-element mesh has been adjusted to accommodate the fault plane, coseismic displacement is prescribed following the approach of Masterlark (2003). For every node pair on the fault plane (i.e. nodes on either side of the fault that have the same coordinates), a third “dummy” node is created at the same location but not connected to any element in the mesh (Fig. 2). Dummy nodes are assigned a displacement boundary condition (~~Abaqus ABAQUS~~ keyword *Boundary) in the x and y directions of a local coordinate system aligned with the fault plane (see Fig. 2) with the amount of displacement in each direction depending on the slip and rake. For example, using basic trigonometry, a slip of 5m at a rake of -60° would equate to slip of 2.5m in the X direction and 4.3m in the Y direction. Kinematic constraint equations (~~Abaqus ABAQUS~~ keyword *Equation) are then constructed for each node pair and its corresponding dummy node which specifies the relative displacement between the node pair in the X and Y direction. There is no relative displacement in the Z direction of the local coordinate system (i.e. normal to the fault plane), as the fault is not allowed to open. Because the constraint equations are specified separately for each node, the fault plane can accommodate a spatially variable slip distribution. The first step of the model run is a static step (~~Abaqus ABAQUS~~ keyword *Static) in which the nodes (and hence the fault plane) displace according to the kinematic constraint equations. During the static step, all materials are treated as elastic.

175

180

3.3 Postseismic Deformation

Following the first step of the model run (i.e. the earthquake), the subsequent time steps simulate postseismic deformation (~~Abaqus ABAQUS~~ keyword *Visco) by allowing the mesh to deform under the stresses caused by the displacement on the

185

fault plane. The kinematic constraint equations remain in place throughout the model run which means that there is no further relative displacement between the node pairs.

4 Benchmarking

190 In order to verify the model we benchmark the results against those produced with the Okada analytical solution for coseismic displacement (Okada, 1985) and the *VISCOID* code (Version 3) for gravitational postseismic relaxation (Pollitz, 1997).

4.1 Test Setup

We perform three benchmarking tests each with different geometry: a strike-slip fault, a 30° dipping reverse fault, and a 45° dipping fault with rake of -60°, as summarised in Table 1. All faults outcrop at the surface of the model. The resolution of the mesh on the fault plane is 10 × 5 km. In plan view, the Abaqus ABAQUS-mesh has 10 km elements in the vicinity of the fault, increasing to 50 km at the edge of the fault region, with elements in the surrounding low-resolution part, starting 1000 km away from the fault, being up to 500 km (Fig. 1). The element size increases with depth as shown in Table 2. For the 30° dipping reverse fault we tested a coarser and a finer mesh and found that our chosen mesh resolution provided a satisfactory trade-off between computation time and accuracy, with the finer mesh giving only small differences in near- and far-field displacement compared to our chosen mesh, for a 10-fold increase in computation time. The results of this sensitivity test are discussed in more detail in Appendix A.

The model is run for 500 years to verify both the short and long term postseismic deformation, and for 4 iterations to ensure convergence of the self-gravitational solution. The Abaqus ABAQUS-input files for the benchmarking tests are included in the supplementary material (Nield, 20202022). *VISCOID* is run for the same time period and with maximum spherical harmonic degree of 2000, equivalent to ~10 km resolution.

In all benchmarking tests the same simple Earth structure is used (details for the Abaqus ABAQUS-model are in Table 2), which is based on the Earth structure used by Pollitz (1997) for the upper most 670 km, and we include a uniform lower mantle layer below. We found that the vertical deformation results for *VISCOID* were sensitive to the number of layers in the input Earth structure and the presence of a lower mantle, so whilst the material properties are the same for both models, the *VISCOID* Earth model contains more layers. We use this simple Earth structure rather than the Preliminary Reference Earth Structure (PREM, Dziewonski & Anderson, 1981) to ensure our results are consistent with the Okada analytical solution for a homogenous half-space and the results presented by Pollitz (1997). We use a linear Maxwell rheology for all three benchmarking tests. We additionally verify the implementation of Burgers rheology against *VISCOID* for the third test, with the transient viscosity (η) given in Table 2. Furthermore, we run the third test case in Abaqus using the elastic properties from PREM, keeping the same three-layer Maxwell viscosity profile as the benchmarking Earth model (Table 2). We do not

benchmark the results from this test case as the Okada analytical solution is only valid for a homogeneous Earth. The input files for each test case and the Earth models used in the *VISCOID* modelling for both Maxwell and Burgers rheology are given in the supplementary material (Nield, 2020, 2022). All output displacements are shown normalised to the fault slip, in other words as a percentage of fault slip. This is consistent with the presentation of results by Pollitz (1997) and provides a useful metric for comparison of results. Differences between the model results are given as the difference between the percentages of fault slip.

4.2 Coseismic Results

The results of the benchmarking exercises are shown in Figs. 3-5. We show coseismic displacement in the east, north and vertical directions for a profile perpendicular to the fault strike for each of the benchmarking tests. Surface displacement is shown in Appendix B, Figs. B1-B3. The Okada analytical solution is shown by the dark green line with the equivalent *ABAQUS* *Abaqus* coseismic output shown by the light green dots. The difference between the models is shown in panel b) of Figs. 3-5. Overall, there is an excellent agreement between the *Abaqus* *ABAQUS*-model and the Okada analytical solution. Of the three cases, the strike-slip fault agrees most closely (Fig. 3), with differences peaking at 1% of the fault slip in the north direction (Fig. 3b). There are larger differences visible for the dipping fault cases (Figs. 4-5). Some of the near-field finer details of displacement in the east and vertical directions for the dipping faults (i.e. the directions with most displacement) are not perfectly captured by *Abaqus* *ABAQUS*, for example at 50 km from the fault (see Fig. 4a, vertical direction), and we attribute this to the mesh resolution and the distorted element shape that is required to mesh around a dipping fault. However, these differences are a maximum of 6% (Fig. 4b) and at distances greater than 300 km from the fault this decreases to less than 0.5%. Since the aim of our model is to predict far-field deformation these differences are acceptable.

4.3 Postseismic Results

Figs. 3-5 also show profiles of the postseismic displacement in the east, north and vertical directions for *VISCOID* (light blue line) and the *Abaqus* *ABAQUS*-model (dark blue dashed line). We show displacement as a percentage of fault slip at three times: 10, 50 and 100 years after the earthquake with corresponding differences between the models shown in panel b) of each figure. Surface postseismic displacement at each of these times is shown in Appendix B, Figs. B1-B3. The *Abaqus* *ABAQUS* predictions closely agree with *VISCOID* for the strike-slip fault case (Fig. 3). Small differences can be observed for the dipping faults particularly in the vertical direction (Figs. 4b and 5b). The mismatch in the coseismic displacement due to limitations in mesh resolution is the cause of mismatch for the postseismic displacement, i.e., less coseismic displacement from the *Abaqus* *ABAQUS*-model would result in less stress and therefore less relaxation. Slight improvements in the near-field displacement could be made by increasing the mesh resolution in the vicinity of the fault but would come at a computational cost (see Appendix A). However, the differences remain small and are concentrated within 100 km of the fault with a maximum difference of 5% of the fault slip after 100 years of relaxation (Fig. 4b) and less than 0.5% at distances greater than 300 km from the fault. Therefore, we conclude that the model results are reliable for far-field postseismic deformation.

250

Figs. 6-7 show displacement through time for the fault geometry in test 3 for two points at 100 km (Fig. 6) and 300 km (Fig. 7) from the fault using both a Maxwell and Burgers rheology. There is clear consistency in the evolution of postseismic relaxation between our model and *VISCOID*, for both rheologies (compare solid with dashed lines on Figs. 6a and 7a). The insets in Figs. 6-7 show the results for the initial 30 years of the model run where a rapid displacement can be observed from the transient viscosity of the Burgers rheology (orange/red lines) before converging with the results from the Maxwell model (blue lines) after approximately 30 years. Over the 500-year period, differences between our ~~*Abaqus*~~ *ABAQUS* model and *VISCOID* for the Burgers rheology are less than 0.6% of the fault slip within 100 km of the fault (Fig. 6b), or less than 0.1% at distances of 300 km or more (Fig. 7b). For the Maxwell rheology, differences peak at 0.5% of the fault slip within 100 km, reducing to 0.2% at 300 km.

260

Figs. 6a and 7a also show the displacement for test case 3 with the PREM elastic properties (green dotted lines). At 100 km distance from the fault (Fig. 6a), the different elastic structure results in slightly more coseismic displacement than the simple elastic structure used in the benchmarking tests, which results in greater postseismic displacement with time. At 300 km distance from the fault (Fig. 7a), the depth varying PREM elastic structure results in only very small differences. The surface coseismic and postseismic displacements at 10, 50 and 100 years after the earthquake are shown in Fig. B4, Appendix B.

265

5 Discussion and Conclusions

We have presented a finite-element model constructed in ~~*Abaqus*~~ *ABAQUS* for the purposes of modelling far-field coseismic and postseismic deformation. The model is global, spherical and self-gravitating, and allows for simple modification to include three-dimensional Earth structure, non-linear rheologies and alternative or multiple sources of stress change.

270

The model performs well when compared with the Okada coseismic analytical solution and predictions from the postseismic *VISCOID* program for all three fault scenarios we have tested. For the coseismic displacement, differences are less than 6% of the fault slip, with the largest differences in the vertical direction and near to the fault; in the fault far-field the differences are negligible. For the postseismic displacement, differences are less than 5% of the fault slip and at distances of 300 km from the fault, i.e. the far-field which is the focus of our model, this reduces to differences of 0.5%. Furthermore, we have verified that the evolution of displacement through time is an excellent match with *VISCOID* for both Maxwell and Burgers rheologies. For interest, we also computed the displacement for test case 3 using the PREM elastic properties, finding differences in results within 100 km of the fault. Although, in the far-field, changing the elastic structure has minimal impact on the resulting postseismic displacement as we used the same viscosity structure.


280

Inclusion of self-gravitation makes only a small difference to the displacement, peaking at 0.2 mm (less than 0.1% of the fault slip) for the reverse fault (test 2) in the vertical displacement and is negligible in the horizontal directions. This demonstrates that it is not necessary to include self-gravitation when modelling postseismic deformation in isolation, but it could become important when modelling postseismic deformation alongside other larger sources of deformation such as changes in ice loading.


The main limitation of the model at present is that the geometry is restricted to a single fault plane within the mesh and it cannot have multiple segments of a fault plane with different strike or dip. This is due to the difficulties of constructing a valid spherical mesh in Abaqus ABAQUS with brick elements that conform to verification checks. For the same reason, including more than one earthquake in the same model would be problematic. This issue could potentially be resolved by employing external meshing software (e.g., Gmsh (Geuzaine and Remacle, 2009)). In the case of a fault inversion that suggests multiple fault segments (e.g. Ye et al., 2014), an approximation of all the fault planes into a single geometry could still provide a realistic far-field estimate of postseismic deformation (e.g. Takeuchi and Fialko, 2013), particularly if the fault geometry and slip are adjusted so that model output matches observations of coseismic displacement (e.g. Sun et al., 2018). Far-field postseismic deformation is less sensitive to simplifications made to the fault geometry and slip distribution than near-field deformation (Khazaradze et al., 2002, Tregoning et al., 2013, Zhou et al. 2012). Alternatively, each fault segment could be analysed in a separate model and resulting deformation be combined, providing a linear rheology is used. The model can, however, account for varying slip and rake along the single fault plane by specifying individual values at each node pair. At present the fault is not permitted to open, and whilst this is a realistic scenario for a fault, it would have negligible impact on the far-field postseismic deformation.

We have demonstrated the validity of this model for far-field coseismic and postseismic deformations. It is an improvement on existing models as it includes global spherical geometry, self-gravitation, and can be adapted to include 3D Earth structure. It will prove particularly useful for investigating earthquakes in regions that may have large lateral variations in Earth properties where a 1D Earth model cannot reproduce geodetic observations. Furthermore, the capability of ABAQUS-Abaqus to model surface loading such as a changing ice load has already been established (e.g. van der Wal et al., 2010; Wu, 2004), and could easily be incorporated into this model.


310



315 Figure 1: ABAQUS-Abaqus mesh; a) full global mesh with high-resolution fault region surrounded by lower resolution elements; b) close up plan view of the fault region with fault marked in red and cross-section x-x' shown in c); c) cross-section x-x' (as marked in b)) through the fault region for 45° dipping fault with fault marked in red.



325 Figure 2: a) Diagram of the fault plane (shaded grey) in the ABAQUS-Abaqus mesh with collocated node pairs and local coordinate system aligned with the fault plane; b) close up of a node pair (m, n) and dummy node (d) with displacement boundary condition applied in the x direction of the local coordinate system (for illustrative purposes only, the fault is not allowed to open in the z direction); c) constraint equations applied to the node pair results in displacement of nodes m and n in the x direction.



330 Figure 3: Top panels of a) and b) show the fault dimensions and material properties of the upper 100 km of the model. Layers and
 and material properties below 100 km depth are given in Table 2. a) Coseismic (green) and postseismic (blue) surface displacements in
 east, north and vertical directions in response to slip on a strike slip fault for a profile perpendicular to the fault strike. Results are
 calculated using the Okada analytical solution, *VISCO1D*, and *ABAQUS-Abaqus* (see legend). Postseismic displacement is shown for
 times 10, 50, and 100 years after fault slip. Earth properties and fault dimension are given in top panel. Displacements are given as
 a percentage of the fault slip. b) Differences between the *Abaqus* *ABAQUS* coseismic displacement and the Okada analytical solution
 335 (green) and the *ABAQUS-Abaqus* postseismic displacement and the *VISCO1D* displacement (blue). Differences are in terms of
 percentage of the fault slip.






Figure 4: As for Figure 3 but for a 30° dipping reverse fault.



350


Figure 5: As for Figure 3 but for a 45° dipping fault.

355



360 Figure 6: a) Postseismic surface displacement through time in the east, north and vertical directions at a location 100 km
perpendicular to the fault in Figure 5. Predictions using two rheologies are shown: Maxwell rheology using *VISCOID* and *Abaqus ABAQUS*;
and Burgers rheology using *VISCOID* and *Abaqus ABAQUS* (see legend). **Predictions from *Abaqus* using the PREM
elastic properties are also shown (green dots).** The main plot for each displacement direction shows 500 years of displacement with
the first 30 years shown in detail in the insets. Displacements are given as a percentage of the fault slip. b) Difference between the
365 *Abaqus ABAQUS* postseismic displacement and the *VISCOID* displacement for Maxwell rheology (light blue line) and Burgers
rheology (orange line). Positive indicates *Abaqus ABAQUS* has less displacement than *VISCOID* and negative indicates *Abaqus
ABAQUS* has more displacement than *VISCOID*. Differences are in terms of percentage of the fault slip. Note **difference-different**
scales on the y-axis.

370



375 **Figure 7:** As for Figure 6 but for a location 300 km perpendicular to the fault in Figure 5. Note difference-different scales on the y-axis.

380

385 **Table 1: Fault geometry used in the three benchmarking exercises. Note that test case 3 is run with 3 Earth models, see Table 2.**

Test	Fault length (km)	Fault width (km)	Fault vertical depth (km)	Dip (°)	Strike (°)	Rake (°)	Slip (m)
1. Strike-slip	200	20	20	90	0	0	5
2. Reverse fault	200	40	20	30	0	90	5
3. Normal oblique	200	28.28	20	45	0	-60	5

Table 2: Earth model used in the Abaqus ABAQUS model for the benchmarking exercises with a Maxwell rheology and a Burgers rheology (transient viscosity given in brackets). The Maxwell viscosity profile is also used in conjunction with the PREM elastic structure for test case 3.

Layer Description	Depth of top of layer (km)	Layer thickness (km)	Density, ρ (kg/m ³)	Young's Modulus (Pa)	Poisson's Ratio, ν	Viscosity, η (Pa s)	Vertical Element Resolution (km)
Elastic Lithosphere	0	30	3300	7.50E+10	0.25	Purely Elastic	5
Lower lithosphere/ Upper Mantle	30	640	3800	7.50E+10	0.25	1.00E+19 (transient viscosity 1.00E+18)	10 (from 30 to 400km depth) 50 (from 400 to 670km depth)
Lower Mantle	670	2221	5000	1.10E+11	0.25	1.00E+21	500

390

Appendix A: Mesh Resolution Test

In general, the higher the mesh resolution the more accurate the predictions of coseismic and postseismic displacement. However, increases in the mesh resolution in the near field of the fault quickly result in a prohibitively large number of elements in the model, and it becomes computationally too expensive to run. To verify that our choice of mesh resolution is sufficient, we set up the 30° reverse fault test with a coarser and a finer mesh resolution and compared the model-predicted displacement in the near- and far-field. Since the aim of our model is to calculate far-field postseismic deformation, the convergence of displacement at distances of 300 km from the fault is what determines the choice of mesh resolution, although results are given for the near-field for interest.

400

Table A1 shows the resolution of each mesh along with computation time for one iteration of the model. Note, this computation time is for [parallel processing on 8 cores](#) on a standard Linux workstation. Due to the way *ABAQUS-Abaqus* licensing works, individual set ups may be faster than the time quoted in Table A1 if users have access to more cores and licences. We term the mesh used in the main body of the paper the “reference mesh”.

405

Table A1: Details of the meshes used in the sensitivity test.

	Coarse Mesh	Reference Mesh	Fine Mesh
Lateral resolution of elements on the fault plane (km)	20	10	5
Depth resolution of elements on the fault plane (km)	10	5	5
Number of elements on the fault plane	20	80	160
Number of elements in the model	161,366	417,309	1,250,590
Computation time for one iteration	45 minutes	8 hours	84 hours

We evaluate overall displacement results in terms of differences in percentage of fault slip to be consistent with Figs. 3-7. The key results are summarised in Table A2. Comparing results for the reference mesh with the coarse mesh shows that near-field coseismic differences peak at 4.5% of the fault slip and the maximum difference in the postseismic deformation after 100 years is 3.1%. When comparing the reference mesh with the fine mesh, this reduces to 1.5% for coseismic differences and 1.2% for postseismic differences.

In the far-field however, differences between the coarse mesh and reference mesh are small, peaking at 0.2% of the fault slip after 100 years of postseismic deformation. Far-field differences between the reference mesh and the fine mesh are negligible. Since the focus of our model is the far-field, these results might suggest that any of the mesh resolutions tested would be sufficient. However, in terms of absolute displacement we see an improvement from differences of 5-9 mm between the coarse mesh and the reference mesh, to 0.1-1.6 mm for differences between the reference and fine meshes. This demonstrates that results have converged at the resolution of our chosen mesh to be less than the magnitude of uncertainty associated with GPS-observed postseismic deformation (e.g., Freed et al., 2006; Wang and Fialko, 2018). We therefore conclude that the chosen mesh resolution is more than fit for purpose, with only small improvements to near-field displacement to be gained by using a finer mesh.

425


Table A2: Differences in displacement (expressed as percentage of fault slip) between the different meshes in Table A1. In brackets is the direction of displacement where the maximum difference is observed.

		Reference Mesh minus Coarse Mesh	Fine Mesh minus Reference Mesh
Near-field (at the fault location)	Coseismic	4.5% (vertical)	1.5% (east)
	Postseismic after 100 years	3.1% (east)	1.2% (east)
Far-field (300 km from the fault)	Coseismic	0.1% (east)	0% (east)
	Postseismic after 100 years	0.2% (east)	0.03% (east)

430


Appendix B

This section shows surface displacement for the [Abaqus ABAQUS](#) model-predicted coseismic and postseismic displacement for each of the three benchmarking tests [with Maxwell rheology, and for test case 3 using the elastic properties from PREM.](#)




435

Figure B1: Model-predicted surface displacement in response to slip on a strike slip fault. Background colours show vertical displacement and arrows show horizontal displacement for: a) Coseismic displacement; b), c) and d) postseismic deformation at 10, 50, and 100 years after fault slip respectively.



440

Figure B2: As for Figure B1 but for a 30° dipping reverse fault. Note the different colour scales for coseismic and postseismic displacement.



445

Figure B3: As for Figure B1 but for a 45° dipping fault. Note the different colour scales for coseismic and postseismic displacement.




Figure B4: As for Figure B3, a 45° dipping fault, but using the PREM Earth model. Note the different colour scales for coseismic and postseismic displacement.

450

Code Availability. ~~Abaqus~~ ABAQUS is a commercial software and can be purchased from the developer (<https://www.3ds.com/products-services/simulia/products/abaqus/>); ~~We~~ We have used version 2018 in this study, but the methods and functionality used are available in older versions of the software as well. ~~Abaqus~~ ABAQUS input files for all ~~four~~ five models presented in this paper are available at https://github.com/ganield/ABAQUS_Postseismic_model/releases/tag/v1.1, https://github.com/ganield/ABAQUS_Postseismic_model/releases/tag/v1.1.2.0, and archived on Zenodo: <https://doi.org/10.5281/zenodo.3891444> <https://doi.org/10.5281/zenodo.5897863> (Nield, 20202022). Instructions on how to run the files are also available at this link.

455

VISCOID version 3 is available for download at: <https://www.usgs.gov/software/visco1d>. The VISCOID input files and Earth model files used in the experiments presented in this paper are included in the github repository, along with some instructions on how to run the code.

460

Author Contributions. GN developed the model. MK conceived the study and consulted in the model implementation. RS contributed meshing code for ~~ABAQUS~~ ~~Abaqus~~ and consulted in the model development. BB contributed the self-gravitational part of the code. All authors contributed to the manuscript.

465

Competing Interests. None.

Acknowledgements. GN is supported by ARC Discovery Project DP170100224. We are grateful to Fred Pollitz for making VISCOID freely available and for his assistance with using the software. We also thank Tim Masterlark for his advice on

470 implementing fault slip in [ABAQUS-Abaqus](#) and Wouter van der Wal for guidance on constructing [ABAQUS-Abaqus](#) models.
The handling editor Lutz Gross and two anonymous reviewers are gratefully acknowledged for their constructive comments.

References

- 475 Agata, R., Barbot, S. D., Fujita, K., Hyodo, M., Inuma, T., Nakata, R., Ichimura, T., and Hori, T.: Rapid mantle flow with power-law creep explains deformation after the 2011 Tohoku mega-quake, *Nat Commun*, 10, 1385, 10.1038/s41467-019-08984-7, 2019.
- Broerse, D. B. T., Vermeersen, L. L. A., Riva, R. E. M., and van der Wal, W.: Ocean contribution to co-seismic crustal deformation and geoid anomalies: Application to the 2004 December 26 Sumatra–Andaman earthquake, *Earth and Planetary Science Letters*, 305, 341-349, <https://doi.org/10.1016/j.epsl.2011.03.011>, 2011.
- 480 Dziewonski, A. M. and Anderson, D. L.: Preliminary Reference Earth Model, *Phys Earth Planet In*, 25, 297-356, 1981.
- Freed, A. M., Burgmann, R., Calais, E., and Freymueller, J.: Stress-dependent power-law flow in the upper mantle following the 2002 Denali, Alaska, earthquake, *Earth and Planetary Science Letters*, 252, 481-489, 10.1016/j.epsl.2006.10.011, 2006.
- Freed, A. M., Hirth, G., and Behn, M. D.: Using short-term postseismic displacements to infer the ambient deformation conditions of the upper mantle, *Journal of Geophysical Research: Solid Earth*, 117, 10.1029/2011jb008562, 2012.
- 485 [Geuzaine C., and Remacle J.-F.: Gmsh: A 3-D finite element mesh generator with built-in pre- and post-processing facilities, *Internat. J. Numer. Methods Engrg.*, 79 \(11\), pp. 1309-1331, 10.1002/nme.2579, 2009.](#)
- Han, S.-C., Sauber, J., and Pollitz, F.: Broadscale postseismic gravity change following the 2011 Tohoku-Oki earthquake and implication for deformation by viscoelastic relaxation and afterslip, *Geophys Res Lett*, 41, 5797-5805, 10.1002/2014gl060905, 2014.
- 490 Hayes, G. P.: The finite, kinematic rupture properties of great-sized earthquakes since 1990, *Earth and Planetary Science Letters*, 468, 94-100, <https://doi.org/10.1016/j.epsl.2017.04.003>, 2017.
- Hibbitt, D., Karlsson, B., and Sorenson, P.: *Getting Started with ABAQUS - Version (6.14)*, Hibbitt, Karlsson & Sorensen, Inc. 2016.
- Hirth, G. and Kohlstedt, D.: Rheology of the upper mantle and the mantle wedge: A view from the experimentalists, in: *Inside the Subduction Factory*, edited by: Eiler, J., *Geophysical Monograph Series, AGU*, 83-105, 2003.
- 495 Hu, Y. and Wang, K.: Spherical-Earth finite element model of short-term postseismic deformation following the 2004 Sumatra earthquake, *Journal of Geophysical Research: Solid Earth*, 117, 10.1029/2012jb009153, 2012.

- Hu, Y., Wang, K., He, J., Klotz, J., and Khazaradze, G.: Three-dimensional viscoelastic finite element model for postseismic deformation of the great 1960 Chile earthquake, *Journal of Geophysical Research: Solid Earth*, 109, 10.1029/2004jb003163, 500 2004.
- Huang, M.-H., Bürgmann, R., and Freed, A. M.: Probing the lithospheric rheology across the eastern margin of the Tibetan Plateau, *Earth and Planetary Science Letters*, 396, 88-96, <https://doi.org/10.1016/j.epsl.2014.04.003>, 2014.
- Karato, S. and Wu, P.: Rheology of the Upper Mantle - a Synthesis, *Science*, 260, 771-778, 10.1126/science.260.5109.771, 1993.
- 505 Khazaradze, G., Wang, K., Klotz, J., Hu, Y., and He, J.: Prolonged post-seismic deformation of the 1960 great Chile earthquake and implications for mantle rheology, *Geophys Res Lett*, 29, 7-1-7-4, 10.1029/2002gl015986, 2002.
- Khazaradze, G. and Klotz, J.: Short- and long-term effects of GPS measured crustal deformation rates along the south central Andes, *Journal of Geophysical Research: Solid Earth*, 108, 10.1029/2002jb001879, 2003.
- King, M. A. and Santamaría-Gómez, A.: Ongoing deformation of Antarctica following recent Great Earthquakes, *Geophys* 510 *Res Lett*, 43, 1918-1927, 10.1002/2016gl067773, 2016.
- Latychev, K., Mitrovica, J. X., Tromp, J., Tamisiea, M. E., Komatitsch, D., and Christara, C. C.: Glacial isostatic adjustment on 3-D Earth models: a finite-volume formulation, *Geophys J Int*, 161, 421-444, 2005.
- Masterlark, T.: Finite element model predictions of static deformation from dislocation sources in a subduction zone: Sensitivities to homogeneous, isotropic, Poisson-solid, and half-space assumptions, *Journal of Geophysical Research: Solid* 515 *Earth*, 108, 10.1029/2002jb002296, 2003.
- Masterlark, T., DeMets, C., Wang, H. F., Sánchez, O., and Stock, J.: Homogeneous vs heterogeneous subduction zone models: Coseismic and postseismic deformation, *Geophys Res Lett*, 28, 4047-4050, 2001.
- Masterlark, T. and Wang, H. F.: Transient Stress-Coupling Between the 1992 Landers and 1999 Hector Mine, California, Earthquakes, *B Seismol Soc Am*, 92, 1470-1486, 2002.
- 520 Nield, G. A.: ganield/ABAQUS_Postseismic_model v2.01.1. Zenodo. —<https://doi.org/10.5281/ZENODO.3891444> <https://doi.org/10.5281/zenodo.5897863>, 20202.
- Okada, Y.: Surface deformation due to shear and tensile faults in a half-space, *B Seismol Soc Am*, 75, 1135-1154, 1985.
- Peña, C., Heidbach, O., Moreno, M., Bedford, J., Ziegler, M., Tassara, A., and Oncken, O.: Role of Lower Crust in the Postseismic Deformation of the 2010 Maule Earthquake: Insights from a Model with Power-Law Rheology, *Pure Appl* 525 *Geophys*, 176, 3913-3928, 10.1007/s00024-018-02090-3, 2019.

- Pollitz, F. F.: Gravitational viscoelastic postseismic relaxation on a layered spherical Earth, *Journal of Geophysical Research: Solid Earth*, 102, 17921-17941, 10.1029/97jb01277, 1997.
- Pollitz, F. F.: Postseismic relaxation theory on the spherical earth, *B Seismol Soc Am*, 82, 422-453, 1992.
- 530 Pollitz, F. F.: Transient rheology of the upper mantle beneath central Alaska inferred from the crustal velocity field following the 2002 Denali earthquake, *Journal of Geophysical Research: Solid Earth*, 110, 10.1029/2005jb003672, 2005.
- Schmidt, P., Lund, B., and Hieronymus, C.: Implementation of the glacial rebound prestress advection correction in general-purpose finite element analysis software: Springs versus foundations, *Comput Geosci-Uk*, 40, 97-106, <https://doi.org/10.1016/j.cageo.2011.07.017>, 2012.
- 535 Shao, Z., Zhan, W., Zhang, L., and Xu, J.: Analysis of the Far-Field Co-seismic and Post-seismic Responses Caused by the 2011 MW 9.0 Tohoku-Oki Earthquake, *Pure Appl Geophys*, 173, 411-424, 10.1007/s00024-015-1131-9, 2016.
- Steffen, R., Wu, P., Steffen, H., and Eaton, D. W.: On the implementation of faults in finite-element glacial isostatic adjustment models, *Comput Geosci-Uk*, 62, 150-159, 10.1016/j.cageo.2013.06.012, 2014.
- Suito, H. and Freymueller, J. T.: A viscoelastic and afterslip postseismic deformation model for the 1964 Alaska earthquake, *Journal of Geophysical Research: Solid Earth*, 114, 10.1029/2008jb005954, 2009.
- 540 Sun, T., Wang, K., and He, J.: Crustal Deformation Following Great Subduction Earthquakes Controlled by Earthquake Size and Mantle Rheology, *Journal of Geophysical Research: Solid Earth*, 123, 5323-5345, 10.1029/2017jb015242, 2018.
- Takeuchi, C. S. and Fialko, Y.: On the effects of thermally weakened ductile shear zones on postseismic deformation, *Journal of Geophysical Research: Solid Earth*, 118, 6295-6310, 10.1002/2013jb010215, 2013.
- 545 Tregoning, P., Burgette, R., McClusky, S. C., Lejeune, S., Watson, C. S., and McQueen, H.: A decade of horizontal deformation from great earthquakes, *Journal of Geophysical Research: Solid Earth*, 118, 2371-2381, <https://doi.org/10.1002/jgrb.50154>, 2013.
- van der Wal, W., Whitehouse, P. L., and Schrama, E. J. O.: Effect of GIA models with 3D composite mantle viscosity on GRACE mass balance estimates for Antarctica, *Earth and Planetary Science Letters*, 414, 134-143, 2015.
- 550 van der Wal, W., Wu, P., Wang, H. S., and Sideris, M. G.: Sea levels and uplift rate from composite rheology in glacial isostatic adjustment modeling, *J. Geodyn.*, 50, 38-48, 10.1016/j.jog.2010.01.006, 2010.
- Wang, K. and Fialko, Y.: Observations and Modeling of Coseismic and Postseismic Deformation Due To the 2015 Mw 7.8 Gorkha (Nepal) Earthquake, *Journal of Geophysical Research: Solid Earth*, 123, 761-779, 10.1002/2017jb014620, 2018.

- Wang, R., Lorenzo-Martín, F., and Roth, F.: PSGRN/PSCMP—a new code for calculating co- and post-seismic deformation, geoid and gravity changes based on the viscoelastic-gravitational dislocation theory, *Comput Geosci-Uk*, 32, 527-541, 555 <https://doi.org/10.1016/j.cageo.2005.08.006>, 2006.
- Wu, P.: Using commercial finite element packages for the study of earth deformations, sea levels and the state of stress, *Geophys J Int*, 158, 401-408, 10.1111/j.1365-246X.2004.02338.x, 2004.
- [Wu, P., Wang, H.S., Steffen, H.: The role of thermal effect on mantle seismic anomalies under Laurentia and Fennoscandia from observations of Glacial Isostatic Adjustment, *Geophys J Int*, 192\(1\), 7-17, 10.1093/gji/ggs009, 2013.](#)
- 560 Ye, L., Lay, T., Koper, K. D., Smalley, R., Rivera, L., Bevis, M. G., Zakrajsek, A. F., and Teferle, F. N.: Complementary slip distributions of the August 4, 2003 Mw 7.6 and November 17, 2013 Mw 7.8 South Scotia Ridge earthquakes, *Earth and Planetary Science Letters*, 401, 215-226, <https://doi.org/10.1016/j.epsl.2014.06.007>, 2014.
- Zhong, S. J., Paulson, A., and Wahr, J.: Three-dimensional finite-element modelling of Earth's viscoelastic deformation: effects of lateral variations in lithospheric thickness, *Geophys J Int*, 155, 679-695, 10.1046/j.1365-246X.2003.02084.x, 2003.
- 565 Zhou, X., Sun, W., Zhao, B., Fu, G., Dong, J., and Nie, Z.: Geodetic observations detecting coseismic displacements and gravity changes caused by the Mw = 9.0 Tohoku-Oki earthquake, *Journal of Geophysical Research: Solid Earth*, 117, <https://doi.org/10.1029/2011JB008849>, 2012.