A spatially-explicit approach to simulate urban heat mitigation with InVEST (v3.8.0)

Martí Bosch¹, Maxence Locatelli¹, Perrine Hamel², Roy P. Remme³, Jérôme Chenal¹, and Stéphane Joost^{4,1}

¹Urban and Regional Planning Community, École Polytechnique Fédérale de Lausanne, Lausanne, Switzerland
 ²Asian School of the Environment, Nanyang Technological University, Singapore
 ³Natural Capital Project, Stanford University, Stanford, USA
 ⁴Laboratory of Geographic Information Systems, École Polytechnique Fédérale de Lausanne, Lausanne, Switzerland

Correspondence: Martí Bosch (marti.bosch@epfl.ch)

Abstract. Mitigating urban heat islands has become an important objective for many cities experiencing heat waves. Despite notable progress, the spatial relationship between land use/land cover patterns and the distribution of air temperature remains poorly understood. This article presents a reusable computational workflow to simulate the spatial distribution of air temperature in urban areas from their land use/land cover data. The approach employs the InVEST urban cooling model, which

- 5 estimates the cooling capacity of the urban fabric based on three biophysical mechanisms, i.e., tree shade, evapotranspiration and albedo. An automated procedure is proposed to calibrate the parameters of the model to best fit air temperature observations from monitoring stations. In a case study in Lausanne, Switzerland, spatial estimates of air temperature obtained with the calibrated model show that the urban cooling model outperforms spatial regressions based on satellite data. This represents two major advances in urban heat island modeling. First, unlike in black-box approaches, the calibrated parameters of the urban
- 10 cooling model can be interpreted in terms of the physical mechanisms that they represent and can therefore help understanding how urban heat islands emerge in a particular context. Second, the urban cooling model requires only land use/land cover and reference temperature data and can therefore be used to evaluate synthetic scenarios such as master plans, urbanization prospects, and climate scenarios. The proposed approach provides valuable insights into the emergence of urban heat islands which can serve to inform urban planning and assist the design of heat mitigation policies.

15 1 Introduction

20

Since the industrial revolution, the earth has seen a global increase of temperature which has been especially prominent in urban areas (Oke, 1973; Arnfield, 2003; Clinton and Gong, 2013). Such a trend concurs with an unprecedented growth of urban areas, making contemporary cities a major source of landscape changes and greenhouse gas emissions (Angel et al., 2005; Grimm et al., 2008; United Nations, 2015). By modifying the energy and water balance processes and influencing the movement of air, urban surfaces alter local climatic characteristics, often resulting in warmer temperatures than its rural surroundings (Oke,

1982). This phenomenon is known as the urban heat island (UHI) effect.

The quantification of UHIs can be broadly divided into two main approaches (Schwarz et al., 2011), namely the canopylayer UHI, measured by the air temperature, usually at 2 m height (Stewart, 2011), and the surface UHI, measured by land surface temperatures (LST) derived from remote sensing data (Voogt and Oke, 2003). The increasing availability of satellite

25

raster datasets has fostered a large body of research on the spatial distribution of LST and its relationship with the spatial composition and configuration of urban landscapes (Voogt and Oke, 2003; Zhou et al., 2019), which contrasts with the spatial sparsity of meteorological stations that measure air temperature. Despite exhibiting some correlations, air temperature and LST are essentially different physical quantities. Air temperature is closer to thermal comfort felt by humans, and can therefore be employed to evaluate the influence of UHIs on key matters such as energy demand for air conditioning or human health. Additionally, depending on the satellite overpass time, the differences between air temperature and LST can range from a 30 few degrees (°C) up to tens of degrees (Jin and Dickinson, 2010; Sobrino et al., 2012), which calls for special caution when employing satellite-derived LST data for the study of UHIs.

Although notable studies have explored the relationship between satellite-derived LST raster data and air temperature measurements to provide high-resolution insights of the canopy-layer UHI (Fabrizi et al., 2010; Schwarz et al., 2012; Anniballe

- et al., 2014; Sheng et al., 2017; Shiflett et al., 2017), they have mostly focused on finding statistical relationships between UHIs 35 and the spatial distribution of terrain features such as vegetation indices, without exploring how the observed patterns relate to the biophysical mechanisms that explain canopy-layer UHI. Such a limitation is important when models are used in simulations, for example to examine the effect of urban planning scenarios on air temperatures. As part of the Integrated Valuation of Ecosystem Services and Tradeoffs (InVEST) software, a suite of spatial models to quantify and value the goods and services
- 40 from nature that sustain and fulfill human life (Sharp et al., 2020), an urban cooling model has been developed following recent research on the effects of surface materials and vegetation cover on UHI (Phelan et al., 2015; Zardo et al., 2017). The aim of the urban cooling model is to simulate the spatial distribution of UHIs based on three key mechanisms, namely the shade provided by trees, the evapotranspiration of urban vegetation and the albedo of the urban surface. In a preliminary application of the model, Hamel et al. (2020) showed its capability to represent the spatial pattern of nighttime air temperature of the 2003
- heatwaves in the Île-de-France region. 45

The main objective of this study is to extend such preliminary experiments by proposing a reusable computational workflow to apply the InVEST urban cooling model to predict the spatial distribution of air temperature in a given study area. The validity of the simulated results is optimized by calibrating some key parameters to best fit a set of air temperature measurements from monitoring stations. Additionally, the simulated spatial pattern of air temperature is compared with the one obtained with an

50 alternative approach, namely a spatial regression over features extracted from satellite data.

2 Materials and methods

2.1 Study area

Situated at the western end of the Swiss Plateau and on the shores of the Lake Léman, Lausanne is the fourth largest Swiss urban agglomeration with 420757 inhabitants as of January 2019 (Swiss Federal Statistical Office, 2018). As the second most 55 important student and research center in Switzerland (after Zurich), the urban agglomeration of Lausanne has experienced substantial growth during recent decades, which has mostly occurred in the form of suburbanization (Bosch et al., 2020).

A notable geographic feature of Lausanne is its elevation difference of about 500 m between the lake shore at 372 m.a.s.l. and the northeastern part of the agglomeration (see Figure 1 below). The area is characterized by a continental temperate climate with mean annual temperatures of 10.9 °C and mean annual precipitation of 1100 mm, and a dominating vegetation of mixed broadleaf forest.

2.1.1 Spatial extent of the study

In line with urban economics and regional sciences, many works rely on administrative boundaries to define the spatial extent of the study. However, the way in which boundaries are constructed overlooks the characteristic scales in which landscape changes and environmental processes unfold, and might thus lead to equivocal results (Liu et al., 2014; Oliveira et al., 2014).

- 65 In consideration of such issues, the spatial extent for this study has been determined quantitatively by following the method employed in the Atlas of Urban Expansion (Angel et al., 2012). The core idea is that a pixel is considered part of the spatial extent depending on the proportion of built-up pixels that surround it. In this study, a pixel is considered part of the spatial extent when more than 15 % of the pixels that lay within a 500 m radius are built-up. Additionally, in order to evaluate how temperatures change across the urban-rural gradient, the spatial extent has been extended by a 1000 m buffer. The above
- 70 procedure has been applied to the rasterized LULC map by means of the Python library Urban footprinter (Bosch, 2020c). The obtained spatial extent, displayed in Figure 1, has a surface of 112.46 km².

2.2 Data

60

2.2.1 Land use/land cover data

The land use/land cover (LULC) maps have been obtained by rasterizing the vector geometries of the official cadastral survey
of August 2019 to the 10 m resolution. Such dataset is provided and maintained (i.e., weekly updated) by the cantonal administration of Vaud, and features the whole spatial extent of the canton of Vaud (Association pour le Système d'information du Territoire Vaudois, 2018). The classification distinguishes 25 LULC classes which are relevant to the urban, rural and wild landscapes encountered in Switzerland (Conference des Services Cantonaux du Cadastre, 2011). On the other hand, a 1 m binary tree canopy mask has been derived from the SWISSIMAGE orthomosaic (Federal Office of Topography, 2019), by
means of the Puthon library DetecTree (Bosch, 2020a) which implements the methods proposed by Yang et al. (2000). The

80 means of the Python library DetecTree (Bosch, 2020a), which implements the methods proposed by Yang et al. (2009). The tree canopy mask of the spatial extent of the study is shown in Figure 1.

2.2.2 Elevation data

The elevation map for the study area, which is displayed in Figure 1, is extracted from the free version of the digital height model of Switzerland (Federal Office of Topography, 2004), provided at the 200 m resolution by the Federal Office of Topog-85 raphy.



Figure 1. Study area. The upper left plot (A) shows the computed spatial extent (in orange) over the repartition of urban pixels (in black) derived from the rasterized cadastral survey (Association pour le Système d'information du Territoire Vaudois, 2018). The upper right plot (B) shows the locations of the air temperature measurement stations (see Appendix A2). The bottom row shows, for the computed spatial extent of the study, (C) the tree canopy map derived from the SWISSIMAGE orthomosaic (Federal Office of Topography, 2019) and (D) the altitude map derived from the free version of the digital height model of Switzerland (Federal Office of Topography, 2004). The basemap of plots A, C and D is based on the World Shaded Relief (Copyright: ©2009 Esri). The basemap tiles of plot B have been provided by Stamen Design, under CC BY 3.0, with data from OpenStreetMap, under ODbL.

2.2.3 Satellite data

The satellite dataset consists of the 8 Landsat 8 images in 2018 and 2019 which do not feature clouds over the study area and for days in which the maximum observed air temperature is over 25 $^{\circ}$ C (see the list of selected image tiles in Appendix A1). Data from Landsat 7 has been excluded because of the scan line corrector malfunction.

90 2.2.4 Air temperature data

A dataset of consistent air temperature measurements in the study area has been assembled by combining data from 11 stations operated by various governmental and research sources, which are shown in Figure 1. The temporal resolution of the stations ranges from 10 minutes to 30 minutes. Given that the UHI effect in Switzerland reaches its maximal intensity around 9 p.m. (Burgstall, 2019), the remainder of this study evaluates it based on the air temperature observations of that hour.

95 2.3 Simulation with the InVEST urban cooling model

The simulation of the spatial distribution of UHI employs the InVEST urban cooling model, version 3.8.0 (Sharp et al., 2020), which is based on the heat mitigation provided by shade, evapotranspiration and albedo. The main inputs are a LULC raster map, a reference evapotranspiration raster and a biophysical table containing model information of each LULC class of the map. Each row of the biophysical table represents a LULC class, and features the following columns:

100 – lucode the LULC class code as represented in the LULC raster map

- Shade a value between 0 and 1 representing the proportion of tree cover in such LULC class
- Kc the evapotranspiration coefficient
- Albedo a value between 0 and 1 representing the proportion of solar radiation directly reflected by the LULC class
- Green_area whether the LULC class should be considered a green area
- 105 Building_intensity a value between 0 and 1 representing the ratio between floor area and land area (for nighttime simulations)

2.3.1 Model description

The data inputs described above are used to compute the cooling capacity index, which is based on the physical mechanisms that contribute to cooling urban temperatures. More precisely, the cooling capacity index used in InVEST urban cooling model

110 builds upon the indices proposed by Zardo et al. (2017), which are based on shading and evapotranspiration, and extends them by adding a factor to account for the albedo. For each pixel *i* of the LULC raster map, the cooling capacity index is computed as in:

$$CC_i = w_S \cdot \mathbf{S}_i + w_{AL} \cdot \mathbf{AL}_i + w_{ET} \cdot \mathbf{ETI}_i \tag{1}$$

where S_i , AL_i and ETI_i respectively represent the tree shading, albedo and evapotranspiration values of pixel *i* as defined in 115 the biophysical table, and w_S , w_{AL} and w_{ET} represent the weights attributed to each component respectively. The values of S_i and AL_i are retrieved from the biophysical table according to the LULC class *k* of the pixel *i* (see Appendix A3). The tree shading is computed by overlaying the binary tree canopy mask with the rasterized LULC map so that for each LULC class *k*, the shade coefficient S_k corresponds to the average proportion of tree cover over all the LULC pixels of class *k*, as in:

$$S_k = \frac{1}{|\Omega_k|} \sum_{j \in \Omega_k} x_j \tag{2}$$

120 where Ω_k is the set of pixels of the tree canopy mask whose location corresponds to class k in the LULC raster, and x_j is the value of pixel j of the tree canopy mask, i.e., 1 if j corresponds to a tree and 0 otherwise. The albedo coefficients are based on the local climate zone classification by Stewart and Oke (2012).

The evapotranspiration index ETI is computed as a normalized value of the potential evapotranspiration as in:

$$ETI = \frac{K_c \cdot ET_{ref}}{ET_{max}} \tag{3}$$

125 where K_c is the evapotranspiration coefficient, ET_{ref} is the reference evapotranspiration raster for the period and area of interest and ET_{max} is the maximum evapotranspiration value observed in the area of interest.

In line with the studies of Nistor et al. (Nistor and Porumb, 2015; Nistor et al., 2016; Nistor, 2016), the evapotranspiration coefficients are attributed to each LULC class by distinguishing four cases, namely the crop coefficient for single crops for vegetation LULC classes, the water evaporation coefficient for surface water, the rock and soil evaporation coefficient for bare

130 soils and rocks, and evaporation coefficients for artificial LULC classes (e.g., urban areas). The evapotranspiration coefficients attributed to the LULC classes of the Swiss cadastral survey are listed in subsection A3.

Following the recommendations of Allen et al. (1998), the daily evapotranspiration ET_{ref} (in mm/day) has been estimated for each pixel using the Hargreaves equation (Hargreaves and Samani, 1985) as in:

$$ET_{ref} = 0.0023 \cdot (T_{avg} + 17.8) \cdot (T_{max} - T_{min})^{0.5} \cdot R_a \tag{4}$$

- 135 where T_{avg} , T_{max} and T_{min} respectively correspond to the average, maximum and minimum T_{air} (in °C) of each day and R_a is the extraterrestrial radiation (in mm/day), which is in turn estimated for the latitude of Lausanne (i.e., 46.519833°) for each date following the methods of (Allen et al., 1998, Equation 21). The temperature values of each day have been extracted from the inventory of gridded datasets provided by the Federal Office of Meteorology and Climatology (MeteoSwiss), which feature the minimum, average and maximum daily T_{air} for the extent of the whole country at a resolution of 1 km. Such a dataset is
- 140

obtained by interpolating 100 T_{air} stations across Switzerland (including the MeteoSwiss Pully station of Figure 1) based on non-linear thermal profiles of major basins and non-Euclidean distance weighting that accounts for terrain effects (Frei, 2014).

In order to account for the cooling effect of large green spaces, the computed cooling capacity index of pixels that are part of large green areas (> 2 ha) is adjusted as in:

$$CC_i^{green} = \sum_{j \in \Omega_i} g_i \cdot CC_j \cdot e^{-\frac{d(i,j)}{d_{cool}}}$$
(5)

145 where g_i is 1 when the pixel *i* is a green area and 0 otherwise (as defined in the biophysical table), d(i, j) is the distance between pixels *i* and *j*, d_{cool} is a parameter that defines the distance over which a green space has a cooling effect, and Ω_i is the set of pixels whose distance to *i* is lower than d_{cool} .

Then, a heat mitigation index is computed as:

$$HM_{i} = \begin{cases} CC_{i} & \text{if } i \text{ is part of a large green area } or \ CC_{i} > CC_{i}^{green} \\ CC_{i}^{green} & otherwise \end{cases}$$
(6)

In order to simulate the spatial distribution of T_{air} , the model requires two additional inputs. The first is the rural reference temperature T_{ref} , where the UHI effect is not observed, e.g., in the rural surroundings of the city. The second is the magnitude of the urban heat island effect UHI_{max} , namely the difference between the rural reference temperature and the maximum T_{air} observed in the city center. The two parameters are combined with HM_i to compute the T_i for each pixel *i* of the study area as in:

$$155 \quad T_i^{nomix} = T_{ref} + (1 - HM_i) \cdot UHI_{max} \tag{7}$$

Finally, the T_{air} values of each pixel T_i^{nomix} are spatially averaged using a Gaussian function with a kernel radius r defined by the user.

2.3.2 Calibration and evaluation of the model

- To compare the InVEST urban cooling model with the spatial regression based on satellite features, the urban cooling model
 is used to simulate the spatial distribution of T_{air} for the same 8 dates used to train the spatial regression model, i.e., the dates of the selected Landsat images. It is implicitly assumed that no significative LULC changes have occurred throughout study period (i.e., from May 2018 to August 2019), and therefore all simulations depart from the same LULC raster, i.e., the rasterized cadastral survey of the canton of Vaud as described above. Given the rugged terrain of the study area, the T_{ref} has been set as the minimum average T_{air} observed among the monitoring stations, while UHI_{max} has been set as the difference
 between the maximum average T_{air} observed among the monitoring stations and T_{ref}. The values of T_{ref} and UHI_{max} for
 - the 8 days considered in this study are displayed in Figure A1.

Although the documentation of the InVEST urban cooling model (Sharp et al., 2020) provides some suggested values for several parameters of the model, their suitability depends strongly on the local geographic conditions of the study area. Therefore, calibration of the parameters is required in order to better understand how the physical mechanisms beyond the

170 emergence of UHIs take place in the context of Lausanne. Following the manual calibration approach drafted by Hamel et al. (2020), the target parameters are the weights attributed to the tree shading w_S , albedo w_A and evapotranspiration w_{ET} , the distance over which green spaces have a cooling effect d_{cool} and the T_{air} mixing radius r. As an additional contribution, this article implements an automated calibrated procedure based on simulated annealing optimization (Kirkpatrick et al., 1983) that aims at the minimization of the R^2 between the T_{air} values observed in the monitoring stations and those predicted by 175 the model¹. The parameter values suggested in the documentation of the model are set as the initial state of the simulation annealing procedure, which corresponds to a T_{air} mixing radius of r = 500 m, a green area cooling distance of $d_{cool} = 100$ m, and weights attributed to tree shading, albedo and evapotranspiration of $w_S = 0.6$, $w_A = 0.2$ and $w_{ET} = 0.2$ respectively. The number of calibration iterations is set to 100.

Given that the T_{ref} and UHI_{max} parameters were here obtained from observations from each simulated day, metrics such as

- 180 the mean absolute error (MAE) and the root mean squared error (RMSE) are effectively constrained to the $[0, UHI_{max}]$ range, which affects the interpretation of these metrics. Therefore, in order to evaluate the ability of the InVEST urban cooling model to spatially simulate UHIs, the coefficient of adjustment R^2 , MAE and RMSE of the calibrated model are compared with those computed in two additional experiments. The first experiment consists in randomly sampling the T_{air} values from a uniform distribution over the $[T_{ref}, UHI_{max}]$ range of each date. In the second experiment, the T_{air} values of each date are randomly
- 185 sampled from a normal distribution with the mean and standard deviation of the T_{air} measurements of the monitoring stations. For both experiments, the three evaluation metrics are reported as their average over 10 runs.

2.4 Spatial regression of air temperature based on satellite data

The spatial regression to predict T_{air} from features derived from satellite data is performed over a raster dataset on a per-pixel basis. A regression model is then trained to fit the observed T_{air} measurements by minimizing the error at the pixels that correspond to the locations of the monitoring stations.

The regression operates in each pixel with the T_{air} as the target variable, and the elevation, the LST and the normalized difference water index (NDWI) (Gao, 1996) as independent variables. Additionally, to account for the influence of temperature and moisture surface conditions of each pixel, the LST and NDWI are spatially averaged over a series of circular neighborhoods with radii 200, 400, 600 and 800 m, thus reckoning 8 supplementary features. Based on previous research on the sensitivity of the landscape patterns-UHI relationships to the spatial resolution (Weng et al., 2004; Song et al., 2014), the target resolution

195 the landscape patterns-UF has been set to 200 m.

190

2.4.1 Computation of satellite-derived features

The estimation of LST from Landsat 8 images follows the methods of Avdan and Jovanovska (2016). On the one hand, the data from the near-infrared (NIR) and red bands of Landsat 8 (i.e., bands 4 and 5 respectively) to compute the normalized difference vegetation index (NDVI), which is then used to estimate the ground emissivity ε_{λ} . On the other hand, following the Landsat 8 data users handbook (Zanter, 2015), the data from the thermal band of Landsat 8 (i.e., band 10) is first converted to top of atmosphere spectral radiance L_{λ} , from which brightness temperature *BT* is estimated (in °C) as in:

$$BT = \frac{K_2}{\ln((K_1/L_\lambda) + 1)} - 273.15\tag{8}$$

¹The calibration module has been designed as a reusable open-source Python package, see https://github.com/martibosch/invest-ucm-calibration

where the K_1 and K_2 are band-specific thermal conversion constants embedded in the Landsat image metadata. Finally, the ground emissivity ε_{λ} and the brightness temperature BT are used to compute the LST by inversion of Planck's Law as in:

$$LST = \frac{BT}{1 + \lambda \cdot (BT/\rho) \cdot \ln(\varepsilon_{\lambda})}$$
(9)

where $\rho = 1.438 \cdot 10^{-2}$ m K is a constant computed as a product of Boltzmann constant and Planck's constants divided by the velocity of the light, and $\lambda = 10.895 \cdot 10^{-9}$ is the average of the limiting wavelengths of the thermal band.

The NDWI is computed from the green and near infrared (NIR) bands of Landsat 8 (i.e., bands 3 and 5 respectively) as in:

210
$$NDWI = \frac{X_{green} - X_{NIR}}{X_{green} + X_{NIR}}$$
 (10)

2.4.2 Model selection and evaluation

Based on the work of Ho et al. (2014), three regression models have been considered, namely a multiple linear regression, support-vector machine (SVM) and random forest. The accuracy of each regression model is assessed by means of a k-fold cross-validation procedure, where the regression samples are first shuffled and partitioned into 3 folds. Then, for each fold k, a

regression model is trained using the other 2 folds and validated using the samples of such k fold. Finally, the model that shows the best validation score (i.e., the R^2 averaged over 10 repetitions of the k-fold procedure) is selected. Additionally, the MAE and RMSE are computed in order to evaluate the deviations between the observed T_{air} and the predictions of each model.

On the other hand, the importance of each feature is evaluated by computing its permutation importance (Breiman, 2001), namely the average decrease of the regression accuracy when such feature is randomly shuffled. The training of the regression models, cross-validation and permutation feature importance described above have been implemented by means of the Scikit-learn library (Pedregosa et al., 2011).

3 Results

220

3.1 Spatial regression of air temperature based on satellite data

When including all the samples, the R^2 for the linear regression, SVM and random forest are respectively 0.832, 0.014 and 0.960, with MAE of 1.198, 2.671 and 0.580 °C, and RMSE of 1.508, 3.652 and 0.738 °C respectively. The coefficients suggest that SVM is not well suited for such a regression in this study area, whereas the linear regression and random forest models obtain a very strong fit — the latter achieving the best performance. Nevertheless, the average cross-validation scores suggest that the linear regression (average score $R^2 = 0.733$) is more robust to missing data and also less likely to over-fit the observations than the random forest regressor (average score $R^2 = 0.658$). The remainder of the article thus considers only the results obtained with a linear regression model trained with all the samples.

The feature importances of the chosen linear regression model can be evaluated by means of an F-test (as implemented in the Python library statsmodels (Seabold and Perktold, 2010), see B1. With a significance level of p = 0.05, the results of the F-test suggest that the significant variables for the linear regression are the NDWI when spatially averaged over a 800m, 600m



Figure 2. Scatter plot of the spatial regression residuals (vertical axis) against the elevation of the monitoring station (horizontal axis of the left plot) and the observed T_{air} (horizontal axis of the right plot), colored by the sample date. See Appendix B1.

and 400m radius (in decreasing order of significance). The following most significant variable is the NDWI spatially averaged over a 200m radius (p = 0.071) and without spatial averaging (p = 0.231), and the LST spatially averaged over a 400m radius (p = 0.277). With a p = 0.420, the does not appear to be significant in this particular regression. The low significance obtained for the LST features in this study might be attributable to the large time lag between the acquisition time of the Landsat images (which ranges from 11:15 to 11:23 CET) and the time of the T_{air} measurements (i.e. 21:00 CET).

The relationship between the predicted and the observed values is displayed in Figure B1. The MAE and RMSE of 1.198 and 1.508 °C respectively demonstrate a stronger fit than the 1.82 and 2.31 °C obtained in the study of Ho et al. (2014) in Vancouver. The two plots of Figure 2 show the relationship between the elevation and T_{obs} of each sample and the regression errors. While there is no discernable relationship regarding the elevation of the samples (i.e., the elevation of the monitoring stations), the regression errors seem to be negatively correlated with T_{obs} . This pattern, which was also noted by Ho et al. (2014), indicates that high temperature samples are systematically underestimated by the regression model whereas low temperature samples are consistently overestimated.

The series of predicted T_{air} maps for the 8 dates as well as the prediction errors at the locations of the monitoring stations are displayed in Figure 3. While the range of temperatures exhibits important differences throughout the dates, the spatial distribution of T_{air} is seemingly consistent. The highest temperatures persistently occur in the most urbanized areas, whereas the lowest temperatures are take place in the higher elevations located east and north-east of the map. Finally, there seems to be no discernable pattern in space nor time regarding the prediction errors at the monitoring stations.

250

3.2 Simulation with the InVEST urban cooling model

The parameters of the model that result in the best fit of the station measurements are a T_{air} mixing radius of r = 236.02 m, a green area cooling distance of $d_{cool} = 89.21$ m, and the weights attributed to tree shading, albedo and evapotranspiration of $w_S = 0.59$, $w_A = 0.24$ and $w_{ET} = 0.17$ respectively (see Appendix B2). The R^2 , MAE and RMSE of the calibrated model



Figure 3. Maps of the T_{air} predicted by the spatial regression for the 8 dates. The points in the map correspond to the location of the monitoring stations, and are colored according to the regression errors.

- are respectively 0.903, 0.955 °C and 1.144 °C, which suggest a better model performance than randomly sampling from the station measurements. The latter yields a R^2 , MAE and RMSE of 0.573, 1.947 °C and 2.405 °C when sampling from a uniform distribution and 0.550, 1.952 °C and 2.468 °C when sampling from a normal distribution. Furthermore, the values of R^2 , MAE and RMSE obtained with the calibrated parameters reveal a stronger fit than the spatial regression reported above.
- The relationship between the T_{air} values at the monitoring stations simulated with the calibrated parameters and the actual observed measurements is shown in Figure B2. The differences between T_{air} simulated at the monitoring stations and the observed values are plotted against the elevation and the observed temperatures T_{obs} in Figure 4. The pattern of such relationships is very similar to that observed in the spatial regression. On the one hand, there is no clear relationship between the prediction error of the urban cooling model and elevation. On the other hand, the prediction errors exhibit a negative correlation with the observed temperature, denoting a systematic tendency to both underestimate high temperatures and overestimate low temperatures — the former being more prominent in this case, as noticeable from the asymmetry of the vertical axis in Figure 4.



Figure 4. Scatter plot of the differences between the T_{air} simulated by the InVEST urban cooling model and the ones observed in the monitoring stations (vertical axis) against the elevation of the monitoring station (horizontal axis of the left plot) and the observed T_{obs} (horizontal axis of the right plot), colored by the sample date.



Figure 5. Maps of the T_{air} simulated by the InVEST urban cooling model for the 8 dates. The points in the map correspond to the location of the monitoring stations, and are colored according to the simulation errors.

The simulated T_{air} maps for the 8 dates and the prediction errors at the monitoring stations are shown in Figure 5. As in the spatial regression, the temperature ranges show important differences across dates yet the same spatial pattern of T_{air} persists. The simulated distribution of T_{air} shows its highest values in the center of Lausanne and along the most urbanized (and hence

270

) less forested) zones along the main transportation axes, whereas the lowest temperatures are found in the forested areas located in the eastern and western extremes of the upper-half of the study area.

3.3 Model comparison

A comparison of the maps predicted by the spatial regression and the urban cooling model is displayed in Figure 6. In line with the temporal consistency of the spatial patterns predicted by the two approaches respectively, the comparison maps also show
a spatial distribution of T_{air} that persists throughout the dates. Such spatial pattern is strongly reminiscent of the elevation maps (see Figure 1 above) and reflects the fact that the elevation is explicitly considered in the spatial regression but not in the urban cooling model. The overall distribution of the T_{air} pixel differences between the two approaches follows a normal distribution that ranges from -9.620 °C to 11.929 °C (respectively reflecting lower and higher temperatures predicted in the spatial regression), which is considerably large range when compared to the small overall MAE and RMSE of both approaches.
Nonetheless, the way in which the histogram is centered around 0 °C suggests that the differences between the two approaches follow approaches follow no particular correlation other than the spatial regression predicting more extreme T_{air} values, which is not surprising considering that the range of T_{air} is systematically bounded in the urban cooling model by the T_{ref} and UHI_{max} parameters.

4 Discussion

The results obtained of this study suggest that both the spatial regression based on satellite data and the InVEST urban cooling model are capable of predicting the spatial distribution of air temperature with a large degree of statistical determination. Furthermore, the fact that a similar spatial pattern is predicted by both models suggests that the biophysical mechanisms embedded in the urban cooling model are well represented. If that is the case, the urban cooling model presents two central advantages with respect to the spatial regression.

Firstly, unlike regressions and black-box approaches, the fact that the biophysical mechanisms that drive the emergence of UHIs are represented explicitly allows for a physical interpretation of the parameters of the model. For example, in a comparative study of the relationship between the LST and the spatial configuration of trees in Baltimore and Sacramento, Zhou et al. (2017) suggest that the distinctive results observed in each city might be related to how the shading of trees and evapotranspiration contribute differently to urban cooling in the climatic context of each city. More precisely, they suggest that in the dry climate of Sacramento, large patches of trees ameliorate the efficiency of the evapotranspiration, whereas with the humid climate of Baltimore, the gains from the tree shading are likely more important. The urban cooling model provides a suitable mean to quantitatively address such matters, i.e., by calibrating the model in the two cities, we can explore the weights obtained for each factor support such hypothesis. In the case study of Lausanne reported above, the weight attributed to the tree shading $w_S = 0.59$ is higher than the one attributed to the evapotranspiration $w_{ET} = 0.17$. This is consistent with



Figure 6. Maps comparing the difference between the T_{air} predicted by the spatial regression \hat{T}_{sr} and the InVEST urban cooling model \hat{T}_{ucm} for the 8 dates. See subsection B3.

300

- the local climatic conditions being more similar in Lausanne and Baltimore than in Sacramento, yet the weights obtained in this study might be partly determined by the initial solution provided. Nonetheless, to further understand this issue, validation and calibration of the InVEST urban cooling model in a broader variety of cities is required. Overall, the way in which the calibrated parameters differ from the recommendations in the documentation of the model are in consonance with the particular characteristics of Lausanne. More precisely, the smaller mixing radius and cooling distances are consistent with the uneven relief of the study area.
- The second major advantage of the urban cooling model is that once the model is calibrated for a given city, it can be used to evaluate synthetic scenarios such as those stemming from master plans, urbanization prospects or the like, and to spatially design solutions. This kind of spatially-explicit evaluation of the impacts of alternative scenarios on ecosystem services is in fact one of the central purposes of the InVEST suite of models (Tallis and Polasky, 2009). Statistical models like the spatial regression are not well suited to such a purpose since they rely on features such as the LST that are hard to obtain other than empirically.

The approach proposed in this article is nevertheless subject to some limitations that merit thoughtful consideration. On the one hand, as acknowledged in its user guide (Sharp et al., 2020), the design of the InVEST urban cooling model presents a number of limitations, the most relevant to this study being the simplified and homogeneous way in which the air is mixed and the cooling effects of large green spaces. In complex terrains such as the Lausanne agglomeration, models with uniform

- 315 weighting of space show considerable deviations from the observed distribution of air temperature (Frei, 2014). On the other hand, the relationship between the calibration parameters and the resulting R^2 is likely to define a complex optimization landscape with multiple local optima. As a metaheuristic that strongly depends on random decisions, the simulated annealing procedure is susceptible to convergence to local optima, arbitrarily leading to different solutions in each run. A sensitivity analysis of the parameters of the urban cooling model as undertaken preliminarily by Hamel et al. (2020) for the Île-de-France
- 320 region could serve as a basis to improve the simulated annealing procedure by careful design of appropriate neighborhood search and annealing schedule. Finally, the approach of the present study based on observations at the moment of maximal UHI intensity (i.e., 9 p.m. in Switzerland), however the factors that influence UHIs are likely to operate differently across the diurnal UHI cycle. In fact, several studies point to distinct relationships between the spatial patterns of vegetation and daytime and nighttime UHIs (Anniballe et al., 2014; Sheng et al., 2017; Shiflett et al., 2017; Hamel et al., 2020). Considering the nature
- 325 of the implications of UHI, e.g., energy consumption, work productivity or human health (Koppe et al., 2004; Santamouris et al., 2015; Zander et al., 2015), a sound understanding of the full diurnal UHI cycle becomes crucial towards the design of robust solutions.

330

Nevertheless, the limitations on how the urban cooling model represents the spatial air mixing and the cooling effects of green spaces seem hard to overcome with the current spatial sparsity of monitoring stations. Such major shortcoming, which contrasts with the growing availability of high-resolution LST datasets, is one of the main reasons why most of the UHI studies have focused on the latter (Jin and Dickinson, 2010; Zhou et al., 2019). As illustrated in this article, spatial regressions based on remote sensing features such as LST and NDWI do not necessarily replicate the air temperature measurements better than biophysical models such as the InVEST urban cooling model. Therefore, improving the spatial density of the monitoring network becomes an imperative for further enlightening of the UHIs phenomena.

335 5 Conclusions

The present article presents a spatially-explicit approach to simulate UHIs with the InVEST urban cooling model, which is based on three biophysical mechanisms, namely tree shade, evapotranspiration and albedo. The proposed approach shows how LULC and air temperature data can be combined to calibrate the parameters of the model to best fit measurements from monitoring stations by means of an automated procedure. The simulations performed for the urban agglomeration of Lausanne

340 show that the InVEST urban cooling model can outperform spatial regressions based on satellite-derived features such as LST, NDWI and elevation. The way in which both approaches consistently predict the highest temperatures in the most urbanized parts of the agglomeration suggests that the enhancement of green infrastructure can be an effective heat mitigation strategy, yet further exploration in other climatic contexts is required to fully understand this issue. To that end, the reusability of the computational workflow paves the way for further application of the urban cooling model to a broad variety of cities, which can serve to improve the understanding of the UHI phenomena and support the design of heat mitigation strategies.

Code availability. The code materials used in this article are available at https://doi.org/10.5281/zenodo.3970608 (Bosch, 2020b), and are maintained in a GitHub repository at https://github.com/martibosch/lausanne-heat-islands.

Appendix A: Data

A1 Landsat tiles

350 The list of product identifiers of the Landsat image tiles are available as comma-separated value (CSV) file at https://github. com/martibosch/lausanne-heat-islands/blob/master/data/raw/landsat-tiles.csv

A2 Monitoring stations

Monitoring stations with their operator and their elevation in meters above sea level. The operators are: Agrometeo, Federal roads office (ASTRA), Federal office for the environment (BAFU), General directorate for the environment of the Canton of

355 Vaud (DGE), and the Federal Institute of Forest, Snow and Landscape Research (WSL) (Rebetez et al., 2018). The source CSV file used in the computational workflow is available at https://github.com/martibosch/lausanne-heat-islands/blob/master/data/raw/tair-stations/station-locations.csv.

A3 Biophysical table

The crop and water coefficients are based on Allen et al. (1998), while rock, soil and urban coefficients are derived from the results of Grimmond and Oke (1999) in the city of Chicago. Given that the evapotranspiration of the vegetation and crops is subject to seasonal changes in temperate zones such as Switzerland (Allen et al., 1998), the values that correspond to the midseason estimation (June to August) in Nistor (2016). The albedo values are based on the work of Stewart and Oke (2012). The shade column, which represents the proportion of tree cover of each LULC class, has been computed with a high resolution tree canopy map of Lausanne and is therefore specific to the study area. Rows with a hyphen sign - in the shade column denote that the corresponding LULC class is not present in the study area. The source CSV file used in the computational workflow is

available at https://github.com/martibosch/lausanne-heat-islands/blob/master/data/interim/biophysical-table-shade.csv.



Figure A1. Reference temperatures T_{ref} (i.e., minimum T_{air} at 9 p.m. among the monitoring stations) and magnitude of the UHI UHI_{max} (i.e., difference between T_{ref} and the maximum T_{air} at 9 p.m. among the monitoring stations) of the 8 dates considered in this study.

Appendix B: Results

B1 Spatial regression

370 The code of the spatial regression of air temperature from satellite data is available as a Jupyter Notebook (IPYNB) at https: //github.com/martibosch/lausanne-heat-islands/blob/master/notebooks/spatial-regression.ipynb.

Feature	Coef.	Std. error	t	P>ltl	[0.025	0.975]
const	1.1760	3.369	0.349	0.728	-5.534	7.886
1st_0	0.4944	0.584	0.846	0.400	-0.669	1.658
ndwi_0	-6.1852	5.127	-1.206	0.231	-16.396	4.026
lst_200	-0.3267	0.885	-0.369	0.713	-2.089	1.435
ndwi_200	-28.5531	15.581	-1.833	0.071	-59.585	2.479
lst_400	-1.9332	1.765	-1.095	0.277	-5.449	1.583
ndwi_400	124.2456	46.749	2.658	0.010	31.138	217.353
lst_600	1.0526	2.963	0.355	0.723	-4.849	6.955
ndwi_600	-156.7220	55.931	-2.802	0.006	-268.119	-45.325
lst_800	1.7306	1.685	1.027	0.308	-1.626	5.087
ndwi_800	85.4412	22.732	3.759	0.000	40.167	130.715
elev	-0.0026	0.003	-0.810	0.420	-0.009	0.004

Table B1. F-test of variable significance of the linear regression.

B1.2 Figures



Figure B1. Scatter plot of the T_{air} predicted by the linear regression model trained with all the samples (vertical axis) versus the observed measurements (horizontal axis).



Figure B2. Scatter plot of the T_{air} values simulated with the InVEST urban cooling model (vertical axis) versus the observed measurements (horizontal axis).

B2 Simulation with the InVEST urban cooling model

375 The code of the spatial simulation of air temperature with the InVEST urban cooling model is available as a Jupyter Notebook (IPYNB) at https://github.com/martibosch/lausanne-heat-islands/blob/master/notebooks/invest-urban-cooling-model.ipynb

B3 Comparison

The code used for the comparison of the spatial regression and simulation of air temperature is available as a Jupyter Notebook (IPYNB) at https://github.com/martibosch/lausanne-heat-islands/blob/master/notebooks/comparison.ipynb

380 Author contributions. MB and ML designed the study and conducted the analysis with technical inputs of PH and RR and overall supervision of JC and SJ. MB developed the code and wrote the manuscript. All authors provided comments and contributed to the final version of the manuscript.

Competing interests. The authors declare no competing interests

Acknowledgements. This research has been supported by the École Polytechnique Fédérale de Lausanne (EPFL). The authors gratefully thank Yves Kazemi and Martin Schlaepfer for their help in the design of the study, and Rémi Jaligot for his careful review of the manuscript.

References

390

- Allen, R. G., Pereira, L. S., Raes, D., Smith, M., et al.: Crop evapotranspiration-Guidelines for computing crop water requirements FAO Irrigation and drainage paper 56, Fao, Rome, 300, D05 109, 1998.
- Angel, S., Sheppard, S., Civco, D. L., Buckley, R., Chabaeva, A., Gitlin, L., Kraley, A., Parent, J., and Perlin, M.: The dynamics of global urban expansion, Citeseer, 2005.
- Angel, S., Blei, A. M., Civco, D. L., and Parent, J.: Atlas of urban expansion, Lincoln Institute of Land Policy Cambridge, MA, 2012. Anniballe, R., Bonafoni, S., and Pichierri, M.: Spatial and temporal trends of the surface and air heat island over Milan using MODIS data,

Remote Sensing of Environment, 150, 163–171, 2014.

- Arnfield, A. J.: Two decades of urban climate research: a review of turbulence, exchanges of energy and water, and the urban heat island,
- International Journal of Climatology: a Journal of the Royal Meteorological Society, 23, 1–26, 2003.
 - Association pour le Système d'information du Territoire Vaudois: Structure es données cadastrales au format SHAPE (MD.01-MO-VD), Available from (in French) https://www.asitvd.ch/md/508. Accessed: 3 September 2019, 2018.
 - Avdan, U. and Jovanovska, G.: Algorithm for automated mapping of land surface temperature using LANDSAT 8 satellite data, Journal of Sensors, 2016, 2016.
- 400 Bosch, M.: DetecTree: Tree detection from aerial imagery in Python, Journal of Open Source Software, https://doi.org/10.21105/joss.02172, 2020a.
 - Bosch, M.: Lausanne heat islands, GMD Discussions, Zenodo https://doi.org/10.5281/zenodo.3970608, https://doi.org/10.5281/zenodo.3970608, 2020b.

Bosch, M.: Urban footprinter: a convolution-based approach to detect urban extents from raster data, Zenodo https://doi.org/10.5281/zenodo.

- 405 3699310, https://doi.org/10.5281/zenodo.3699310, 2020c.
 - Bosch, M., Jaligot, R., and Chenal, J.: Spatiotemporal patterns of urbanization in three Swiss urban agglomerations: insights from landscape metrics, growth modes and fractal analysis, Landscape Ecology, pp. 1–13, 2020.

Breiman, L.: Random forests, Machine learning, 45, 5-32, 2001.

Burgstall, A.: Representing the Urban Heat Island Effect in Future Climates, Scientific Report MeteoSwiss No. 105, 2019.

- 410 Clinton, N. and Gong, P.: MODIS detected surface urban heat islands and sinks: Global locations and controls, Remote Sensing of Environment, 134, 294–304, 2013.
 - Conference des Services Cantonaux du Cadastre: Degré de spécification en mensuration officielle Couche d'information de la couverture du sol, Available from (in French) https://www.cadastre.ch/content/cadastre-internet/fr/manual-av/publication/guidline.download/ cadastre-internet/fr/documents/av-richtlinien/Richtlinie-Detaillierungsgrad-BB-fr.pdf. Accessed: 26 Februrary 2020, 2011.
- 415 Fabrizi, R., Bonafoni, S., and Biondi, R.: Satellite and ground-based sensors for the urban heat island analysis in the city of Rome, Remote sensing, 2, 1400–1415, 2010.
 - Federal Office of Topography: DHM25/200 m The free version of the digital height model of Switzerland, Available from https://shop. swisstopo.admin.ch/en/products/height_models/dhm25200. Accessed: 21 March 2020, 2004.

Federal Office of Topography: SWISSIMAGE La mosaïque d'ortophotos de la Suisse, Available from (in French) https://shop.swisstopo.
 admin.ch/fr/products/images/ortho_images/SWISSIMAGE. Accessed: 3 March 2020, 2019.

Frei, C.: Interpolation of temperature in a mountainous region using nonlinear profiles and non-Euclidean distances, International Journal of Climatology, 34, 1585–1605, 2014.

Gao, B.-C.: NDWI—A normalized difference water index for remote sensing of vegetation liquid water from space, Remote sensing of environment, 58, 257–266, 1996.

- 425 Grimm, N. B., Faeth, S. H., Golubiewski, N. E., Redman, C. L., Wu, J., Bai, X., and Briggs, J. M.: Global change and the ecology of cities, science, 319, 756–760, 2008.
 - Grimmond, S. and Oke, T.: Evapotranspiration rates in urban areas, in: Proceedings of the Impacts of Urban Growth on Surface Water and Groundwater Quality HS5, pp. 235–243, International Association of Hydrological Sciences Publications, 1999.

Hamel, P., Tardieu, L., Lemonsu, A., de Munck, C., and Viguié, V.: Co-développement du module rafraîchissement offert par la végétation
de l'outil InVEST, Report submited to the Agence de l'environnement et de la Maîtrise de l'energie (ADEME), 2020.

- Hargreaves, G. H. and Samani, Z. A.: Reference crop evapotranspiration from temperature, Applied engineering in agriculture, 1, 96–99, 1985.
 - Ho, H. C., Knudby, A., Sirovyak, P., Xu, Y., Hodul, M., and Henderson, S. B.: Mapping maximum urban air temperature on hot summer days, Remote Sensing of Environment, 154, 38–45, 2014.
- 435 Jin, M. and Dickinson, R. E.: Land surface skin temperature climatology: Benefitting from the strengths of satellite observations, Environmental Research Letters, 5, 044 004, 2010.
 - Kirkpatrick, S., Gelatt, C. D., and Vecchi, M. P.: Optimization by simulated annealing, science, 220, 671–680, 1983.
 - Koppe, C., Sari Kovats, R., Menne, B., Jendritzky, G., Wetterdienst, D., Organization, W. H., et al.: Heat-waves: risks and responses, Tech. rep., Copenhagen: WHO Regional Office for Europe, 2004.
- 440 Liu, Z., He, C., Zhou, Y., and Wu, J.: How much of the world's land has been urbanized, really? A hierarchical framework for avoiding confusion, Landscape Ecology, 29, 763–771, 2014.
 - Nistor, M.-M.: Mapping evapotranspiration coefficients in the Paris metropolitan area, GEOREVIEW Scientific Annals of Ştefan cel Mare University of Suceava, Geography Series, 26, 138–153, 2016.

Nistor, M.-M. and Porumb, G. C. G.: How to compute the land cover evapotranspiration at regional scale? A spatial approach of Emilia-

- 445 Romagna region, GEOREVIEW: Scientific Annals of Stefan cel Mare University of Suceava. Geography Series, 25, 38–53, 2015.
 - Nistor, M.-M., Gualtieri, A. F., Cheval, S., Dezsi, Ş., and Boţan, V. E.: Climate change effects on crop evapotranspiration in the Carpathian Region from 1961 to 2010, Meteorological applications, 23, 462–469, 2016.
 - Oke, T. R.: City size and the urban heat island, Atmospheric Environment (1967), 7, 769–779, 1973.

Oke, T. R.: The energetic basis of the urban heat island, Quarterly Journal of the Royal Meteorological Society, 108, 1–24, 1982.

- 450 Oliveira, E. A., Andrade Jr, J. S., and Makse, H. A.: Large cities are less green, Scientific reports, 4, 2014.
- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., et al.: Scikit-learn: Machine learning in Python, Journal of machine learning research, 12, 2825–2830, https://doi.org/10.5555/1953048.2078195, 2011.
- Phelan, P. E., Kaloush, K., Miner, M., Golden, J., Phelan, B., Silva III, H., and Taylor, R. A.: Urban heat island: mechanisms, implications,
 and possible remedies, Annual Review of Environment and Resources, 40, 285–307, 2015.
 - Rebetez, M., von Arx, G., Gessler, A., Pannatier, E. G., Innes, J. L., Jakob, P., Jetel, M., Kube, M., Nötzli, M., Schaub, M., et al.: Meteorological data series from Swiss long-term forest ecosystem research plots since 1997, Annals of Forest Science, 75, 41, 2018.
 - Santamouris, M., Cartalis, C., Synnefa, A., and Kolokotsa, D.: On the impact of urban heat island and global warming on the power demand and electricity consumption of buildings—A review, Energy and Buildings, 98, 119–124, 2015.

- 460 Schwarz, N., Lautenbach, S., and Seppelt, R.: Exploring indicators for quantifying surface urban heat islands of European cities with MODIS land surface temperatures, Remote Sensing of Environment, 115, 3175–3186, 2011.
 - Schwarz, N., Schlink, U., Franck, U., and Großmann, K.: Relationship of land surface and air temperatures and its implications for quantifying urban heat island indicators—An application for the city of Leipzig (Germany), Ecological indicators, 18, 693–704, 2012.
 Seabold, S. and Perktold, J.: statsmodels: Econometric and statistical modeling with python, in: 9th Python in Science Conference, 2010.
- 465 Sharp, R., Tallis, H., Ricketts, T., Guerry, A., Wood, S., Chaplin-Kramer, R., Nelson, E., Ennaanay, D., Wolny, S., Olwero, N., et al.: InVEST 3.8.0 User's Guide. The Natural Capital Project, 2020.

Sheng, L., Tang, X., You, H., Gu, Q., and Hu, H.: Comparison of the urban heat island intensity quantified by using air temperature and Landsat land surface temperature in Hangzhou, China, Ecological Indicators, 72, 738–746, 2017.

Shiflett, S. A., Liang, L. L., Crum, S. M., Feyisa, G. L., Wang, J., and Jenerette, G. D.: Variation in the urban vegetation, surface temperature, air temperature nexus, Science of the Total Environment, 579, 495–505, 2017.

- Sobrino, J., Oltra-Carrió, R., Sòria, G., Bianchi, R., and Paganini, M.: Impact of spatial resolution and satellite overpass time on evaluation of the surface urban heat island effects, Remote Sensing of Environment, 117, 50–56, 2012.
 - Song, J., Du, S., Feng, X., and Guo, L.: The relationships between landscape compositions and land surface temperature: Quantifying their resolution sensitivity with spatial regression models, Landscape and Urban Planning, 123, 145–157, 2014.
- 475 Stewart, I. D.: A systematic review and scientific critique of methodology in modern urban heat island literature, International Journal of Climatology, 31, 200–217, 2011.
 - Stewart, I. D. and Oke, T. R.: Local climate zones for urban temperature studies, Bulletin of the American Meteorological Society, 93, 1879–1900, 2012.
- Swiss Federal Statistical Office: City Statistics (Urban Audit), Data collection. Available from https://www.bfs.admin.ch/bfs/en/home/
 statistics/cross-sectional-topics/city-statistics.html. Accessed: 14 May 2020, 2018.
 - Tallis, H. and Polasky, S.: Mapping and valuing ecosystem services as an approach for conservation and natural-resource management, Annals of the New York Academy of Sciences, 1162, 265–283, 2009.

United Nations: World Urbanization Prospects: The 2014 Revision, 2015.

470

Voogt, J. A. and Oke, T. R.: Thermal remote sensing of urban climates, Remote sensing of environment, 86, 370–384, 2003.

- 485 Weng, Q., Lu, D., and Schubring, J.: Estimation of land surface temperature–vegetation abundance relationship for urban heat island studies, Remote sensing of Environment, 89, 467–483, 2004.
 - Yang, L., Wu, X., Praun, E., and Ma, X.: Tree detection from aerial imagery, in: Proceedings of the 17th ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems, pp. 131–137, ACM, 2009.
 - Zander, K. K., Botzen, W. J., Oppermann, E., Kjellstrom, T., and Garnett, S. T.: Heat stress causes substantial labour productivity loss in
- Australia, Nature Climate Change, 5, 647–651, 2015.Zanter, K.: Landsat 8 (L8) Data User Handbook Version 1.0, EROS. South Dakota, 2015.
 - Zardo, L., Geneletti, D., Pérez-Soba, M., and Van Eupen, M.: Estimating the cooling capacity of green infrastructures to support urban planning, Ecosystem services, 26, 225–235, 2017.
- Zhou, D., Xiao, J., Bonafoni, S., Berger, C., Deilami, K., Zhou, Y., Frolking, S., Yao, R., Qiao, Z., and Sobrino, J. A.: Satellite remote sensing
 of surface urban heat islands: progress, challenges, and perspectives, Remote Sensing, 11, 48, 2019.
 - Zhou, W., Wang, J., and Cadenasso, M. L.: Effects of the spatial configuration of trees on urban heat mitigation: A comparative study, Remote Sensing of Environment, 195, 1–12, 2017.