

## Response to reviewers' comments

"Two-way coupling between the sub-grid land surface and river networks in Earth system models" by N. W. Chaney, L. Torres-Rojas, N. Vergopolan, C. K. Fisher

We thank the reviewers for their time and helpful comments. We have addressed each point below. Reviewer comments are shown in *blue italics*, while author responses are shown in unformatted text.

**Executive director:** *Please note that for your paper, the following requirements have not been met in the Discussions paper: 1) "The main paper must give the model name and version number (or other unique identifier) in the title." 2) "If the model development relates to a single model then the model name and the version number must be included in the title of the paper. If the main intention of an article is to make a general (i.e. model independent) statement about the usefulness of a new development, but the usefulness is shown with the help of one specific model, the model name and version number must be stated in the title. The title could have a form such as, "Title outlining amazing generic advance: a case study with Model XXX (version Y)".* In order to simplify reference to your developments, please add a model name (and/or its acronym) and a version number in the title of your article in your revised submission to GMD.

We thank the executive director for this feedback. We will add the model name and version number in the title of the revised manuscript.

**Reviewer #1:** *This manuscript presents a high-resolution land-river coupling strategy in an earth system modeling context. The major conclusions are (I am directly quoting the authors): "1) the implementation of the two-way coupling between the land surface and the river network leads to appreciable differences in the simulated spatial heterogeneity of the surface energy balance; 2) a limited number of tiles (~300 per 0.25-degree cell) are required to approximate the fully distributed simulation adequately; 3) the surface energy balance partitioning is sensitive to the river routing model parameters." The study is properly motivated and overall well written. I do have a couple of major comments for the authors to consider.*

We thank the reviewer for the constructive feedback. We provide responses to the reviewer's comments below.

*The innovations could be better justified. It is intuitive that accounting for land-river two-way coupling will lead to non-negligible difference in the land surface water and energy balance, and high-resolution modeling of that will overall help to better capture spatial heterogeneity. This is not a very new understanding.*

We agree that the role of a two-way coupling between the land surface and river network is not a new understanding and indeed it is known to play a large role in water limited regions that rely on recharge from upstream water sources (e.g., Nile river in Egypt). However, this process is almost completely missing in Earth system models where rivers mostly only receive water from the land surface but are unable to

recharge the surrounding regions. As such, the innovation of this work is to design a scheme that is able to effectively and efficiently model this process by enabling a two-way connection between the modeled rivers and the sub-grid tiling schemes.

*The benefits of this high-resolution land-river coupling strategy could be more clearly demonstrated. Typically, a new modeling strategy should help either reduce uncertainty or improve prediction. Uncertainty does not seem to be the focus here. Then how about improving prediction? Has it helped to improve the simulation of surface inundation, streamflow, or energy fluxes? In the study area, ARM SGP provides lots of observational data, but the authors did not show any comparison between the model simulations and observations.*

The main purpose of this paper is to develop a new parameterization that is able to couple the sub-grid approaches to river networks and land surface heterogeneity in Earth system models which remains a known weakness in these models. Although we certainly agree that the scheme should be evaluated with observations, an exhaustive evaluation of the scheme using observations is beyond the scope of this paper and is the focus of subsequent work among the co-authors. That being said, we agree that moving forward, there is a need to comprehensively evaluate the scheme and thus we will enhance the discussion section to note the need to evaluate the scheme with an emphasis on what available in-situ and remote sensing data could be used.

*The impulse response function at the HRU level is constructed in a simplified way, e.g., assuming uniform and constant velocity 0.1m/s. How would this simplification affect the model fidelity? Moreover, the impulse response function or unit hydrograph concept was originally developed at the small catchment scale, and theoretically it is not clear to me whether it can be applied at the HRU level. For instance, is the travel time histogram within a HRU statistically.*

We appreciate the reviewers feedback about the arbitrary and constraining impact of fixing the overland flow velocity to 0.1 m/s. As noted in the manuscript, the travel time histogram of the HRU to the reach is precalculated from the high-resolution DEM via path of steepest descent. In essence, the travel time of each 30-meter grid cell that belongs to a given HRU is calculated and then used to assemble the histogram of travel times. Since the fixed flow velocity assumes the flow to the channel is not impacted by more/less water down the hillslope, this assumption will be valid. We will clarify this assumption in the revised manuscript. It is also important to note that one could also use a kinematic wave on the hillslopes (height bands + HRUs) and this option will most likely be implemented in the near future (we will include this note in the revised manuscript). Time permitting we will also add a sensitivity analysis of how the uniform flow velocity impacts the modeling results.

**Reviewer #2:** *This manuscript represents the new two-way coupling scheme between land and river implemented in the HydroBlocks model. As the importance of surface water dynamics in land hydrology modelling and Earth system modelling is discussed recently, the model improvement proposed in this study has a contribution to the science community. The description of the model is mostly adequate, and the test*

*simulation results look reasonable. I think the manuscript still need some improvement focusing on more detailed and kind description of the method, before acceptance.*

We thank the reviewer for the constructive feedback. We provide responses to reviewers comments below.

*L139: "The basins are first delineated from a 30m DEM". Please provide the definition of "basins". This is a specific technical concept in the developed model, and different from the general-use meaning. As far as I understand, the river network is divided into multiple "reaches", and the 30m pixels drained to each "reach" is defined as the "basin" corresponding to the reach. Also, I recommend to briefly explain how river channels and reaches are defined in this study. Even in the case this is mentioned in the previous paper (Chaney et al, 2016; 2018), the explanation will enhance the understanding of readers, as this is the core of the approach proposed in this manuscript.*

Thank you for highlighting the importance to be more specific regarding our use of the term "basin". We will make its definition more explicit in the revised manuscript by focusing more on the term "reach". We will also provide further details on the algorithm used to delineate the rivers. Although the details are provided in Chaney et al., 2018, we agree that it would be useful to have it be more explicit in this paper as well.

*L143: "These characteristic basins were identified using latitude, longitude, flow accumulation area, and the natural logarithm of the flow accumulations area as feature predictors." Please explain the background reason of using these variables as input to clustering. (for example: log-scale accumulation area to separate the small hilltop basins from large rivers; lat-lon to represent the difference of atmospheric forcing by locations).*

We thank the reviewer for this great idea. As suggested, we will add more background for the use of each predictor in the clustering algorithm.

*L150: "First, all channel grid cells within a given characteristic basin". Please explain how the "channel grid cells" are defined. Also, it is better to provide some info on "what is grid cells, and what is macro-scale grids".*

The channel grid cells are computed from the flow accumulation area computed at 30 meters for the domain. The channel grid cells that belong to a characteristic basin are all the 30-meter grid cells defined as "channel" from the channel delineation algorithm that belong to a given clustered characteristic basin. We will clarify this in the revised manuscript as well as make a better distinction between the fine-scale and macro-scale grid cells.

*L152: "The binning involves creating groups of HAND values that have an areal coverage  $n$  (user-defined) times larger than its adjacent lower height band". Please explain the background reason of this methodology? Why upstream band has larger area compared to downstream band?*

It is important to first note that the height bands will be upslope/downslope since these will be away from each channel and not how one normally thinks of upstream/downstream along the channel. With regards to the height band discretization, the purpose for this approach has to do mostly with the interest to “zoom” in on the region immediately surrounding each reach. Using the uniform discretization of height bands defined in Chaney et al., 2018 led to too coarse height bands in riparian areas; this led to too many height bands being necessary to ensure the floodplain dynamics “converged” (i.e., it didn’t change that much the more height bands we added). With the added module, we changed the algorithm to have it have very high resolution around the reaches and then have the height bands become larger as we move away from the reach. Note that this does not mean that the final stage of intra-band clustering cannot still have a large number of HRUs in the upslope height bands; they just won’t play as big of a role in the riparian dynamics so there is not a need to further increase the hillslope discretization. We will further clarify this in the revised manuscript.

*L159: “to represent intra-band heterogeneity of land use, soils, and elevation, among others.” I think it is better to write the purpose of intra-band cluster implementation, rather than explaining the parameters to define intra-band clusters. (i.e. representation of different land type is not the ultimate purpose, rather than that, I guess authors want to represent different land hydrological reactions due to the difference of land types, such as water and heat flux.).*

This is an excellent suggestion, thank you. We agree that providing the reader with a reason why we are doing the intra-band clustering in the first place would help make the text more intuitive. We will add this clarification in the revised manuscript.

*L210: “much larger than many of the computed channel widths of the delineated streams (<\_1 meter)” This assumption is only valid for small scale river basins. The authors should mention the limitation of this assumption, and further development is needed to apply the proposed method to large-scale rivers (for example, how river channel pixels are defined appropriately, if pixel size is smaller than river width? We do need additional data source and pre-processing in this case).*

Although not mentioned currently in the text, the alternative described by the reviewer is already mostly implemented in the scheme as well. As in, if we know the channel width, we can have the channel HRU “grow” into the adjacent pixels to ensure the width matches the predicted/observed channel width. Given the minor effort required at this point to include this feature, we will add it to the model for the revised manuscript and mention this feature in the revision. In any case, this also brings up the important question of what data we are using to describe the channel width. Although for this paper we use regressions that were made for CONUS; we are fully aware that for continental-scale applications we would need to combine these regressions with the emerging global datasets of channel width and depth.

*Section 2.3, Section 2.6, Figure 4:*

*The relationship among “reach”, “basin”, “characteristic basin”, “height band”, and “HRU” is not very clear, and I need to read this parts several times to understand the*

*model structure. To improve the explanation, I suggest followings: - Update Figure 4D, or add another figure to explain the above relationship. Figure 4D is from the previous paper, and clustering approach of Figure 4D is not consistent to the explanation in this manuscript. I recommend to add a figure/panel to clearly explain the relationship between “characteristic basin, reach/basin, reach topography”. – Clearly explain that “one characteristic basin has several reaches inside”. “each reach has its corresponding basin, and each reach has height bands information to represent flood stage; these are used for the river routine component”. (I suggest moving descriptions on delineation of the reach/basin topography just after Section 2.3, then readers can better understand the relationship between HRU generation and reach topography generation.*

We appreciate the reviewer’s feedback. We understand how the current terminology can be confusing at times. We will revise the distinction between characteristic basin, reach/basin, and reach topography accordingly.

*L222: “the inundation heights per height band are averaged across all basins that belong to a given characteristic basin (Figure 5B)”. By this process, the surface water extent in the lower bottom part of each height band is distributed widely to the entire land surface of the corresponding height band, causing the overestimation of the inundated water surface. This will lead to the overestimation of the infiltration from floodplain to soil, and affect the heat and water flux accordingly. This should be discussed as the limitation of current approach. In addition, “Figure 5B” should be “Figure 4B”.*

As the reviewer suggests, this is one of the main limitations of the proposed method. However, we should note that this is a rationale for the clustering of the characteristic basins. Although, there will always be a limitation by grouping the floodplains of upstream/downstream reaches, the clustering ensures that although not perfect the two-way coupling can happen in lower order vs higher order streams, higher vs lower elevation, high vs low flow accumulation area, etc... In the end, this is the general rationale behind HydroBlocks, where it is a trade-off between fully representing the fully distributed simulation and ensuring computational tractability for implementation in large scale applications.

*L297: “lakes throughout the region.” Is it possible to explain how lakes are represented in the proposed model? As lakes are apparent in the result figures, some explanation should be essential.*

As currently implemented, lakes are independent water bodies in the 1d land surface model that don’t interact with the river network. We understand how the lakes can be confusing since it might seem that the lakes emerge from the routing model. While we do think that the proposed method could eventually represent them, it is misleading at this stage to make it seem like it is already represented. In the revised manuscript, we will make this distinction more explicit.

*L374: “the 16 interconnected cells take 5 minutes” It is not clear what this “the 16 interconnected cells” corresponds to. Please clearly mention that this means “16 macroscale grids within the target 1deg domain. Also, it is better if authors mentioned the expected calculation cost for potential larger scale simulations, if HydroBlocks is planned to be applied on continental or global scales.*

We will clarify this sentence in the revised manuscript. We will also discuss advantages and disadvantages of the scalability of the current algorithm. In the end, the full scalability won't be fully understood until it is run over the entire Contiguous United States (which is ongoing work); however, that work will be a follow-up to this paper and is thus seen as beyond the scope of this paper.

*L405: “One approach being explored by the co-authors is to cluster the lower stream orders.” This will also increase the discrepancy between “vector-shaped basins” and “rectangular macro-scale grid (and atmospheric forcing data as a result). This difficulty is also better to be mentioned.*

The clustering of lower stream orders would only occur for networks that fall completely within each macroscale grid cell. Lower stream orders that cross grid cells would have to be resolved more explicitly. As the reviewer suggests, another option is to further adapt the grid cell to minimize cross-cell lower-stream orders. The future work will try these different concepts. In the end, the approach that minimizes computation and stays as close as possible to the regular grid will be adopted.

*L411: “update the boundary conditions iteratively” It is not clear which “boundary conditions” authors want to mention in this sentence (e.g. upstream river inflow? Atmospheric forcing? Or between-basin horizontal water exchange?)*

Given the implicit solver used, the upstream river inflow at each inlet reach in a given macroscale “grid cell” will need to be updated iteratively per time step (Picard iteration) to ensure convergence. Given that the study domain is a patchwork of different macroscale grid cells, this is necessary. We will clarify this section in the revised manuscript.

*L424: “The flooding component of the scheme will then enable the valley to fill-up and, thus, producing a first-order representation of the time-varying reservoir spatial coverage.” This assumption is only valid for small-scale reservoirs which can be represented within a single grid. Further consideration is needed to represent large lakes/reservoirs which spans multiple grid boxes.*

Thank you for this feedback. We will add this clarification to the text. In any case, reservoirs would only be split from reservoirs covering multiple reaches since reaches are not split at the boundary. In any case, we agree that reservoirs can (and will!) flood multiple reaches so cross-cell reservoirs will certainly exist; however, this should be able to be managed especially given the implemented iterations of the inflow/outflow boundary conditions. However, this will need to be tested in future work.

We would again like to thank the reviewers for their time and helpful comments.