# 1 An automatic lake-model application using near real-time data

# 2 forcing: Development of an operational forecast workflow

# **3** (COASTLINES) for Lake Erie

# 4 Shuqi Lin<sup>1</sup>, Leon Boegman<sup>1</sup>, Shiliang Shan<sup>2</sup>, Ryan Mulligan<sup>1</sup>

<sup>1</sup>Department of Civil Engineering, Queen's University, Kingston ON Canada K7L 3N6

<sup>2</sup>Department of Physics and Space Science, Royal Military College of Canada, Kingston ON Canada K7K 7B4.

7 Correspondence to: Shuqi Lin (shuqi.lin@queensu.ca)

8 Abstract. For enhanced public safety and water resource management, a three-dimensional operational lake

9 hydrodynamic forecasting system COASTLINES (Canadian cOASTal and Lake forecastINg modEl System) was

- 10 developed. The modelling system is built upon the Aquatic Ecosystem Model (AEM3D) model, with predictive
- 11 simulation capabilities developed and tested for a large lake (i.e., Lake Erie). The open-access workflow derives

12 model forcing, code execution, post-processing, and web-based visualization of the model outputs, including water

- 13 level elevations and temperatures, in near real-time. COASTLINES also generates 240-h predictions using
- 14 atmospheric forcing from 15 km and 25 km horizontal-resolution operational meteorological products from the
- 15 Environment Canada Global Deterministic Forecast System (GDPS). Simulated water levels were validated against
- 16 observations from 6 gauge stations, with model error increasing with forecast horizon. Satellite images and lake
- 17 buoys were used to validate forecast lake surface temperature and the water column thermal stratification. The
- 18 forecast lake surface temperature is as accurate as hindcasts, with a root-mean-square-deviation <2°C.
- 19 COASTLINES predicted storm-surges and up-/down-welling events that are important for coastal flooding and
- 20 drinking water/fishery management, respectively. Model forecasts are available in real-time at
- 21 <u>https://coastlines.engineering.queensu.ca/</u>. This study provides an example of the successful development of an
- 22 operational forecasting workflow, entirely driven by open-access data, that may be easily adapted to simulate
- 23 aquatic systems or to drive other computational models, as required for management and public safety.

## 24 1 Introduction

Lakes hold a large proportion of the global surface freshwater, which supports biodiversity and supplies water

resources for drinking, transportation, and recreation. However, anthropogenic stressors are causing significant

27 changes in the properties of lakes, such as rapid warming of surface water (O'Reilly et al., 2015), large seasonal

water level fluctuations (Gronewold and Rood, 2019), increased frequency of extreme events (Saber et al., 2020)

and severe water quality issues such as oxygen depletion (Rowe et al., 2019; Scavia et al., 2014) harmful algal

30 blooms (Brookes and Carey, 2011; Watson et al., 2016). Effort has focussed on investigating the long-term

responses of physical processes in lakes to climate change (O'Reilly et al., 2015; Woolway and Merchant, 2019;

32 Jabbari et al., 2021), but improving lake monitoring and developing short-term forecast models, to predict the

33 occurrence of extreme events is also necessary (Woolway et al., 2020). The biogeochemical cycles in lakes are

34 complex and often regulated by physical forcing; therefore, the first step to model and forecast water quality issues,

such as harmful algal blooms (Paerl and Paul, 2012; O'Neil et al., 2012) and hypoxia (Rao et al., 2008; Rao et al.,

36 2014) is the development of accurate hydrodynamic models.

Over the past several decades, many computer models have been applied to hindcast (running models
forced with and validated against historically collected data) lake hydrodynamics to aid management. These range
from one-dimensional (1D) models such as DYRESM (Antenucci and Imerito, 2000), Simstrat (Gaudard et al.,
2017), and GLM (Hipsey et al., 2014), to three-dimensional (3D) models such as Delft3D (Lesser et al., 2004),

41 FVCOM (Chen et al., 2012; Rowe et al., 2019) ELCOM (Hodges et al., 2000). Several of these hydrodynamic

42 models may be coupled to biogeochemical models to allow for prediction of water quality. In the case of hindcast

43 applications, the complex and time-consuming setup and calibration procedure, of these models, can result in a

44 significant time lag (months to years) between when a project is initiated and when the model results are

45 communicated to stakeholders. This delay severely limits the utility of computational models for policy and

46 management decision making. For better application of these powerful computational tools, the ability for rapid

47 monitoring and simulation forecasts should be established.

48 In addition to the significant effort required to setup and calibrate models, other hurdles exist such as data-

49 sharing agreements between the agencies collecting forcing/validation data and those running the models. For

50 example, the US National Oceanic and Atmospheric Administration (NOAA) Great Lakes Coastal Forecasting

51 System (Chu et al., 2011; Anderson et al., 2018), is a comparatively large-budget multi-institutional (NOAA-

52 GLERL and U. Michigan-CIGLR) project that predicts water levels, temperature profiles, currents, and wave

beights over a 120-h timeframe in the five Laurentian Great Lakes and connecting channels, using FVCOM on a 3D

54 unstructured grid with 30-2000 m horizontal resolution. Similarly, meteolakes.ch (Baracchini et al., 2020b) applies

55 Delft3D for short-term 3D forecasts (4.5 days) of four Swiss lakes and simstrat.eawag.ch (Gaudard et al., 2019)

applies Simstrat for near-realtime 1D simulation of 54 Swisss lakes. These latter applications employ a data sharing

57 agreement between Swiss Federal Institute of Aquatic Science and Technology (EAWAG), École Polytechnique

58 Fédérale de Lausanne (EPFL) and MeteoSwiss.

59 Owing to the present online proliferation of near real-time lake observation data (e.g., National Data Buoy
60 Center (NDBC; <u>https://www.ndbc.noaa.gov/</u>); Great Lakes Observation System (GLOS; <u>https://www.glos.us/</u>)) and

- 61 high-resolution meteorological forecasts (e.g., Global Deterministic Prediction System, GDPS;
- 62 <u>https://dd.weather.gc.ca/model\_gem\_global/;</u> High Resolution Rapid Refresh, HRRR;
- 63 <u>https://rapidrefresh.noaa.gov/hrrr/</u>) the data-sharing agreements and managed data transfer protocols are no longer
- 64 required. When coupled with recent dramatic improvements in workflow efficiency (e.g., Gaudard et al. (2019);
- Baracchini et al. (2020b)) near real-time inclusion of forcing from meteorological forecasts allow for the
- 66 development of specific simulations tailored to meet diverse lake-management needs (e.g., prediction of coastal
- 67 flooding, spill modelling, fish habitat, beach closures, and optimization of treatment or source water monitoring
- 68 strategies).
- 69 In the present study we developed and tested the COASTLINES (Canadian cOASTal and Lake forecastINg
- 70 modEl System; https://coastlines.engineering.queensu.ca/) lake-model application workflow, that rapidly accesses
- 71 near real-time online data (weather forecasts, water level and temperature observations) for automated model
- 72 forcing, execution and validation. Hydrodynamic forecasts are automatically post-processed and posted on a web
- 73 platform. We provide an overview of the COASTLINES system, including model implementation for Lake Erie
- 74 (Section 2 Data and methods) and the accuracy of COASTLINES in forecasting water levels and temperature fields
- 75 over timescales of 24-h and 240-h (Section 3 Results). In Section 4 Discussion, the predictive ability of
- 76 COASTLINES for decision making is showcased through prediction of hydrodynamic events associated with fish
- kills, hypoxia near a drinking water intake and coastal flooding from a storm surge. We also discuss the relative
- 78 advantages of COASTLINES in comparison to other model products, including bias and uncertainty.

#### 79 2 Data and methods

#### 80 2.1 Study site

- 81 Lake Erie, the shallowest lake of the Great Lakes with a mean depth of 19 m. Lake-wide hydrodynamics
- 82 predominantly exhibits free surface and current oscillations from the 14-h barotropic seiche (Hamblin, 1987;
- 83 Boegman et al., 2001). The lake morphometry consists of distinct, yet interconnected western, central, and eastern
- 84 basins (Fig. 1), each with its own water quality concerns: The 11-m deep western basin is typically well mixed and
- 85 has frequent harmful algae blooms related to climate-driven meteorological forcing (Michalak et al., 2013). The
- 86 ephemeral stratification in late summer (Loewen et al., 2007) regulates vertical biogeochemical fluxes (Boegman et
- 87 al., 2008). The 20-m deep central basin is prone to large-scale hypolimnetic hypoxia (Scavia et al., 2014).
- 88 Hydrodynamics are governed by an internal Poincaré wave (Bouffard et al., 2012; Valipour et al., 2015) and a bowl-
- shaped depression of the summer thermocline, which influence the oxygen budget (Beletsky et al., 2012; Bouffard et
- 90 al., 2014). The 65-m deep eastern basin has nearshore water quality concerns from *cladophora* (Higgins et al., 2006)
- 91 and ecosystem engineering by dreissenid mussels (Hecky et al., 2004). Hydrodynamics of this region are controlled
- 92 by the coastal internal Kelvin wave (Valipour et al., 2019).



Fig.1 Map of Lake Erie showing the bathymetric depths and observation sites. The bathymetric map is at the
resolution of the 500 m grid applied in the model. The western, central, and eastern basins are labeled as WB,
CB, and EB, respectively. Blue circles indicate lake buoys and black squares indicate water level gauges.

## 97 2.2 Model description

98 COASTLINES applies the three-dimensional Aquatic Ecosystem Model (AEM3D, version 1.1.1, HydroNumerics 99 Pty Ltd.). This model solves the unsteady 3D Reynolds-averaged Navier-Stokes equations for incompressible flow 100 employing the Boussinesq and hydrostatic approximations. Momentum advection is based on the Euler-Lagrange 101 method with a conjugate-gradient solution for the free-surface height (Casulli and Cheng, 1992), and a conservative 102 ULTIMATE QUICKEST discretization scheme for advection of scalars (Leonard, 1991). AEM3D is a parallel 103 version of the commonly applied Estuary and Lake Computer Model (ELCOM; (Hodges et al., 2000). ELCOM has 104 been applied to Lake Erie to simulate currents and seasonal circulation (León et al., 2005), the internal Poincaré 105 (Valipour et al., 2015) and Kelvin waves (Valipour et al., 2019), ice cover (Oveisy et al., 2012) and the response of 106 the thermal structure, in Lake Erie, to air temperature and wind speed changes (Liu et al., 2014). ELCOM has been 107 coupled with the biogeochemical CAEDYM model to simulate Lake Erie phytoplankton and nutrients (León et al., 108 2011), and the response of hypoxia (Bocaniov and Scavia, 2016) and algae blooms (Scavia et al., 2016) to nutrient 109 load reductions. Recent applications of AEM3D include a study of the water level in Lake Arrowhead, California 110 (Saber et al., 2020), ice cover in Lake Constance (Caramatti et al., 2019) and pollutant transport in Lake St. Clair 111 (Madani et al., 2020).

## 112 2.3 Model setup and meteorological forcing variables

- 113 To adequately resolve the coastal boundary layer (~ 3 km width (Rao and Murthy, 2001)) and basin-scale internal
- 114 waves (Poincaré (16.8 h) and Kelvin waves), the bathymetry of Lake Erie
- 115 (<u>https://www.ngdc.noaa.gov/mgg/greatlakes/erie.html</u>) was discretized into a 500 m  $\times$  500 m horizontal grid, which
- 116 is ~10 % of the internal Rossby radius (Schwab and Beletsky, 1998). The lake was discretized into 45 vertical
- 117 layers, with fine resolution (0.5 m) through the surface layer, metalimnion and bottom of the central basin, and
- 118 coarse layers (5 m) through the hypolimnion of the deeper eastern basin to the maximum depth of 64 m.
- 119 The model was 'cold started' on April 8, 2020 (day of year (day) 99) with an initial temperature field spatially
- 120 interpolated from observed water temperatures at stations 45142 and MHRO1; a time when spring turnover causes
- 121 thermal stratification to be minimal. The model time step is dt = 300 s to satisfy the CFL =  $\sqrt{2}$  (Courant-Friedrichs-
- 122 Lewy) condition for internal waves (Hodges et al., 2000).
- 123 The model is forced by the surface meteorology (wind speed, wind direction, air temperature, shortwave
- solar radiation, relative humidity, air pressure, and net longwave radiation), with net longwave radiation being
- 125 computed internally within AEM3D from cloud cover and the modelled surface temperature. In order to address the
- spatial variability of meteorological conditions across the lake, the computational domain was forced with
- 127 meteorological data on horizontal grids at 15 km (<u>https://dd.weather.gc.ca/model\_gem\_global/15km/</u>) and 25 km
- 128 (<u>https://dd.weather.gc.ca/model\_gem\_global/25km/</u>) resolution using meteorological forecasts from the
- 129 Environment and Climate Change Canada Global Deterministic Forecast System (GDPS). This resulted in 31 and 23
- 130 meteorological sections for the 15 km and 25 km models, respectively. Wind speed, wind direction, air temperature,
- 131 relative humidity, air pressure, dew point, and cloud cover are direct outputs from GDPS, with solar radiation
- 132 calculated based on dew point and air pressure ((Meyers and Dale, 1983); Appendix C. in (Gaudard et al., 2019)).
- 133 The meteorological forecast has an output timestep of 3-h and a forecast length of 240 h. The .GRIB2
- 134 meteorological data were retrieved with the 'urllib' library in Python and formatted into AEM3D input files using
- the nctoolbox in MATLAB.
- 136 In this pilot application, the Lake Erie inflows and outflows, which roughly balance, are neglected,
- 137 however evaporation and precipitation are accounted for in the water balance. Over short timescales (<10 days), the
- 138 contributions from evaporation and precipitation to water level change are minor, with water level oscillations
- resulting from storm surges and surface seiches (Trebitz, 2006).

#### 140 2.4 Observations, implementation, and model validation

141 The water levels and temperatures simulated by COASTLINES were validated using both in situ and satellite

- 142 observations. Near real-time water level data was used from six stations along the Canadian coastline, which
- reported hourly observations (Bar Point, Kingsville, Erieau, Port Stanley, Port Dover, and Port Colborne; Fig. 1;
- 144 Table 1), retrieved from Fisheries and Oceans Canada (<u>https://marees.gc.ca/eng/find/zone/44</u>). The data are parsed
- using the 'BeautifulSoup' library in Python and saved as .csv files, to be read with MATLAB for model validation.
- 146 The observations showed higher fluctuations in the western (Bar Point and Kingsville) and eastern (Port Dover and

Port Colborne) basins (Fig. 1). Thus, we quantify the water level forecast capability and uncertainty in terms of theRoot Mean Square Deviation (RMSD) and Relative Error (RE):

149 
$$RMSD = \left[\frac{1}{N}\sum_{i=1}^{N}(x_i - y_i)^2\right]^{1/2},$$
 (1)

150 
$$RE = 100 \frac{RMSD}{\log. mean(daily range)}$$
, (2)

where  $x_i$  and  $y_i$  (i = 1, 2, 3, ..., N) are the model and observed water level timeseries and N is the number of samples.

152 RMSD is the absolute error of the model against the observation. The difference between the observed daily

153 minimum and maximum value was defined as the daily water level fluctuation range, where RE is the ratio between

the RMSD and lognormal mean of daily range over April to September 2020. Given that our study focusses on a

155 240-h forecast, RE can characterize the forecast bias, regardless of the instantaneous water level position. Here,

156 forecast uncertainty is in the evaluation statistic from combining forecast dates – not actual uncertainty in an

157 individual forecast.

Eight in situ lake buoys, distributed over the nearshore areas of the three basins (Fig. 1; Table 1), provided near real-time model validation data through the Great Lakes Observing System (GLOS: <u>https://www.glos.us/</u>) and National Data Buoy Center (NDBC: <u>https://www.ndbc.noaa.gov/</u>) portals. For each station, the text-based NDBC observations are parsed using the 'BeautifulSoup' Python library, and the GLOS observations are retrieved using 'webdriver' from the 'selenium' Python library. All the lake buoy observations are saved as .csv files and read into

163 MATLAB for post-processing. Attempts to retrieve missing variables would result in run-time errors.

The lake buoys are deployed from April or May through mid-October, spanning the spring/fall turnover
 and seasonal summer stratification periods. However, due to COVID-19 related delays in instrument deployments in

166 2020, only two buoys located offshore of Cleveland, near the water intake crib (station 45176 and station 45164),

167 were equipped with thermistor chains to monitor temperature profiles. The other six buoys provide air and lake

surface temperature as well as wind speed and direction observations for hydrodynamic and meteorological forecast

- validation. Satellite-based observations of lake surface temperature were obtained from the Great Lakes Surface
- 170 Environmental Analysis (GLSEA2), which is derived from NOAA CoastWatch AVHRR (Advanced Very High-

171 Resolution Radiometer) imagery and updated on NOAA GLERL website

172 (<u>https://coastwatch.glerl.noaa.gov/erddap/files/GLSEA\_GCS/</u>). GLSEA2 produced daily observations, with 2.6 km

173 resolution, from the cloud-free portions of the satellite images (Schwab et al., 1999). The netCDF data are retrieved

using the 'BeautifulSoup' library and 'webdriver' from 'selenium'.

We quantified the temperature forecast capability using the statistical measures of RMSD (eq. 1) and MeanBias Deviation (MBD):

177 
$$MBD = 100 \frac{\frac{1}{N} \sum_{i=1}^{N} (x_i - y_i)}{\frac{1}{N} \sum_{i=1}^{N} y_i}$$
 (3)

178 For the spatial MBD and RMSD (s-MBD and s-RMSD),  $x_i$  and  $y_i$  are the model and observed temperature in each

grid, and N is the total number of grids. For timeseries MBD and RMSD (t-MBD and t-RMSD),  $x_i$  and  $y_i$  are the

180 model and observed temperature at each sample time, and N is the total number of samples.

1	Q	1
4	-0	т

### 183 Table 1

184 Details of field stations with water level gauges and lake buoys.

Station	Parameter	Sampling interval (min)	Depth of measurement (m)	
Bar Point	Water level	60	Surface	
Kingsville	Water level	60	Surface	
Erieau	Water level	60	Surface	
Port Stanley	Water level	60	Surface	
Port Dover	Water level	60	Surface	
Port Colborne	Water level	60	Surface	
TWCO1	Temperature	10	Surface	
45005	Temperature	10	Surface	
45176	Temperature	10	1, 3, 4, 6, 7, 9, 10, 12, 14, 15	
45169	Temperature	30	surface	
45164	Temperature	60	1, 2, 4, 6, 8 10	
45132	Temperature	60	Surface	
45167	Temperature	10	Surface	
45142	Temperature	60	Surface	

# 185 2.5 System operation

186 The COASTLINES operational forecast system is run on a local server supported by Queen's University ITS 187 (Kingston, Canada). The COASTLINES workflow is presented in Fig. 2. The system consists of input data 188 acquisition and preparation, 24-h hydrodynamic simulations, 240-h hydrodynamic simulations, validation against in 189 situ observations, and uploading the model forecasts and validation to the web platform. Given that the standard 190 deviations of meteorological forecast variables increase with forecast lead time (Buehner et al., 2015), we performed 191 separate 24-h and 240-h forecast simulations each day. The model advances every day according to the 24-h forecast 192 simulation and terminates by generating 're-start' files. These files are then used to hot-start the 240-h forecast 193 simulation and the 24-h simulations for the next day. The input files for the 240-h forecast simulations are 194 iteratively replaced by the new 240-h meteorological forecast generated each day. The 24-h and 240-h forecast 195 model outputs are compared against observations to evaluate the forecast performance against forecast lead time. 196 The long-term stability of employing daily 'hot' restarts can be seen in a comparison between simulated 197 temperature profiles from a continuous run and that from stitching together the 24-h hot-start simulations (Appendix 198 A; Fig. A1). At present, the initial water level cannot be modified using the AEM3D re-start files. Therefore, to 199 account for long term drift in surface water level, we used real time gauge observations as the datum point for water 200 level forecasts (automatically performed by MATLAB in post processing) and only consider errors resulting from 201 simulation of storm surges and seiches, as opposed to those from seasonal changes in mean lake level. Automation 202 of the processing tasks in the workflow is performed by Python scripts triggered by the Windows Task Scheduler 203 every 24-h at midnight. The online meteorological forecast data are retrieved from GDPS once updated at 3 am 204 EST. Forcing variables are then formatted in MATLAB, called by the Python scripts once the meteorological 205 forecast data has been retrieved. The AEM3D pre-compiled executable is then run as a black-box code, triggered by 206 Python. The 24-h and 240-h simulations take 0.5 h and 4 h to complete, respectively. The observed data, including 207 water levels from gauge stations, water temperatures from lake buoys and satellite images are scraped with Python

- at 8 am, followed by post-processing in MATLAB to validate model output, calculate statistical metrics (RMSD,
- MBD) and generate figures. The results are exported to Google sheets and published to the COASTLINES website
- 210 (e.g., Appendix B). The authors (supervisors of COASTLINES) and Queen's ITS monitor forecast results and
- 211 maintain system operation.
- 212 Global coverage of the GDPS forecasts enable this operational system to be readily implemented at other
- sites where lake bathymetry, boundary flows and in-situ validation data are available. The workflow may be easily
- 214 modified to include additional meteorological forecasts or other black-box hydrodynamic drivers (e.g., HRRR and
- 215 Delft3D, respectively (Rey and Mulligan, 2021)). This would require simple modification of the COASTLINES
- 216 MATLAB-based write statements to meet the formatting requirements of a particular driver.



Fig. 2 Daily workflow and automated processes in the COASTLINES operational system as performed on the local server.

# 220 3 Results

- 221 The COASTLINES water level and temperature forecasts have been operational since April and July 2020,
- respectively. The 24-h and 240-h forecast water levels from the 15 km and 25 km resolution models were validated
- against real-time gauge station observations. The water level statistical metrics (RMSD and RE) were averaged over
- April to September 2020. The 24-h and the 240-h forecast lake surface temperature and temperature profiles, from

the models, were also validated against real-time lake buoy data and daily averaged satellite imagery. The timeseries
 and spatial MBD and RMSD (t-RMSD, t-MBD and s-RMSD, s-MBD) were averaged over July to September 2020.

#### 227 3.1 Water level

228 The Relative Error (RE) of the forecast water level increases with forecast time when averaged over April to

- 229 September 2020; the 24-h forecast error being ~ 40% at all six gauge stations (Fig. 3 a, c, e, g, i, k). Given the large
- water level fluctuation at Port Colborne (Fig. 31), the 240-h forecast RE is highest at this station, exceeding 70%
- (Fig. 3 k). Of the six gauge stations reported in this study, those at the western (Bar Point and Kingsville) and
- eastern (Port Dover and Port Colborne) ends of Lake Erie longitudinal axis had the largest water level fluctuations,
- resulting from the predominant south-westerly winds generating strong wind set-up and surface seiches (Fig. 3 b, d,
- f, h, j, l). The lognormal means of the daily range in water level at the six gauge stations are 0.21 cm (Bar Point),
- 235 0.16 cm (Kingsville), 0.07 cm (Erieau), 0.10 cm (Port Stanley), 0.15 cm (Port Dover), 0.17 cm (Port Colborne).
- 236 The 24-h forecasts show qualitative agreement with observations in phase and magnitude (Fig. 4). The 24-h
- 237 forecasts reproduce the dramatic surface seiches induced by westerly winds > 15 m s<sup>-1</sup> (Fig. C2) on day 251 (RMSD
- 238 < 0.1 cm), especially the obvious water level fluctuations at stations in the western and eastern basins (Fig. 4 a, b, e).
- However, the prediction of water level at Bar Point showed large bias (Fig. 4 f), with the model overestimating the
- 240 water level fluctuation. The uncertainty in the model forecast, which increased with the range of the daily
- fluctuation, was captured by the 24-h forecast RE over April to September (the shaded areas in Fig. 4). Overall, the
- confidence interval of the 24-h forecast included most of the discrepancies between the observations and the model





Fig. 3 Relative error (RE) in water level predictions against forecast time at six stations (a, c, e, g, i, k). Panels (b, d, f, h, j, l) are the corresponding frequency distribution of lognormal means of the daily water level fluctuation range (x-axes, unit in meter) at Bar Point, Kingsville, Erieau, Stanley, Port Dover, Port Colborne, respectively.





Fig. 4 Comparison between observed and stitched 24-h forecast modeled water level at (a) Port Colborne, (b)
Port Dover, (c) Port Stanley, (d) Erieau, (e) Kingsville, and (f) Bar Point. The shaded areas show the confidence
interval of the 15 km model (red shading) and the 25 km model (blue shading), as given by the 24-h RE in Fig.
3.

254 Timeseries validations for the 240-h model forecast (Fig. 5) include confidence intervals from the RE (Fig. 3). As

shown, the forecast began 6 days in advance of the large surface seiche event on day 251 and predicted the seiche to

crest at Port Colborne 1-2 h ahead of the observations, and to trough at Kingsville 1-2 h behind the observations

257 (Fig. 5 a, c). Damping of the seiche oscillations (~144 hours in the future) was excessive, with the water levels being

underestimated and the phase shifted by approximately 12 hours (Fig 5. a, b). Despite the wide confidence intervals,

due to the increasing RE with forecast time, large bias existed after the seiche event (forecast time >168 hours).

260 When the forecast was initiated close to the event (3 days before), the prediction of seiche phase was more accurate

- 261 (Fig. 5 d, e, f); however, the seiche decay still had a 12-h phase shift. The discrepancies in seiche amplitude (< 0.1
- 262 m) were within the confidence intervals of the models.



Fig. 5 Comparison between the observed water level and 240-h forecast hot-started on day 245 (a, b, c) and day
248 (d, e, f) at Port Colborne, Port Dover, and Kingsville, respectively. The shaded areas show the confidence
interval of the 15 km model (red shading) and the 25 km model (blue shading), as given by the 240-h RE in Fig.
4.

268 3.2 Water temperature

# 269 3.2.1 Lake surface temperature

270 Using satellite-based and lake buoy-based observations, we evaluated the lake surface temperature forecast (Fig. 6).

271 The 24-forecast captured the seasonal variation of lake surface temperature, particularly the rapid increase in

temperature on days 180-190, and the gradual decrease in temperature after day 240; at all eight stations. However,

the forecast overestimated the lake surface temperature in July by 3-5 °C (days 180-210), particularly at STN 45167

and 45142. Due to the 3-h output interval associated with the meteorological forecast data, the forecast model was
 insensitive to temperature fluctuations over shorter timescales, as recorded by the lake buoys, and it underestimated

insensitive to temperature fluctuations over shorter timescales, as recorded by the lake buoys, and it underestimated

the sudden decrease in temperature near day 220 and 255 at STN 45005.

277 Overall, the t-MBD and t-RMSD, over these eight stations, were ~6% and 1.4 °C (15 km model) and ~5%

278 1.3 °C (25 km model) for the 24-h forecast, respectively (Table 2). The average s-MBD and s-RMSD over the 50

days from July-September were ~4% and 1.2 °C, respectively, for both 15 km and 25 km resolution models.





Fig. 6 Comparison between the stitched 24-h forecast and observed lake surface temperature at 8 stations (a) TWCO1, (b) 45164, (c) 45005, (d) 45132, (e) 45176, (f) 45167, (g) 45169, and (h) 45142. The green lines are

timeseries observations from lake buoys, the black lines are daily observations derived from satellite imagery.



Fig. 7 (a) Mean-Bias Deviation (MBD) against forecast time; (b) Root-Mean-Square Deviation (RMSD) against forecast time. (c-f) Timeseries of 240-h forecast and observed lake surface temperature at stations 45164, 45167, 45169, 45176, respectively, and daily averaged satellite lake surface temperature (black asterisks). The confidence interval (shaded areas) in (c-f) represents the uncertainty of the 240-h forecast model through the

timeseries RMSD with the forecast time (panel b).

290 The 240-h forecast MBD and RMSD, surprisingly, do not show an increase in error with forecast time (Fig. 7 a, b).

Both t-MBD and s-MBD, over the 240-h forecast, are ~4-5%, with s-MBD 0.5-1% higher than t-MBD. Although

- both 240-h s- and t-RMSD are under 2 °C, the t-RMSD show the error with forecast time to be higher than s-RMSD.
  Both timeseries observations from lake buoys and daily averaged observations from satellite imagery fall into the
  forecast confidence interval based on the 240-h t-RMSD (Fig 7 c-f).
- 295 Spatial comparisons of satellite-based observations to the 24-h, 48-h, 120-h, 168-h surface temperature 296 forecasts illustrate that the forecast system (with 15 km meteorological data) predicted the cooler water mass along 297 the northwest shoreline of the central basin with a cold bias  $\sim 2$  °C (Fig. 8); this may be up-welling hypolimnetic 298 water (see following Discussion 4.2). The model also predicted lower surface temperatures in coastal regions of the 299 western basin with a cold bias ~2 °C (Fig. 8 m-t); the bias presumably was induced by neglecting riverine inflows 300 (e.g., Detroit River and Maumee River; see also Discussion 4.3), which are typically near the air temperature and 301 several degrees warmer than the lake surface (Wang and Boegman, 2021). Further comparisons between model 302 predictions and satellite-based observations of lake surface temperature can be found in the Supporting material 303 (Fig. D1-2).
- 304



Fig. 8 Comparison of lake surface temperature from (a-d) satellite observations, (e-h) 15 km model forecast,
 and (i-l) 25 km model forecast during late summer. The models were hot-started on day 251. The difference
 between observations and models are shown in (m-t).

# 309 3.2.2 Thermal structure

- 310 The 3D AEM3D model structure applied in COASTLINES enables the prediction of the thermal profiles in the lake.
- 311 On 15 Jun. 2020 (day 168), a rapid drop (~ 6°C) in surface temperature, was recorded by the thermistor at STN 45176,
- and predicted by the stitched 24-h COASTLINES model (15 km meteorological input) (Fig. 9 a, b). The timing and
- intensity of this up-welling event were accurately forecast, but before and after the upwelling event, the mixed layer
- depth was modelled to be deeper than observed; perhaps a result of spurious numerical diffusion resulting from the

315 thermocline swashing along the stair-step z-level grid at the lake perimeter. The 240-h forecast model was not yet 316 operational at this time.

- Both the 240-h 15 km and 25 km resolution forecasts predicted the down-welling event on 11 Jul. 2020 (day 193) at STN 45176 (Fig. 10). The forecasts were hot-started 7 days before the event (day 187), successfully predicting when warm surface water down-welled toward the bed displacing the thermocline (Fig. 10 b, c), but the 15 km resolution underestimated the intensity of down-welling, predicting thermocline recovery on day 193. The forecast hot-started 5 days before the event (day 189) gave a more accurate prediction with the down-welling persisting over
- 322 2 days (Fig. 10 d, e) as observed (Fig. 10 a).



323

Fig. 9 Temperature profile comparisons between (a) observations and (b) stitched daily 24-h forecasts from the

325 15 km resolution model at station 45176. (c) Observed dissolved oxygen concentration at station 45164 from 326 lake buoy (<u>https://www.glos.us/</u>). The inset image shows the bathymetry and locations of lake buoys. The black

square indicates the timing of the up-welling event.



329 Fig. 10 Comparisons of (a) observed temperature profile, (b, d) 240-h 15 km resolution modeled, and (c, e) 240-

330 h 25 km resolution modeled temperature profiles at STN 45176. The forecast models were hot-started on day

**187** (b, c), and day 189 (d, e). The black square indicates the down-welling event.

332 Table 2

Statistical measures of t-MBD (Mean-Bias Deviation) and t-RMSD (Root-Mean-Square Deviation) between
 the 24-h forecast model and observations of water temperature.

Station	RMS	RMSD (°C)		MBD (%)	
_	15 km model	25 km model	15 km model	25 km model	
45176	2.6	2.6	6.8	6.8	
45164	1.8	2.1	2.2	2.3	
45132	1.5	1.5	5.5	5.7	
45142	2.4	2.1	9.9	8.8	
45167	1.2	1.1	4.6	4.0	
45169	1.3	1.2	4.7	4.6	
TWCO1	1.0	1.0	3	1.9	
45005	1.2	1.1	8.2	7.9	

## 335 4 Discussion

# **4.1** Prediction of coastal up-welling for fishery and drinking water management

337 The central basin of Lake Erie is vulnerable to hypoxia in summer from near-bed thermal stratification and the

relatively large ratio of sediment area to hypolimnetic volume (Bouffard et al., 2013; Nakhaei et al., 2021).

Associated fish kill events (10s of thousands) are regularly reported, including an event on north shore of the central

basin in the late summer of 2012, which was presumably was caused by up-welling of cold anoxic water from the

341 hypolimnion (MOE, 2012; Rao et al., 2014). Similarly, 1000s of freshwater drum were killed in a rapid warming

event (~5 °C /week) in the western basin in 2020 (https://www.13abc.com/content/news/Hundreds-of-dead-fish-

343 <u>wash-up-in-Sandusky-Bay-571025541.html</u>). Similarly, shoreward advection of hypoxic water, from up-welling or

- 344 internal waves also adversely affects source water quality at drinking water intakes (<u>https://epa.ohio.gov</u>), whereby
- high Fe and Mn or low pH, associated with hypoxic water requires adjustment of treatment processes. This is a
- particular issue along the Ohio coast of the central basin (Ruberg et al., 2008; Rowe et al., 2019).
- 347 The ability to predict these movements of hypolimnion water would aid management of both Lake Erie
- 348 fisheries and drinking water treatment. Here, we test the ability of the model to predict up-welling of cold bottom
- water in the region where the fish kill was observed in 2012. On days 249-253, 2020 (Fig. 8) strong southwesterly
- winds (~ 12 m s<sup>-1</sup>; Fig. C2) were modelled and observed to create up-welling along the north shore, as expected

from Ekman drift of the surface layer (Jabbari et al., 2019). The upwelled cold hypolimnetic water is shown near the

- coast of Erieau in the satellite observations and the 15 km resolution model (Fig. 8 a, b, e, f). The depth-averaged
- water temperature and current circulation in the forecast shows up-welling to persist for several days (Fig. 11), with
- 354 cold hypolimnetic water accumulating along north shore and strong eastward currents along the northern shoreline
- of the east-central basin. The up-welling region matched that shown in a 2013 hindcast simulation (Valipour et al.,
- 2019), revealing the hotspots of vertical transport of nutrients and anoxic hypolimnetic water.
- Another up-welling event occurred near the Cleveland drinking water intake crib on days 167-170 (Fig. 9).
- 358 This event was accompanied by simultaneous  $\sim 8 \text{ mg L}^{-1}$  oscillations in the observed dissolved oxygen concentration
- 359 (Fig. 9 c) at STN 45164 (~20 km away from STN 45176), followed by the dissolved oxygen concentration
- becoming locally hypoxic (< 2 mg/L) for ~2 days. The COASTLINES model predicted this event (section 3.2.2),
- 361 which would have provided sufficient notice for drinking water plane operators to implement the additional
- treatment required for hypoxic water (Rowe et al., 2019). Future work, using the coupled iWaterQuality
- biogeochemical module (formerly CAEDYM) could extend COASTLINES to forecast water quality in Lake Erie
- 364 (León et al., 2011), including dissolved oxygen concentrations and formation of algae blooms (Bocaniov et al.,
- 365 2020).



Fig. 11 Color maps showing the forecast depth-averaged temperature throughout the lake. The red arrows
 represent forecast depth-averaged currents. The model results are from the 240-h forecast model hot-started
 on day 247.

# **370 4.2 Prediction of storm surge events for public safety**

371 Due to its shallowness and long fetch aligned with the predominant southwest winds (Hamblin, 1979), Lake Erie has

the largest daily range of water level amongst the Great Lakes (Trebitz, 2006); these water level fluctuations are

- mainly due to storm surges and surface seiches (Mortimer, 1987). In every month of 2020, Lake Erie set new mean
- water level records (<u>https://www.tides.gc.ca/C&A/bulletin-eng.html</u>), causing the shoreline to be exposed to high
- risk from erosion and flooding and making the shoreline communities susceptible to costly damage and economic
- 376 loss (e.g., <u>https://www.lowerthames-conservation.on.ca/flood-forecasting/flood-notices/</u>). Given the ability of
- 377 COASTLINES to predict water level fluctuations induced by storm surges and seiches (Fig. 3, 5), we tested the
- ability of the model to act as a coastal flooding warning system. Due to the unpredictability and severity of water

379 level fluctuations in Lake Erie, there is currently a need to improve short-term water level forecasts and water level

380 warning systems (Gronewold and Stow, 2014). This would assist early decision making during natural hazards

**381** (Gronewold and Rood, 2019).

382 We forecast the storm event on 15 Nov. 2020, which generated a wind-induced storm surge (~1-1.5 m) in 383 the eastern basin with associated strong surface currents (Fig. 12). The inset image, taken during the event, shows 384 the coastal flooding from this event. COASTLINES successfully predicted the high-water level phase at Port Dover 385 72 hours in advance, but underestimated the water level increase by 0.5 m. The hot-start forecast 24 hours in 386 advance was more accurate in predicting the water level prediction, with a difference <0.5 m from the observations 387 (Fig. 12 d). Note that both forecasts missed the small (~0.5 m) seiche before the significant increase at the end of 388 day 320, presumably due to the low temporal resolution of the meteorological forecast input or local topography 389 near the gauge. The overall wind-induced tilt of the free surface was less from the 72 hours hot-start, relative to the 390 24 hour hot start (Fig. E1), which predicted a larger local storm surge (Fig. 12d).

The impacts of coastal flooding could be improved by including simulation of wind-waves through
 enabling the coupled surface wave model SWAN (Booij et al., 1999) in AEM3D. Similarly coupled Delft3D-SWAN
 models have recently been applied in the development of a real-time predictive system for the coastal ocean and
 large estuaries (Rey and Mulligan, 2021).



396 Fig. 12 Color maps showing the water level change compared to Nov 15th 00h from (a) 12 h, (b) 15 h, and (c) 397 18 h forecasts from 15 km resolution model. The black arrows are depth-averaged mean current fields. Panel 398 (d) shows a comparison between forecast and observed water level at Port Dover. The upper panel shows the 399 forecast hot-started on 15 Nov. 2020 (day 320), and the lower panel shows the forecast hot-started on 12 Nov. 400 2020 (day 317). The shaded region indicates the confidence interval. The inset image (extracted from a footage 401 by J. Homewood from Lower Thames Valley Conservation Authority) shows the flooding induced by the 402 dramatic water level increase during this event. The two cottages shown in the images were destroyed later in 403 the afternoon.

## 404 4.3 Bias and uncertainty

405 The AEM3D model (formerly ELCOM) employed in COASTLINES has shown skill in temperature hindcasts in the 406 Great Lakes with RMSD ~ 0.9 - 3 °C in Lake Erie (Liu et al., 2014; Oveisy et al., 2012) and 1.5 - 1.9 °C in Lake 407 Ontario (Paturi et al., 2012). Similarly, the 24-h COASTLINES forecast predicted water temperatures with an 408 average s-RMSD and t-RMSD < 2 °C at the surface (Table 2). Therefore, the forecasts are within ~1 °C RMSD in 409 comparison to hindcasts, showing sufficient model skill for predictive simulations to aid lake management (e.g., 410 movements of hypoxic water, fish thermal habitat, etc.). The accuracy of the COASTLINES forecasts may result 411 from the high spatial resolution and coverage of meteorological forecast compensating for the inherent inaccuracies 412 in the weather forecast data. Errors in forcing data may be compensated for using data assimilation (Baracchini et 413 al., 2020b). In the hindcast models, Liu et al. (2014) applied uniform Lake Erie meteorological forcing over 4 zones 414 and Valipour et al. (2019) utilized 6 zones, each spanning ~100 km. These included land-based observations, when 415 there was no available lake buoy data, which induces error, especially in large shallow lakes (Hamblin, 1987). The 416 comparatively high-resolution GDPS meteorological forecast was four to five times higher in horizontal resolution than used in the hindcast simulations, improving the representation of regional meteorological and climatological 417 418 conditions. 419 Compared to other operational lake forecast systems, the 240-h COASTLINES forecast is longer (e.g., 420 GLCFS forecasts 120 hours and meteolakes.ch forecasts 108 hours) and is the only one forced with open-access 421 meteorological data that has global coverage. The GLCFS provided 48-h water level forecasts with RMSD ~0.12 m 422 at the Buffalo gauge and ~0.14 m at the Toledo gauge, corresponding to RE ~ 60% and 51%, respectively (O'connor

- 423 et al., 1999; Trebitz, 2006); using the older 4 km grid Princeton Ocean Model implementation, as opposed to the
- 424 newer unstructured grid FVCOM GLCFS. COASTLINES gives better 48-h water level forecast performance (RE ~
- 425 40 %) at six gauge stations. For temperature, benefitting from a smaller domain, finer resolution meteorological
- 426 input (~2.2 km) and data assimilation, the 4.5-day lake surface temperature predicted by meteolakes.ch has a RMSD
- 427 =  $0.8 \degree C$  (Baracchini et al., 2020b), whereas COASTLINES predicted the 120-h (5 d) lake surface temperature with
- 428 RMSD ~ 1.7 °C. COASTLINES also outperforms 1D climatological hindcasts (e.g., Freshwater Lake (FLake)),
- 429 with 2–4 °C RMSD over a 120-h lake surface temperature forecast (Lv et al., 2019; Gu et al., 2015) and has similar
- error to the 3D Princeton Ocean Model (Kelley et al., 1998), with 0.6-0.9 °C mean absolute error in the 36-h lake
- 431 surface temperature forecast at station 45005.
- 432 The uncertainty and bias in the COASTLINES forecast results from error induced by the initial conditions433 at each hot-start, error in the meteorological forecasts and error in the numerical methods. These errors could be
- 434 reduced by improving model calibration through data assimilation. For example, Baracchini et al. (2020b) reduced
- the RMSE temperature simulation of Lake Geneva from ~ 2 °C to ~ 1 °C by employing a sequential data
- 436 assimilation routine; this would correspond to a <5% improvement in simulation of Lake Erie summer surface
- 437 temperature. Before implementing data assimilation in our system, the limitations of such a scheme must be
- 438 considered: (*i*) As we are performing forecasts, not hindcasts, we are unable to assimilate observations during model
- runtime (e.g., as done in the NCEP North American Regional Reanalysis: NARR); (*ii*) Sequential assimilation could
- 440 be employed to nudge the initial conditions for the 24-h runs with real-time-observed data. This could be achieved

- by modifying the binary AEM3D restart files using model specific read/write statements in our Python workflow
- 442 (e.g., from aem3d\_restart\_v3\_type.f90), followed by smoothing (e.g., with a Kalman filter). Future work will focus
- 443 on adding real time model calibration (e.g., Gaudard et al. (2019)), which is not presently included in the
- 444 COASTLINES forecast workflow. For example, Baracchini et al. (2020a) employed OpenDA as a black-box
- 445 wrapper to calibrate DELFT3D for Lake Geneva.
- 446 The errors induced by hot-starting were shown to be negligible (Fig. 4, 6, 7 (a, b), Fig. A1). However, 447 uncertainty from boundary conditions, especially the meteorological forcing, may introduce error. The 23 to 31 448 meteorological zones from the forecast wind field provides spatial variability required to simulate the mean surface 449 circulation (Laval et al., 2003), water level (Trebitz, 2006), and thermocline motions (Valipour et al., 2015; Valipour 450 et al., 2019). However, the 3-h time interval between GDPS forecast dataset updates is much less than the 10-min 451 interval associated with meteorological data observed at lake-buoys (typically one to six) used to drive hindcasts 452 (e.g., León et al. (2005)) and so the coarse temporal resolution in GDPS forecast may alias temporal events, such as 453 wind gusts (Fig. C1). This is of particular concern in large shallow lakes, such as Lake Erie, where winds play the 454 dominant role in driving hydrodynamics. The rapid response of the water level to windstorms (Hamblin, 1987) 455 could result in the effects of aliasing and forecast error being passed to the water level, leading to the growth of RE 456 against forecast time (Fig. 3). The meteorological forecast from the 15 km and 25 km GDPS models did not show 457 discrepancies (Fig. C2-5) and the evaluation metrics indicate that forecast results were largely insensitive to the 458 meteorological inputs in Lake Erie (Fig. 3, 7). However, the 15 km model better predicted the mesoscale upwelling 459 event (Fig. 8, 9, D2). The 24-h air temperature and wind speed forecasts had ~ 1.5 °C and ~ 2 m s<sup>-1</sup> RMSD, 460 respectively. However, bias in the 240-h forecast increases with forecast time (Buehner et al., 2015). The 168-h 461 forecast meteorological data overestimated wind speeds by up to 10 m s<sup>-1</sup> (Fig. C4), and bias in the air temperature 462 forecast (Fig. C5) may cause the consistent warm bias (up to 3°C) in forecast lake surface temperature (Fig. 8). 463 These errors may be corrected through real time calibration using data assimilation (Baracchini et al., 2020a, b). The 464 growing bias in air temperature, with forecast time, does not affect the lake surface temperature (Fig. 7), presumably 465 owing to the buffer effect of surface mixing layer (Schertzer et al., 1987). 466 Neglecting the inflows and outflows in the predictive simulation could induce bias in the forecast. The
- verse integreeting the inflows and outflows in the predetive simulation could induce outs in the forecast. The
  overestimation of water level fluctuation range near Bar Point (Fig. 4f) may result from neglecting the large Detroit
  River inflow, which regulates the seiche magnitude. The inflows also adjust more rapidly to air temperatures
  compared to deep lake waters. Thus, the up to 2 °C cold bias in coastal regions of the western basin (Fig. 8 m-t, Fig.
  D2) could be induced by neglecting the heated flux from two major inflows (i.e., Detroit River and Maumee River)
  of Lake Erie.
- In addition to inaccuracy in initial and boundary conditions, the discrepancies in simulating temperature profiles forecast may result from numerical diffusion arising due to the discrete nature of the vertical and horizontal grids. The simulated thermocline depth is overestimated (Fig. 9, 10), as occurred in applications of ELCOM with both higher (Nakhaei et al., 2019) and lower resolution (Paturi et al., 2012). COASTLINES has the potential to predictively simulate mesoscale physical processes, such as Kelvin waves (Bouffard and Lemmin, 2013) and

477 nearshore-offshore exchange (Valipour et al., 2019); however, model performance is poor in nearshore areas, where478 topographic features remain poorly resolved.

#### 479 5 Conclusions

We developed an operational forecast system COASTLINES, using the Windows Task Scheduler, Python-based data scrapping/formatting, and MATLAB data processing scripts, to automate application of a black-box hydrodynamic driver (AEM3D) to Lake Erie as an operational forecast tool. The resulting real-time and predictive lake modelling system used meteorological forecasts to generate 240-h forecasts of the lake surface level and 3D temperature and current fields on a 500 m × 500 m (horizontal) × ~ 1 m (vertical) grid, compares model output with near real time observations and publishes the model output on a web-based platform.

486 The favorable agreement between forecast model results and observed physical variables (e.g., water level 487 RE ~ 40 % and temperature t-RMSD and s-RMSD < 2 °C) in Lake Erie demonstrates the ability of the forecast 488 system to make predictions of hydrodynamic processes on time horizons up to 240-h that are as accurate as 489 traditional hindcast simulations using directly observed meteorological forcing. This enables the near real-time 490 updates to the web platform to be used as a communication tool that rapidly disseminate forecast results to managers 491 and stakeholders. Examples include >24-h prediction of: (i) up- and down-welling events leading to fish kills; (ii) 492 up-welling events transporting hypoxic water to a drinking water intake; and (*iii*) coastal flooding events from storm 493 surges.

494 This operational system shows the feasibility of applying freely available meteorological forecasts (e.g., 495 GDPS, HRRR), in situ buoy data and satellite images to drive and validate any computational lake model (e.g., 496 AEM3D, DELFT3D, GLM), without modifying the source code. The global coverage of the weather model allows 497 generalization of model application to and lake or coastal domain. To facilitate further development of open-access 498 predictive modelling systems, agencies are encouraged to share model validation observations, in real-time, through 499 organizations such as GLEON (www.gleon.org) and GLOS (www.glos.us). This will enable extension of 500 COASTLINES to include prediction of the physical-biogeochemical variables that drive sediment transport, 501 hypoxia, and harmful algal blooms.

502

### 503 Code and data availability.

504 The observed data and meteorological forcing used in this study is openly accessible online as cited in the text. The 505 COASTLINES model output is archived on the server and can be obtained by contacting the corresponding author.

506 The Python and MATLAB scripts as well as the timeline set in Windows Task Scheduler are archived in the

- 507 Scholars Portal Dataverse (https://doi.org/10.5683/SP2/VTN7WC, Lin, 2021). The AEM3D executable was used as
- 508 a black box hydrodynamic transport code. The executable used in COASTLINES is available for a nominal license
- 509 fee from from Hydronumerics (https://www.hydronumerics.com.au/). The AEM3D source code was not modified
- 510 in this application but is available with permission from Hydronumerics.

# 511 Author contributions.

- 512 The concept of the COASTLINES workflow was designed by LB, SL, SS, and RM, and SL carried them out. SL
- 513 developed the model code and performed the simulations. All authors contributed to the validation of the model and
- interpretation of the results. SL wrote the manuscript with contributions from LB, SS, and RM.

#### 515 Acknowledgements.

- 516 This project was funded by the Dean's Research Fund from the Faculty of Engineering and Applied Science at
- 517 Queen's University. Computational support was provided by Alexander Rey and FEAS-ITS. LB thanks Damien
- 518 Bouffard for discussions during visits to EAWAG, which inspired this research. James Homewood, from the Lower
- 519 Thames Valley Conservation Authority (LTVCA) providing footages of the storm event on Nov. 15<sup>th</sup>, 2020.

# 520 Reference

- 521 Anderson, E. J., Fujisaki-Manome, A., Kessler, J., Lang, G. A., Chu, P. Y., Kelly, J. G. W., Chen, Y., and Wang, J.:
- 522 Ice forecasting in the next-generation Great Lakes Operational Forecast System (GLOFS), J. Mar. Sci. Eng., 6,
   523 10.3390/jmse6040123, 2018.
- 524 Antenucci, J., and Imerito, A.: The CWR dynamic reservoir simulation model DYRESM, Science Manual, The
- 525 University of Western Australia, Perth, Australia, 2000.
- 526 Baracchini, T., Hummel, S., Verlaan, M., Cimatoribus, A., Wüest, A., and Bouffard, D.: An automated calibration
- 527 framework and open source tools for 3D lake hydrodynamic models, Environmental Modelling & Software, 134, 104787, 2000
- **528** 104787, 2020a.
- 529 Baracchini, T., Wüest, A., and Bouffard, D.: Meteolakes: An operational online three-dimensional forecasting
- 530 platform for lake hydrodynamics, Water Res., 172, 10.1016/j.watres.2020.115529, 2020b.
- 531 Beletsky, D., Hawley, N., Rao, Y. R., Vanderploeg, H. A., Beletsky, R., Schwab, D. J., and Ruberg, S. A.: Summer
- thermal structure and anticyclonic circulation of Lake Erie., Geophys. Res. Lett., 39, 10.1029/2012GL051002, 2012.
- 533 Bocaniov, S. A., and Scavia, D.: Temporal and spatial dynamics of large lake hypoxia: Integrating statistical and
- three-dimensional dynamic models to enhance lake management criteria, Water Resour. Res., 52, 4247-4263,
  10.1002/2015WR018170, 2016.
- 536 Bocaniov, S. A., Lamb, K. G., Liu, W., Rao, Y. R., and Smith, R. E.: High sensitivity of lake hypoxia to air
- temperatures, winds, and nutrient loading: Insights from a 3-D lake model, Water Resources Research, 56,
   e2019WR027040, 2020.
- 539 Boegman, L., Loewen, M. R., Hamblin, P., and Culver, D.: Application of a two-dimensional hydrodynamic
- reservoir model to Lake Erie, Canadian Journal of Fisheries and Aquatic Sciences, 58, 858-869, 2001.
- 541 Boegman, L., Loewen, M., Hamblin, P. F., and A., C. D.: Vertical mixing and weak stratification over zebra mussel
  542 colonies in western Lake Erie, Limnol. Oceanogr., 53, 1093-1110, 10.4319/lo.2008.53.3.1093, 2008.
- 542 coolies in western Lake Life, Linnoi, Occanogr., 55, 1095-1110, 10.4519/10.2000.553.51095, 2008.
  543 Booij, N., Ris, R. C., and Holthuijsen, L. H.: A third-generation wave model for coastal regions 1. Model description
- 545 and validation J. Geophys. Res. Oceans, 104, 7649–7666, 10.1029/98JC02622, 1999.
- 545 Bouffard, D., Boegman, L., and Rao, Y. R.: Poincaré wave–induced mixing in a large lake, Limnology and oceanography, 57, 1201-1216, 2012.
- 547 Bouffard, D., Ackerman, J. D., and Boegman, L.: Factors affecting the development and dynamics of hypoxia in a
- 548 large shallow stratified lake: hourly to seasonal patterns, Water Resources Research, 49, 2380-2394, 2013.
- 549 Bouffard, D., and Lemmin, U.: Kelvin waves in Lake Geneva, J. Great Lakes Res., 39, 637-645,
- 550 10.1016/j.jglr.2013.09.005, 2013.
- 551 Bouffard, D., Boegman, L., Ackerman, J. D., Valipour, R., and Rao, Y. R.: Near-inertial wave driven dissolved
- 552 oxygen transfer through the thermocline of a large lake, J. Great Lakes Res., 40, 300-307,
- 553 10.1016/j.jglr.2014.03.014, 2014.
- 554 Brookes, J. D., and Carey, C. C.: Resilence to blooms, Science, 334, 46-47, 10.1126/science.1207349, 2011.
- 555 Buehner, M., McTaggart-Cowan, R., Beaulne, A., Charette, C., Garand, L., Heilliette, S., Lapalme, E., Laroche, S.,
- 556 Macpherson, S. R., Morneau, J., and Zadra, A.: Implementation of deterministic weather forecasting systems based
- on ensemble-variational data assimilation at Environment Canada. Part I: the global system, Mon. Wea. Rev., 143,
- 558 2532-2559, 10.1175/MWR-D-14-00354.1, 2015.
- Caramatti, I., Peeters, F., Hamilton, D., and Hofmann, H.: Modelling inter-annual and spatial variability of ice cover
  in a temperate lake with complex morphology, Hydrol. Process., 34, 691-704, 10.1002/hyp.13618, 2019.
- 561 Casulli, V., and Cheng, R.: Semi-implicit finite difference methods for three-dimensional shallow water flow. , Int.
- 562 J. Numer. Methods Fluids 15, 629-648, 10.1002/fld.1650150602 1992.
- 563 Chen, C., Beardsley, R. C., Cowles, G., Qi, J., Lai, Z., Gao, G., Stuebe, D., Xu, Q., Xue, P., Ge, J., Ji, R., Tian, R.,
- Huang, H., Wu, L., and Lin, H.: An unstructured grid, finite-volume community ocean model FVCOM user manual,
- 565 SMAST/UMASSD Tech. Rep. 11-1101, 373 pp., Dartmouth, Mass., 2012.
- 566 Chu, P. Y., Kelley, J. G. W., Mott, G. V., Zhang, A., and Lang, G. A.: Development, implementation, and skill
- assessment of the NOAA/NOS Great Lakes Operational Forecast System, Ocean Dyn., 61, 1305-1316,
- 568 10.1007/s10236-011-0424-5, 2011.
- 569 Gaudard, A., Schwefel, R., Vinnå, L. R., Schmid, M., Wüest, A., and Bouffard, D.: Optimizing the parameterization
- 570 of deep mixing and internal seiches in one-dimensional hydrodynamic models: a case study with Simstrat v1.3,
- 571 Geosci. Model Dev., 10, 3411-3423, 10.5194/gmd-10-3411-2017, 2017.
- 572 Gaudard, A., Vinnå, L. R., Bärenbold, F., Schmid, M., and Bouffard, D.: Toward an open-access of high-frequency
- 573 lake modelling and statistics data for scientists and practitioners. The case of Swiss Lakes using Simstrat v2.1,
- 574 Geosci. Model Dev., 12, 3955-3974, 10.5194/gmd-2018-336, 2019.

- 575 Gronewold, A. D., and Rood, R. B.: Recent water level changes across Earth's largest lake system and implications
- 576 for future variability, J. Great Lakes Res., 45, 1-3, 10.1016/j.jglr.2018.10.012, 2019.
- 577 Gu, H., Jin, J., Wu, Y., Ek, M. B., and Subin, Z. M.: Calibration and validation of lake surface temperature
- 578 simulations with the coupled WRF-lake model, Climatic Change, 129, 471-483, 2015.
- Hamblin, P. F.: Great Lakes storm surge of April 6, 1979, J. Great Lakes Res., 5, 312-315, 10.1016/S03801330(79)72157-5, 1979.
- Hamblin, P. F.: Meteorological forecing and water level fluctuations on Lake Erie, J. Great Lakes Res., 13, 436-453, 10.1016/S0380-1330(87)71665-7, 1987.
- Hecky, R. E., Smith, R. E. H., Barton, D. R., Guildford, S. J., Taylor, W. D., Charlton, M. N., and Howell, T.: The
- nearshore phosphorus shunt: a consequence of ecosystem engineering by dreissenids in the Laurentian Great Lakes,
  Can. J. Fish. Aquat. Sci., 61, 1285-1293, 10.1139/F04-065, 2004.
- 586 Higgins, S. N., Hecky, R. E., and Guildford, S. J.: Environmental controls of cladophora growth dynamics in eastern
- Lake Erie: Application of the Cladophora Growth Model (CGM), J. Great Lakes Res., 32, 629-644, 10.3394/03801330(2006)32[629:ECOCGD]2.0.CO;2, 2006.
- 589 Hipsey, M. R., Bruce, L. C., and Hamilton, D. P.: GLM General Lake Model. Model overview and user
- information, Technical Manual, The University of Western Australia, Perth, Australia., 2014.
- Hodges, B. R., Imberger, J., Saggio, A., and Winters, K. B.: Modeling basin-scale internal waves in a stratified lake,
- 592 Limnology and Oceanography, 45, 1603-1620, 10.4319/lo.2000.45.7.1603, 2000.
- Jabbari, A., Ackerman, J. D., Boegman, L., and Zhao, Y.: Episodic hypoxia in the western basin of Lake Erie,
- Limnology and Oceanography, 64, 2220-2236, 2019.
- 595 Jabbari, A., Ackerman, J. D., Boegman, L., and Zhao, Y.: Increases in Great Lake winds and extreme events
- facilitate interbasin coupling and reduce water quality in Lake Erie, Scientific Reports, 11, 5733, 10.1038/s41598021-84961-9, 2021.
- 598 Kelley, J. G. W., Hobgood, J. S., Bedford, K. W., and Schwab, D. J.: Generation of Three-Dimensional Lake Model
- 599 Forecasts for Lake Erie, Weather and Forecasting, 13, 659-687, 10.1175/1520-
- 600 0434(1998)013<0659:GOTDLM>2.0.CO;2, 1998.
- 601 Laval, B., Imberger, J., Hodges, B. R., and Stocker, R.: Modeling circulation in lakes: Spatial and temporal
- 602 variations, Limnology and oceanography, 48, 983-994, 2003.
- León, L. F., Imberger, J., Smith, R. E. H., Hecky, R. E., Lam, D. C. L., and Schertzer, W. M.: Modeling as a tool for
- nutrient management in Lake Erie: a hydrodynamics study, J. Great Lakes Res., 31, 309-318, 10.1016/S0380 1330(05)70323-3, 2005.
- 606 León, L. F., Smith, R. E. H., Hipsey, M. R., Bocaniov, S. A., Higgins, S. N., Hecky, R. E., Antenucci, J. P.,
- Imberger, J. A., and Guildford, S. J.: Application of a 3D hydrodynamic-biological model for seasonal and spatial
   dynamics of water quality and phytoplankton in Lake Erie, J. Great Lakes Res., 37, 41-53,
- 609 10.1016/i.jglr.2010.12.007, 2011.
- Leonard, B. P.: The ULTIMATE conservative difference scheme applied to unsteady one-dimensional advection.,
  Comp. Methods Appl. Mech. Eng., 88, 17-74, 1991.
- 612 Lesser, G. R., Roelvink, J. V., Van Kester, J. A. T. M., and Stelling, G. S.: Development and validation of a three-
- dimensional morphological model., Coastal Engineering, 51, 883-915, 10.1016/j.coastaleng.2004.07.014, 2004.
- 614 Liu, W., Bocaniov, S. A., Lamb, K. G., and Smith, R. E. H.: Three dimensional modeling of the effects of changes
- 615 in meteorological forcing on the thermal structure of Lake Erie, J. Great Lakes Res., 40, 827–840,
- 616 10.1016/j.jglr.2014.08.002, 2014.
- Loewen, M., Ackerman, J. D., and Hamblin, P. F.: Environmental implications of stratification and turbulent mixing
  in a shallow lake basin, Can. J. Fish. Aquat. Sci., 64, 43-57, 10.1139/F06-165, 2007.
- 619 Lv, Z., Zhang, S., Jin, J., Wu, Y., and Ek, M. B.: Coupling of a physically based lake model into the climate forecast
- 620 system to improve winter climate forecasts for the Great Lakes region, Climate Dynamics, 53, 6503-6517,
- 621 10.1007/s00382-019-04939-2, 2019.
- 622 Madani, M., Seth, R., León, L. F., Valipour, R., and McCrimmon, C.: Three dimensional modelling to assess
- 623 contributions of major tributaries to fecal microbial pollution of lake St. Clair and Sandpoint Beach, J. Great Lakes
  624 Res., 46, 159-179, 10.1016/j.jglr.2019.12.005, 2020.
- 625 Meyers, T., and Dale, R.: Predicting daily insolation with hourly cloud height and coverage, Journal of Applied
- 626 Meteorology and Climatology, 22, 537-545, 1983.
- 627 Michalak, A. a. M., Anderson, E. J., Beletsky, D., Boland, S., Bosch, N. S., Bridgeman, T. B., Chaffin, J. D., Cho,
- 628 K., Confesor, R., Daloğlu, I., DePinto, J. V., Evans, M. A., Fahnenstiel, G. L., He, L., Ho, J. C., Jenkins, L.,
- Johengen, T. H., Kuo, K. C., LaPorte, E., Liu, X., McWilliams, M. R., Moore, M. R., Posselt, D. J., Richards, R. P.,
- 630 Scavia, D., Steiner, A. L., Verhamme, E., Wright, D. M., and Zagorski, M. A.: Record-setting algal bloom in Lake

- Erie caused by agricultural and meteorological trends consistent with expected future conditions, Proceedings of the
- 632 National Academy of Sciences, 110, 6448-6452, 10.1073/pnas.1216006110, 2013.
- 633 MOE: Lake Erie fish kill incident on September 1, 2012. Summary Report.Ontario Ministry of the Environment

634 Southwestern Region 14 ((Available from OntarioMinistry of Environment).), 2012.

- Mortimer, C. H.: Fifty Years of Physical Investigations and Related Limnological Studies on Lake Erie, 1928–1977,
  Journal of Great Lakes Research, 13, 407-435, 10.1016/S0380-1330(87)71664-5, 1987.
- 637 Nakhaei, N., Boegman, L., Mehdizadeh, M., and Loewen, M.: Hydrodynamic modeling of Edmonton storm-water
- 638 ponds, Environ. Fluid Mech., 19, 305-327, 10.1007/s10652-018-9625-5, 2019.
- Nakhaei, N., Ackerman, J. D., Bouffard, D., Rao, Y. R., and Boegman, L.: Empirical modeling of hypolimnion and
  sediment oxygen demand in temperate Canadian lakes, Inland Waters, 1-17, 2021.
- 641 O'Reilly, C. M., Sharma, S., Gray, D. K., Hampton, S. E., Read, J. S., and Rowley, R. J., et al.: Rapid and highly
- variable warming of lake surface waters around the globe, Geophys. Res. Lett., 42, 10773-10781,
- 643 10.1002/2015GL066235., 2015.
- 644 O'connor, W. P., Schwab, D. J., and Lang, G. A.: Forecast verification for Eta Model winds using Lake Erie storm 645 surge water levels, Weather and forecasting, 14, 119-133, 1999.
- 646 O'Neil, J. M., Davis, T. W., Burford, M. A., and Gobler, C. J.: The rise of harmful cyanobacteria blooms: The
- potential roles of eutrophication and climate change, Harmful Algae, 14, 313-334, 10.1016/j.scitotenv.2011.02.001,
  2012.
- 649 Oveisy, A., Boegman, L., and Imberger, J.: Three-dimensional simulation of lake and ice dynamics during winter,
- 650 limnol. Oceanogr., 57, 42-57, 10.4319/lo.2012.57.1.0043, 2012.
- Paerl, H. W., and Paul, V. J.: Climate change: Links to global expansion of harmful cyanobacteria, Water Research,
  46, 1349-1363, 10.1016/j.watres.2011.08.002, 2012.
- Paturi, S., Boegman, L., and Rao, Y. R.: Hydrodynamics of eastern Lake Ontario and the upper St. Lawrence River,
  J. Great Lakes Res., 38, 194-204, 10.1016/j.jglr.2011.09.008, 2012.
- Rao, Y. R., and Murthy, C. R.: Coastal boundary layer characteristics during summer stratification in Lake Ontario.,
- 656 J. Phys. Oceanogr., 31, 1088-1104, 10.1175/1520-0485(2001)031<1088:CBLCDS>2.0.CO;2, 2001.
- Rao, Y. R., Hawley, N., Charlton, M. N., and Schertzer, W. M.: Physical processes and hypoxia in the central basin
  of Lake Erie, Limnol. Oceanogr., 53, 2007-2020, 10.4319/lo.2008.53.5.2007, 2008.
- ol Lake Erie, Limnol. Oceanogr., 53, 2007-2020, 10.4519/10.2008.55.5.2007, 2008.
- Rao, Y. R., Howell, T., Watson, S. B., and Abernethy, S.: On hypoxia and fish kills along the north shore of Lake
  Erie, J. Great Lakes Res., 40, 187-191, 10.1016/j.jglr.2013.11.007, 2014.
- Rey, A., and Mulligan, R. P.: Influence of Hurricane Wind Field Variability on RealTime Forecast Simulations of
   the Coastal Environment, J. Geophys. Res. Oceans, 126, 10.1029/2020JC016489, 2021.
- Rowe, M. D., Anderson, E. J., Beletsky, D., Stow, C. A., Moegling, S. D., and Chaffin, J. D., et al: Coastal
- upwelling influences hypoxia spatial patterns and nearshore dynamics in Lake Erie., J. Geophys. Res. Oceans, 124,
   10.1029/2019JC015192, 2019.
- 666 Ruberg, S. A., Guasp, E., Hawley, N., Muzzi, R. W., Brandt, S. B., and Vanderploeg, H. A., et al.: Societal benefits
- of the Real-time Coastal Observation Network (ReCON): Implications for municipal drinking water quality., Mar.
- 668 Technol. Soc. J., 42, 103-109, 10.4031/002533208786842471, 2008.
- 669 Saber, A., James, D. E., and Hannoun, I. A.: Effects of lake water level fluctuation due to drought and extreme
- 670 winter precipitation on mixing and water quality of an alpine lake, Case Study: Lake Arrowhead, California, Sci.
- 671 Total Environ., 714, 10.1016/j.scitotenv.2020.136762, 2020.
- 672 Scavia, D., Allan, J. D., Arend, K. K., Bartell, S., Beletsky, D., Bosch, N. S., Brandt, S. B., Briland, R. D., Daloglu,
- 673 I., DePinto, J. V., Dolan, D. M., and Evans, M. A. e. a.: Assessing and addressing the re-eutrophication of Lake Erie:
- 674 Centralbasin hypoxia, J. Great Lakes Res., 40, 226-246, 10.1016/j.jglr.2014.02.004, 2014.
- 675 Scavia, D., DePinto, J. V., and Bertani, I.: A multi-model approach to evaluating target phosphorus loads for Lake
- 676 Erie, J. Great Lakes Res., 42, 1139-1150, 10.1016/j.jglr.2016.09.007, 2016.
- 677 Schertzer, W. M., Saylor, J. H., Boyce, F. M., Robertson, D. G., and Rosa, F.: Seasonal Thermal Cycle of Lake Erie,
- **678** Journal of Great Lakes Research, 13, 468-486, 10.1016/S0380-1330(87)71667-0, 1987.
- Schwab, D. J., and Beletsky, D.: Propagation of kelvin waves along irregular coastlines in finite-difference models.,
  Adv. Water Resour., 22, 239-245, 10.1016/S0309-1708(98)00015-3, 1998.
- Schwab, D. J., Leshkevich, G. A., and Muhr, G. C.: Automated Mapping of Surface Water Temperature in the Great
  Lakes, J. Great Lakes Res., 25, 468-481, 10.1016/S0380-1330(99)70755-0, 1999.
- 683 Trebitz, A. S.: Characterizing seiche and tide-driven daily water level fluctuations affecting coastal ecosystems of
- 684 the Great Lakes, J. Great Lakes Res., 32, 102-116, 10.3394/0380-1330(2006)32[102:CSATDW]2.0.CO;2, 2006.
- Valipour, R., Bouffard, D., Boegman, L., and Rao, Y. R.: Near-inertial waves in Lake Erie, Limnol. Oceanogr., 60,
- vanpour, R., Boullard, D., Boegman, L., and Rao, Y. K.: Near-inertial waves in Lake Erie, Limnol. Oceanogr., 60
   1522–1535, 10.1021/es301422r, 2015.

- 687 Valipour, R., Rao, Y. R., León, L. F., and Depew, D.: Nearshore-offshore exchanges in multi-basin coastal waters:
- 688 Observations and three-dimensional modeling in Lake Erie, J. Great Lakes Res., 45, 50-60,
- 689 10.1016/j.jglr.2018.10.005, 2019.
- 690 Wang, Q., and Boegman, L.: Multi-Year Simulation of Western Lake Erie Hydrodynamics and Biogeochemistry to
- 691 Evaluate Nutrient Management Scenarios, Sustainability, 13, 7516, 2021.
- Watson, S. B., Miller, C., Arhonditsis, G., Boyer, G. L., and al, e.: The re-eutrophication of Lake Erie: Harmful algal
- **693** blooms and hypoxia, Harmful Algae, 56, 44-66, 10.1016/j.hal.2016.04.010, 2016.
- 694 Woolway, R. I., and Merchant, C. J.: Worldwide alteration of lake mixing regimes in response to climate change.,
- 695 Nat. Geosci., 12, 271-276, 10.1038/s41561-019-0322-x, 2019.
- 696 Woolway, R. I., Kraemer, B. M., and Lenters, J. D., et al.: Global lake responses to climate change, Nat Rev Earth
- **697** Environ, 10.1038/s43017-020-0067-5, 2020.





Fig. A1 Temperature profile comparison between (a) stitched 24 h model run with re-start files, and (b) model run with continuous input files.



# Port Dover

# **Port Colborne**



705

Fig. B1 Snapshot of water level forecast validation web page displayed on COASTLINES online platform:
 https://coastlines.engineering.queensu.ca/erie/water-level-forecast. Status on Sep 23rd, 2020.



Fig. C1 Comparisons of stitched GDPS wind forecast with 3 h delivery interval and lake buoy measured wind
speed at (a) station 45005 (10 min sampling interval), and (b) station 45142 (1 h sampling interval). The wind
gusts on day 327 at station 45005 and day 324 at station 45142 were missed by wind forecast.



Fig. C2 Comparisons of 24-h meteorological forecast and lake buoy observations of wind speed (a, b) and wind

direction (c, d). The gray rectangle indicates the storm that led to up-welling along northern shoreline on days
 248-253.



719 Fig. C3 Comparisons of 24-h air temperature forecast and lake buoy observations of air temperature.





Fig. C4 Comparisons of 240-h meteorological forecast and lake buoy observations of wind speed (a, b) and wind
 direction (c, d).



725 Fig. C5 Comparisons of 240-h air temperature forecast and lake buoy observations.

# 726 Appendix D: Temperature validation against satellite observations

## 727



728

- Fig. D1 comparisons of (a-d) satellite observations, (e-h) 15 km model 240-h forecast, and (i-l) 25 km model
- 730 240-h forecast during summer. The models were hot-started on Day 215. The difference between observations
- 731 and models are shown in (m-t).
- 732

(a) Satellite observation on Day 245 (b) Satellite observation on Day 246 (c) Satellite observation on Day 249 (d) Satellite observation on Day 251



- Fig. D2 comparisons of (a-d) satellite observations, (e-h) 15 km model 240-h forecast, and (i-l) 25 km model
- 735 240-h forecast during late summer. The models were hot-started on Day 244. The difference between
- 736 observations and models are shown in (m-t).



737 Appendix E: Water level change during windstorm on Nov 15<sup>th</sup>, 2020

Fig. E1 Spatial distribution of water level change from forecasts hot-started on Nov 15th (a, b) and Nov 12th
(c, d). The water level at Nov 15th 00:00 is the reference level. The black arrows are depth-averaged mean

- current fields. The black squares in the upper right corners of each map indicate the location of Port Dover
- 742 (Fig. 12d).
- 743

738