Exploring Deep Learning for Air Pollutant Emission Estimation

Lin Huang,^{*,1} Song Liu, ^{*,2,3} Zeyuan Yang,⁴ Jia Xing,^{2,3} Jia Zhang,¹ Jiang Bian,¹ Siwei Li,^{5,6} Shovan Kumar Sahu,^{2,3} Shuxiao Wang,^{2,3} Tie-Yan Liu¹

¹Microsoft Research, Beijing, China

5 ²State Key Joint Laboratory of Environmental Simulation and Pollution Control, School of Environment, Tsinghua University, Beijing, China

³State Environmental Protection Key Laboratory of Sources and Control of Air Pollution Complex, Beijing, China ⁴School of Economics and Management, Tsinghua University, Beijing, China

⁵School of Remote Sensing and Information Engineering, Wuhan University, Wuhan, China

⁶State Key Laboratory of Information Engineering in Surveying, Mapping and Remote Sensing, Wuhan University, Wuhan, China

*These authors contributed equally to this work.

Correspondence to: Jia Xing (xingjia@tsinghua.edu.cn); Jia Zhang (zhangjia@microsoft.com)

Abstract. The inaccuracy of anthropogenic emission inventory on a high-resolution scale due to insufficient basic data is one

- 15 of the major reasons for the deviation between air quality model and observation results. A bottom-up approach, as a typical emission inventory estimation approach, requires a lot of human labor and material resources, and a top-down approach focuses on individual pollutants that can be measured directly and relies heavily on traditional numerical modelling. Lately, deep neural network has achieved rapid development due to its high efficiency and non-linear expression ability. In this study, we proposed a novel method to model the dual relationship between emission inventory and pollution concentration for emission inventory
- 20 estimation. Specifically, we utilized a neural network based comprehensive chemical transport model (NN-CTM) to learn the complex correlation between emission and air pollution. We further updated the emission inventory based on backpropagating the gradient of the loss function measuring the deviation between NN-CTM and observations from surface monitors. We first mimicked the CTM model with neural networks (NN) and achieved a relatively good representation of CTM with similarity reaching 95%. To reduce the gap between CTM and observations, the NN model would suggest an updated emission of NO_x,
- 25 NH₃, SO₂, VOC and primary PM_{2.5} which changes by -1.34%, -2.65%, -11.66%, -19.19% and 3.51%, respectively, on average of China in 2015. Such ratios of NO_x and PM_{2.5} are even higher (~10%) particularly in Northwest China where suffers from large uncertainties in original emissions. The updated emission inventory can improve model performance and make it closer to observations. The mean absolute error for NO₂, SO₂, O₃ and PM_{2.5} concentrations are reduced significantly by about 10%~20%, indicating the high feasibility of NN-CTM in terms of significantly improving both the accuracy of emission
- 30 inventory as well as the performance of air quality model.

样式定义:列出段落

1 Introduction

The clean air policies have been implemented by China government since 2010 which has been effectively reducing the pollutant concentrations such as sulfur dioxide (SO₂), nitrogen oxides (NO₃) (Zheng et al., 2018). Nevertheless, China still faces challenges in addressing O₃ and PM_{2.5} pollutions. Particularly, the level of ozone (O₃) in China has increased by 1.3%

- 35 from 2013 to 2017 (Li, 2019); moreover, concentrations of PM_{2.5} (particulate matter with an aerodynamic diameter less than 2.5 μm) in most Chinese cities still far exceed the World Health Organization (WHO) recommended values (<10 μgm⁻³), leading to frequent heavy pollution events (Guo et al., 2014; Richter et al., 2005; Vesilind et al., 1988). Such high pollutant concentration may substantially affect human health given air pollution has being ranked fifth in global risk factors for mortality (Institute, 2019).
- 40 A prerequisite of effectively controlling air pollution lies in accurate knowledge of the related emission sources. A wellestablished emission inventory should summarize the amount of pollutants emitted into atmosphere from all sources in a specific region and time span (Institute, 2019). A typical bottom-up approach is adopted to develop the emission inventory through investigation of emission sources in Air Benefit and Cost and Attainment Assessment System Emission Inventory (ABaCAS-EI) (Zheng et al., 2019) and Multi-resolution Emission Inventory (MEIC) (He, 2012) developed by Tsinghua
- 45 University, wherein the activity rate of each source is multiplied with emission factor (Vallero and Daniel, 2018). Such technology-oriented bottom-up emission inventory can reflect the types of technology operated in China but has limitation in actual application because of its need for labor power and material resources, especially in cities where it is hard to support thorough investigation (Xing et al., 2020b). What's more, varied assumptions for activity rate and emission factor from different studies result in large uncertainties (Aardenne and Pulles, 2002). Therefore, the development of a method for efficient, 50 low-cost, and sufficiently accurate grid-emission information is being considered.
- The top-down method, as another typical emission invention is oring constant approach, can be used to constrain emission estimation by combining observation results from surface monitors and satellite retrievals. Brioude et al. (2012) has estimated emissions of anthropogenic CO, NO_x and CO₂ in the Los Angeles Basin using the FLEXPART Lagrangian particle dispersion model based on the top-down method. Recently, Yang et al. (2021) linked the bottom-up MAPLE model with the top-down CGE
- 55 model to evaluate deep decarbonization pathways' (DDP) comprehensive impacts in China. However, most of previous studies merely focused on individual pollutants that can be measured directly (Brioude et al., 2012; Xing et al., 2020a; Yang et al., 2021) and relied on traditional numerical modelling.

On the contrary, neural networks (NN), as a more efficient tool, can also model complex nonlinear relations in the atmospheric system thus converting precursor emissions into ambient concentrations. Due to its ability of end-to-end learning, NN can

60 automatically extract key features of input data and capture the behaviour of target data, thus has been widely used in atmospheric science recently (Fan et al., 2017; Tao et al., 2019; Wen et al., 2019; Xing et al., 2020a; Xing et al., 2020c). For example, many studies (Fan et al., 2017; Tao et al., 2019; Wen et al., 2019) combined recurrent NN (RNN) and convolutional NN (CNN) to capture spatial and temporal features in air pollution related questions since RNN has a strong capability in

mining temporal patterns from time series data (Cho et al., 2014; Chung et al., 2014; Hochreiter and Schmidhuber, 1997) with

- 65 certain ability to handle missing values efficiently (Fan et al., 2017) and CNN exhibits potentials in leveraging spatial dependencies, e.g., in meteorological prediction (Krizhevsky et al., 2012). Furthermore, Xing et al. (2020d) applied NN to the surface response model (RSM), thus significantly enhancing the computational efficiency, demonstrating the utility of deep learning approaches for capturing the nonlinearity of atmospheric chemistry and physics. The application of deep learning improves the efficiency of air quality simulation and can quickly provide data support for the formulation of emission control
- 70 policies, so as to adapt to the dynamic pollution situation and international situation. But the use of deep NN to estimate emission inventory is more complex compared to traditional machine learning problems, because there is no precise emission observation that can be used as supervision for model training.

To address all these issues, we proposed a novel method based on dual learning (He et al., 2016), which leverages the primaldual structure of artificial intelligence (AI) tasks to obtain informative feedbacks and regularization signals, thus enhancing

- 75 both the learning and inference process. In terms of emission inventory estimation, if we have a precise relationship from emission inventory to pollution concentrations, we can use the pollution concentrations as a constraint to get accurate emission inventory. In particular, we proposed to employ a neural network based chemical transport model (NN-CTM) with a delicately designed architecture, which is *efficient* and *differentiable* compared to <u>the</u> chemical transport model (CTM). Furthermore, when a well-trained NN-CTM can accurately reflect the *direct* and *indirect* physical and chemical reactions between emission
- inventory and pollutant concentrations, the emission inventory can be updated by backpropagating the gradient of the error between observed and NN-CTM predicted pollutant concentrations. Figure 1 shows the framework of this study.
 The method used for this study is described in Section 2. Section 3 takes China emission inventory estimation as an example to demonstrate the superiority of our method. In section 4, we make a conclusion and discuss some possible future work.



Function g: Pollutants \rightarrow Emissions

Figure 1: Framework of this study.

85

2.Method

2.1 Main Framework

90 The task of emission inventory estimation can be naturally formalized into a typical dual learning framework. Concretely, we denote x_t as the data of emission volumes and meteorological conditions and y_t as the corresponding pollutant concentration at time t. In addition, we denote the mapping function from emission to pollutant concentration as f and that from pollutant concentration to emission as g. Since the transformation from emission to pollutant concentration is a continuous process in time, approximately, we have the following equations:

95
$$y_t = f(x[(t-k+1):t]),$$
 (1)

$$x_t = g(y[(t-k+1):t]),$$

(2)

where x[i:j] is defined as $\{x_i, x_{i+1}, ..., x_j\}$ for convenience, so is y[i:j].

The formulas above are based on two assumptions:

1. The pollutant concentration is only dependent on the emission and meteorological conditions in the past k time steps, 100 e.g., hours or days.

2. There is a bijection relationship between emission and pollutant concentration. This is a necessary prerequisite for the existence of function *g*.

The first assumption will hold true as long as setting a sufficiently large k. The second assumption may not be true unless we introduce more external constraints on emission inventory, since there exists information loss in the process from emission to

105 pollutant concentration.



Figure 2: The whole process of emission inventory estimation.

- 110 In fact, it is quite difficult to learn the function g directly without emission observations as supervision. Hence, we employ dual learning framework to learn function g indirectly through leveraging function f. The framework of this process is illustrated in Figure 2. In particular, the whole process of emission inventory estimation includes the following steps:
 - 1. Use the existing emission inventory which is still not accurate enough as the initial emission data \hat{X} .
 - 2. Given \hat{X} , calculate the corresponding predicted pollutant concentration data \hat{Y} .
- 115 3. Calculate the loss between the observed values of pollutants \mathcal{Y} and the predicted pollutant concentrations $\hat{\mathcal{Y}}$.
 - 4. Adjust the estimated emission inventory \hat{X} by backpropagating the gradient of the loss based on function f.
 - 5. Repeat <u>steps</u> 2-4 until achieving sufficient accuracy for predicted concentration.

Although the chemical transport model (CTM) system can handle the transition from emission to pollutant concentration, it is not differentiable, which makes it quite hard to update emission inventory through backpropagation algorithm in the dual

120 learning framework. In order to establish a differentiable CTM, we propose to build a neural network based chemical transport model (NN-CTM) as the system approximation. More details will be described in the following subsections.

2.2 Deep Neural Network based Chemical Transition Model Approximation

Pollutant concentration is usually estimated using CTM which uses emission inventory as input. In the dual learning framework, this input will be updated in turn based on observed concentrations through the backpropagation algorithm. This
requires the CTM to be differentiable. To this end, we propose to use deep neural networks to approximate the CTM system. Concretely, to learn this neural network based chemical transport model (NN-CTM), we apply a supervised learning approach that leverages the training data whose input is the same as that of CTM and corresponding label is the output of CTM. The whole architecture is shown in Figure 3.

删除的内容: step

删除的内容: to



Figure 3: NN-CTM structure. *c* represents channel, which consists of emission inventory and meteorological data. *h*, *w* represent the height, width of input. *ge* is geographic information. We employ long short term memory (LSTM) to capture the temporal information, and U-Net to capture the spatial information. CNN represents convolution network. P-ReLU (He et al., 2015b) is a nonlinear activation function. MLP means multiple layers of perceptrons with threshold activation. The model structure is also named as LSTM-U-Net.

The input data of our NN-CTM are similar to that of CTM, including emission inventory, meteorology and geographical data. 140 The first two are time-dependent data, while the last one, denoted as ge, is static data. In the Eulerian grid based CTM system, for each time step t, the dynamic input data x_t is a matrix with dimension $w \times h \times c$. The concentration is simulated continuously in a continuous time sequence. Unlike CTM, the NN-CTM cannot deal with too long data sequences. Thus, we just use the data from past k time steps (i.e, x[t - k + 1:t]) as input for the pollutant concentration estimation y_t . At the same time, we add y_{t-k} as supplementary input data into the network. Same as CTM, the output y_t of NN-CTM is a matrix with

145 dimension $w \times h \times l$, where *l* is the number of concerned pollutant species.

The NN-CTM consists of three branches: two CNN branches for y_{t-k} and ge, and one long short term memory (LSTM) (Hochreiter and Schmidhuber, 1997) with U-Net (Ronneberger et al., 2015) branch. The CNN branches are used to extract features for y_{t-k} and geographical information. We employ parametric rectified linear unit (P-RELU) (He et al., 2015b) as the non-linear activation function in these branches to improve model fitting with nearly zero extra computational cost and little

150 overfitting risk. We adopt the architecture of combining LSTM and U-Net based on the understanding of temporal-spatial relationship in emission inventory. In temporal dimension, pollutants are the accumulation of historical emissions. In spatial 6 删除的内容: sequence

删除的内容: a

dimension, adjacent grids will affect each other because of meteorological and diffusion factors. The LSTM layer is used to
aggregate information from time series data x[t - k + 1:t]. The aggregated sequence of hidden states h_{t-k+1}, ..., h_t will be concatenated and entered into U-Net block. U-Net is a widely adopted pixel-to-pixel model which can effectively utilize neighbour information. In U-Net, the stacked of convolution can get the neighbour information with a bigger receptive field (e.g. stacking 5×5 convolution and 5×5 convolution can get a 9×9 convolution), the non-linear function (P-RELU) is employed to improve model fitting with nearly zero extra computational cost and little overfitting risk, and the batch normalization and dropout are employed to enhance the robustness of the model. We calculate that the receptive field of our model is 38×38 grid. In other words, the predicted pollutant concentration is related to its surrounding 38×38 grid's

information, which represents the transmission between different grids. Meanwhile, the closer the distance, the greater the

contribution. We employ 2-layers U-Net as shown in Figure 4 to capture the spatial information between grids.



165



170 In the training process, we take $(\chi_{CTM}, \mathcal{Y}_{CTM})$ as training dataset, where χ_{CTM} is the input data of the CTM system while \mathcal{Y}_{CTM} is the corresponding output. Since relative changes in pollutant concentrations are the metric often used by policymakers, we adopt an objective function that measures the relative loss between NN-CTM predicted and CTM-simulated pollutant concentrations. We denote the output of NN-CTM as $\hat{\mathcal{Y}}_{NN}$, and have:

$$L(\hat{\mathcal{Y}}_{NN}, \mathcal{Y}_{CTM}) = \frac{1}{Nhwl} \sum_{n=1}^{N} \sum_{i,j,c} \left(|\hat{y}_{i,j,c}^{(n)} - y_{i,j,c}^{(n)}| \right),$$
(3)

175
$$g_w = \frac{\partial L(\hat{y}_{NN}, y_{CTM})}{\partial w},$$
 (4)

where *N* is the number of samples, $i \in [1, h]$, $j \in [1, w]$ and $c \in [1, l]$, and $y_{i,j,c}^{(n)}$ represents the concentration of pollutant *c*-th in grid with location (i, j) in the *n*-th sample. The parameters of NN-CTM will be updated based on the gradients given by g_w , and the Adaptive Moment (Adam) estimation (Kingma and Ba, 2014) is used as optimizer.

Model robustness. We ensure the robustness of the model from three aspects: 1) Model structure. Inspired by computer vision

180 tasks, we adopt the batch-normalization (Ioffe and Szegedy, 2015), dropout (Srivastava et al., 2014), L2 regularization (Zhang et al., 2016) to improve the generalization and robustness. 2) Early stop. When we train the NN-CTM, we split the data into train dataset and validation dataset, and we stop the model training when the evaluation in validation dataset does not improve within 1000 iterations. 3) Data augmentation. During training, we employ the noise injection, random rescaling, random rotation method to avoid the overfitting in training dataset.

185 2.3 Emission Inventory Estimation Based On NN-CTM

Given a well-trained NN-CTM whose approximation accuracy is high enough for predicting pollutant concentrations, the emission inventory can be updated based <u>on</u> the error between observed and NN-CTM predicted pollutant concentrations. The observation data will help update the surrounding grids' emission inventory within the receptive field. However, in extreme circumstances, if we have no observation data, our method will not work as we have no more information to adjust the emission inventory. If the observation data is denser, the emission inventory estimation is more accurate as it can consider more

observation data.

190

200

In particular, we make the relationship between emission and pollutant concentration more robust by fixing the trained LSTM-U-Net model parameter. Then by training NN-CTM parameter, we adjust the input emission inventory to minimize the loss between NN-CTM output and observation. Such loss can be formally defined as:

195
$$L(\hat{\mathcal{Y}}_{NN}, \mathcal{Y}_{obs}^*) = \frac{1}{Nhwl} \sum_{n=1}^{N} \sum_{i,j,c} M_{i,j} (|\hat{\mathcal{Y}}_{i,j,c}^{(n)} - \mathcal{Y}_{i,j,c}^{*(n)}|),$$
 (5)

$$g_e = \frac{\partial L(\hat{y}_{NN}, y_{obs}^*)}{\partial e}$$

where \mathcal{Y}_{obs}^* represents observed pollutant concentration (we use average value in case of multiple observation stations in a grid), $M_{i,j}$ is a binary indicator variable indicating whether or not there is a site monitoring equipment in grid (i, j). The emission inventory will be updated by backpropagating the gradient g_e . The stochastic gradient descent (SGD) method (Bottou, 2010) is used as optimizer.

Meanwhile, aiming at ensuring the reasonableness and effectiveness of estimated emission inventory, we set two constrains: 1) The update rate of emission inventory to be a maximum of 200% compared with the prior emission for each grid. There exist biases in meteorological conditions and chemical mechanism, which determines that we cannot attribute all the errors to the emission inventory. If the update ratio is very large, the NN-CTM cannot well reflect the correlation of the unseen data.

8

删除的内容: will

(6)

Furthermore, the prior emission is accurate to a certain extent in terms of the spatial and temporal dimensions. 2) The updated emission inventory must be positive.

3. Experiments and Results Analysis

In this section, we apply our proposed method for emission inventory estimation in China <u>in</u> 2015. In the following, we will first describe the data and CTM configuration. After that, we will show experimental results in terms of the accuracy of NN-CTM. Then, we conduct further analysis on the prior emission inventory and our emission inventory estimation results.

3.1 Data and CTM Configuration

The prior emission inventory ABaCAS-EI with high spatial and temporal resolution is based on the bottom-up method, including primary pollutants such as NO_x , ammonia (NH₃), SO_2 , volatile organic compounds (VOC) and primary PM_{2.5}.

- 215 ABaCAS-EI is a grid-unit-based emission inventory including sources of power, cement, steel industries, and mobile sources. It also takes into consideration of technical progress and more stringent emission standards (Zheng et al., 2019). The prior emission inventory is initially used for NN-CTM training and then updated as per the proposed method of dual learning. Geographical data is a fixed attribute of one grid, like land type, mountains, depressions or elevation, etc. and in this study is obtained from the Moderate Resolution Imaging Spectroradiometer (MODIS) with 15s resolution (Friedl et al., 2002).
- 220 Meteorological conditions are simulated from the Weather Research and Forecasting model (WRF, version 3.7). WRF configuration includes Morrison microphysics scheme (Morrison et al., 2009), RRGM radiation scheme (Mlawer et al., 1998; Mlawer et al., 1997), Pleim-Xiu land surface scheme (Pleim and Xiu, 1995; Xiu and Pleim, 2001), ACM2 planetary boundary layer (PBL) physics scheme (Pleim, 2007) and Kain-Fritsch cumulus cloud parameterization (Kain, 2004), which matches our previous studies (Ghil and Malanotte-Rizzoli, 1991; Wikle, 2003). Data assimilation is adopted in
- WRF simulations based on observation data for the upper air and surface from National Centers for Environmental Prediction (NCEP) datasets. The simulated temperature, humidity, wind speed and direction have good agreement with the observations from the National Climatic Data Center (NCDC, https://www.ncdc.noaa.gov/data-access/land-based-station-data/) (Ding et al., 2019; Liu et al., 2019; Zhao et al., 2013).

The Community Multiscale Air Quality Model (CMAQ, version 5.2) configured with the AERO6 aerosol module (Appel et 230 al., 2013) and the Carbon Bond 6 (CB6) gas-phase chemical mechanism (Sarwar et al., 2008) is chosen as the representative CTM to simulate pollutant concentrations (Appel et al., 2018; Byun, 1999). Hourly observation data for air pollution (including SO₂, NO₂, O₃ and PM_{2.5}) is obtained from the China National Environmental Monitoring Centre (http://beijingair.sinaapp.com/), which are used for adjusting emission inventory.

The simulation domain covers mainland China and portions of surrounding countries with a 27km × 27km horizontal resolution (with h = 182 and w = 232) and 14 vertical layers from ground to 100 hPa. Simulations are performed in January, 删除的内容: has

April, July, and October 2015 to represent winter, spring, summer, and autumn, respectively. A 5-day simulation spin-up was performed to minimize the effects of initial conditions. Pollutant concentrations are analysed at monthly averages.

3.2 NN-CTM Learning and Evaluation

240 *Training parameters*. The parameter of NN-CTM was optimized using Adam optimizer with a mini-batch size of 8. A learning rate of 0.001 was used. To reduce the risk of over-fitting, we applied weight regularization on all trainable parameters during training and fine-tuning. The NN-CTM was trained for 30000 epochs.

Metrics. Model performance was evaluated using mean absolute error (MAE) calculated using the following equation:

$$L(\mathcal{G}_{NN}, \mathcal{Y}_{CTM}) = \frac{1}{Nhwl} \sum_{n,i,j,c} (|\hat{y}_{i,j,c}^{(n)} - y_{i,j,c}^{(n)}|),$$

245 Where N, h, w, l are the number of samples, height, width and the number of observed pollutants in each grid, respectively, further $n \in [1, N], i \in [1, h], j \in [1, w]$ and $c \in [1, l]$.

Evaluation. We examined the performance of NN-CTM to check whether it has learnt the relationship between emission and pollutant concentration.

We trained NN-CTM on the data of first 22 days in January, April, July and October 2015 and tested it on the remaining successive 8 days of each month. As listed in Table 1, NN-CTM (with LSTM-U-Net) can well reproduce the spatial and temporal relation with a small MAE of 0.27, 0.17, 1.39 ppbv and 1.46 µg m⁻³ for NO₂, SO₂, O₃ and PM_{2.5}, respectively, on average of four months. Results suggest that the NN-CTM can well reproduce the CTM within an acceptable bias, thus can be used for emission adjustment. Such bias (<4%) is much smaller than that of simulation compared to observations which <u>are</u> normally more than 10% even 20%.

255

Table 1: Evaluation of NN-CTM simulation in China (mean absolute error between CTM and NN-CTM). LSTM-U-Net is our proposed method. And then, to compare the model performance, we select another professional deep neural network method residual network (ResNet) (He et al., 2015a).

Model	NN-CTM (with LSTM-U-Net)				NN-CTM (with ResNet)			
Variables	$PM_{2.5}$ (µg m ⁻³)	O ₃ (ppbv)	NO ₂ (ppbv)	SO ₂ (ppbv)	$PM_{2.5}$ (µg m ⁻³)	O ₃ (ppbv)	NO ₂ (ppbv)	SO ₂ (ppbv)
Jan.	1.65	1.39	0.34	0.25	1.65	1.44	0.36	0.26
Ari.	1.74	1.46	0.25	0.16	1.73	1.64	0.26	0.18
Jul.	1.04	1.38	0.23	0.12	1	1.45	0.25	0.13
Oct.	1.43	1.34	0.27	0.16	1.53	1.44	0.29	0.17
Average	1.46	1.39	0.27	0.17	1.48	1.49	0.29	0.19
Error (Unit: %)	3.6	3.9	1.9	2.2	3.7	4.3	2.1	2.5

删除的内容: is

(7)

In order to further verify the superiority of our model architecture, we employed the ResNet (He et al., 2015a), another widely adopted deep NN method in image processing. Compared to ResNet, the performance of NN-CTM (with LSTM-U-Net) was superior, with improved MAE of 0.02, 0.02, 0.10 ppbv and 0.02 μ g m⁻³ for NO₂, SO₂, O₃ and PM_{2.5}, respectively, on average of four months, as listed in Table 1.

265 3.3 Emission Inventory Updating and Analysis

A well trained NN-CTM is used to update the emission inventory through back propagation using stochastic gradient descent SGD (Bottou, 2010) optimizer with a mini-batch size of 2. The learning rate is 0.1. The optimization of emissions is achieved after 10000 epochs.



270 Figure 5: Emission rates of NO_x, NH₃, SO₂, VOC and primary PM_{2.5} in P-Emis and their changes in N-Emis.

For convenience, we denote the emission inventory from ABaCAS-EI as prior emissions (P-Emis) and the updated emission inventory as NN-emission (N-Emis), which is constrained by station observations. Compared with P-Emis, N-Emis has 275 adjusted emission rates of NO_x, NH₃, SO₂, VOC and primary PM_{2.5} as per the difference between simulated concentrations and the observed values of pollutants in each grid, as shown in Figure 5. Average emission rates of NH3, SO2 and VOC in most grids tend to decrease, while that of primary PM2.5 tend to increase except for in the Yangtze River Basin, which may be related to the non-included dust emission. Changes in emission rate of NOx vary a lot by region, and such changes are concentrated in urban areas. The distribution of N-Emis for each grid is consistent with P-Emis, indicating that the deep

删除的内容: regions

learning method in this study can identify the distribution of emission sources and focus on the calibration in high-emission areas.

Annual anthropogenic emissions in China for NO_x, NH₃, SO₂, VOC and primary PM_{2.5} in P-Emis are 20.44, 10.39, 14.40, 23.05 and 7.19 Mt, respectively (Liu et al., 2020), while in N-Emis changed by -1.34%, -2.65%, -11.66%, -19.19% and 3.51%, respectively.

Table 2: Change ratios of N-Emis compared with P-Emis in four months. Unit: %.

285

Month			Variable	s		
Wolth	NO _x	NH ₃	SO_2	VOC	PM _{2.5}	
Jan.	3.72	1.88	-12.38	-25.36	4.64	
Apr.	-1.49	-2.56	-8.96	-18.27	4.69	
Jul.	-11.68	-2.29	-11.42	-12.8	1.8	
Oct.	3.6	-4.61	-13.32	-19.03	2.4	
Average	-1.34	-2.65	-11.66	-19.19	3.51	

The sensitivity of change ratios to different seasons varies. Table 2 lists the change ratios of N-Emis compared to P-Emis in four months. As for N-Emis, NO_x increases in January and October by about 3.5~4.0%, while it decreases by more than 10% in July. Emission of NH₃ increases in January while decreases in other three months with the highest decrease registered in October. Emission of SO₂ tends to decrease in all four months with ratios around 10%. Emission of VOC also tends to decrease but with a larger magnitude of about 20% compared to SO₂, which may be related to the overestimation of O₃. Emission of primary PM_{2.5} tends to increase by less than 5% in four months.

- 295 Such changes in emissions are based on mathematical algorithms and thus cannot be explained by physical and chemical processes. The NN method tries to give a solution to make simulation results of all pollutant species closer to observations by compensating the errors in emission inventory. For example, concentrations of PM_{2.5} obtained using P-Emis are generally lower than the observed level, so the emission of primary PM_{2.5} will be increased during the adjustment. SO₂ tends to be overestimated using P-Emis, so the adjustment tends to decrease. However, because sulfate is an important component of
- 300 PM_{2.5}, the adjustment of SO₂ will be restricted by the underestimation of PM_{2.5}. Concentrations of O₃ obtained using P-Emis are generally higher than the observed level, so it tends to reduce the emissions of NO_x and VOC, which are precursors of O₃, during the adjustment. It is worth noting that the adjustment range of NO_x is much lower than of VOC, because only the observed concentration of NO₂ is used as a constraint. Such results are consistent with our previous study (Xing et al., 2020a). In order to further analyse the change of emissions at a regional level, we calculated the four-month average emissions of P-
- 305 Emis and change ratios of N-Emis for five emission species in <u>the</u> Beijing-Tianjin-Hebei region (BTH), the Yangtze River Delta (YRD), the Pearl River Delta (PRD), the Sichuan Basin (SCH) and northwest China (NWC), as highlighted in Figure 6.

The first four areas were selected because they are the main population clusters, and NWC was selected because there are so few observation sites in this area that the constraints are relatively insufficient.



310

Figure 6: Five typical regions of China : Beijing-Tianjin-Hebei region (denoted as BTH), the Yangtze River Delta (denoted as YRD, covering Jiangsu, Zhejiang and Shanghai), the Pearl River Delta (denoted as PRD, covering Guangdong), the Sichuan Basin (denoted as SCH, covering Sichuan and Chongqing) and northwest China (denoted as NWC, covering Xinjiang), and their month-average emissions of four months in P-Emis (with unit of kt except for VOC with Mmol) and change ratios in N-Emis (with unit of %).

The adjustment of emission varies greatly by seasons and regions. Seasonal details are listed in Table 3. The four-month average changes of N-Emis in BTH are highest for SO₂ and VOC emissions reaching about -20% while that of NO_x, NH₃ and primary PM_{2.5} vary by less than 5%. In YRD, NOx and VOC emissions record the highest extent of changes with -14.73% for NO_x and 12.54% for VOC. The range of changes in other emission species is less than 5% (all decrease). Emission of primary PM_{2.5} in PRD increases by about 7%, which is the largest change ratio among four urban regions. Emission of NH₃ in PRD changes the least compared with other regions. In SCH, emissions of SO₂ and VOC decrease the most (change ratio) compared with other emission species (>20%). Emission of primary PM_{2.5} in SCH, which decreases by 5.95%, shows an opposite trend to that in PRD. As for in NWC, emissions of NH₃ and VOC show a small decrease (<5%), while emissions of NO_x and primary PM_{2.5} have a large percentage increase compared with other regions (10%), thus particularly indicating the large inaccuracy in emission inventory in NWC.

Table 3: Emissions and change ratios in five typical regions of four months.

Month	Variables	Version		Regions					
	variables		BTH	YRD	PRD	SCH	NWC		
			14						

³¹⁵

	No	P-Emis (kt)	68.05	70.56	37.07	43.29	10.26	
	NO _x	N-Emis (%)	-7.19	6.24	4.55	2.65	8.74	
		P-Emis (kt)	28.65	24.42	6.5	24.84	5.52	
	NH ₃	N-Emis (%)	0.67	0.59	8.3	5.13	8.64	
		P-Emis (kt)	90.13	40.16	21.72	150.67	34.06	
Jan.	SO_2	N-Emis (%)	-11.93	-11.38	-13.92	-26.14	-1.5	
	Noc	P-Emis (Mmol)	0.81	0.99	0.25	0.28	0.05	
	VOC	N-Emis (%)	-5.53	-12.73	-37.52	-36.39	2.61	
	DM	P-Emis (kt)	4.66	2.22	1.14	3.6	0.85	
	PM _{2.5}	N-Emis (%)	1.27	10.14	15.59	-0.8	9.61	
	NO	P-Emis (kt)	52.43	67.17	35.21	39.05	8.72	
	NO _x	N-Emis (%)	8.93	-15.05	-5.22	-7.8	14.59	
	NUT	P-Emis (kt)	85.56	90.34	70.52	192.37	56.06	
	NH_3	N-Emis (%)	-3.63	-2.6	-0.18	-1.78	-0.43	
Apr	50	P-Emis (kt)	33.93	34.44	20.43	110.74	20.2	
Apr.	SO_2	N-Emis (%)	-28.14	-0.92	-14.17	-22.97	6.77	
	Voc	P-Emis (Mmol)	0.38	0.85	0.23	0.19	0.05	
	VUC	N-Emis (%)	-28.87	13.71	-25.61	-29.06	-2.29	
	DM	P-Emis (kt)	1.81	1.96	0.94	1.79	0.62	
	PM2.5	N-Emis (%)	-5.12	-3.93	4.34	-8.89	9.54	
	NO	P-Emis (kt)	50.51	72.03	36.61	41.35	9.01	
	NO _x	N-Emis (%)	-10.62	-29.84	-11.46	-11.94	6.86	
	NH ₃	P-Emis (kt)	108.78	114.78	89.82	245.68	71.16	
		N-Emis (%)	-5.41	-2.7	-1.1	-0.9	0.08	
T1	SO_2	P-Emis (kt)	35.65	36.95	21.26	115.74	17.51	
Jul.		N-Emis (%)	-38.45	-4.18	-19.26	-19.71	12.71	
	VOC	P-Emis (Mmol)	0.39	0.92	0.24	0.21	0.05	
	VUC	N-Emis (%)	-22.87	23.85	-21.29	-16.47	8.85	
	DM	P-Emis (kt)	2.34	3.18	1.06	2.27	0.72	
	P 1 V 12.5	N-Emis (%)	0.88	-4.94	4.17	-5.4	6.91	
	NO	P-Emis (kt)	54.83	70.11	37.11	40.84	9.96	
	NO _x	N-Emis (%)	14.56	-19.99	-9.62	-1.5	25.41	
	NUT	P-Emis (kt)	50.43	53.4	41.24	110.75	32.28	
	NH ₃	N-Emis (%)	-0.53	-4.52	1.54	-3.79	-2.54	
Oct.	50	P-Emis (kt)	35.68	36.08	21.52	116.47	21.74	
	SO_2	N-Emis (%)	-39.8	-2.73	-19.63	-27.43	-2.39	
	VOC	P-Emis (Mmol)	0.4	0.89	0.25	0.19	0.06	
	VUC	N-Emis (%)	-38.33	27.98	-20.39	-34.42	-16.41	
	PM _{2.5}	P-Emis (kt)	1.94	1.95	1.15	1.85	1.04	

N-Emis (%) 0.26 -4.86 3.8 -13.68 9.32						
	N-Emis (%)	0.26	-4.86	3.8	-13.68	9.32

3.4 Accuracy Improvements of CTM Simulation for pollutants with N-Emis

- 330 We use the CTM to evaluate the accuracy of P-Emis and N-Emis. The configuration of CTM keeps constant. Generally, simulations using P-Emis tend to underestimate the PM_{2.5} concentrations and overestimate the O₃ concentrations on average of four months in China, which are consistent with our previous studies (Ding et al., 2019; Liu et al., 2019). The underestimation of PM_{2.5} using P-Emis usually appears in Northern and South eastern China, and sometimes occurs in some provinces of the Yangtze River Basin. The simulations of O₃ using P-Emis are generally overestimated at observation sites.
- 335 Such errors can be narrowed when using N-Emis. We calculated the MAE for each simulation to compare the performances considering all observation sites. After using adjusted emissions (i.e., N-Emis), the MAE for NO₂, SO₂, O₃ and PM_{2.5} concentrations reduced significantly from 7.39 to 5.91 (20.03%), 3.64 to 3.22 (11.54%), 14.33 to 11.56 (19.33%) ppbv and 18.94 to 16.67 (11.99%) µg m⁻³, respectively, average for total 612 observation stations, as shown in Figure 7. Such improvements prove the advantages of using N-Emis compared with P-Emis. Spatial distributions of comparison between
- 340 simulations and observations in 612 sites can be found in Figure 8. The model performance of most stations has been improved, and a small number of stations with worsen performance show the link between compound pollutants. For example, stations with larger deviations between PM₂₅ simulation results and observations tend to have greatly improved O₃ performance, and vice versa.



Figure 7. The MAE of NO2 (ppbv), SO2 (ppbv), O3 (ppbv) and PM2.5 (µg m⁻³) concentrations based on P-/N-Emis.



Figure 8: The MAE of NO₂ (ppbv), SO₂ (ppbv), O₃ (ppbv) and PM_{2.5} (µg m⁻³) concentrations based on P-/N-Emis.

350

Difference of monthly simulations using N-emis & P-Emis as input can be used to estimate the seasonal impacts of emission changes. Concentrations of O_3 and $PM_{2.5}$ tend to increase in July while decrease in other months on average for China. Concentrations of NO_2 and SO_2 tend to decrease in four months, which are consistent with the direct trend of emission adjustments.

We also calculated the average concentrations of four pollutants in five typical regions to quantify the degree of improvement in pollutant concentrations after adjusting the emission inventory, as listed in Table 4. Changes in NO₂ and SO₂ concentrations are consistent with adjustments in emissions but are more sensitive, i.e. a small change (~10%) in emission results in a larger proportional change (~20%) in concentration. The reduced SO₂ emission is an important reason for the improvement of PM_{2.5} overestimations in the Yangtze River Basin. PM_{2.5} concentrations in NWC show the highest increase (15%) compared with other regions. As the emission inventory in NWC has great potential for improvement (subject to production methods and the acquisition of basic data), the qualitative changes in PM_{2.5} concentrations brought about using NN method seem meaningful. The increase and decrease of NO_x and VOC emissions directly control the variance in O₃ concentration. Effect of using N-Emis on O₃ concentration is not obvious, with <u>a</u> change range of less than 5% in typical regions. Although the adjustment ratio of emissions of O₃ precursors is considerable, the O₃ concentration doesn't change by much. The same can be linked to the complex relationship of precursor emissions of NO_x and VOC which might not change simultaneously and in the same

direction (e.g. increase NO_x and decrease in VOC or vice-versa) thus resulting in only <u>a</u> slight change in O_3 concentration.

-{	删除的内容: emissions)
-{	删除的内容: shows)

```
删除的内容: seems
```

Table 4: Four-month average concentrations of NO₂, SO₂, O₃ and PM_{2.5} in five typical regions using different emission inventories.

Variables	Varsion		Regions						
v arrables	Version	BTH	YRD	PRD	SCH	NWC			
NO ₂ (ppbv)	P-Emis	15.69	13.31	6.25	4.82	0.31			
	N-Emis	11.85	10.79	5.29	4.45	0.33			
SO ₂ (ppbv)	P-Emis	6.97	4.32	1.89	4.88	0.26			
	N-Emis	5.77	3.95	1.67	3.2	0.37			
O ₃ (ppbv)	P-Emis	34.79	41.63	40.16	41.94	41.42			
	N-Emis	35.51	39.7	38.43	40.06	41.47			
$PM_{2.5} (\mu g m^{-3})$	P-Emis	46.28	44.29	22.6	25.96	2.02			
	N-Emis	45.28	41.66	22.08	23.71	2.33			

4. Conclusion and Discussion

- In this study, we pioneer the use of machine learning to re-formulate the problem of emission inventory estimation. It creates a new perspective that the data-driven approach can be applied to automatically improve the quality of the emission inventory, avoiding manual intervention and empirical error. We proposed a differential neural network based chemical transport model (NN-CTM), which <u>achieves</u> a relatively good representation of CTM. And then, we employed backpropagation algorithm to update the emission inventory based on the deviation between observed and NN-CTM predicted pollutant concentrations. In terms of method, we have proposed a novel emission inventory estimation method based on dual learning which consists of
- 380 dual-loop of emission-to-pollution and pollution-to-emission. Results indicate that our NN based method with adjusted emission inventory performed better than using prior emissions.

Compared with previous studies, our framework employs dual learning mechanism where in the simulated concentrations are compared to ground observation and the gradient is back propagated to update the emission inventory in each epoch. Results show that new emissions after the adjustment can improve the model performance in simulating the concentrations close to

385 observations. The mean absolute error for NO₂, SO₂, O₃ and PM_{2.5} concentrations reduced significantly by 10% to 20%. This application uses a constant biogenic emission inventory, so the potential errors in biogenic emissions are also included in the learning of anthropogenic emissions.

Our method can be naturally extended to other fundamental problems, such as CO_2 and other greenhouse gas emission inventory estimation, and has broad application prospects, such as building a real-time emission monitoring system based on

390 real-time pollutant observation data.

删除的内容: achieve

Code/Data availability

The codes for machine learning are available in https://doi.org/10.5281/zenodo.4607127 (Huang et al., 2021), including demo case for this study with input data from Ding et al. (2016) and the China National Environmental Monitoring Centre (http://beijingair.sinaapp.com/). CMAQv5.2 is an open-source and publicly available model developed by the United States

395 (http://beijingair.sinaapp.com/). CMAQv5.2 is an open-source and publicly available model developed by the United States Environmental Protection Agency, which can be downloaded at https://doi:10.5281/zenodo.1167892 (Appel et al., 2018).

Author Contribution

Lin Huang and Song Liu conceived the research project; Zeyuan Yang analyzed the data; Jia Xing, Jia Zhang, Jiang Bian, Siwei Li, Shuxiao Wang and Tie-Yan Liu provided valuable discussions on research and paper organization; Lin Huang, Song

400 Liu, Zeyuan Yang, Shovan Kumar Sahu, Jia Xing, Jia Zhang and Jiang Bian wrote the paper with contributions from all the authors.

Competing interests

The authors declare that they have no conflict of interest.

Acknowledgement

405 This work was supported in part by the National Natural Science Foundation of China (41907190, 51861135102) and the National Key R&D program of China (2017YFC0213005). This work was completed on the "Explorer 100" cluster system of Tsinghua National Laboratory for Information Science and Technology.

References

- 410 Aardenne, J. V. and Pulles, T.: Uncertainty in emission inventories: What do we mean and how could we assess it?, 2002.
- Appel, K., Pouliot, G., Simon, H., Sarwar, G., Pye, H., Napelenok, S., Akhtar, F., and Roselle, S.: Evaluation of dust and trace metal estimates from the Community Multiscale Air Quality (CMAQ) model version 5.0, Geoscientific Model Development, 6, 883-899, 2013.
- [415 Appel, K. W., Napelenok, S., Hogrefe, C., Pouliot, G., Foley, K. M., Roselle, S. J., Pleim, J. E., Bash, J., Pye, H. O. T., and Heath, N.: Overview and Evaluation of the Community Multiscale Air Quality (CMAQ) Modeling System Version 5.2, In: Mensink C., Kallos G. (eds) Air Pollution Modeling and its Application XXV. ITM 2016. Springer Proceedings in Complexity. Springer, Cham, doi: https://doi.org/10.1007/978-3-319-57645-9_11, 2018. 69-73, 2018.
- 420 Bottou, L.: Large-Scale Machine Learning with Stochastic Gradient Descent, Physica-Verlag HD, 2010. Brioude, J., Angevine, W. M., Ahmadov, R., and Kim, S.-W.: Top-down estimate of surface flux in the Los Angeles Basin using a mesoscale inverse modeling technique: assessing anthropogenic emissions of CO, NOx and CO2 and their impacts, Atmospheric Chemistry and Physics Discussions, doi: 10.5194/acpd-12-31439-2012, 2012.
- 425 Byun, D.: Science algorithms of the EPA Models-3 community multiscale air quality (CMAQ) modeling system, EPA/600/R-99/030, 1999. 1999.
- Cho, K., Merrienboer, B. v., Bahdanau, D., and Bengio, Y.: On the Properties of Neural Machine Translation: Encoder-Decoder Approaches, Computer Science, 2014. 2014.
- Chung, J., Gulcehre, C., Cho, K., and Bengio, Y.: Empirical Evaluation of Gated Recurrent Neural Networks on Sequence Modeling, Computer Science, 2014. 2014.
- Ding, D., Xing, J., Wang, S., Liu, K., and Hao, J.: Estimated contributions of emissions controls, meteorological factors, population growth, and changes in baseline mortality to reductions in ambient PM2.5 and PM2.5-related mortality in China, 2013–2017, Environmental Health Perspectives, doi: 10.1289/EHP4157, 2019. 2019.
- [435 Ding, D., Yun, Z., Jang, C., Lin, C. J., Wang, S., Fu, J., and Jian, G.: Evaluation of health benefit using BenMAP-CE with an integrated scheme of model and monitor data during Guangzhou Asian Games, J Environ, 42, 9-18, 2016.
- Fan, J., Li, Q., Hou, J., Feng, X., Karimian, H., and Lin, S.: A spatiotemporal prediction framework for air pollution based on deep RNN, ISPRS Annals of the Photogrammetry, Remote Sensing and Spatial Information Sciences, 4, 15, 2017.
- Friedl, M. A., Mciver, D. K., Hodges, J. C. F., Zhang, X. Y., Muchoney, D., Strahler, A. H., Woodcock, C. E., Gopal, S., Schneider, A., and Cooper, A.: Global land cover mapping from MODIS: algorithms and early results, Remote Sensing of Environment, 83, 287-302, 2002.
- Ghil, M. and Malanotte-Rizzoli, P.: Data Assimilation in Meteorology and Oceanography, Advances in Geophysics, 33, 141-266, 1991.
- Guo, S., Hu, M., Zamora, M. L., Peng, J., and Zhang, R.: Elucidating severe urban haze formation in China, Proceedings of the National Academy of Sciences of the United States of America, 111, 17373, 2014.
- He, D., Xia, Y., Qin, T., Wang, L., Yu, N., Liu, T.-Y., and Ma, W.-Y.: Dual learning for machine
 translation, Proceedings of the 30th International Conference on Neural Information Processing Systems, Barcelona, Spain, 820–828, 2016.
- He, K.: Multi-resolution Emission Inventory for China (MEIC): model framework and 1990-2010 anthropogenic emissions, 2012.

带格式的: EndNote Bibliography

域代码已更改

- He, K., Zhang, X., Ren, S., and Sun, J.: Deep Residual Learning for Image Recognition, Computer 455 Science, 2015a, 2015a.
- He, K., Zhang, X., Ren, S., and Sun, J.: Delving Deep into Rectifiers: Surpassing Human-Level Performance on ImageNet Classification, Computer Science, 2015b. 2015b.
- Hochreiter, S. and Schmidhuber, J.: Long Short-Term Memory, Neural Computation, 9, 1735-1780, 1997. Huang, G., Liu, Z., Laurens, V. D. M., and Weinberger, K. Q.: Densely Connected Convolutional 460 Networks, 2016. 2016.
- Huang, L., Liu, S., Yang, Z., Xing, J., Zhang, J., Bian, J., Li, S., Sahu, S. K., Wang, S., and Liu, T.-Y.: The Inventory Optimization Code for Exploring Deep Learning in Air Pollutant Emission Estimation Scale. Zenodo, 2021.
- Institute, H. E.: State of global air 2019. Health Effects Institute Boston, M. (Ed.), 2019.
- Ioffe, S. and Szegedy, C.: Batch Normalization: Accelerating Deep Network Training by Reducing 465 Internal Covariate Shift, JMLR.org, 2015. 2015.
- Kain, J. S.: The Kain–Fritsch convective parameterization: an update, Journal of Applied Meteorology, 43, 170-181, 2004.
- Kingma, D. and Ba, J.: Adam: A Method for Stochastic Optimization, Computer Science, 2014. 2014. Krizhevsky, A., Sutskever, I., and Hinton, G.: ImageNet Classification with Deep Convolutional Neural 470 Networks, 2012.
- Li, G.: Report on the completion of environmental conditions and environmental protection targets for 2018, (in Chinese), 2019. 2019.
- Liu, S., Xing, J., Westervelt, D. M., Liu, S., Ding, D., Fiore, A. M., Kinney, P. L., Zhang, Y., He, M. Z.,
- 475 and Zhang, H.: Role of emission controls in reducing the 2050 climate change penalty for PM2. 5 in China, Science of The Total Environment, 2020. 144338, 2020.
- Liu, S., Xing, J., Zhang, H., Ding, D., Zhang, F., Zhao, B., Sahu, S. K., and Wang, S.: Climate-driven trends of biogenic volatile organic compound emissions and their impacts on summertime ozone and secondary organic aerosol in China in the 2050s, Atmospheric Environment, 218, 117020, 2019.
- Mlawer, E., Clough, S., and Kato, S.: Shortwave clear-sky model measurement intercomparison using 480 RRTM, 1998, 23-27.
- Mlawer, E. J., Taubman, S. J., Brown, P. D., Iacono, M. J., and Clough, S. A.: Radiative transfer for inhomogeneous atmospheres: RRTM, a validated correlated-k model for the longwave, Journal of Geophysical Research: Atmospheres, 102, 16663-16682, 1997.
- 485 Morrison, H., Thompson, G., and Tatarskii, V.: Impact of cloud microphysics on the development of trailing stratiform precipitation in a simulated squall line: Comparison of one-and two-moment schemes, Monthly weather review, 137, 991-1007, 2009.
- Pleim, J. E.: A combined local and nonlocal closure model for the atmospheric boundary layer. Part I: Model description and testing, Journal of Applied Meteorology and Climatology, 46, 1383-1395, 2007.
- 490 Pleim, J. E. and Xiu, A.: Development and testing of a surface flux and planetary boundary layer model
- for application in mesoscale models, Journal of Applied Meteorology, 34, 16-32, 1995. Richter, A., Burrows, J. P., Nüss, H., Granier, C., and Niemeier, U.: Increase in nitrogen dioxide over China observed from space. Nature, Nature, 437, 129-132, 2005.
- Ronneberger, O., Fischer, P., and Brox, T.: U-Net: Convolutional Networks for Biomedical Image Segmentation, Computer Science, 2015. 2015. 495
- Sarwar, G., Luecken, D., Yarwood, G., Whitten, G. Z., and Carter, W. P. L.: Impact of an Updated Carbon Bond Mechanism on Predictions from the CMAQ Modeling System: Preliminary Assessment, Journal of Applied Meteorology & Climatology, 47, 3-14, 2008.

带格式的: EndNote Bibliography

- Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., and Salakhutdinov, R.: Dropout: A Simple Way
 to Prevent Neural Networks from Overfitting, Journal of Machine Learning Research, 15, 1929-1958, 2014.
- Tao, Q., Liu, F., Li, Y., and Sidorov, D.: Air Pollution Forecasting Using a Deep Learning Model Based on 1D Convnets and Bidirectional GRU, IEEE Access, 7, 76690-76698, 2019.
- Vallero and Daniel: Translating Diverse Environmental Data into Reliable Information, 2018. 25-41, 2018.
- Vesilind, P. A., Peirce, J. J., and Weiner, R. F.: Chapter 18 Air Pollution, Elsevier Inc., 1988. Wen, C., Liu, S., Yao, X., Peng, L., Li, X., Hu, Y., and Chi, T.: A novel spatiotemporal convolutional long short-term neural network for air pollution prediction, Science of the Total Environment, 654, 1091-1099, 2019.
- 510 Wikle, C. K.: Atmospheric modeling, data assimilation, and predictability, 2003. 2003.
- Xing, J., Li, S., Ding, D., Kelly, J. T., and Hao, J.: Data Assimilation of Ambient Concentrations of Multiple Air Pollutants Using an Emission-Concentration Response Modeling Framework, Atmosphere, 11, 1289, 2020a.
- Xing, J., Li, S., Jiang, Y., Wang, S., Ding, D., Dong, Z., Zhu, Y., and Hao, J.: Quantifying the emission changes and associated air quality impacts during the COVID-19 pandemic in North China Plain: a response modeling study, Atmospheric Chemistry and Physics Discussions, 2020, 1-28, 2020b.
- Xing, J., Zheng, Š., Ding, D., Kelly, J. T., and Hao, J.: Deep Learning for Prediction of the Air Quality Response to Emission Changes, Environmental Science and Technology, XXXX, 2020c.
- Xing, J., Zheng, S., Ding, D., Kelly, J. T., Wang, S., Li, S., Qin, T., Ma, M., Dong, Z., Jang, C., Zhu, Y.,
 Zheng, H., Ren, L., Liu, T.-Y., and Hao, J.: Deep Learning for Prediction of the Air Quality Response to Emission Changes, Environmental Science & Technology, 54, 8589-8600, 2020d.
- Xiu, A. and Pleim, J. E.: Development of a land surface model. Part I: Application in a mesoscale meteorological model, Journal of Applied Meteorology, 40, 192-209, 2001.
- Yang, X., Pang, J., Teng, F., Gong, R., and Springer, C.: The environmental co-benefit and economic impact of China's low-carbon pathways: Evidence from linking bottom-up and top-down models, Renewable and Sustainable Energy Reviews, 136, 110438, 2021.
- Zeiler, M. D., Krishnan, D., Taylor, G. W., and Fergus, R.: Deconvolutional networks, 2010. Zhang, C., Be Ngio, S., Hardt, M., Recht, B., and Vinyals, O.: Understanding deep learning requires rethinking generalization, 2016.
- 530 Zhao, B., Wang, S., Wang, J., Fu, J. S., Liu, T., Xu, J., Fu, X., and Hao, J.: Impact of national NOx and SO2 control policies on particulate matter pollution in China, Atmospheric Environment, 77, 453-463, 2013.
- Zheng, B., Tong, D., Li, M., Liu, F., and Zhang, Q.: Trends in China's anthropogenic emissions since 2010 as the consequence of clean air actions, Atmospheric Chemistry and Physics, 18, 14095-14111, 535 2018.
- Zheng, H., Zhao, B., Wang, S., Wang, T., Ding, D., Chang, X., Liu, K., Xing, J., Dong, Z., and Aunan, K.: Transition in source contributions of PM 2.5 exposure and associated premature mortality in China during 2005–2015, Environment International, 132, 2019.

带格式的: EndNote Bibliography

带格式的: EndNote Bibliography